




BAHR Modultechnik











Firmenstammsitz in Luhden

Ihr Spezialist für modulare Positioniersysteme

Unsere modularen Positioniersysteme bestehen aus selbsttragenden, verschleißfreien Aluminiumprofilen. Je nach geforderter Applikation bieten wir Ihnen unterschiedliche Führungs- und Antriebskonzepte wie z.B. Zahnriemen, Kugelroll-, und Trapezgewindespindeln sowie Zahnstangen oder Linearmotoren. Dabei gilt es Anforderungen an die Dynamik, Belastung und die Verfahr- und Positioniergenauigkeit optimal aufeinander abzustimmen. Der Vielfalt und den Kombinationsmöglichkeiten sind bei uns keine Grenzen gesetzt. Wir bieten Ihnen für jeden Bereich und jede Branche die passende Lösung.

Vom Vertrieb über Konstruktion und Fertigung bis zur Logistik stehen bei uns kompetente Fachleute zur Verfügung. So ist die Einhaltung hoher Qualitätsstandards stets gewährleistet. Dies macht sich bei den extrem kurzen Durchlauf- und Lieferzeiten positiv bemerkbar.

Qualität, produziert in Deutschland

Unsere Techniker beraten Sie gern.

Wir bieten einen umfassenden Kundenservice, wozu z.B. auch Beratungen und Vorführungen vor Ort oder in unserem Unternehmen gehören.





Unsere Aluminiumprofile werden nach der halben EN 12020-2 gefertigt:

Geradheit:	0,35 mm/m
max. Verwindung:	0,35 mm/m max.
Winkeltoleranz:	0,2 mm/40 mm
Parallelität:	0,2 mm
Legierung:	EN AW 6063-T66
Eloxal:	E6 EV1, 10 – 20 µm.

All profiles are produced in accordance with the medium EN 12020-2 standard:

Linearity:	0,35 mm/m
Max. torsion:	0,35 mm/m
Angular torsion:	0,2 mm/40 mm
Parallelity:	0,2 mm
Alloy:	EN AW 6063-T66
Anodizing quality:	E6 EV1, 10 – 20 µm



Location of the headquarter in Luhden



The specialist for linear module systems

Our linear module systems consist of self-supporting, wear-free aluminium profiles. We offer different guide and drive systems including timing belts, ballscrew or trapezoidal thread spindles, toothed racks or linear motors according to the required application. The most important thing in this regard is to match the dynamic and load requirements as well as the path and positioning accuracy in an optimal way. There are endless variations and combination possibilities. We have the right solution for each area and sector of industry.

The competence of Bahr Modultechnik bases on skilled staff in all areas including sales, design and production as well as logistics. This ensures that the highest quality standards are always met, which also leads to extremely short lead times and delivery periods.

If you have any questions, please do not hesitate to contact our engineers. We offer a comprehensive customer service, including advisory service and presentations at your premises or in our company.

Quality, made in Germany

Industrie Forum Design Hannover 92

Design Award Winner 2000

iF product design award 2011

iF DESIGN AWARD 2017

TÜV NORD CERT GmbH DIN EN ISO 14001/DIN EN ISO 9001



Fertigungshalle / production hall

Index

Positioning system		Chapter/Page
Spindle driven positioning systems / G - EG - EH - EL		
GGT – GGK	1.1	2 – 3
GDGT – GDGK	1.1	4 – 5
EGT – EGK	1.1	6 – 8
EGTH – EGKH	1.1	10 – 11
EHT – EHK	1.1	12 – 13
ELT – ELK	1.1	14 – 16
Non driven positioning systems EL - UL		
ELR	2.1	2 – 3
ELRZ	2.1	4
ER	2.1	5
E	2.1	6 – 7
UL	2.1	8 – 9
Belt driven positioning systems EL		
ELZ (ex)	3.1	2 – 6
ELZG	3.1	7
ELZ W	3.1	8 – 9
ELZZ	3.1	10 – 11
ELZD W	3.1	12 – 13
ELSZ with standard belt performance	3.1	14 – 15
ELSZ with belt widening	3.1	16 – 17
ELSD with standard belt performance	3.1	18 – 19
ELSD with belt widening	3.1	20 – 21
ELZT	3.1	22 – 23
ELHZ	3.1	24 – 25
ELVZ	3.1	26 – 28
ELFZ (ex)	3.1	30 – 33
ELZU	3.1	34 – 35
ELZU W	3.1	36 – 37
ELZI	3.1	38 – 39
Rack and pinion driven positioning systems EL		
ELZA/ELDZA	4.1	2 – 3
ELZQ	4.1	4 – 5
Roller guide positioning systems ML		
MLZ	5.1	2 – 3
MLN	5.1	4 – 5
MLZ W	5.1	6 – 7
MLZD W	5.1	8 – 9
Roller guide positioning systems QL		
QLZ	6.1	2 – 3
QLR	6.1	4 – 5
Rail guide positioning systems QS		
QSZ	7.1	2 – 3
QSSZ	7.1	4 – 5
QST – QSK	7.1	6 – 8
QSR	7.1	10 – 11
QSSR	7.1	12 – 13
QSRZ	7.1	14 – 15
Roller guide positioning systems DL		
DLT – DLK	8.1	2 – 4
DLT P – DLK P	8.1	6 – 7
DLZ	8.1	8 – 9
DLZZ	8.1	10 – 11
DLZPVI	8.1	12 – 13
DLZA	8.1	14 – 15
DLSZ	8.1	16 – 17
DLVZ	8.1	18 – 19
DLR	8.1	20 – 21
D Dust sealing	8.1	22
Rail guide positioning systems DS		
DST – DSK	9.1	2 – 4
DST P – DSK P	9.1	6 – 7
DSZ	9.1	8 – 9
DSZA	9.1	10 – 11
DSZPVI	9.1	12 – 14
DSSZ	9.1	16 – 17
DSR	9.1	18 – 19
DSZS	9.1	20 – 21
DSZS-P	9.1	22 – 23
Linear motor driven positioning systems DLM - DSM		
DLM	10.1	2 – 3
DLVM	10.1	4 – 5
DSM	10.1	6 – 7
DSM P	10.1	8 – 9
Digital controller and linear encoder	10.1	10
Belt driven positioning systems LL		
LLZ	11.1	2 – 3
LLR	11.1	4 – 5

Positioning system		Chapter/Page
Rail guide positioning systems LS		
LSZ	12.1	2 – 3
LSN	12.1	4 – 5
LSZ HP	12.1	6 – 7
LSR	12.1	8 – 9
Positioning systems CLL		
CLLZ	13.1	2 – 3
CLLT/K	13.1	4 – 5
Positioning systems W		
WGVZ / WKVZ	14.1	2 – 4
WGT/K – WKT/K	14.1	6 – 8
Positioning systems with stainless steel cover		
QLZE	15.1	2 – 3
QSZE	15.1	4 – 5
QST/KE	15.1	6 – 7
LLZE	15.1	8 – 9
LSZE	15.1	10 – 11
DSZPVIE	15.1	12 – 13
Roller guide positioning systems ALL		
ALLM	16.1	2 – 3
ALLZ	16.1	4 – 5
ALLZQ	16.1	6 – 7
ALLR	16.1	8 – 9
Positioning system heavy duty traverse		
SLTZA	17.1	2 – 3
SLTR	17.1	4 – 5

Spare parts and accessories		Chapter/Page
Spare parts		
Carriage complete	1.2	2 – 4
Slides, carriage roller, carriage roller block, runner blocks	1.2	5
Eccentric, wiper end plates	1.2	6
Eccentric keys, wiper end plates, slider	1.2	7
Cover bands, jointing plates	1.2	8
Guide rails, guide rods	1.2	9
Trapezoidal spindles, trapezoidal screws	1.2	10
Ballscrew spindles, ballscrew nuts	1.2	11
Leading nut receiver, cover caps	1.2	12
Belt-adjusters	1.2	13
Toothed belt	1.2	14 – 15
Toothed pulleys	1.2	16 – 18
Plug-in shafts, tensioning sets	1.2	18
Pulley with integrated tension set D 120, 160, 200	1.2	19
Spur gears, lubricants	1.2	20
Accessories		
Square nuts, T-nuts, rhombus nuts, half round nuts	2.2	2
Mounting possibility	2.2	3
Handwheel, positional indicator, spindle clamp	2.2	4
Carriage clamp, mounting systems	2.2	5
Mounting systems	2.2	6 – 8
Switches	2.2	9 – 10
Activating strips, bellows	2.2	11
Motor adapter, bevel gear, combination cube	2.2	12
Splinded shafts	2.2	13
Coupling	2.2	14 – 15
Angular gear box, transmission unit, toothed pulley	2.2	16
Toothed belt, parallel transfer unit	2.2	17
Cable condult, cable chain	2.2	18
Profiles		
Angular mounting profile	3.2	2 – 3
Mounting profiles	3.2	4
Technical specifications		
Calculation of toothed belt	4.2	2 – 4
Weights, Diagram for maximum rpm of spindle units	4.2	5
Calculation of torsional twist	4.2	6
Service manuals		
Service manuals	5.2	2 – 20
Fax inquiry		
Inquiry form	6.2	2 – 4
Terms and conditions		
Terms and conditions of sale and payment	7.2	2 – 4

Product index

GG / EG / EH / EL Positioning systems
Trapezoidal and ballscrew units **1.1**

ELR / ELRZ / ER / E / UL Positioning systems
Roller guide units without drive **2.1**

EL Positioning systems
Belt units **3.1**

EL Positioning systems
with rack and pinion drive **4.1**

ML - Positioning systems
with roller guides **5.1**

QL Positioning systems *with roller guides*
Belt driven *or without drive* **6.1**

QS Positioning systems *with rail guides*
Trapezoidal and ballscrew drive
Belt driven *or without drive* **7.1**

DL Positioning systems *with roller guides*
Trapezoidal and ballscrew drive, belt driven
Rack and pinion drive *or without drive* **8.1**

DS Positioning systems *with rail guides*
Trapezoidal and ballscrew drive
Belt driven *or without drive* **9.1**

DLM / DLVM Positioning systems
with roller guides and linear motor drive
DSM / DSB / DSM P Positioning systems
with rail guides and linear motor drive **10.1**

LL - Positioning systems
with roller guides **11.1**

LS - Positioning systems
with rail guides **12.1**

CLL - Positioning systems
with roller or rail guides **13.1**

W - Positioning systems
with ball or sliding bushings **14.1**

Stainless steel positioning systems
with roller or rail guides **15.1**

ALL Positioning systems
with roller guides **16.1**

SLT Positioning systems
Heavy duty traverse **17.1**















Product overview

ALLM 203, 204

Mechanical system with roll guides outside of profile.
Driven by linear motor.



ALLR 203, 204 *non-driven*

Mechanical system with roll guides outside of profile.

Repeating accuracy: *± 0,05mm*
Velocity: *v ≤ 8 m/s*

ALLZ 203, 204

Mechanical system with roll guides outside of profile.
Belt driven



Repeating accuracy: *± 0,1mm*
Velocity: *v ≤ 5 m/s*

ALLZQ 203, 204

Mechanical system with roll guides outside of profile.
Rach and pinion driven



Repeating accuracy: *± 0,1mm*
Velocity: *v ≤ 5 m/s*

CLL 60

Expanded positioning system of the LL 60 series with elegantly rounded outer edges and internal roller guide. The system is driven either by highly precise threaded spindles or a timing belt.


This unit is ideal for the system build-up of housings with minimum component requirements. Developed for building large-size delta 3D printers.

The CLLT/K unit is driven either by a trapezoidal threaded spindle or a ball screw spindle. The carriage of the CLLZ system is moved by means of a revolving interior timing belt.

Repeating accuracy: *± 0,1 mm*
Velocity: *v ≤ 6 m/s*

CLL






CLLT/K



CLLZ








Product overview

EGT/EGK 30, 40, 60, 80

Mechanical system with plastic prismatic guides.
System is driven by an integrated trapezoidal thread or ballscrew.

Repeating accuracy:
Trapezoidal thread: *± 0,2 mm*
Ballscrew: *± 0,025 mm*






EGTH/EGKH 40, 60, 80

Mechanical telescopic system with plastic prismatic guides.
System is driven by an integrated trapezoidal thread or ballscrew.
Result is a telescopic movement.

Repeating accuracy:
Trapezoidal thread: *± 0,2 mm*
Ballscrew: *± 0,025 mm*






EHT/EHK 60, 80

The rotary motion of the threaded spindle is converted into a linear motion of the pressure tube. Due to the piston rod principle, high axial forces can be realised, e. g. for shelf and dosing applications.

Repeating accuracy:
Trapezoidal thread: *± 0,2 mm*
Ballscrew: *± 0,025 mm*






ELR 30, 40, 60, 60S, 80, 80S, 100, 125 *non-driven*
ELRZ 30, 40, 60, 60S, 80, 80S, 100, 125 *non-driven*
ER 30, 40, 60, 60S, 80, 80S, 100, 125 *non-driven*
Mechanical system with roll guides outside of profile.


E 40, 60, 60S, 80, 80S *non-driven*
Mechanical system with roll guides outside of profile.

UL 40, 60, 80 *non-driven*
Mechanical system with roll guides inside of profile.


Velocity: *v ≤ 10 m/s*




ELR




ELRZ




ER



E



UL





Product overview

ELZA 40
ELDZA 60, 60S, 80, 80S, 100

Same function as ELSZ. A rack is mounted onto the leading profile. A pinion gear is fitted to the carriage.

Repeating accuracy: ± 0,2 mm
Velocity: v ≤ 3 m/s





ELFZ 60S, 80S, 100, 125


Special lifting system with roll guides outside of profile. System is driven by one rotating timing belt with one drive. The function corresponds to a simple pulley block.


Repeating accuracy: ± 0,1 mm
Velocity: v ≤ 4 m/s

ELFZex 60S, 80S, 100, 125

Special lifting system with roll guides outside of profile. System is driven by one rotating timing belt with one drive. The function corresponds to a simple pulley block. This system is additionally ATEX 2014/34/EU certified.

Repeating accuracy: ± 0,1 mm
Velocity: v ≤ 1 m/s






ELHZ 60, 60S, 80, 80S, 100, 125

Mechanical system with roll guides outside of profile.
System is driven by an internal belt. Position of shaft is horizontal to the carriage.

Repeating accuracy: ± 0,1 mm
Velocity: v ≤ 8 m/s







ELSD 40, 60, 60S, 80, 80S, 100

Same function as ELSZ. An additional turning shaft is integrated into the leading profile. Grippers and other components can be adapted to the shaft.

Repeating accuracy: ± 0,1 mm
Velocity: v ≤ 6 m/s







Product overview

ELSZ 30, 40, 60, 60S, 80, 80S, 100, 125

Same function as ELZ, but with driven carriage.

Repeating accuracy: *± 0,1 mm*
Velocity: *v ≤ 6 m/s*






ELVZ 60, 60S, 80, 80S, 100, 125

Mechanical system with roll guides outside of profile.
System is driven by an internal belt. Position of shaft is vertical to carriage.

Fraunhofer IPA TESTED DEVICE Lineareinheit ELVZ 60

Repeating accuracy: *± 0,1 mm*
Velocity: *v ≤ 8 m/s*






ELT/ELK 30, 40, 60, 60S, 80, 80S, 100, 125

Mechanical system with roll guides outside of profile.
System is driven by an integrated trapezoidal thread or ballscrew.

Repeating accuracy:
Trapezoidal thread: *± 0,2 mm*
Ballscrew: *± 0,025 mm*







ELZ/ELZex 30, 40, 60, 60S, 80, 80S, 100, 125

Mechanical system with roll guides outside of profile. System is belt driven. ELZex like ELZ. The positioning system is suitable for use according to the intended purpose in potentially explosive areas (see ATEX 2014/34/EU marking).

Repeating accuracy: *± 0,1 mm*
Velocity: *v ≤ 10 m/s*
(ELZex: v ≤ 1m/s)







ELZ 60-W, 60S-W

Mechanical linear unit with external roller guides. Due to the rectangular profile higher torques and loads can be taken up. In addition, a very high stability and low deflection are ensured for long axis systems.

Repeating accuracy: *± 0,1 mm*
Velocity: *v ≤ 10 m/s*







Product overview

ELZD 60-W, 60S-W

Mechanical linear unit with external roller guides. Two carriages, which are driven individually by a timing belt, move along the guide body independently of one another. Due to the rectangular profile higher torques and loads can be taken up. In addition, a very high stability and low deflection are ensured for long axis systems.

Repeating accuracy: ± 0,1 mm
Velocity: v ≤ 10 m/s







ELZG 30, 40, 60, 60S, 80, 80S

Mechanical system with 2 roll guides outside of profile. System is driven by one rotating timing belt. At each end of this belt a carriage is fixed. Result is two carriages moving in opposite direction over the complete length of the leading the profile.

Repeating accuracy: ± 0,1 mm
Velocity: v ≤ 10 m/s







ELZI 30, 40, 60

X/Z gantry consisting of a double guide in the horizontal X level and a vertical Z axis. The unit is driven by a rotating belt, which remains connected through various deflection points.

Repeating accuracy: ± 0,5 mm
Velocity: v ≤ 5 m/s






ELZQ 60, 80, 80S

Special lifting unit with function as ELZA. High dynamic and accuracy is achieved by a precision rack and pinion.

Repeating accuracy: ± 0,1 mm
Velocity: v ≤ 3 m/s







ELZT 40, 60, 60S, 80, 80S, 100

Same function as ELZ. Two carriages are moving in different directions. Result is a telescopic movement.

Repeating accuracy: ± 0,1 mm
Velocity: v ≤ 6 m/s






Product overview

ELZU 30, 40, 60, 60S, 80, 80S, 100

Surface portal, consisting of 2 Y-axes and 1 X-axis, driven by one rotating belt. This belt runs around different deflection pulleys. Positioning is achieved by two motors. The coordinate is diagonal to the deflection points of the Y-axes.
Advantage: Only small masses are moved, so that high acceleration can be realized.

Repeating accuracy: *± 0,5 mm*
Velocity: *v ≤ 6 m/s*
Acceleration: *max. 20 m/s²*






ELZU 60-W, 60S-W

Surface gantry consisting of two Y-axes and one reinforced X-axis. The unit is driven by a rotating belt, which remains connected through various deflection points. Due to the reinforced rectangular profile higher torques and loads can be taken up. In addition, a very high stability and low deflection are ensured for long axis systems. Advantage: Only small masses are moved and thus it is possible to achieve high accelerations.

Repeating accuracy: *± 0,5 mm*
Velocity: *v ≤ 6 m/s*
Acceleration: *max. 20 m/s²*






ELZZ 60, 60S, 80, 80S, 100, 125

Same function as ELZ, but each carriage with separate drive.
Divided pulleys have separate bearings, so two parallel moving belts are connected each with one carriage.

Repeating accuracy: *± 0,1 mm*
Velocity: *v ≤ 5 m/s*





DLM/DLVM 120, 160, 200

Mechanical system with double roll guides inside of profile. Driven by linear motor.

Repeating accuracy: *± 0,1 mm*
Velocity: *v ≤ 8 m/s*



Product overview

DLR 120, 160, 200 *non-driven*

Mechanical system with double roll guides inside of profile.


Velocity: *v ≤ 6 m/s*



DLSZ 120, 160, 200

Mechanical system with roll guides inside of profile.
Same function as DLZ but with driven carriage.

Repeating accuracy: *± 0,1 mm*
Velocity: *v ≤ 6 m/s*






DLT/DLK 120, 160, 200

Mechanical system with double roll guides inside of profile.
System is driven by an integrated trapezoidal thread or ballscrew.

Repeating accuracy:
Trapezoidal thread: *± 0,2 mm*
Ballscrew: *± 0,025 mm*






DLT/DLK 120 P, 160 P, 200 P

Mechanical system with double roll guides inside of profile.
System is driven by an integrated trapezoidal thread or ballscrew.
A special curved aluminium sheet is covering the carriage side.

Repeating accuracy:
Trapezoidal thread: *± 0,2 mm*
Ballscrew: *± 0,025 mm*






DLVZ 120, 160

Mechanical system with roll guides inside of profile.
System is driven by an internal belt.
Position of shaft is vertical to carriage.

Repeating accuracy: *± 0,1 mm*
Velocity: *v ≤ 6 m/s*






Product overview

DLZ 120, 160, 200

Mechanical system with roll guides inside of profile.
System is driven by an internal belt.

Repeating accuracy: *± 0,1 mm*
Velocity: *v ≤ 6 m/s*






DLZA 120, 160, 200

Rack and pinion system for high dynamic operations.

Repeating accuracy: *± 0,2 mm*
Velocity: *v ≤ 3 m/s*






DLZPVI 120, 160, 200

This unit consists of a rectangular aluminium profile with 2 integrated roller guides. The carriage is moved by a belt drive. On the drive side the pulley is beared on the shaft of a planetary gear. A special curved aluminium sheet is covering the carriage side.

Repeating accuracy: *± 0,1 mm*
Velocity: *v ≤ 6 m/s*






DLZPVIE 120, 160, 200

This unit consists of a rectangular aluminium profile with 2 integrated roller guides. The carriage is moved by a belt drive. On the drive side the pulley is beared on the shaft of a planetary gear. A special curved aluminium sheet is covering the carriage side. Enclosed with a stainless steel casing and components.

Repeating accuracy: *± 0,1 mm*
Velocity: *v ≤ 6 m/s*






DLZZ 120, 160, 200

Mechanical system with roll guides inside of profile. Each carriage with separate drive. Divided pulleys have separate bearings, so two parallel moving belts are connected each with one carriage.

Repeating accuracy: *± 0,1 mm*
Velocity: *v ≤ 6 m/s*






Product overview

DSM 160, 200

Mechanical system with a double integrated ball rail inside of profile. Driven by linear motor.

Repeating accuracy: *± 0,02 mm*
Velocity: *v ≤ 8 m/s*




DSM 160P

Mechanical system with a double integrated ball rail inside of profile. Driven by linear motor, but with a covered guide profile.

COLANDIS
the clean air company

Repeating accuracy: *± 0,02 mm*
Velocity: *v ≤ 6 m/s*





DSR 120, 160, 200 *non-driven*

Mechanical system with a double integrated ball rail inside of profile.


Velocity: *v ≤ 6 m/s*



DSSZ 120, 160, 200

Mechanical system with a double integrated ball rail inside of profile. Same function as DSZ but with driven carriage.

Repeating accuracy: *± 0,1 mm*
Velocity: *v ≤ 6 m/s*







DST/DSK 120, 160, 200

Mechanical system with a double integrated ball rail inside of profile. System is driven by an integrated trapezoidal thread or ballscrew.

Repeating accuracy:
Trapezoidal thread: *± 0,2 mm*
Ballscrew: *± 0,025 mm*






Product overview

DST/DSK 120 P, 160 P, 200 P

This unit consists of a rectangular aluminium profile with 2 integrated rail guides. The carriage is driven by means of a rotating spindle with leading nut. A special curved aluminium sheet is covering the carriage side.

Repeating accuracy:
Trapezoidal thread: *± 0,2 mm*
Ballscrew: *± 0,025 mm*







DSZ 120, 160, 200

Mechanical system with a double integrated ball rail inside of profile. System is driven by an internal belt.

Repeating accuracy: *± 0,1 mm*
Velocity: *v ≤ 6 m/s*






DSZA 160, 200

Mechanical system with a double integrated ball rail inside of profile. The carriage is driven by a pinion on a high precision rack. The rack and pinion system is suitable for highly dynamic servo operation and ideal for lifting movements. The pinion is equipped with maintenance-free ball bearings.

Repeating accuracy: *± 0,1 mm*
Velocity: *v ≤ 5 m/s*






DSZPVI 120, 160, 200

Mechanical system with a double integrated ball rail inside of profile. System is driven by an internal belt. One pulley is beared on a planetary gear shaft.

Repeating accuracy: *± 0,1 mm*
Velocity: *v ≤ 6 m/s*






DSZPVIE 120, 160, 200

Mechanical system with a double integrated ball rail inside of profile. System is driven by an internal belt. One pulley is beared on a planetary gear shaft. Enclosed with a stainless steel casing and components.

Repeating accuracy: *± 0,1 mm*
Velocity: *v ≤ 6 m/s*






Product overview

DSZS 120, 160, 200

Same funktion as DSSZ but with fixed drive under the profile.

Repeating accuracy: *± 0,1 mm*
Velocity: *v ≤ 6 m/s*






DSZS 120 P, 160 P, 200 P

Mechanical system with a double integrated ball rail inside of profile and with fixed drive under the profile. A special curved aluminium sheet is covering the carriage side.

Repeating accuracy: *± 0,1 mm*
Velocity: *v ≤ 6 m/s*






DSZZ 120, 160, 200

Mechanical system with a double integrated ball rail inside of profile. Each carriage with separate drive. Divided pulleys have separate bearings, so two parallel moving belts are connected each with one carriage.

Repeating accuracy: *± 0,1 mm*
Velocity: *v ≤ 6 m/s*






GGT / GGK 90

Spindle axis for wheelchair lifting systems, lifting platforms and other lifting applications. Mechanical linear unit with two internal sliding guides. The carriage is moved by means of a rotating thread spindle with an assigned follower nut. The openings in the guide body are closed by a plastic cover band.

Repeating accuracy:
Trapezoidal thread: *± 0.2 mm*
Ball screw: *± 0.025 mm*






DESIGN AWARD 2017

GDGT/GDGK 90

Optimized spindle axis for lift systems, bicycle assembly stands and other lifting applications. Mechanical linear unit with internal sliding guides. The guide carriages are moved by means of threaded spindles. The double “GG” profile ensures a very high stability.

Repeating accuracy:
Trapezoidal thread: *± 0.2 mm*
Ball screw: *± 0.025 mm*





Product overview

LLZ 60, 80

The guide body consists of an aluminium square profile, with an integrated roller guide. The carriage is moved by means of an internal rotating toothed belt.

Repeating accuracy: *± 0,1 mm*
Velocity: *v ≤ 6 m/s*





LLZE 60

Function like LLZ 60, but with a stainless steel casing and components.

Repeating accuracy: *± 0,1 mm*
Velocity: *v ≤ 6 m/s*






LSN 60

Mechanical linear unit with internal rail guide. The system is driven by a revolving knobbed belt. The knobbed belt is self-tracking and has a very low operating noise level thanks to its knobs being offset by 45°. Furthermore, it is almost vibration-free in the transition sections.

Repeating accuracy: *± 0,1 mm*
Velocity: *v ≤ 6 m/s*






LSZ 60, 80

The guide body consists of an aluminium square profile, with an integrated rail guide. The carriage is moved by means of an internal rotating toothed belt.

LSZ 60, 80 HP

Function like LSZ. Positioning system with very high accuracy.

Repeating accuracy: *± 0,1 mm*
Velocity: *v ≤ 6 m/s*






LSZE 60

The guide body consists of an aluminium square profile, with an integrated rail guide. The carriage is moved by means of an internal rotating toothed belt. With a stainless steel casing and components.

Repeating accuracy: *± 0,1 mm*
Velocity: *v ≤ 6 m/s*





Product overview

LLR 60, 80 *non-driven*

Mechanical system with roll guides.

LSR 60, 80 *non-driven*

Mechanical system with an integrated ball rail inside of profile.

Velocity: $v \leq 6$ m/s




MLN 60, 60S

Mechanical linear unit with external roller guides. The system is driven by a knobbed belt guided within the guide profile. The knobbed belt is self-tracking and has a very low operating noise level thanks to its knobs being offset by 45°. Furthermore, it is almost vibration-free in the transition sections.

Repeating accuracy: ± 0,1 mm
Velocity: $v \leq 8$ m/s






MLZ 60, 60S, 80, 80S, 100

Mechanical system with roll guides outside of profile.
The system is driven by a belt that is guided inside the profile.

Repeating accuracy: ± 0,1 mm
Velocity: $v \leq 8$ m/s







MLZ 60-W, 60S-W

Mechanical linear unit with external roller guides. Due to the rectangular profile higher torques and loads can be taken up. In addition, a very high stability and low deflection are ensured for long axis systems.

Repeating accuracy: ± 0,1 mm
Velocity: $v \leq 8$ m/s







MLZD 60, 60S

Mechanical linear unit with external roller guides. Due to the rectangular profile higher torques and loads can be taken up. In addition, a very high stability and low deflection are ensured for long axis systems. Two guide carriages, each with its own drive, move along the guide body.

Repeating accuracy: ± 0,1 mm
Velocity: $v \leq 8$ m/s





Product overview

QLR 60, 80, 100 *non-driven*

Mechanical system with roll guides inside of profile.


Velocity: *v ≤ 6 m/s*



QLZ 60, 80, 100

Mechanical system with roll guides inside of profile. System is driven by a belt which is guided within the profile.
This unit is suitable for cleanroom applications (Clean room classification: VDI 2083, class 4; ISO 14644-1, class 6; US Federal Standard 209E, class 1.000

Repeating accuracy: *± 0,1 mm*
Velocity: *v ≤ 6 m/s*





QLZE 60, 80, 100

Like QLZ, but enclosed with a stainless steel casing and components.

Fraunhofer IPA TESTED DEVICE Lineareinheit QLZ 80 Report No. BA 0005-171

Repeating accuracy: *± 0,1 mm*
Velocity: *v ≤ 4 m/s*





QSR 60, 80, 100, 125 *non-driven*

Mechanical system with an integrated ball rail inside of profile.

Velocity: *v ≤ 6 m/s*



QSRZ 60, 80, 100, 125 *non-driven*

Same function as QSZ, but without drive.

Repeating accuracy: *± 0,1 mm*
Velocity: *v ≤ 6 m/s*



Product overview

QSSR 60, 80, 100 *non-driven*

Mechanical system with an integrated ball rail inside of profile.

Velocity: *v ≤ 6 m/s*



QSSZ 60, 80

Same function as QSZ, but with driven carriage.


Repeating accuracy: *± 0,1 mm*
Velocity: *v ≤ 6 m/s*



QST/QSK 60, 80, 100

Mechanical system with an integrated ball rail inside of profile. System is driven by an integrated trapezoidal thread or ballscrew.

Repeating accuracy:
Trapezoidal thread: *± 0,2 mm*
Ballscrew: *± 0,025 mm*






QST/KE 60, 80, 100

Like QST/K, but enclosed with a stainless steel casing and components.

Repeating accuracy:
Trapezoidal thread: *± 0,2 mm*
Ballscrew: *± 0,025 mm*






QSZ 60, 80, 100, 125

Mechanical system with an integrated ball rail inside of profile. System is driven by a timing belt which is guided within the profile.

Repeating accuracy: *± 0,1 mm*
Velocity: *v ≤ 6 m/s*







Product overview

QSZE 60, 80, 100

Like QSZ, but enclosed with a stainless steel casing and components.

Repeating accuracy: *± 0,1 mm*
Velocity: *v ≤ 4 m/s*





SLTR/SLTZA 30, 50

Heavy Duty Traverse without drive (SLTR) and with rack and pinion drive (SLTZA).


Repeating accuracy: *± 0,1mm*
Velocity: *v ≤ 5 m/s*





WGVZ / WKVZ 16

This positioning system is guided either by means of ball bushings (WKVZ) or sliding bushings (WGVZ). The carriage is moved by means of a revolving vertical timing belt. The open arrangement ensures that no dirt can accumulate in the interior parts. Optionally, the unit is also available with two carriages (right/left).

Repeating accuracy: *± 0,1 mm*
Velocity: *v ≤ 10 m/s*









WGT/K / WKT/K 16

This positioning system is guided either by means of ball bushings (WK) or sliding bushings (WG). The carriage is moved by means of a rotating thread spindle. The open arrangement ensures that no dirt can accumulate in the interior parts. Optionally, the unit is also available with two carriages (right/left).

Repeating accuracy:
Trapezoidal thread: *± 0,2 mm*
Ballscrew: *± 0,025 mm*







Product overview

Spare parts

Carriages, V-slides, wiper end plates, jointing plates for closed carriage, rollers, end plates, eccentrics, guide rods, cover bands, lubricants, ball- and trapezoidal screws, spindles, leading-nuts, belts, belt pulleys, plug-in shafts, belt adjusters.






Accessories

Slide nuts, handwheels, positional indicators, spindle clamps, carrier clamps, plates, mounting blocks, switch holders, cable cover tubes, cable chains, switches, activating strips, motor adapters, couplings, bevel gears, combination cubes, cover caps, gearboxes, keyed shafts, bellows, toothed pulleys, toothed belts.









Appendix

Profiles, specifications, service manual







Trapezoidal or ballscrew spindle driven positioning systems
GG | EG | EH | EL

Slide with spindle drive


Positioning system to be used in lifting systems



Function:
Optimized spindle axis for wheelchair lifting systems, lifting platforms and other lifting applications. The guide body consists of an aluminium square profile with an integrated sliding guide. The plastic slide bushes integrated in the carriage ensure a very low friction resistance on anodized aluminium. The carriage is moved by means of a rotating thread spindle with an assigned follower nut. The opening in the guide body is closed by a plastic cover band. This plastic cover band is abrasion-free and is pressed into the profile by means of ball bearings.

Fitting position: As required. Max. length 3.000 mm
Carriage mounting: By tapped holes in the carriage.
Unit mounting: By T-slots or tapped holes in the bearing block and mounting sets.

Forces and torques



Size	GGT/K 90	
Forces / Torques	static	dynamic
F_x (N)	4200	3500
F_y (N)	1000	900
F_z (N)	1125	1000
M_x (Nm)	82	75
M_y (Nm)	220	200
M_z (Nm)	165	150
All forces and torques relate to the following: existing values / table values $\frac{Fy}{Fy_{dyn}} + \frac{Fz}{Fz_{dyn}} + \frac{Mx}{Mx_{dyn}} + \frac{My}{My_{dyn}} + \frac{Mz}{Mz_{dyn}} \leq 1$		
No-load torque		
Trapezoidal thread	24x5	24x10
(Nm)	0,50	0,80
Ballscrew	25x5	25x10
(Nm)	0,40	0,60
Geometrical moments of inertia of aluminium profile		
I_x mm^4	11,05x10^5	
I_y mm^4	23,60x10^5	
Elastic-modulus N/mm^2	70000	

Driving torque:

$$M_a = \frac{F * P * S_i}{2000 * \pi * \mu} + M_n$$

$$P_a = \frac{M_a * n}{9550}$$

F = force (N)
P = thread pitch (mm)
Si = safety factor 1,2 ... 2
M_n = no-load torque (Nm)
n = rpm of screw (min^{-1})
M_a = driving torque (Nm)
μ = screw efficiency
P_a = motor power (KW)


Efficiency of lead screws:

All ballscrew 0,900

Tr 24x5 0,384
Tr 24x10 0,550

Deflection:

$$f = \frac{F * L^3}{E * I * 192}$$




f = deflection (mm)
F = load (N)
L = free length (mm)
E = elastic modulus 70000 (N/mm²)
I = second moment of area (mm⁴)

For the diagram for critical speeds of lead screws refer to chapter 4.2

Positioning system GGT / GGK 90

Dimensions (mm)



*For slide nuts refer to chapter 2.2 page 2

Increasing the carriage length will increase the basic length by the same amount.

Size	Basic length L	A	B	C	D -0,05	E	F ❐	G	M	N for	P	Q	Shaft R key	Shaft S Ø h6 x length	T for	U1	U2	X	Basic weight	Weight per 100 mm
GGT/K 90	242	90	78	44	47	80	42	87	M8	M8	15	170	5x5x28	14x35	M6	120	60	44	4,5 kg	1,134 kg

T **Spindle:**
(T) Trapezoidal thread **(K)** Ballscrew

1 **Selection of screw:**
(1) right hand (Standard) **(2)** left hand (Ballscrew by inquiry)

0 **Choice of guide body profile:**
(0) Standard **(1)** corrosion-protected screws
(4) expanded corrosion-protected version (depending on the availability of components)

0 **Choice of carriages:**

(0)



0 **Drive version:**
(0) right (locating bearing side) **(1)** left (non-locating bearing side) **(2)** shaft on both sides

0 **Selection of screw:** Tr = trapezoidal thread Kg = ballscrew

Size	Standard	Multistart screw	Standard	Multistart screw	
90	**(0)** Tr 24x5	**(1)** Tr 24x10	**(0)** Kg 25x5	**(1)** Kg 25x10	**(2)** Kg 25x25

0 **Ballscrew pitch accuracy:** *(only ballscrew)*
(0) 0,05 mm / 300 mm **(2)** 0,025 mm / 300 mm

0 **End play of ball nut:** *(only ballscrew)*
(0) 0,04 mm *(Standard)*, **(1)** < 0,02 mm, **(2)** 2% apply prestress

GG	T	90	1	0	0	0	0	0	0	1500
		Pos.	1	2	3	4	5	6	7	


Basic length + stroke = total length


Sample ordering code:
GGT 90, trapezoidal thread right hand thread, standard body profile, carriage version 0, drive version 0, spindle Tr 24x5, 1258 mm stroke

Positioning system GDGT/K 90

Slide with spindle drive

Positioning system to be used in lifting systems






Function:
Optimized spindle axis for lift systems, bicycle assembly stands, lifting platforms and other lifting applications. The guide body consists of an aluminium profile with an integrated sliding guide. The plastic slide bushes integrated in the carriage ensure a very low friction resistance on anodized aluminium. The so-called double G profile ensures a very high stability. The carriage is moved by a rotating threaded spindle provided with a follower nut. The opening in the guide body is closed by a cover band made of plastic material. This plastic cover band is abrasion-free and is pressed into the profile by means of ball bearings.

Fitting position: As required. Max. length 3.000 mm
Carriage mounting: By tapped holes in the carriage.
Unit mounting: By T-slots or tapped holes in the bearing block.

Forces and torques



Size	90	
Forces / Torques	statisch	dynamisch
F_x (N)	4200	3500
F_y (N)	1000	900
F_z (N)	1125	1000
M_x (Nm)	82	75
M_y (Nm)	220	200
M_z (Nm)	165	150
All forces and torques relate to the following: existing values / table values $\frac{Fy}{Fy_{dyn}} + \frac{Fz}{Fz_{dyn}} + \frac{Mx}{Mx_{dyn}} + \frac{My}{My_{dyn}} + \frac{Mz}{Mz_{dyn}} \leq 1$		
No-load torque		
Trapezoidal thread	24x5	24x10
(Nm)	0,50	0,80
Ballscrew	25x5	25x10
Nm	0,40	0,60
Geometrical moments of inertia of aluminium profile		
I_x mm⁴	4,1x10⁶	
I_y mm⁴	4,0x10⁶	
Elastic-modulus N/mm²	70000	

Driving torque:

$$M_a = \frac{F * P * S_i}{2000 * \pi * \mu} + M_n$$

$$P_a = \frac{M_a * n}{9550}$$

F = force (N)
P = thread pitch (mm)
Si = safety factor 1,2 ... 2
M_n = no-load torque (Nm)
n = rpm of screw (min^{-1})
M_a = driving torque (Nm)
μ = screw efficiency
P_a = motor power (KW)


Efficiency of lead screws:

All ballscrew 0,900

Tr 24x5 0,384
Tr 24x10 0,550

Deflection:

$$f = \frac{F * L^3}{E * I * 192}$$




f = deflection (mm)
F = load (N)
L = free length (mm)
E = elastic modulus 70000 (N/mm²)
I = second moment of area (mm⁴)

For the diagram for critical speeds of lead screws refer to chapter 4.2

Positioning system GDGT/K 90

Dimensions (mm)



*For slide nuts refer to chapter 2.2 page 2

Increasing the carriage length will increase the basic length by the same amount.

Size	Basic length L	A	B	C	D -0,05	E	F ❐	G	M for	P	Q	Shaft R key	Shaft S ∅ h6 x length	T for	U1	U2	X	Basic weight	Weight per 100 mm
GDGT/K 90	242	90	78	35,5	47	144	42	158	M8	15	170	5x5x28	14x35	M6	120	60	44	7,8 kg	1,5 kg


T **Spindle:**
(T) Trapezoidal thread **(K)** Ballscrew

1 **Selection of screw:**
(1) right hand (Standard) **(2)** left hand (Ballscrew by inquiry)

0 **Choice of guide body profile:**
(0) Standard **(1)** corrosion-protected screws
(4) expanded corrosion-protected version (depending on the availability of components)

0 **Choice of carriages:**

(0)



0 **Drive version:**
(0) right (locating bearing side) **(1)** left (non-locating bearing side) **(2)** shaft on both sides

0 **Selection of screw:** Tr = trapezoidal thread Kg = ballscrew

Size	Standard	Multistart screw	Standard	Multistart screw	
90	**(0)** Tr 24x5	**(1)** Tr 24x10	**(0)** Kg 25x5	**(1)** Kg 25x10	**(2)** Kg 25x25

0 **Ballscrew pitch accuracy:** *(only ballscrew)*
(0) 0,05 mm / 300 mm **(2)** 0,025 mm / 300 mm

0 **End play of ball nut:** *(only ballscrew)*
(0) 0,04 mm *(Standard)*, **(1)** < 0,02 mm, **(2)** 2% apply prestress


GDG	T	90	1	0	0	0	0	0	0	1500
		Pos.	1	2	3	4	5	6	7	

Basic length + stroke = total length

Sample ordering code:
GDGT 90, trapezoidal thread right hand thread, carriage version 0, drive version 0, spindle Tr 24x5, 1258 mm stroke

Positioning system EGT/EGK 30, 40, 60, 80


Spindle driven with trapezoidal or ballscrew spindle



Function:
This unit consists of an aluminium square profile with lateral V-guides. The carriage, which is driven by means of a trapezoidal/ballscrew threaded spindle with lead screw, moves along the unit guided by V-slides that are adjustable free of play. Where two linear units are used in parallel or where two carriages are mounted on one unit, the leading-nut receiver can be used to adjust the symmetry of the carriages. The linear opening of the unit is sealed with a stainless steel cover band to make the unit splash-proof and dust-tight.

Fitting position: As required. Max. length 3.000 mm
Carriage mounting: T-slots, tapped holes (size 40)
Unit mounting: By T-slots or tapped holes in the bearing block, mounting sets.

Forces and torques



Size	EG 30		EG 40		EG 60		EG 80	
Forces / Torques	static	dynamic	static	dynamic	static	dynamic	static	dynamic
F_x (N)	750	600	1500	1200	2500	2000	4200	3500
F_y (N)	90	60	350	315	500	450	1000	900
F_z (N)	90	60	500	450	750	675	1125	1000
M_x (Nm)	10	5	20	18	33	30	82	75
M_y (Nm)	13	6	44	40	77	70	220	200
M_z (Nm)	14	7	33	30	55	50	165	150
All forces and torques relate to the following: existing values / table values	$\frac{Fy}{Fy_{dyn}} + \frac{Fz}{Fz_{dyn}} + \frac{Mx}{Mx_{dyn}} + \frac{My}{My_{dyn}} + \frac{Mz}{Mz_{dyn}} \leq 1$							
No-load torque								
Trapezoidal thread	10x3	-	18x4	18x8	24x5	24x10	28x5	28x10
(Nm)	0,4	-	0,70	0,70	0,50	0,80	0,80	1,0
Ballscrew	8x2,5	-	16x5	16x10	25x5	25x10	32x5	32x10
(Nm)	0,25	-	0,40	0,60	0,40	0,70	0,80	1,0
Geometrical moments of inertia of aluminium profile								
I_x mm^4	$4,09 \times 10^4$		$1,35 \times 10^5$		$5,65 \times 10^5$		$19,14 \times 10^5$	
I_y mm^4	$4,00 \times 10^4$		$1,48 \times 10^5$		$6,12 \times 10^5$		$20,12 \times 10^5$	
Elastic-modulus N/mm^2	70000		70000		70000		70000	

Driving torque:

$$M_a = \frac{F * P * S_i * w}{2000 * \pi * \mu} + M_n$$

$$P_a = \frac{M_a * n}{9550}$$


F	= force	(N)
P	= thread pitch	(mm)
Si	= safety factor 1,2 ... 2	
M_n	= no-load torque	(Nm)
n	= rpm of screw	(min^{-1})
M_a	= driving torque	(Nm)
μ	= screw efficiency	
w	= friction coefficient	~1,22
P_a	= motor power	(KW)

Efficiency of lead screws:

All ballscrew		0,900
Tr	10x3	0,375
Tr	18x4	0,399
Tr	18x8	0,565
Tr	24x5	0,384
Tr	24x10	0,550
Tr	28x5	0,349
Tr	28x10	0,513

Deflection:

$$f = \frac{F * L^3}{E * I * 192}$$





f = deflection	(mm)
F = load	(N)
L = free length	(mm)
E = elastic modulus 70000	(N/mm^2)
I = second moment of area	(mm^4)


For the diagram for critical speeds of lead screws refer to chapter 4.2

Positioning system EGT/EGK 30, 40, 60, 80


Dimensions (mm)







Size 40 without T-slots



*For slide nuts refer to chapter 2.2 page 2

Increasing the carriage length will increase the basic length by the same amount.

Size ❐	Basic length L	A	B	C	D ± 0,05	E	F	H	J	K	MM for	NN for	OO for	P	Q	R	S Ø h6 x length	T	Basic weight	Weight per 100 mm
EG 30	120	70	56	42	40x1	13	35	-	26	47	-	M 6	M 6	18	82	-	5x15	4,2	0,6 kg	0,16 kg
EG 40	170	70	-	58	48x1	18	47	-	35	64	-	M 6	M 6	25	117	3x3x25	10x27	6,5	1,3 kg	0,36 kg
EG 60	235	100	80	82	62x1	30	69	-	49	90	-	M 8	M 8	35	165	5x5x28	14x35	8,5	4,0 kg	0,67 kg
EG 80	286	140	110	102	80x1	40	88	30	70	121	M 6	M 10	M 10	45	193	6x6x40	18x45	8,5	6,7 kg	1,14 kg


T **Spindle:**
(T) Trapezoidal thread **(K)** Ballscrew

1 **Selection of screw:**
(1) right hand **(2)** left hand (Ballscrew by inquiry)

0 **Choice of guide body profile:**
(0) Standard **(2)** corrosion-protected guide rods (only size 30) and screws

0 **Choice of carriages:**

(0)



(1)



Size	Version 1	
	Q	L
30	94	132
40	133	186
60	181	251
80	209	302

0 **Drive version:**
(0) one shaft (locating bearing side) **(1)** one shaft (non-locating bearing side) **(2)** shaft on both sides

0 **Selection of screw:**

Size	Standard trapezoidal thread	Multistart screw trapezoidal thread	Standard ballscrew	Multistart screw ballscrew		
30	**(0)** Tr 10x3		**(0)** Kg 8x2,5			
40	**(0)** Tr 18x4	**(1)** Tr 18x8	**(0)** Kg 16x5	**(1)** Kg 16x10	**(2)** Kg 16x16	
60	**(0)** Tr 24x5	**(1)** Tr 24x10	**(0)** Kg 25x5	**(1)** Kg 20x20	**(2)** Kg 25x10	**(3)** Kg 20x50
80	**(0)** Tr 28x5	**(1)** Tr 28x10	**(0)** Kg 32x5	**(1)** Kg 25x25	**(2)** Kg 32x10	

0 **Ballscrew pitch accuracy:**
(0) 0,05 mm / 300 mm (Standard) **(2)** 0,025 mm / 300 mm

0 **End play of ball nut:**
(0) 0,04 mm (Standard), **(1)** < 0,02 mm, **(2)** 2% apply prestress

Repeatability:
± 0,2 mm Trapezoidal
± 0,025 mm Ballscrew

1500 Basic length + stroke = total length

Pos.	1	2	3	4	5	6	7
EG	**T**	**40**	**1**	**0**	**0**	**0**	**0**	**0**	**0**	**01500**


For combination kits and connecting elements refer to chapter 2.2


Sample ordering code:
EGT40, trapezoidal right hand thread, standard body profile, top carriage, one shaft (locating bearing side), spindle 18x4, 1331 mm stroke


Positioning system EGT/EGK 30, 40, 60, 80

Dimensions (mm)

with trapezoidal thread or ballscrew, right-hand and left-hand thread or divided spindles







*For slide nuts refer to chapter 2.2 page 2

Increasing the carriage length will increase the basic length by the same amount.

Size □	Basic length L	A	B	C	D ± 0,05	E	F	H	J	K	MM for	NN for	OO for	P	Q	R	S Ø h6 x length	T	Basic weight	Weight per 100 mm
EG 30	202	70	56	42	40x1	13	35	-	26	47	-	M 6	M 6	18	82	-	5x15	4,2	1,0 kg	0,16 kg
EG 40	287	70	-	58	48x1	18	47	-	35	64	-	M 6	M 6	25	117	3x3x25	10x27	6,5	2,5 kg	0,36 kg
EG 60	400	100	80	82	62x1	30	69	-	49	90	-	M 8	M 8	35	165	5x5x28	14x35	8,5	6,2 kg	0,67 kg
EG 80	479	140	110	102	80x1	40	88	30	70	121	M6	M 10	M 10	45	193	6x6x40	18x46	8,5	12,0 kg	1,14 kg

T **Spindle:**
(T) Trapezoidal thread **(K)** Ballscrew

3 **Selection of screw:**
(3) right - left hand **(4)** divided spindle

0 **Choice of guide body profile:**
(0) Standard **(2)** corrosion-protected guide rods (only size 30) and screws

0 **Choice of carriages:**

(0)



(1)



Size	Version 1	
	Q	L
30	94	226
40	133	319
60	181	432
80	209	511

0 **Drive version:**
(0) shaft right hand thread **(1)** shaft left hand thread **(2)** shaft on both sides

0 **Selection of screw:**

Size	Standard	Multistart screw	Standard	Multistart screw
	trapezoidal thread		ballscrew	
30	**(0)** Tr 10x3		**(0)** Kg 8x2,5*	
40	**(0)** Tr 18x4	**(1)** Tr 18x8	**(0)** Kg 16x5	**(1)** Kg 16x10* / **(2)** 16x16*
60	**(0)** Tr 24x5	**(1)** Tr 24x10	**(0)** Kg 25x5	**(1)** Kg 20x20* / **(2)** 25x10*
80	**(0)** Tr 28x5	**(1)** Tr 28x10	**(0)** Kg 32x5	**(1)** Kg 25x25* / **(2)** 32x10*

* = only for selection of divided spindle

0 **Ballscrew pitch accuracy:**
(0) 0,05 mm / 300 mm (Standard) **(2)** 0,025 mm / 300 mm

0 **End play of ball nut:**
(0) 0,04 mm (Standard), **(1)** < 0,02 mm, **(2)** 2% apply prestress

Repeatability:
± 0,2 mm Trapezoidal
± 0,025 mm Ballscrew

2200 Basic length + stroke = total length

EG	T	40	3	0	0	0	0	0	0	02200
		Pos.	1	2	3	4	5	6	7	

For combination kits and connecting elements refer to chapter 2.2

Sample ordering code:
EGT40, trapezoidal right - left hand thread, standard body profile, 2 top carriage, one shaft on right hand side, spindle 18x4, 1914 mm stroke



EGT 30



ELT 60S



EHT 80



EHT 60 | EHT 80

Positioning system EGTH/EGKH 40, 60, 80


Spindle driven with trapezoidal or ballscrew spindle



Function:
The rotary movement of the spindle is translated into a linear motion. Carriage and square tube are connected by a clamping block. The result is a telescopic movement.

Fitting position: As required. Max. length 3.000 mm
Carriage mounting: By T-slots and tapped holes
Unit mounting: By T-slots and tapped holes in the mounting surface.

Forces and torques



Size	EG(T/K)H 40		EG(T/K)H 60		EG(T/K)H 80	
Forces / Torques	static	dynamic	static	dynamic	static	dynamic
F_x (N)	1500	1200	2500	2000	4200	3500
F_y (N)	350	315	500	450	1000	900
F_z (N)	500	450	750	675	1125	1000
M_x (Nm)	20	18	33	30	82	75
M_y (Nm)	44	40	77	70	220	200
M_z (Nm)	33	30	55	50	165	150
All forces and torques relate to the following: existing values / table values	$\frac{Fy}{Fy_{dyn}} + \frac{Fz}{Fz_{dyn}} + \frac{Mx}{Mx_{dyn}} + \frac{My}{My_{dyn}} + \frac{Mz}{Mz_{dyn}} \leq 1$					
No-load torque						
Trapezoidal thread	18x4	18x8	24x5	24x10	28x5	28x10
(Nm)	0,70	0,70	0,50	0,80	0,80	1,0
Geometrical moments of inertia of aluminium profile						
I_x mm^4	$1{,}35 \times 10^5$		$5{,}65 \times 10^5$		$19{,}14 \times 10^5$	
I_y mm^4	$1{,}48 \times 10^5$		$6{,}12 \times 10^5$		$20{,}12 \times 10^5$	
E-modulus N/mm^2	70000		70000		70000	

Driving torque:

$$M_a = \frac{F * P * S_i * w}{2000 * \pi * \mu} + M_n$$

$$P_a = \frac{M_a * n}{9550}$$


F	= force	(N)
P	= thread pitch	(mm)
Si	= safety factor 1,2 ... 2	
M_n	= no-load torque	(Nm)
n	= rpm of screw	(min^{-1})
M_a	= driving torque	(Nm)
μ	= screw efficiency	
w	= friction coefficient	~1,22
P_a	= motor power	(KW)

Efficiency of lead screws:

All ballscrew		0,900
Tr	10x3	0,375
Tr	18x4	0,399
Tr	18x8	0,565
Tr	24x5	0,384
Tr	24x10	0,550
Tr	28x5	0,349
Tr	28x10	0,513

Deflection:

$$f = \frac{F * L^3}{E * I * 192}$$





f = deflection	(mm)
F = load	(N)
L = free length	(mm)
E = elastic modulus 70000	(N/mm^2)
I = second moment of area	(mm^4)

For the diagram for critical speeds of lead screws refer to chapter 4.2

Positioning system EGTH /EGKH 40, 60, 80

Dimensions (mm)





*For slide nuts refer to chapter 2.2 page 2


** The basic length (minimum length) of the unit (L+100) includes a stroke of 100mm

Size ❐	Basic length L +**	A	B	C	D ± 0,05	E	F	G	H	J	K	MM for	NN for	OO for	P	Q	R	S Ø h6 x length	T	Basic weight	Weight per 100 mm
EG H40	255	70	-	58	48x1	18	47	50	-	35	70	-	M 6	-	25	190	3x3x25	10x27	6,5	3,0 kg	0,44 kg
EG H60	345	100	80	82	62x1	30	69	70	-	49	98	-	M 8	M 8	35	250	5x5x28	14x35	8,5	7,0 kg	0,71 kg
EG H80	390	140	110	102	80x1	40	88	90	30	70	140	M 6	M 10	M 10	45	300	6x6x40	18x45	8,5	12,8 kg	1,35 kg

T **Spindle:**
(T) Trapezoidal thread **(K)** Ballscrew

1 **Selection of screw:**
(1) right hand **(2)** left hand

0 **Choice of guide body profile:**
(0) Standard **(1)** stainless screws



0 **Selection of screw:**

Size	Standard	Multistart screw	Standard
	trapezoidal thread		ballscrew
40	**(0)** Tr 18x4	**(1)** Tr 18x8	**(0)** Kg 16x5
60	**(0)** Tr 24x5	**(1)** Tr 24x10	**(0)** Kg 25x5
80	**(0)** Tr 28x5	**(1)** Tr 28x10	**(0)** Kg 32x5

0 **Ballscrew pitch accuracy:**
(0) 0,05 mm / 300 mm (Standard) **(2)** 0,025 mm / 300 mm

0 **End play of ball nut:**
(0) 0,04 mm (Standard), **(1)** < 0,02 mm, **(2)** 2% apply prestress

755 Basic length + stroke = total length


Repeatability:
± 0,2 mm Trapezoidal
± 0,025 mm Ballscrew

EG	T	H	40	1	0	0	0	0	0	00755
			Pos.	1	2	3	4	5	6	7

For combination kits and connecting elements refer to chapter 2.2

Sample ordering code:
EGTH40, trapezoidal right hand thread, standard body profile, 500 mm stroke


Spindle driven



Function:
The rotary motion of the threaded spindle is converted into a linear motion of the pressure tube.
Due to the piston rod principle, high axial forces can be realised, e. g. for shelf and dosing applications.

Mounting position: Variable, max. length size 80 = 1500 mm
Fixation: By T-nuts or mounting sets

Forces and torques



Size	EH 60		EH 80	
Forces / Torques	static	dynam	static	dynam
F_x (N)	1800	1200	3000	2500
F_y (N)	130	80	210	140
F_z (N)	130	80	210	140
M_x (Nm)	20	11	27	16
M_y (Nm)	95	60	190	110
M_z (Nm)	95	60	190	110
All forces and torques relate to the following:				
existing values / table values	$\frac{Fy}{Fy_{dyn}} + \frac{Fz}{Fz_{dyn}} + \frac{Mx}{Mx_{dyn}} + \frac{My}{My_{dyn}} + \frac{Mz}{Mz_{dyn}} \leq 1$			
No-load torque				
Trapezoidal thread	18x4	18x8	24x5	24x10
(Nm)	0,40	0,50	0,60	0,80
Ballscrew	16x5	16x10	25x5	25x10
(Nm)	0,20	0,40	0,40	0,60
Geometrical moments of inertia of aluminium profile				
I_x mm^4	4,75x10^5		15,41x10^5	
I_y mm^4	4,88x10^5		16,02x10^5	
Elastic-modulus N/mm^2	70000		70000	

Driving torque:

$$M_a = \frac{F * P * S_i}{2000 * \pi * \mu} + M_n$$

$$P_a = \frac{M_a * n}{9550}$$

F	= force	(N)
P	= thread pitch	(mm)
Si	= safety factor 1,2 ... 2	
M_n	= no-load torque	(Nm)
n	= rpm of screw	(min^{-1})
M_a	= driving torque	(Nm)
μ	= screw efficiency	
P_a	= motor power	(KW)


Efficiency of lead screws:

All ballscrew 0,900

Tr 18x4 0,399
Tr 18x8 0,565
Tr 24x5 0,384
Tr 24x10 0,550

Deflection:


$$f = \frac{F * L^3}{E * I * 192}$$



f	= deflection	(mm)
F	= load	(N)
L	= free length	(mm)
E	= elastic modulus 70000	(N/mm^2)
I	= second moment of area	(mm^4)

For the diagram for critical speeds of lead screws refer to chapter 4.2

Positioning system EHT/EHK 60, 80



*For slide nuts refer to chapter 2.2 page 2

Size ❐	Pressure pipe Spindle	Basic length L	C	D	E	F	G Ø x length	H	NN for	P	R	S Ø x length	SW	T	U	V Ø	Basic weight	Weight per 100 mm
EH 60	Ø 30 KG 16x5	165	82	60	30	69	M16x1,5x32	20	M8	35	3x3x25	10x27	24	8,5	77	30	2,33 kg	0,93 kg
EH 60	Ø 30 KG 16x10-16	175	82	60	30	69	M16x1,5x32	20	M8	35	3x3x25	10x27	24	8,5	77	30	2,42 kg	0,96 kg
EH 60	Ø 30 Tr 18x4-8	165	82	60	30	69	M16x1,5x32	20	M8	35	3x3x25	10x27	24	8,5	77	30	2,37 kg	0,84 kg
EH 80	Ø 40 KG 25x5	183	102	80	40	88	M20x1,5x40	22	M10	45	5x5x28	14x35	30	8,5	100	40	5,01 kg	1,50 kg
EH 80	Ø 40 KG 25x10	202	102	80	40	88	M20x1,5x40	22	M10	45	5x5x28	14x35	30	8,5	100	40	5,07 kg	1,26 kg
EH 80	Ø 40 KG 25x25	233	102	80	40	88	M20x1,5x40	22	M10	45	5x5x28	14x35	30	8,5	100	40	5,07 kg	1,50 kg
EH 80	Ø 40 Tr 24x5-10	183	102	80	40	88	M20x1,5x40	22	M10	45	5x5x28	14x35	30	8,5	100	40	5,07 kg	1,26 kg

K **Spindle:**
(T) Trapezoidal thread **(K)** Ballscrew

1 **Selection of screw:**
(1) right hand **(2)** left hand

0 **Choice of guide body profile:**
(0) Standard **(2)** corrosion-protected screws **(4)** expanded corrosion-protected version (depending on the availability of components)

0

Selection of screw:	Tr = trapezoidal thread		Kg = ballscrew	
Size	**Standard**	**Multistart screw**	**Standard**	**Multistart screw**
60	**(0)** Tr 18x4	**(1)** Tr 18x8	**(0)** Kg 16x5	**(1)** Kg 16x10 / KG 16x16 **(2)** Kg 25x25
80	**(0)** Tr 24x5	**(1)** Tr 24x10	**(0)** Kg 25x5	**(1)** Kg 25x10

Repeatability: ± 0,2 mm Trapezoidal ± 0,025 mm Ballscrew

0 **Ballscrew pitch accuracy:** *(only ballscrew)*
(0) 0,05 mm / 300 mm **(2)** 0,025 mm / 300 mm

0 **End play of ball nut:** *(only ballscrew)*
(0) 0,04 mm *(Standard)*, **(1)*** < 0,02 mm, **(2)*** 2% apply prestress

EH	K	80	1	0	0	0	0	0	0	1000
		Pos.	1	2	3	4	5	6	7	


Basic length + stroke = total length

Sample ordering code:
EHK80, ballscrew right hand thread, standard body profile, spindle Kg 25x5, 817 mm stroke

For combination kits and connecting elements refer to chapter 2.2


Positioning system ELT/ELK 30, 40, 60, 60S, 80, 80S, 100, 125

Spindle driven with trapezoidal or ballscrew spindle **Specifications**



Function:

This linear unit consists of an aluminium hollow section with integral, parallel ground and hardened steel guide rods. The carriage has play-adjustable ball-bearing rollers which engage with the guide rods. The rotating trapezoidal/ballscrew causes linear motion of the ballnut, which is connected to the carriage. The slot necessary for this is covered by a stainless steel strip, making the unit dust- and splash-proof. Lateral adjustment of movement for parallel units, or when two carriages are mounted on one unit, is provided by the ballnut mounting.



Forces and torques

Fitting position: As required, max. length 3.000 mm (EL 30 / max. 1500 mm, EL 40 / max. 2000 mm)

Carriage mounting: By T-slots and tapped holes

Unit mounting: By T-slots and tapped holes in the mounting surfaces.

Size	EL 30		EL 40		EL 60		EL 60 S		EL 80		EL 80S		EL 100		EL 125	
Forces/Torques	static	dyna.	static	dyna.	static	dyna.	static	dyna.	static	dyna.	static	dyna.	static	dyna.	static	dyna.
F_x (N)	750	600	1500	1200	2500	2000	2500	2000	5000	4000	5000	4000	10000	8000	15000	12000
F_y (N)	90	60	1200	700	3000	2000	4100	3100	3000	2000	4600	3600	8000	6500	12000	9000
F_z (N)	90	60	900	650	1700	1100	2160	1600	1700	1100	3000	1800	3600	2200	6000	4500
M_x (Nm)	12	10	25	20	67	43	88	65	90	55	170	140	300	230	600	450
M_y (Nm)	12	10	32	18	90	70	190	140	110	80	270	230	400	270	750	600
M_z (Nm)	15	12	35	25	120	100	230	170	150	120	300	220	750	500	1350	1150

All forces and torques relate to the following:

existing values / table values

$$\frac{Fy}{Fy_{dyn}} + \frac{Fz}{Fz_{dyn}} + \frac{Mx}{Mx_{dyn}} + \frac{My}{My_{dyn}} + \frac{Mz}{Mz_{dyn}} \leq 1$$

No-load torque								
Trapezoidal thread	10x3	18x4/18x8	24x5/24x10	24x5/24x10	28x5/28x10	28x5/28x10	32x6/32x12	40x7/40x14
(Nm)	0,3	0,4/0,5	0,6/0,8	0,6/0,8	0,8/1,0	0,8/1,0	0,9/1,1	1,2/1,4
Ballscrew	8x2,5	16x5/16x10	25x5/25x10	25x5/25x10	32x5/32x10	32x5/32x10	32x5/32x10	40x10/40x20
(Nm)	0,15	0,2/0,4	0,4/0,6	0,4/0,6	0,6/0,8	0,6/0,8	0,7/0,9	1,0/1,2
Geometrical moments of inertia of aluminium profile								
I_x mm^4	4,09x10^4	1,32x10^5	6,79x10^5	6,79x10^5	18,99x10^5	18,99x10^5	44,4x10^5	101,5x10^5
I_y mm^4	4,00x10^4	1,34x10^5	6,97x10^5	6,97x10^5	18,97x10^5	18,97x10^5	44,8x10^5	101,5x10^5
E-Modulus N/mm^2	70000	70000	70000	70000	70000	70000	70000	70000

For life-time calculation of rollers use our homepage.

Driving torque:

$$M_a = \frac{F * P * S_i}{2000 * \pi * \mu} + M_n$$

$$P_a = \frac{M_a * n}{9550}$$

F	= force	(N)
P	= thread pitch	(mm)
Si	= safety factor 1,2 ... 2	
M_n	= no-load torque	(Nm)
n	= rpm of screw	(min^{-1})
M_a	= driving torque	(Nm)
μ	= screw efficiency	
P_a	= motor power	(KW)


Efficiency of lead screws:

All ballscrew 0,900

Tr 10x3	0,375	Tr 32x6	0,360
Tr 18x4	0,399	Tr 32x12	0,524
Tr 18x8	0,565	Tr 40x7	0,344
Tr 24x5	0,384	Tr 40x14	0,509
Tr 24x10	0,550		
Tr 28x5	0,349		
Tr 28x10	0,513		

Deflection:


$$f = \frac{F * L^3}{E * I * 192}$$



f	= deflection	(mm)
F	= load	(N)
L	= free length	(mm)
E	= elastic modulus 70000	(N/mm^2)
I	= second moment of area	(mm^4)


For the diagram for critical speeds of lead screws refer to chapter 4.2

Positioning system ELT/ELK 30, 40, 60, 60S, 80, 80S, 100, 125





Dimensions (mm)



*For slide nuts refer to chapter 2.2 page 2

Increasing the carriage length will increase the basic length by the same amount.

Size ❒	Basic length L	A	B	C	D ± 0,05	E	F	G	H	J	K	MM for	NN for	OO for	P	Q	R	S Ø h6 x length	T	Basic weight	Weight per 100 mm
EL 30	120	70	56	42	40x1	13	35	-	-	26	47	-	M 6	M 6	18	82	-	5x15	4,2	0,7 kg	0,16 kg
EL 40	175	100	66	58	48x1	18	47	–	-	35	64	-	M 6	M 6	25	122	3x3x25	10x27	6,5	1,7 kg	0,37 kg
EL 60	245	144	96	82	62x1	30	69	-	-	49	90	-	M 8	M 8	35	168	5x5x28	14x35	8,5	5,1 kg	0,89 kg
EL 60S	270	170	108	82	62x1	30	69	-	-	53	94	-	M 8	M 8	35	194	5x5x28	14x35	8,5	5,1 kg	0,89 kg
EL 80	285	170	117	102	80x1	40	88	10	30	70	121	M 6	M 10	M 10	45	194	6x6x40	18x45	8,5	10,0 kg	1,48 kg
EL 80S	305	190	126	102	80x1	40	88	12,5	30	71	122	M 6	M 10	M 8	45	214	6x6x40	18x45	8,5	11,0 kg	1,48 kg
EL 100	410	230	155	130	110x1	50	112	-	29	89	154	M 10	M 10	M 10	55	300	6x6x40	22x45	10,5	19,0 kg	2,00 kg
EL 125	510	295	200	165	130x1	60	142	-	30	107,5	190	M 10	M 12	M 12	65	365	8x7x50	25x55	13,0	33,0 kg	2,89 kg

T **Spindle:**
(T) Trapezoidal thread **(K)** Ballscrew

1 **Selection of screw:**
(1) right hand **(2)** left hand (Ballscrew by inquiry)

0 **Choice of guide body profile:**
(0) Standard **(2)** corrosion-protected guide rods and screws
(4) expanded corrosion-protected version (depending on the availability of components)

0 **Choice of carriages:**

(0)



(1)



Size	Version 1	
	Q	L
30	94	132
40	138	191
60	184	261
60S	214	290
80	210	301
80S	234	325
100	316	426
125	389	534

0 **Drive version:**
(0) one shaft (locating bearing side) **(1)** one shaft (non-locating bearing side)
(2) shaft on both sides

0 **Selection of screw:**

Size	Standard trapezoidal thread	Multistart screw trapezoidal thread	Standard ballscrew	Multistart screw ballscrew		
30	**(0)** Tr 10x3		**(0)** Kg 8x2,5			
40	**(0)** Tr 18x4	**(1)** Tr 18x8	**(0)** Kg 16x5	**(1)** Kg 16x10	**(2)** Kg 16x16	
60	**(0)** Tr 24x5	**(1)** Tr 24x10	**(0)** Kg 25x5	**(1)** Kg 20x20	**(2)** Kg 25x10	**(3)** Kg 20x50
80	**(0)** Tr 28x5	**(1)** Tr 28x10	**(0)** Kg 32x5	**(1)** Kg 25x25	**(2)** Kg 32x10	
100	**(0)** Tr 32x6	**(1)** Tr 32x12	**(0)** Kg 32x5	**(1)** Kg 32x10	**(2)** Kg 32x20	**(3)** Kg 32x32
125	**(0)** Tr 40x7	**(1)** Tr 40x14	**(0)** Kg 40x10	**(1)** Kg 40x20	**(2)** Kg 40x40	

0 **Ballscrew pitch accuracy:**
(0) 0,05 mm / 300 mm (Standard) **(2)** 0,025 mm / 300 mm

0 **End play of ball nut:**
(0) 0,04 mm (Standard), **(1)** < 0,02 mm, **(2)** 2% apply prestress

Repeatability:
± 0,2 mm Trapezoidal
± 0,025 mm Ballscrew

1500 Basic length + stroke = total length

Pos.	1	2	3	4	5	6	7
EL	T	40	1	0	0	0	0	0	0	01500


For combination kits and connecting elements refer to chapter 2.2


Sample ordering code:
ELT40, trapezoidal right hand thread, standard body profile, top carriage, one shaft (locating bearing side), spindle 18x4, 1325 mm stroke


Positioning system ELT/ELK 30, 40, 60, 60S, 80, 80S, 100, 125

with trapezoidal thread or ballscrew, right-hand and left-hand thread or divided spindles

Dimensions (mm)







*For slide nuts refer to chapter 2.2 page 2

Increasing the carriage length will increase the basic length by the same amount.

Size ❒	Basic length L	A	B	C	D ± 0,05	E	F	G	H	J	K	MM for	NN for	OO for	P	Q	R	S Ø h6 x length	T	Basic weight	Weight per 100 mm
EL 30	202	70	56	42	40x1	13	35	-	-	26	47	-	M 6	M 6	18	82	-	5 x 15	4,2	1,1 kg	0,16 kg
EL 40	300	100	66	58	48x1	18	47	-	-	35	64	-	M 6	M 6	25	122	3x3x25	10 x 27	6,5	2,5 kg	0,37 kg
EL 60	410	144	96	82	62x1	30	69	-	-	49	90	-	M 8	M 8	35	168	5x5x28	14 x 35	8,5	8,1 kg	0,89 kg
EL 60S	460	170	108	82	62x1	30	69	-	-	53	94	-	M 8	M 8	35	194	5x5x28	14 x 35	8,5	10,1 kg	0,89 kg
EL 80	480	170	117	102	80x1	40	88	10	30	70	121	M 6	M10	M10	45	194	6x6x40	18 x 45	8,5	15,0 kg	1,48 kg
EL 80S	520	190	126	102	80x1	40	88	12,5	30	71	122	M 6	M10	M 8	45	214	6x6x40	18 x 45	8,5	17,0 kg	1,48 kg
EL 100	720	230	155	130	110x1	50	112	-	29	89	154	M10	M10	M10	55	300	6x6x40	22 x 45	10,5	32,0 kg	2,00 kg
EL 125	880	295	200	165	130x1	60	142	-	30	107,5	190	M10	M12	M12	65	365	8x7x50	25 x 55	13	48,0 kg	2,89 kg


T **Spindle:**
(T) Trapezoidal thread **(K)** Ballscrew

3 **Selection of screw:**
(3) right - left hand **(4)** divided spindle

0 **Choice of guide body profile:**
(0) Standard **(2)** corrosion-protected guide rods and screws
(4) expanded corrosion-protected version (depending on the availability of components)

0 **Choice of carriages:**

(0)



(1)



Size	Version 1	
	Q	L
30	94	226
40	138	332
60	184	442
60S	214	502
80	210	512
80S	234	560
100	316	752
125	389	928

0 **Drive version:**
(0) shaft right hand thread **(1)** shaft left hand thread **(2)** shaft on both sides

0 **Selection of screw:**

Size	Standard trapezoidal thread	Multistart screw trapezoidal thread	Standard ballscrew	Multistart screw ballscrew
30	**(0)** Tr 10x3		**(0)** Kg 8x2.5*	
40	**(0)** Tr 18x4	**(1)** Tr 18x8	**(0)** Kg 16x5	**(1)** Kg 16x10* **(1)** Kg 16x16*
60	**(0)** Tr 24x5	**(1)** Tr 24x10	**(0)** Kg 25x5	**(1)** Kg 20x20* **(2)** Kg 25x10*
80	**(0)** Tr 28x5	**(1)** Tr 28x10	**(0)** Kg 32x5	**(1)** Kg 25x25* **(2)** Kg 32x10*
100	**(0)** Tr 32x6	**(1)** Tr 32x12	**(0)** Kg 32x5	**(1)** Kg 32x10* **(2)** Kg 32x20* **(3)** Kg 32x32*
125	**(0)** Tr 40x7	**(1)** Tr 40x14	**(0)** Kg 40x10	**(1)** Kg 40x20* **(2)** Kg 40x40*

* = only for selection of devided spindle

0 **Ballscrew pitch accuracy:**
(0) 0,05 mm / 300 mm (Standard) **(2)** 0,025 mm / 300 mm

0 **End play of ball nut:**
(0) 0,04 mm (Standard), **(1)** < 0,02 mm, **(2)** 2% apply prestress

Repeatability:
± 0,2 mm Trapezoidal
± 0,025 mm Ballscrew

2200 Basic length + stroke = total length

Pos.	1	2	3	4	5	6	7
EL	**T**	**40**	**3**	**0**	**0**	**0**	**0**	**0**	**0**	**02200**

For combination kits and connecting elements refer to chapter 2.2

Sample ordering code:
ELT40, trapezoidal right - left hand thread, standard body profile, 2 top carriage, shaft on right hand side, spindle 18x4, 1900 mm stroke




Non driven positioning systems
E / EL / UL

Positioning system ELR 30, 40, 60, 60S, 80, 80S, 100, 125

Roller guide unit without drive **Specifications**



Function:
This unit consists of an aluminium hollow section with integral, parallel ground and hardened steel guide rods. The carriage has play-adjustable ball bearing rollers which engage with the guide rods. Two bearing blocks without bearings are fitted. Actuation can be by pneumatic cylinder or other device, or the unit may be used as load-carrying linear slide.



Forces and torques


Fitting position: As required, max. length 6.000 mm
Carriage connection: By T-slots and tapped holes
Unit mounting: By T-slots and tapped holes in the mounting surface, mounting sets.

Size	ELR 30		ELR 40		ELR 60		ELR 60 S		ELR 80		ELR 80S		ELR 100		ELR 125	
Forces/Torques	static	dynam.	static	dynam.	static	dynam.	static	dynam.	static	dynam.	static	dynam.	static	dynam.	static	dynam.
F_x (N)	-	-	-	-	-	-			-	-	-	-	-	-	-	-
F_y (N)	90	60	1200	700	3000	2000	4100	3100	3000	2000	4600	3600	8000	6500	12000	9000
F_z (N)	90	60	900	650	1700	1100	2160	1600	1700	1100	3000	1800	3600	2200	6000	4500
M_x (Nm)	10	5	25	20	67	43	88	65	90	55	170	140	300	230	600	450
M_y (Nm)	13	6	32	18	90	70	190	140	110	80	270	230	400	270	750	600
M_z (Nm)	14	7	35	25	120	100	230	170	150	120	300	220	750	500	1350	1150
All forces and torques relate to the following: existing values / table values $\frac{Fy}{Fy_{dyn}} + \frac{Fz}{Fz_{dyn}} + \frac{Mx}{Mx_{dyn}} + \frac{My}{My_{dyn}} + \frac{Mz}{Mz_{dyn}} \leq 1$																
No-load torque																
max. (m/s)	3		4		5		5		6		8		10		10	
Geometrical moments of inertia of aluminium profile																
I_x mm⁴	4,09x10⁴		1,32x10⁵		6,79x10⁵		6,79x10⁵		18,99x10⁵		18,99x10⁵		44,4x10⁵		10,2x10⁶	
I_y mm⁴	4,00x10⁴		1,34x10⁵		6,97x10⁵		6,97x10⁵		18,97x10⁵		18,97x10⁵		44,8x10⁵		10,2x10⁶	
E-Modulus N/mm²	70000		70000		70000		70000		70000		7000		70000		70000	

For life-time calculation of rollers use our homepage.

Deflection:


$$f = \frac{F * L^3}{E * I * 192}$$





f = deflection (mm)
F = load (N)
L = free length (mm)
E = elastic modulus 70000 (N/mm²)
I = second moment of area (mm⁴)

Positioning system ELR 30, 40, 60, 60S, 80, 80S, 100, 125

Dimensions (mm)







*For slide nuts refer to chapter 2.2 page 2

Increasing the carriage length will increase the basic length by the same amount.

Size ❒	Basic length L	A	B	C	D ± 0,05	E	F	G	H	J	K	MM for	NN for	OO for	P	Q	T	Basic weight	Weight per 100 mm
ELR 30	120	70	56	42	40x1	13	35	-	-	26	47	-	M 6	M 6	18	82	4,2	0,5 kg	0,12 kg
ELR 40	175	100	66	58	48x1	18	47	-	-	35	64	-	M 6	M 6	25	122	6,5	0,9 kg	0,23 kg
ELR 60	245	144	96	82	62x1	30	69	-	-	49	90	-	M 8	M 8	35	168	8,5	3,1 kg	0,61 kg
ELR 60S	265	170	108	82	62x1	30	69	-	-	53	94	-	M 8	M 8	35	194	8,5	4,1 kg	0,61 kg
ELR 80	285	170	117	102	80x1	40	88	10	30	70	121	M 6	M 10	M 10	45	194	8,5	5,3 kg	0,90 kg
ELR 80S	305	190	126	102	80x1	40	88	12,5	30	71	122	M 6	M 10	M 8	45	214	8,5	6,3 kg	0,90 kg
ELR 100	410	230	155	130	110x1	50	112	-	29	89	154	M 10	M 10	M 10	55	300	10,5	15,1 kg	1,50 kg
ELR 125	510	295	200	165	130x1	60	142	-	30	107,5	190	M 10	M 12	M 12	65	365	13	26,8 kg	2,05 kg

0 **Choice of guide body profile:**
(0) Standard **(2)** corrosion-protected guide rods and screws
(4) expanded corrosion-protected version (depending on the availability of components)

0 **Choice of carriages:**

(0)



(1)



Size	Version 1	
	Q	L
30	94	132
40	138	191
60	184	261
60S	214	284
80	210	301
80S	234	325
100	316	426
125	389	534

1500 Basic length + stroke = total length

ELR	40	0	0	0	0	0	0	0	01500
Pos.	1	2	3	4	5	6	7		


For combination kits and connecting elements refer to chapter 2.2


Sample ordering code:
ELR 40, non driven system, standard body profile, standard carriage, 1325 mm stroke


Positioning system ELRZ 30, 40, 60, 60S, 80, 80S, 100, 125


Roller guide unit without drive

Dimensions (mm)









*For slide nuts refer to chapter 2.2 page 2


Increasing the carriage length will increase the basic length by the same amount.

Size ❒	Basic length L	A	B	C	D -0,05	E	F	G	H	J	K	MM for	N	OO for	P	Q	T	U	V	W	X	Y	Basic weight	Weight per 100 mm
ELRZ 30	158	70	56	42	28	13	25	-	-	44	47	-	M 6	M 6	36	82	M 4	10	16	21	16	16	0,6 kg	0,13 kg
ELRZ 40	225	100	66	58	37	18	32	-	-	58	64	-	M 6	M 6	49	122	M 5	12,5	24	29	20,5	20,5	1,2 kg	0,23 kg
ELRZ 60	290	144	96	80	47	30	42	-	-	82	90	-	M 8	M 8	59	168	M 6	15	30	41	27	26	3,4 kg	0,61 kg
ELRZ 60S	315	170	108	80	47	30	42	-	-	82	94	-	M 8	M 8	59	194	M 6	15	30	41	27	26	4,4 kg	0,61 kg
ELRZ 80	375	170	117	100	68	40	60	10	30	110	121	M 6	M 10	M 10	90	194	M 8	22,5	45	51	39	38	6,7 kg	0,90 kg
ELRZ 80S	395	190	126	100	68	40	60	12,5	30	110	122	M 6	M 10	M 8	90	214	M 8	22,5	45	51	39	38	7,7 kg	0,90 kg
ELRZ 100	530	230	155	130	90	50	80	-	29	135	154	M 10	M 12	M 10	110	300	M 10	23	64	65	50	50	17,5 kg	1,50 kg
ELRZ 125	625	295	200	160	110	60	100	-	30	167	191	M 10	M 12	M 12	130	365	M 12	38	50	82	60	60	28,3 kg	2,05 kg

0 **Choice of guide body profile:**
(0) Standard **(2)** corrosion-protected guide rods and screws
(4) expanded corrosion-protected version (depending on the availability of components)

0 **Choice of carriages:**

(0)



(1)



Size	Version 1	
	Q	L
30	94	170
40	138	241
60	184	306
60S	214	335
80	210	391
80S	234	415
100	316	546
125	389	649

Application:
This unit can be used as a load-carrying linear slide, or it may be fitted with a suitable pneumatic drive.

ELRZ	40	0	0	0	0	0	0	0	01500
Pos.	1	2	3	4	5	6	7		

1500 Basic length + stroke = total length


For combination kits and connecting elements refer to chapter 2.2


Sample ordering code:
ELRZ 40, Non driven system, standard body profile, standard carriage, 1275 mm stroke

Positioning system ER 30, 40, 60, 60S, 80, 80S, 100, 125


Roller guide unit without drive

Dimensions (mm)





Guiding rods have to be fixed by an additional device, bracket or plate.



*For slide nuts refer to chapter 2.2 page 2


Increasing the carriage length will increase the basic length by the same amount.

Size ❒	Basic length L	A	B	F	G	H	J	K	MM for	OO for	Q	T	Basic weight	Weight per 100 mm
ER 30	86	70	56	23	-	-	M 6	41	-	M 6	82	M 4	0,5 kg	0,12 kg
ER 40	126	100	66	29	-	-	M 6 - M10	55	-	M 6	122	M 5	0,7 kg	0,23 kg
ER 60	172	144	96	48	–	-	M 6 - M10	79	-	M 8	168	M 6	2,4 kg	0,61 kg
ER 60S	198	170	108	48	–	-	M 6 - M10	83	-	M 8	194	M 6	3,4 kg	0,61 kg
ER 80	198	170	117	64	10	30	M 6 - M10	110	M 6	M 10	194	M 8	3,7 kg	0,90 kg
ER 80S	218	190	126	64	12,5	30	M 6 - M10	111	M 6	M 8	214	M 8	4,7 kg	0,90 kg
ER 100	304	230	155	80	-	29	M 10	139	M 10	M 10	300	M 10	10,8 kg	1,50 kg
ER 125	369	295	200	100	-	30	M 12	170	M 10	M 12	365	M 12	20,3 kg	2,05 kg

0 **Choice of guide body profile:**
(0) Standard **(2)** corrosion-protected guide rods and screws
(4) expanded corrosion-protected version (depending on the availability of components)

0 **Choice of carriages:**

(0)



(1)



Size	Version 1	
	Q	L
30	94	98
40	138	142
60	184	188
60S	214	218
80	210	214
80S	234	238
100	316	320
125	389	393

Application:
This unit can be used as a load-carrying linear slide, or it may be fitted with a suitable pneumatic drive.

1500 Basic length + stroke = total length


ER	40	0	0	0	0	0	0	0	01500
Pos.	1	2	3	4	5	6	7		

For combination kits and connecting elements refer to chapter 2.2

Sample ordering code:
ER 40, Non driven system, standard body profile, standard carriage, 1374 mm stroke

Positioning system E 40, 60, 60S, 80, 80S


Roller guide unit without drive **Specifications**



Function:
Very low building system achieved by an aluminium guide body with integrated, hardened steel guide rods. The carriage, which has internal linear ball bearings that can be adjusted free of play, moves along the body.

Fitting position: As required, max. length 6.000 mm.
Carriage connection: By T-slots.
Unit mounting: By tapped holes in the mounting surface, bottom surface with T-slots.

Forces and torques




Size	E 40		E 60		E 60 S		E 80		E 80S	
Forces/Torques	static	dynamic	static	dynamic	static	dynamic	static	dynamic	static	dynamic
F_x (N)	-	-	-	-	-	-	-	-	-	-
F_y (N)	1200	700	3000	2000	4100	3100	3000	2000	4600	3600
F_z (N)	900	650	1700	1100	2160	1600	1700	1100	3000	1800
M_x (Nm)	25	20	67	43	88	65	90	55	170	140
M_y (Nm)	32	18	90	70	190	140	110	80	270	230
M_z (Nm)	35	25	120	100	230	170	150	120	300	220
All forces and torques relate to the following: existing values / table values $\frac{Fy}{Fy_{dyn}} + \frac{Fz}{Fz_{dyn}} + \frac{Mx}{Mx_{dyn}} + \frac{My}{My_{dyn}} + \frac{Mz}{Mz_{dyn}} \leq 1$										
Speed										
max. (m/s)	4		5		5		6		8	
Geometrical moments of inertia of aluminium profile										
I_x mm^4	0,157x10^5		1,71x10^5		1,71x10^5		2,8x10^5		2,8x10^5	
I_y mm^4	0,654x10^5		6,1x10^5		6,1x10^5		10,59x10^5		10,59x10^5	
E-Modulus N/mm^2	70000		70000		70000		70000		70000	

For life-time calculation of rollers use our homepage.

Deflection:


$$f = \frac{F * L^3}{E * I * 192}$$




f = deflection (mm)
F = load (N)
L = free length (mm)
E = elastic modulus 70000 (N/mm^2)
I = second moment of area (mm^4)

Positioning system E 40, 60, 60S, 80, 80S

Dimensions (mm)




Size 80



Size 40, 60





*For slide nuts refer to chapter 2.2 page 2

Increasing the carriage length will increase the basic length by the same amount.

Size	Basic length L	A	B	C	D	E	F	G	H	K	MM for	OO for	P	Q	R	Basic weight	Weight per 100 mm
E 40	136	100	66	34,5	10	40	7	12,5	22	37	-	M 6	6	122	-	1,0 kg	0,13 kg
E 60	186	144	96	48	10	60	7	12,5	30	49	-	M 8	8	168	-	2,2 kg	0,20 kg
E 60S	212	170	108	52	10	60	7	12,5	30	53	-	M 8	8	194	-	3,2 kg	0,20 kg
E 80	215	170	117	66,5	10	80	7	12,5	40	70	M 6	M 10	10	194	40	3,4 kg	0,48 kg
E 80S	245	190	126	67,5	10	80	7	12,5	40	71	M 6	M 8	10	214	40	4,4 kg	0,48 kg

0 **Choice of guide body profile:**
(0) Standard **(2)** corrosion-protected guide rods and screws
(4) expanded corrosion-protected version (depending on the availability of components)

1500 Basic length + stroke = total length

E	40	0	0	0	0	0	0	0	01500
Pos.	1	2	3	4	5	6	7		


For combination kits and connecting elements refer to chapter 2.2

Sample ordering code:
E 40, non driven system, standard body profile, 1364 mm stroke

Positioning system UL 40, 60, 80

Roller guide unit without drive


Specifications



Function:
Very low building roller system achieved by an aluminium guide body with integrated, hardened steel guide rods. The carriage, which has internal linear ball bearings that can be adjusted free of play, moves along the body.

Fitting position: As required, max. length 6.000 mm.
Carriage connection: By tapped holes
Unit mounting: Afterwards by holes or tapped holes

Forces and torques




Size	UL 40		UL 60		UL 80	
Forces/Torques	static	dynamic	static	dynamic	static	dynamic
F_x (N)	-	-	-	-	-	-
F_y (N)	1200	700	3000	2000	3000	2000
F_z (N)	900	650	1700	1100	1700	1100
M_x (Nm)	25	20	67	43	90	55
M_y (Nm)	32	18	90	70	110	80
M_z (Nm)	35	25	120	100	150	120
All forces and torques relate to the following:						
existing values / table values	$\frac{Fy}{Fy_{dyn}} + \frac{Fz}{Fz_{dyn}} + \frac{Mx}{Mx_{dyn}} + \frac{My}{My_{dyn}} + \frac{Mz}{Mz_{dyn}} \leq 1$					
Speed						
max. (m/s)	4		5		6	
Geometrical moments of inertia of aluminium profile						
I_x mm^4	0,157x10^5		1,71x10^5		2,8x10^5	
I_y mm^4	0,654x10^5		6,1x10^5		10,59x10^5	
E-Modulus N/mm^2	70000		70000		70000	

For life-time calculation of rollers use our homepage.

Deflection:


$$f = \frac{F * L^3}{E * I * 192}$$




f = deflection (mm)
F = load (N)
L = free length (mm)
E = elastic modulus 70000 (N/mm^2)
I = second moment of area (mm^4)

Positioning system UL 40, 60, 80

Dimensions (mm)





Size	Basic length L	A	B	C	E	H	OO for	P	Q	R	Basic weight	Weight per 100 mm
UL 40	160	40/20	31/13	33	40	22	M 5/M 5x8	6	146*	120	1,2 kg	0,13 kg
UL 60	215	60/29	48/20	43	60	30	M 6/M 6x10	8	194*	180	2,1 kg	0,20 kg
UL 80	285	80/42	66/28	58,5	80	40	M 8/M 8x12	10	260*	245	4,2 kg	0,48 kg

* = the carriage is not available in different lengths

0 **Choice of guide body profile:**
(0) Standard **(2)** corrosion-protected guide rods and screws
(4) expanded corrosion-protected version (depending on the availability of components)

0 **Choice of carriage:**

(0) Standard



(1) harrow carriage




1500 Basic length + stroke = total length

UL	40	0	0	0	0	0	0	0	01500
	Pos.	1	2	3	4	5	6	7	


For combination kits and connecting elements refer to chapter 2.2

Sample ordering code:
UL 40, non driven system, standard body profile, standard carriage (wide version), 1340 mm stroke

Possible mounting styles








EL - Belt driven positioning systems

Positioning system ELZ 30, 40, 60, 60S, 80, 80S, 100, 125

Belt drive **Specifications**



Function:
This linear unit consists of an aluminium square profile with integrated, hardened steel guide rods. The carriage, which has internal linear ball bearings that can be adjusted free of play, is driven along the guide rods by a timing belt. The pulleys have maintenance-free ball bearings. Belt tension can be readjusted by a simple screw adjustment device in the carriage. This device can also be used for symmetrical adjustment of two or more linear units running parallel.



Forces and torques

Fitting position: As required. Max. length 6.000 mm without joints.
Carriage mounting: By T-slots.
Unit mounting: By T-slots or tapped holes in the bearing block, mounting sets.
Belt type: HTD with steel reinforcement, no backlash when changing direction, repeatability: ± 0,1 mm.

Size	ELZ 30		ELZ 40		ELZ 60		ELZ 60 S		ELZ 80		ELZ 80 S		ELZ 100		ELZ 125	
Forces/Torques	static	dynamic	static	dynamic	static	dynamic	static	dynamic	static	dynamic	static	dynamic	static	dynamic	static	dynamic
F_x (N)	200	180	390	350	894	800	894	800	1900	1800	1900	1800	4000	3800	5900	5750
F_y (N)	90	60	1200	700	3000	2000	4100	3100	3000	2000	4600	3600	8000	6500	12000	9000
F_z (N)	90	60	900	650	1700	1100	2160	1600	1700	1100	3000	1800	3600	2200	6000	4500
M_x (Nm)	10	5	25	20	67	43	88	65	90	55	170	140	300	230	600	450
M_y (Nm)	13	6	32	18	90	70	190	140	110	80	270	230	400	270	750	600
M_z (Nm)	14	7	35	25	120	100	230	170	150	120	300	220	750	500	1350	1150
All forces and torques relate to the following: existing values / table values $\frac{Fy}{Fy_{dyn}} + \frac{Fz}{Fz_{dyn}} + \frac{Mx}{Mx_{dyn}} + \frac{My}{My_{dyn}} + \frac{Mz}{Mz_{dyn}} \leq 1$																
No-load torque																
Nm	0,2		0,3		0,6		0,7		0,9		1,2		1,4		1,8	
Speed																
(m/s) max	2		4		5		7		6		8		10		10	
Tensile force																
permanent (N)	200		390		900		900		1900		1900		4000		5900	
0,2 s (N)	280		480		1000		1000		2090		2090		4300		6350	
Geometrical moments of inertia of aluminium profile																
I_x mm^4	4,09x10^4		1,32x10^5		6,79x10^5		6,79x10^5		18,99x10^5		18,99x10^5		44,4x10^5		101,5x10^5	
I_y mm^4	4,00x10^4		1,34x10^5		6,97x10^5		6,97x10^5		18,97x10^5		18,97x10^5		44,8x10^5		101,5x10^5	
E-Modulus N/mm^2	70000		70000		70000		70000		70000		70000		70000		70000	

For life-time calculation of rollers use our homepage.

Driving torque:


$$M_a = \frac{F * P * S_i}{2000 * \pi} + M_n$$

$$P_a = \frac{M_a * n}{9550}$$

F = force (N)
P = pulley action perimeter (mm)
Si = safety factor 1,2 ... 2
M_n = no-load torque (Nm)
n = rpm pulley (min^{-1})
M_a = driving torque (Nm)
P_a = motor power (KW)

Deflection:


$$f = \frac{F * L^3}{E * I * 192}$$



f = deflection (mm)
F = load (N)
L = free length (mm)
E = elastic modulus 70000 (N/mm^2)
I = second moment of area (mm^4)

Positioning system ELZ 30, 40, 60, 60S, 80, 80S, 100, 125

Dimensions (mm)



*For slide nuts refer to chapter 2.2 page 2

Increasing the carriage length will increase the basic length by the same amount.


Size ❒	Basic length L	A	B	C	D -0,05	E	F	G	H	J	K	MM for	N	OO for	P	Q	T	U	V	W	X	Y	Basic weight	Weight per 100 mm
ELZ 30	158	70	56	42	28	13	25	-	-	44	47	-	M 5	M 6	36	82	M 4	10	16	21	16	16	0,8 kg	0,13 kg
ELZ 40	225	100	66	58	37	18	32	-	-	58	64	-	M 6	M 6	49	122	M 5	12,5	24	29	20,5	20,5	1,9 kg	0,24 kg
ELZ 60	290	144	96	80	47	30	42	-	-	82	90	-	M 8	M 8	59	168	M 6	15	30	41	27	26	4,8 kg	0,62 kg
ELZ 60 S	315	170	108	80	47	30	42	-	-	82	94	-	M 8	M 8	59	194	M 6	15	30	41	27	26	5,8 kg	0,62 kg
ELZ 80	375	170	117	100	68	40	60	10	30	110	121	M 6	M 10	M 10	90	194	M 8	22,5	45	51	39	38	10,0 kg	1,00 kg
ELZ 80 S	395	190	126	100	68	40	60	12,5	30	110	122	M 6	M 10	M 8	90	214	M 8	22,5	45	51	39	38	11,0 kg	1,00 kg
ELZ 100	530	230	155	130	90	50	80	-	29	135	154	M 10	M 12	M 10	110	300	M 10	23	64	65	50	50	24,0 kg	1,60 kg
ELZ 125	625	295	200	160	110	60	100	-	30	167	191	M 10	M 12	M 12	130	365	M 10	38	50	82	60	60	37,0 kg	2,10 kg

0 **Choice of guide body profile:**
(0) Standard **(2)** corrosion-protected guide rods and screws
(4) expanded corrosion-protected version (depending on the availability of components)

Size	Version1	
	Q	L
30	94	170
40	138	241
60	184	306
60S	214	335
80	210	391
80S	234	415
100	316	546
125	389	649

0 **Choice of carriages:**

(0)



(1)




0 **Drive version:**

0



0 1 2 3 4 5 6 7 8 9



Version 9 is the same as 0, but with double sided coupling claw.

The standard version is supplied without shaft. A shaft can be retrofitted by inserting it into the pulley bore and securing it with 2 locking rings or tension sets (size 100 and 125).

Belt table

Code No.		Size	Belt	mm/rev.	Number of teeth
0	**1**	**30**	3M12	75	25
0	**3**	**40**	5M15	100	20
0	**4**	**60 (S)**	5M25	130	26
0	**7**	**80 (S)**	8M30	192	24
0	**9**	**100**	8M50	256	32
1	**0**	**125**	8M70	304	38

Shaft dimensions / Coupling claw

Size	Shaft ø h6 x length	Key	Coupling
30	6 x 15	2x2x12	7
40	10 x 27	3x3x22	9
60 (S)	14 x 35	5x5x28	14
80 (S)	18 x 45	6x6x40	19
100	22 x 45	6x6x40	24
125	30 x 55	8x7x50	28

Basic length + stroke = total length


ELZ	40	1	0	0	0	0	3	1	01500
	Pos.	1	2	3	4	5	6	7	

For combination kits and connecting elements refer to chapter 2.2

Sample ordering code:
ELZ 40 with standard body profile, standard carriage, coupling claw on one side, 1275 mm stroke.

Positioning system ELZ 40, 60, 60S, 80, 80S, 100, 125

Belt drive



Specifications


ATEX 2014/34/EU
II 2G Ex h IIB T4 Gb
II 3D Ex h IIIB T125 °C Dc

3.1

Function:
Like ELZ. The positioning system is suitable for use according to the intended purpose in potentially explosive areas (see ATEX 2014/34/EU marking). An operating manual is included in the scope of delivery. The system is certified for the following areas:

ATEX 2014/34/EU II 2G EX h IIB T4 Gb:
All application areas except for underground mining. Gas atmosphere category 2, explosion protection category: protection due to secure construction (design security). Equipment group IIB. Temperature class T4=135°C, EPL Gb.

ATEX 2014/34/EU II 3D EX h IIIB T125 °C Dc:
All application areas except for underground mining. Dust atmosphere category 3. Maximum permissible surface temperature: 125°C, EPL Dc.



Forces and torques

Fitting position: As required, max. length 6.000 mm.
Carriage mounting: T-slots
Unit mounting: By T-slots or tapped holes in the bearing block, mounting sets.
Belt type: HTD with steel reinforcement, no backlash when changing direction, repeatability: ± 0,1 mm.

Size	ELZex 40		ELZex 60		ELZex 60 S		ELZex 80		ELZex 80 S		ELZex 100		ELZex 125	
Forces/Torques	static	dynamic	static	dynamic	statisch	dynamic	static	dynamic	static	dynamic	static	dynamic	static	dynamic
F_x (N)	178	142	312	250	312	250	1083	866	1083	866	1127	902	2067	1654
F_y (N)	517	414	1330	1064	1910	1528	1584	1267	2219	1775	3100	2480	4980	3984
F_z (N)	355	284	742	594	935	748	613	490	1052	842	1292	1034	2190	1752
M_x (Nm)	12	10	36	29	52	41	36	29	67	54	101	81	220	176
M_y (Nm)	13	11	39	32	66	53	39	32	87	70	136	109	280	224
M_z (Nm)	19	15	70	56	137	110	100	81	182	146	326	260	636	509
All forces and torques relate to the following existing values / table values	$\frac{Fy}{Fy_{dyn}} + \frac{Fz}{Fz_{dyn}} + \frac{Mx}{Mx_{dyn}} + \frac{My}{My_{dyn}} + \frac{Mz}{Mz_{dyn}} \leq 1$													
No-load torque														
Nm	0,3		0,6		0,7		0,9		1,2		1,4		1,8	
Speed														
(m/s) max	1		1		1		1		1		1		1	
Tensile force														
permanent (N)	178		312		312		1083		1083		1127		2067	
Geometrical moments of inertia of aluminium profile														
I_x mm⁴	$1{,}32 \times 10^5$		$6{,}79 \times 10^5$		$6{,}79 \times 10^5$		$18{,}99 \times 10^5$		$18{,}99 \times 10^5$		$44{,}4 \times 10^5$		$101{,}5 \times 10^5$	
I_y mm⁴	$1{,}34 \times 10^5$		$6{,}97 \times 10^5$		$6{,}97 \times 10^5$		$18{,}97 \times 10^5$		$18{,}97 \times 10^5$		$44{,}8 \times 10^5$		$101{,}5 \times 10^5$	
E-Modulus N/mm²	70000		70000		70000		70000		70000		70000		70000	

For life-time calculation of rollers use our homepage.

Driving torque:


$$M_a = \frac{F * P * S_i}{2000 * \pi} + M_n$$

$$P_a = \frac{M_a * n}{9550}$$

F = force (N)
P = pulley action perimeter (mm)
Si = safety factor 1,2 ... 2
M_n = no-load torque (Nm)
n = rpm pulley (min^{-1})
M_a = driving torque (Nm)
P_a = motor power (KW)

Deflection:

$$f = \frac{F * L^3}{E * I * 192}$$





f = deflection (mm)
F = load (N)
L = free length (mm)
E = elastic modulus 70000 (N/mm^2)
I = second moment of area (mm^4)


Positioning system ELZ 40, 60, 60S, 80, 80S, 100, 125

Dimensions (mm)

ATEX 2014/34/EU
II 2G Ex h IIB T4 Gb
II 3D Ex h IIIB T125 °C Dc







*For slide nuts refer to chapter 2.2 page 2

Increasing the carriage length will increase the basic length by the same amount.


Size ❐	Basic length L	A	B	C	D -0,05	E	F	G	H	J	K	MM for	N	OO for	P	Q	T	U	V	W	X	Y	Basic weight	Weight per 100 mm
ELZex 40	225	100	66	58	37	18	32	-	-	58	64	-	M 6	M 6	49	122	M 5	12,5	24	29	20,5	20,5	1,9 kg	0,24 kg
ELZex 60	290	144	96	80	47	30	42	-	-	82	90	-	M 8	M 8	59	168	M 6	15	30	41	27	26	4,8 kg	0,62 kg
ELZex 60 S	315	170	108	80	47	30	42	-	-	82	94	-	M 8	M 8	59	194	M 6	15	30	41	27	26	5,8 kg	0,62 kg
ELZex 80	375	170	117	100	68	40	60	10	30	110	121	M 6	M 10	M 10	90	194	M 8	22,5	45	51	39	38	10,0 kg	1,00 kg
ELZex 80 S	395	190	126	100	68	40	60	12,5	30	110	122	M 6	M 10	M 8	90	214	M 8	22,5	45	51	39	38	11,0 kg	1,00 kg
ELZex 100	530	230	155	130	90	50	80	-	29	135	154	M 10	M 12	M 10	110	300	M 10	23	64	65	50	50	24,0 kg	1,60 kg
ELZex 125	625	295	200	160	110	60	100	-	30	167	191	M 10	M 12	M 12	130	365	M 10	38	50	82	60	60	37,0 kg	2,10 kg

0 **Choice of guide body profile:**
(0) Standard **(2)** corrosion-protected guide rods and screws

Size	Version 1	
	Q	L
40	138	241
60	184	306
60S	214	335
80	210	391
80S	234	415
100	316	546
125	389	649

0 **Choice of carriages:**

(0)




(1)



0 **Drive version:**





Version 9 is the same as 0, but with double sided coupling claw.

The standard version is supplied without shaft. A shaft can be retrofitted by inserting it into the pulley bore and securing it with 2 locking rings or tension sets (size 100 and 125).

Belt table

Code No.		Size	Belt	mm/rev.	Number of teeth
0	**3**	**40**	5M15	100	20
0	**4**	**60 (S)**	5M25	130	26
0	**7**	**80 (S)**	8M30	192	24
0	**9**	**100**	8M50	256	32
1	**0**	**125**	8M70	304	38

Shaft dimensions / Coupling claw

Size	Shaft ø h6 x length	Key	Coupling
40	10 x 27	3x3x22	9
60 (S)	14 x 35	5x5x28	14
80 (S)	18 x 45	6x6x40	19
100	22 x 45	6x6x40	24
125	30 x 55	8x7x50	28

Basic length + stroke = total length

ELZex	40	1	0	0	0	0	3	1	01500
Pos.		1	2	3	4	5	6	7	


For combination kits and connecting elements refer to chapter 2.2


Sample ordering code:
ELZex 40, standard body profile, standard carriage, coupling claw on one side, 1275 mm stroke.


Positioning system ELZ 30, 40, 60, 60S, 80, 80S, 100, 125


Belt drive with two carriages moving in opposite directions

Dimensions (mm)









*For slide nuts refer to chapter 2.2 page 2

Increasing the carriage length will increase the basic length by the same amount.

Size ❒	Basic length L	A	B	C	D - 0,05	F	G	H	J	K	MM for	OO for	P	Q	T	X	Y	Basic weight	Weight per 100 mm
ELZ 30	250	70	56	42	28	25	-	-	5	52	-	M 6	36	82	M 4	16	16	1,2 kg	0,13 kg
ELZ 40	350	100	66	58	37	32	-	-	6	70	-	M 6	49	122	M 5	20,5	20,5	2,8 kg	0,24 kg
ELZ 60	460	144	96	80	47	42	-	-	8	98	-	M 8	59	168	M 6	27	26	7,4 kg	0,62 kg
ELZ 60S	510	170	108	80	47	42	-	-	12	106	-	M 8	59	194	M 6	27	26	7,4 kg	0,62 kg
ELZ 80	570	170	117	100	68	60	10	30	19	140	M 6	M10	90	194	M 8	39	39	15,0 kg	1,00 kg
ELZ 80S	610	190	126	100	68	60	12,5	30	21	142	M 6	M 8	90	214	M 8	39	39	17,0 kg	1,00 kg
ELZ 100	830	230	155	130	90	80	-	29	24	178	M10	M10	110	300	M10	50	50	34,0 kg	1,60 kg
ELZ 125	990	295	200	160	110	100	-	30	25,5	216	M10	M12	130	365	M10	60	60	53,5 kg	2,10 kg

0 **Choice of guide body profile:**
(0) Standard **(2)** corrosion-protected guide rods and screws
(4) expanded corrosion-protected version (depending on the availability of components)

Size	Version 1	
	Q	L
30	94	274
40	138	382
60	184	492
60S	214	554
80	210	602
80S	234	650
100	316	862
125	389	1038

0 **Choice of carriages:**

(0)




(1)



0 **Coupling - shaft mounting:**





Version 8 is the same as 0, but with double sided coupling claw.

The standard version is supplied without shaft. A shaft can be retrofitted by inserting it into the pulley bore and securing it with 2 locking rings or tension sets (size 100 and 125).

Belt table

Code No.		Size	Belt	mm/rev.	Number of teeth
0	**1**	**30**	3M12	75	25
0	**3**	**40**	5M15	100	20
0	**4**	**60 (S)**	5M25	130	26
0	**7**	**80 (S)**	8M30	192	24
0	**9**	**100**	8M50	256	32
1	**0**	**125**	8M70	304	38

Shaft dimensions / Coupling claw

Size	Shaft ø h6 x length	Key	Coupling
30	6 x 15	2x2x12	7
40	10 x 27	3x3x22	9
60 (S)	14 x 35	5x5x28	14
80 (S)	18 x 45	6x6x40	19
100	22 x 45	6x6x40	24
125	30 x 55	8x7x50	28

Basic length + stroke = total length

ELZ	40	3	0	0	0	0	3	1	01500
Pos.	1	2	3	4	5	6	7		


For combination kits and connecting elements refer to chapter 2.2


Sample ordering code:
ELZ 40, right/left hand with standard body profile, standard carriage, coupling claw on one side, 1150 mm stroke.


Positioning system ELZG 30, 40, 60, 60S, 80, 80S

Belt drive

Dimensions (mm)







*For slide nuts refer to chapter 2.2 page 2

Increasing the carriage length will increase the basic length by the same amount.

Size ❒	Basic length L	A	B	C	D - 0,05	F	G	H	K	MM for	OO for	P	Q	T	X	Y	Basic weight	Weight per 100 mm
ELZG 30	195	70	56	48	47	42	-	-	52	-	M 6	55	82	M 6	52	27	1,1 kg	0,13 kg
ELZG 40	265	100	66	60	55	55	-	-	70	-	M 6	70	122	M 6	70	33	4,0 kg	0,29 kg
ELZG 60	365	144	96	88	80	70	-	-	98	-	M 8	95	168	M 8	98	46	10,3 kg	0,65 kg
ELZG 60S	390	170	108	88	80	70	-	-	106	-	M 8	95	194	M 8	98	46	12,3 kg	0,65 kg
ELZG 80	460	170	117	118	110	100	10	30	140	M 6	M 10	130	194	M 10	140	60	20,5 kg	1,15 kg
ELZG 80S	480	190	126	118	110	100	12,5	30	142	M 6	M 8	130	214	M 10	140	60	21,5 kg	1,15 kg

0 **Choice of guide body profile:**
(0) Standard **(2)** corrosion-protected guide rods and screws
(4) expanded corrosion-protected version (depending on the availability of components)

0 **Choice of carriages:**

(0)




For standard carriage length see 'Q' in table. The carriages can be delivered in any non-standard length upon request; the longer the carriage, the higher the load capacity.

0 **Drive version:**

0





Version 9 is the same as 0, but with double sided coupling claw.

The standard version is supplied without shaft. A shaft can be retrofitted by inserting it into the pulley bore and securing it with 2 locking rings or tension sets (size 80).

Belt table

Code No.		Size	Belt	mm/rev.	Number of teeth
0	**1**	**30**	3M12	120	40
0	**3**	**40**	5M15	160	32
0	**4**	**60 (S)**	5M25	220	44
0	**7**	**80 (S)**	8M30	320	40

Shaft dimensions / Coupling claw

Size	Shaft Ø h6 x length	Key	Coupling
30	10 x 27	3x3x25	7
40	14 x 35	5x5x28	14
60 (S)	18 x 45	6x6x40	19
80 (S)	22 x 45	6x6x40	24

Basic length + stroke = total length


ELZG	40	1	0	0	0	0	3	1	01500
	Pos.	1	2	3	4	5	6	7	

For combination kits and connecting elements refer to chapter 2.2

Sample ordering code:
ELZG 40, standard body profile, standard carriage and coupling claw on one side, 1235 mm stroke.

Positioning system ELZ 60 (S) W


Belt drive



Function:
The guide body consists of an aluminium square profile with lateral, parallel, form-fit, internal hardened steel rods. The guide carriage, which is driven along the shafts by a timing belt, moves on the guide body with internal linear ball bearings that are adjustable free of play. Due to the rectangular profile high torques and loads can be taken up. In addition, a very high stability and low deflection are ensured for long axis systems. The belt tension can be easily readjusted via a tensioning device within the carriage. This device also helps to adjust the symmetry of the carriages in applications where two parallel linear units are used.

Fitting position: As required. Max. length 6.000 mm without joints.
Carriage mounting: By T-slots.
Unit mounting: By T-slots or tapped holes in the bearing block, mounting sets.
Belt type: HTD with steel reinforcement, no backlash when changing direction, repeatability: ± 0,1 mm.

Forces and torques



Size	60		60 S	
Forces/Torques	static	dynamic	static	dynamic
F_x (N)	894	800	894	800
F_y (N)	3000	2000	4100	3100
F_z (N)	1700	1100	2160	1600
M_x (Nm)	67	43	88	65
M_y (Nm)	90	70	190	140
M_z (Nm)	120	100	230	170
All forces and torques relate to the following: existing values / table values $\frac{Fy}{Fy_{dyn}} + \frac{Fz}{Fz_{dyn}} + \frac{Mx}{Mx_{dyn}} + \frac{My}{My_{dyn}} + \frac{Mz}{Mz_{dyn}} \leq 1$				
No-load torque				
Nm	0,6		0,7	
Speed				
(m/s) max	5		7	
Tensile force				
permanent (N)	900		900	
0,2 s (N)	1000		1000	
Geometrical moments of inertia of aluminium profile				
I_x mm⁴	2,8 x 10⁶		2,8 x 10⁶	
I_y mm⁴	9,6 x 10⁵		9,6 x 10⁵	
E-Modulus N/mm²	70000		70000	

For life-time calculation of rollers use our homepage.

Driving torque:


$$M_a = \frac{F * P * S_i}{2000 * \pi} + M_n$$

$$P_a = \frac{M_a * n}{9550}$$

F = force (N)
P = pulley action perimeter (mm)
Si = safety factor 1,2 ... 2
M_n = no-load torque (Nm)
n = rpm pulley (min^{-1})
M_a = driving torque (Nm)
P_a = motor power (KW)

Deflection:


$$f = \frac{F * L^3}{E * I * 192}$$





f = deflection (mm)
F = load (N)
L = free length (mm)
E = elastic modulus 70000 (N/mm²)
I = second moment of area (mm⁴)

Positioning system ELZ 60 (S) W

Dimensions (mm)







*For slide nuts refer to chapter 2.2 page 2


Increasing the carriage length will increase the basic length by the same amount.

Size	Basic length L	A	B	C	D -0,05	E	F	G	H	J	K	M	N	OO for	P	Q	T	W	X	Y	Z	Basic weight	Weight per 100 mm
ELZ 60 **W**	290	144	96	80	47	30	42	60	139	79	48	71	M8	M8	59	168	M6	60	27	26	55	5,4 kg	0,8 kg
ELZ 60S **W**	315	170	108	80	47	30	42	60	143	83	52	71	M8	M8	59	194	M6	60	27	26	55	6,4 kg	0,8 kg


0 **Choice of guide body profile:**
(0) Standard **(2)** corrosion-protected guide rods and screws
(4) expanded corrosion-protected version (depending on the availability of components)

0 **Choice of carriages:**

(0)




(1)



Size	Version 1	
	Q	L
60	184	306
60 S	214	335

0 **Drive version:**



Version 9 is the same as 0,
but with double sided coupling claw.

Belt table

Code No.		Size	Belt	mm/rev.	Number of teeth
0	**4**	**60 (S)**	5M25	130	26

Shaft dimensions / Coupling claw

Size	Shaft ø h6 x length	Key	Coupling
60 (S)	14 x 35	5x5x28	14

ELZ	60 W	1	0	0	0	0	4	1	01500
	Pos.	1	2	3	4	5	6	7	

Basic length + stroke = total length

For combination kits and connecting elements refer to chapter 2.2

Sample ordering code:
ELZ 60 W, standard body profile, standard carriage, coupling claw on one side, 1210 mm stroke

Positioning system ELZZ 60, 60S, 80, 80S, 100, 125


Belt drive with two separately driven carriages **Specifications**



Function:
Same functions as ELZ, but each carriage can be moved separately by its own drive. This unit has twin pulleys, which run on separate bearings, and two independent, parallel drive belts, one for each carriage.

Fitting position: As required. Max. length 4.000 mm without joints.
Carriage mounting: By T-slots.
Unit mounting: By T-slots or tapped holes in the bearing block, mounting sets.
Belt type: HTD with steel reinforcement, no backlash when changing direction, repeatability ± 0,1 mm.

Forces and torques



Size	ELZZ 60		ELZZ 60 S		ELZZ 80		ELZZ 80 S		ELZZ 100		ELZZ 125	
Forces/Torques	static	dynamic	static	dynamic	static	dynamic	static	dynamic	static	dynamic	static	dynamic
F_x (N)	298	250	298	250	679	500	679	500	1210	1100	1900	1800
F_y (N)	3000	2000	4100	3100	3000	2000	4600	3600	8000	6500	12000	9000
F_z (N)	1700	1100	2160	1600	1700	1100	3000	2600	3600	2200	6000	4500
M_x (Nm)	67	43	88	65	90	55	170	140	300	230	600	450
M_y (Nm)	90	70	190	140	110	80	270	230	400	270	750	600
M_z (Nm)	120	100	230	170	150	120	300	220	750	500	1350	1150
All forces and torques relate to the following: existing values / table values	$\frac{Fy}{Fy_{dyn}} + \frac{Fz}{Fz_{dyn}} + \frac{Mx}{Mx_{dyn}} + \frac{My}{My_{dyn}} + \frac{Mz}{Mz_{dyn}} \leq 1$											
No-load torque												
Nm	0,6		0,7		0,9		1,2		1,4		1,8	
Speed												
(m/s) max	5		5		6		8		10		10	
Tensile force												
permanent (N)	298		298		679		679		1210		1900	
0,2 s (N)	333		333		746		746		1331		2090	
Geometrical moments of inertia of aluminium profile												
I_x mm⁴	6,79x10⁵		6,79x10⁵		18,99x10⁵		18,99x10⁵		44,4x10⁵		101,5x10⁵	
I_y mm⁴	6,97x10⁵		6,97x10⁵		18,97x10⁵		18,97x10⁵		44,8x10⁵		101,5x10⁵	
E-Modulus N/mm²	70000		70000		70000		70000		70000		70000	

For life-time calculation of rollers use our homepage.


Driving torque:

$$M_a = \frac{F * P * S_i}{2000 * \pi} + M_n$$

$$P_a = \frac{M_a * n}{9550}$$

F = force (N)
P = pulley action perimeter (mm)
Si = safety factor 1,2 ... 2
M_n = no-load torque (Nm)
n = rpm pulley (min^{-1})
M_a = driving torque (Nm)
P_a = motor power (KW)

Deflection:




$$f = \frac{F * L^3}{E * I * 192}$$

f = deflection (mm)
F = load (N)
L = free length (mm)
E = elastic modulus 70000 (N/mm^2)
I = second moment of area (mm^4)

Positioning system ELZZ 60, 60S, 80, 80S, 100, 125

Dimensions (mm)





*For slide nuts refer to chapter 2.2 page 2

Increasing the carriage length will increase the basic length by the same amount.

Size ❒	Basic length L	A	B	C	D -0,05	E	F	G	H	J	K	MM for	N	OO for	P	Q	T	U	V	W	X	Y	Basic weight	Weight per 100 mm
ELZZ 60	460	144	96	80	47	30	42	-	-	82	90	-	M 8	M 8	59	168	M 6	15	30	41	27	26	7,4 kg	0,62 kg
ELZZ 60S	510	170	108	80	47	30	42	-	-	82	94	-	M 8	M 8	59	194	M 6	15	30	41	27	26	9,4 kg	0,62 kg
ELZZ 80	570	170	117	100	68	40	60	10	30	110	121	M 6	M 10	M 10	90	194	M 8	22,5	45	51	39	38	12,8 kg	1,00 kg
ELZZ 80S	610	190	126	100	68	40	60	12,5	30	110	122	M 6	M 10	M 8	90	214	M 8	22,5	45	51	39	38	14,8 kg	1,00 kg
ELZZ 100	830	230	155	130	90	50	80	-	29	135	154	M 10	M 12	M 10	110	300	M 10	23	64	65	50	50	33,0 kg	1,60 kg
ELZZ 125	990	295	200	160	110	60	100	-	30	167	191	M 10	M 12	M 12	130	365	M 10	38	50	82	60	60	52,0 kg	2,10 kg

0 **Choice of guide body profile:**
(0) Standard **(2)** corrosion-protected guide rods and screws
(4) expanded corrosion-protected version (depending on the availability of components)

0 **Choice of carriages:**

(0)



(1)




Size	Version 1	
	Q	L
60	184	492
60S	214	550
80	210	602
80S	234	650
100	316	862
125	389	1038

0 **Drive version:**



The standard version is supplied without shaft.



connected with the left belt

Coupling claw on one side

Standard-shaft[1]

Shaft one size smaller[2]

Belt table

Code No.		Size	Belt	mm/rev.	Number of teeth
0	**2**	**60 (S)**	5M09	130	26
0	**5**	**80 (S)**	8M12	192	24
0	**6**	**100**	8M20	256	32
0	**7**	**125**	8M30	304	38

Shaft dimensions / Coupling claw

Size	Shaft ø h6 x length	Key	Coupling
60 (S)[1]	14 x 35	5x5x30	14
60 (S)[2]	10 x 27	3x3x25	14
80 (S)[1]	18 x 45	6x6x40	19
80 (S)[2]	14 x 35	5x5x28	19
100[1]	22 x 45	6x6x40	24
100[2]	18 x 45	6x6x40	24
125[1]	30 x 55	8x7x50	28
125[2]	22 x 45	6x6x40	28

Basic length + stroke = total length


ELZZ	60	4	0	0	0	0	2	1	01500
	Pos.	1	2	3	4	5	6	7	


For combination kits and connecting elements refer to chapter 2.2

Sample ordering code:
ELZZ 60 with standard body profile, standard carriage and coupling claw on one side, 1040 mm stroke

Positioning system ELZD 60 (S) W

Belt drive with two separately driven carriages






The carriages can be moved independently of one another.

Function:
The guide body consists of an aluminium square profile with lateral, parallel, form-fit, internal hardened steel rods. Two carriages, which are driven individually by a timing belt, move along the guide body independently of one another. Due to the rectangular profile high torques and loads can be taken up. In addition, a very high stability and low deflection are ensured for long axis systems. The belt tension can be easily readjusted via a tensioning device within the carriage. This device also helps to adjust the symmetry of the carriages in applications where two parallel linear units are used.

Fitting position: As required. Max. length 3.000 mm without joints.
Carriage mounting: By T-slots.
Unit mounting: By T-slots or mounting sets.
Belt type: HTD with steel reinforcement, no backlash when changing direction, repeatability: ± 0,1 mm.

Forces and torques



Size	60		60 S	
Forces/Torques	static	dynamic	static	dynamic
F_x (N)	894	800	894	800
F_y (N)	3000	2000	4100	3100
F_z (N)	1700	1100	2160	1600
M_x (Nm)	67	43	88	65
M_y (Nm)	90	70	190	140
M_z (Nm)	120	100	230	170
All forces and torques relate to the following: existing values / table values $\frac{Fy}{Fy_{dyn}} + \frac{Fz}{Fz_{dyn}} + \frac{Mx}{Mx_{dyn}} + \frac{My}{My_{dyn}} + \frac{Mz}{Mz_{dyn}} \leq 1$				
No-load torque				
Nm	0,6		0,7	
Speed				
(m/s) max	5		7	
Tensile force				
permanent (N)	900		900	
0,2 s (N)	1000		1000	
Geometrical moments of inertia of aluminium profile				
I_x mm^4	2,8 x 10^6		2,8 x 10^6	
I_y mm^4	9,6 x 10^5		9,6 x 10^5	
E-Modulus N/mm^2	70000		70000	

For life-time calculation of rollers use our homepage.

Driving torque:


$$M_a = \frac{F * P * S_i}{2000 * \pi} + M_n$$

$$P_a = \frac{M_a * n}{9550}$$

F = force (N)
P = pulley action perimeter (mm)
Si = safety factor 1,2 ... 2
M_n = no-load torque (Nm)
n = rpm pulley (min^{-1})
M_a = driving torque (Nm)
P_a = motor power (KW)

Deflection:


$$f = \frac{F * L^3}{E * I * 192}$$





f = deflection (mm)
F = load (N)
L = free length (mm)
E = elastic modulus 70000 (N/mm^2)
I = second moment of area (mm^4)

Positioning system ELZD 60 (S) W

Dimensions (mm)







*For slide nuts refer to chapter 2.2 page 2

Increasing the carriage length will increase the basic length by the same amount.

Size	Basic length L	A	B	C	D -0,05	F	H	J	K	M	OO for	P	Q	T	X	Y	Basic weight	Weight per 100 mm
ELZD 60 **W**	290	144	96	80	47	42	158	79	48	71	M8	59	168	M6	27	26	9,6 kg	1,0 kg
ELZD 60S **W**	315	170	108	80	47	42	166	83	52	71	M8	59	194	M6	27	26	11,6 kg	1,0 kg

0 **Choice of guide body profile:**
(0) Standard **(2)** corrosion-protected guide rods and screws
(4) expanded corrosion-protected version (depending on the availability of components)

0 **Choice of carriages:**


(0)




0 **Drive version:**

(0)






Top drive version:
Version 9 is the same as 0, but with double sided coupling claw.



Mirror plane
Drive version
(top and bottom identical)

(0)





Bottom drive version:
Version 9 is the same as 0, but with double sided coupling claw.

Belt table

Code No.	Size	Belt	mm/rev.	Number of teeth
0 **4**	**60 (S)**	5M25	130	26

Shaft dimensions / Coupling claw

Size	Shaft ø h6 x length	Key	Coupling
60 (S)	14 x 35	5x5x28	14

ELZD	60 W	1	0	0	0	0	4	1	01500
	Pos.	1	2	3	4	5	6	7	

Basic length + stroke = total length


For combination kits and connecting elements refer to chapter 2.2

Sample ordering code:
ELZD 60 W, standard body profile, standard carriage, coupling claw on one side, 1210 mm stroke

Positioning system ELSZ 30, 40, 60, 60S, 80, 80S, 100, 125

With standard belt

Specifications




Function:

This linear unit consists of an aluminium square profile with hardened steel guide rods. The carriage, which has internal linear ball bearings that can be adjusted free of play, is driven along the guide rods by a timing belt. The pulley has maintenance-free ball bearings. Belt tension can be readjusted by a simple tensioning device in one of the end blocks. This device can also be used for symmetrical adjustment of two or more linear units running parallel.

Fitting position: As required. Max. length without joints 6.000 mm.
Carriage mounting: By T-slots.
Unit mounting: By T-slots or tapped holes in the bearing blocks, or mounting sets.
Belt type: HTD with steel reinforcement, no backlash when changing direction, repeatability ± 0,1 mm.

Forces and torques



Size	ELSZ 30		ELSZ 40		ELSZ 60		ELSZ 60 S		ELSZ 80		ELSZ 80 S		ELSZ 100		ELSZ 125	
Forces/Torques	static	dynam.	static	dynam.	static	dynam.	static	dynam.	static	dynam.	static	dynam.	static	dynam.	static	dynam.
F_x (N)	200	180	390	350	894	800	894	800	1900	1800	1900	1800	4000	3800	5900	5750
F_y (N)	90	60	1200	700	3000	2000	4100	3100	3000	2000	4600	3600	8000	6500	12000	9000
F_z (N)	90	60	900	650	1700	1100	2160	1600	1700	1100	3000	1800	3600	2200	6000	4500
M_x (Nm)	10	5	25	20	67	43	88	65	90	55	170	140	300	230	600	450
M_y (Nm)	13	6	32	18	90	70	190	140	110	80	270	230	400	270	750	600
M_z (Nm)	14	7	35	25	120	100	230	170	150	120	300	220	750	500	1350	1150
All forces and torques relate to the following: existing values / table values $\frac{Fy}{Fy_{dyn}} + \frac{Fz}{Fz_{dyn}} + \frac{Mx}{Mx_{dyn}} + \frac{My}{My_{dyn}} + \frac{Mz}{Mz_{dyn}} \leq 1$																
No-load torque																
Nm	0,2		0,7		0,9		0,9		1,1		1,2		1,5		1,8	
Speed																
(m/s) max	2		4		5		7		6		8		8		10	
Tensile force																
permanent (N)	200		390		900		900		1900		1900		4000		5900	
0,2 s (N)	280		480		1000		1000		2090		2090		4300		6350	
Geometrical moments of inertia of aluminium profile																
I_x mm⁴	4,09x10⁴		1,32x10⁵		6,79x10⁵		6,79x10⁵		18,99x10⁵		18,99x10⁵		44,4x10⁵		101,5x10⁵	
I_y mm⁴	4,00x10⁴		1,34x10⁵		6,97x10⁵		6,97x10⁵		18,97x10⁵		18,97x10⁵		44,8x10⁵		101,5x10⁵	
E-Modulus N/mm²	70000		70000		70000		70000		70000		70000		70000		70000	

For life-time calculation of rollers use our homepage.


Driving torque:

$$M_a = \frac{F * P * S_i}{2000 * \pi} + M_n$$

$$P_a = \frac{M_a * n}{9550}$$

F = force (N)
P = pulley action perimeter (mm)
Si = safety factor 1,2 ... 2
M_n = no-load torque (Nm)
n = rpm pulley (min^{-1})
M_a = driving torque (Nm)
P_a = motor power (KW)

Deflection:





$$f = \frac{F * L^3}{E * I * 192}$$


f = deflection (mm)
F = load (N)
L = free length (mm)
E = elastic modulus 70000 (N/mm^2)
I = second moment of area (mm^4)

Positioning system ELSZ 30, 40, 60, 60S, 80, 80S, 100, 125

Dimensions (mm)







*For slide nuts refer to chapter 2.2 page 2

Increasing the carriage length will increase the basic length by the same amount.

Size ❒	Basic length L	A	B	C	D -0,05	E1	E2	F	G	H	I	J	K	MM for	N	NN for	O	OO for	P	Q	T	V	Basic weight	Weight per 100 mm
ELSZ 30	182	70	16	42	28	-	56	25	45	42	-	26	4,2	-	90	M 6	35	M 6	12	108	M 4	-	1,33 kg	0,16 kg
ELSZ 40	230	100	20	58	37	25	66	32	65	60	-	35	6,5	-	110	M 6	47	M 6	12	142	M 5	-	2,1 kg	0,24 kg
ELSZ 60	280	144	30	82	47	30	96	42	80	80	-	49	8,5	-	130	M 8	69	M 8	16	168	M 6	-	5,1 kg	0,62 kg
ELSZ 60S	305	170	30	82	47	30	108	42	80	80	-	53	8,5	-	130	M 8	69	M 8	16	194	M 6	-	6,1 kg	0,62 kg
ELSZ 80	365	170	39	102	68	40	117	60	100	100	30	70	8,5	M 6	180	M 10	88	M 10	20	214	M 8	10	11,0 kg	1,00 kg
ELSZ 80S	365	190	39	102	68	40	126	60	100	100	30	71	8,5	M 6	180	M 8	88	M 8	20	214	M 8	12,5	12,0 Kg	1,00 Kg
ELSZ 100	535	230	60	130	90	50	155	80	130	130	29	89	10,5	M 10	270	M 12	112	M 10	30	310	M 10	-	25,8 kg	1,60 kg
ELSZ 125	595	295	62	165	110	60	200	100	139	160	30	107,5	M 10	M 10	310	M 12	140	M 12	30	365	M 10	-	54,5 kg	1,94 kg

0 **Choice of guide body profile:**
(0) Standard **(2)** corrosion-protected guide rods and screws
(4) expanded corrosion-protected version (depending on the availability of components)

0 **Choice of carriages:**

(0)



(1)



(2)



(3)




Size	Version 1		Version 2		Version 3	
	Q	L	Q	L	Q	L
30	175	245	124	194	197	267
40	237	325	158	246	253	341
60	303	415	184	296	319	431
60S	329	431	214	325	349	451
80	379	525	230	381	395	541
80S	379	525	234	395	419	565
100	535	760	326	551	551	776
125	640	870	389	619	664	894

0 **Drive version:**

0



0 1 2 3 4 5 6 7 8



The standard version is supplied without shaft. A shaft can be retrofitted by inserting it into the pulley bore and securing it with 2 locking rings or tension sets (size 100 + 125).

Version 8 is the same as 0,
but with double sided coupling claw.

Belt table

Code No.		Size	Belt	mm/rev.	Number of teeth
0	**1**	**30**	3M12	75	25
0	**3**	**40**	5M15	100	20
0	**4**	**60 (S)**	5M25	130	26
0	**7**	**80 (S)**	8M30	192	24
0	**9**	**100**	8M50	256	32
1	**0**	**125**	8M70	304	38

Shaft dimensions / Coupling claw

Size	Shaft ø h6 x length	Key	Coupling
30	6 x 15	2x2x12	7
40	10 x 27	3x3x25	9
60 (S)	14 x 35	5x5x28	14
80 (S)	18 x 45	6x6x40	19
100	22 x 45	6x6x40	24
125	30 x 55	8x7x50	28

Basic length + stroke = total length

ELSZ	60	0	0	0	0	0	4	1	01500
	Pos.	1	2	3	4	5	6	7	

For combination kits and connecting elements refer to chapter 2.2


Sample ordering code:
ELSZ 60 with standard body profile, standard carriage and coupling claw on one side, 1220 mm stroke.

Positioning system ELSZ 30, 40, 60, 60S, 80, 80S, 100, 125

With widened belt drive


Specifications





Function:

This linear unit consists of an aluminium square profile with hardened steel guide rods. The carriage, which has internal linear ball bearings that can be adjusted free of play, is driven along the guide rods by a timing belt. The pulley has maintenance-free ball bearings. Belt tension can be readjusted by a simple tensioning device in one of the end blocks. This device can also be used for symmetrical adjustment of two or more linear units running parallel.



Forces and torques

Fitting position: As required. Max. length without joints 6.000 mm.
Carriage mounting: By T-slots.
Unit mounting: By T-slots, threads or tapped holes in the bearing blocks, or mounting sets.
Belt type: HTD with steel reinforcement, no backlash when changing direction, repeatability ± 0,1 mm.

Size	ELSZ 30		ELSZ 40		ELSZ 60		ELSZ 60 S		ELSZ 80		ELSZ 80 S		ELSZ 100		ELSZ 125	
Forces/Torques	static	dynam.	static	dynam.	static	dynam.	static	dynam.	static	dynam.	static	dynam.	static	dynam.	static	dynam.
F_x (N)	390	350	894	800	1900	1800	1900	1800	4000	3800	4000	3800	5900	5750	7900	7500
F_y (N)	90	60	1200	700	3000	2000	4100	3100	3000	2000	4600	3600	8000	6500	12000	9000
F_z (N)	90	60	900	650	1700	1100	2160	1600	1700	1100	3000	1800	3600	2200	6000	4500
M_x (Nm)	10	5	25	20	67	43	88	65	90	55	170	140	300	230	600	450
M_y (Nm)	13	6	32	18	90	70	190	140	110	80	270	230	400	270	750	600
M_z (Nm)	14	7	35	25	120	100	230	170	150	120	300	220	750	500	1350	1150
All forces and torques relate to the following: existing values / table values $\frac{Fy}{Fy_{dyn}} + \frac{Fz}{Fz_{dyn}} + \frac{Mx}{Mx_{dyn}} + \frac{My}{My_{dyn}} + \frac{Mz}{Mz_{dyn}} \leq 1$																
No-load torque																
Nm	0,5		0,7		0,9		0,9		1,2		1,2		1,5		1,8	
Speed																
(m/s) max	2		4		5		7		8		8		8		8	
Tensile force																
permanent (N)	390		894		1 900		1900		4000		4000		5900		7900	
0,2 s (N)	480		480		2090		2090		4300		4300		6350		8500	
Geometrical moments of inertia of aluminium profile																
I_x mm^4	4,09x10^4		1,32x10^5		6,79x10^5		6,79x10^5		18,99x10^5		18,99x10^5		44,4x10^5		101,5x10^5	
I_y mm^4	4,00x10^4		1,34x10^5		6,97x10^5		6,97x10^5		18,97x10^5		18,97x10^5		44,8x10^5		101,5x10^5	
E-Modulus N/mm^2	70000		70000		70000		70000		70000		70000		70000		70000	

For life-time calculation of rollers use our homepage.

Driving torque:


$$M_a = \frac{F * P * S_i}{2000 * \pi} + M_n$$

$$P_a = \frac{M_a * n}{9550}$$

F = force (N)
P = pulley action perimeter (mm)
Si = safety factor 1,2 ... 2
M_n = no-load torque (Nm)
n = rpm pulley (min^{-1})
M_a = driving torque (Nm)
P_a = motor power (KW)

Deflection:


$$f = \frac{F * L^3}{E * I * 192}$$




f = deflection (mm)
F = load (N)
L = free length (mm)
E = elastic modulus 70000 (N/mm^2)
I = second moment of area (mm^4)

Positioning system ELSZ 30, 40, 60, 60S, 80, 80S, 100, 125


Dimensions (mm)



ELSZ 40 - 100



ELSZ 30, 125



*For slide nuts refer to chapter 2.2 page 2

Increasing the carriage length will increase the basic length by the same amount.

Size ❒	Basic length L	A	B	C	D -0,05	E1	E2	F	G	H	I	J	K	MM for	N	NN for	O	OO for	P	Q	T	V	Basic weight	Weight per 100 mm
ELSZ 30	210	70	20	42	37	-	56	32	55	60	-	26	4,2	-	110	M 6	35	M 6	12	128	M 5	-	1,5 kg	0,16 kg
ELSZ 40	260	100	30	58	47	18	66	42	83	80	-	35	6,5	-	130	M 6	47	M 6	12	164	M 6	-	2,7 kg	0,24 kg
ELSZ 60	355	144	39	82	68	30	96	60	105	100	-	49	8,5	-	180	M 8	69	M 8	16	214	M 8	-	6,3 kg	0,62 kg
ELSZ 60S	355	170	39	82	68	30	108	60	105	100	-	53	8,5	-	180	M 8	69	M 8	16	214	M 8	-	7,3 kg	0,62 kg
ELSZ 80	460	170	60	102	90	40	117	80	140	130	30	70	8,5	M 6	270	M 10	88	M 10	20	304	M 10	10	14,0 kg	1,00 kg
ELSZ 80S	460	190	60	102	90	40	126	80	140	130	30	71	8,5	M 6	270	M 10	88	M 8	20	304	M 10	12,5	15,0 Kg	1,00 Kg
ELSZ 100	575	230	62	130	110	50	155	100	143	160	29	89	M 12	M 10	310	M 10	112	M 10	30	350	M 10	-	31,0 kg	1,60 kg
ELSZ 125	605	295	62	165	110	60	200	100	139	180	30	107,5	M 12	M 10	310	M 12	140	M 12	30	365	M 10	-	57,4 kg	1,96 kg

0 **Choice of guide body profile:**
(0) Standard **(2)** corrosion-protected guide rods and screws
(4) expanded corrosion-protected version (depending on the availability of components)

0 **Choice of carriages:**

(0)



(1)



(2)



(3)




Size	Version 1		Version 2		Version 3	
	Q	L	Q	L	Q	L
30	195	279	140	222	207	291
40	257	355	180	276	273	371
60	353	494	230	371	369	510
60S	379	520	234	375	399	540
80	469	625	320	476	485	641
80S	489	645	324	480	509	665
100	575	800	366	591	591	816
125	640	870	389	619	664	894

0 **Drive version:**

0





The standard version is supplied without shaft. A shaft can be retrofitted by inserting it into the pulley bore and securing it with 2 locking rings or tension sets (size 80 + 100).

Version 8 is the same as 0, but with double sided coupling claw.

Belt table

Code No.		Size	Belt	mm/rev.	Number of teeth
0	**3**	**30**	5M15	100	20
0	**4**	**40**	5M25	130	26
0	**7**	**60 (S)**	8M30	192	24
0	**9**	**80 (S)**	8M50	256	32
1	**0**	**100**	8M70	304	38
1	**4**	**125**	8M100	304	38

Shaft dimensions / Coupling claw

Size	Shaft ø h6 x length	Key	Coupling
30	10 x 27	3x3x25	9
40	14 x 35	5x5x28	14
60 (S)	18 x 45	6x6x40	19
80 (S)	22 x 45	6x6x40	24
100	30 x 55	8x7x50	28
125	40 x 55	12x8x50	—

Basic length + stroke = total length


ELSZ	60	0	0	0	0	0	7	1	01500
Pos.		1	2	3	4	5	6	7	

For combination kits and connecting elements refer to chapter 2.2

Sample ordering code:
ELSZ 60 with standard body profile, standard carriage with widened belt and coupling claw on one side, 1170 mm stroke.

Positioning system ELSD 40, 60, 60S, 80, 80S, 100


Belt drive with rotary shaft **Specifications**



Function:
Same as ELSZ, but with an additional rotary shaft, fitted within the aluminium body. One end can be driven by any suitable motor, and the other end is provided with a shaft with feather key and an axial tapped hole for fitting grippers or other components.

Fitting position: As required. Max. length 2.000 mm.
Carriage mounting: By T-slots.
Unit mounting: By T-slots or tapped holes in the bearing blocks, mounting sets.
Belt type: HTD with steel reinforcement, no backlash when changing direction, repeatability ± 0,1 mm.

Forces and torques



Size	ELSD 40		ELSD 60		ELSD 60 S		ELSD 80		ELSD 80 S		ELSD 100	
Forces/Torques	static	dynamic	static	dynamic	static	dynamic	static	dynamic	static	dynamic	static	dynamic
F_x (N)	390	350	894	800	894	800	1900	1800	1900	1800	4000	3800
F_y (N)	1200	700	3000	2000	4100	3100	3000	2000	4600	3600	8000	6500
F_z (N)	900	650	1700	1100	2160	1600	1700	1100	3000	1800	3600	2200
F_D (N)	50		150		150		250		250		400	
M_x (Nm)	25	20	67	43	88	65	90	55	170	140	300	230
M_y (Nm)	32	18	90	70	190	140	110	80	270	230	400	270
M_z (Nm)	35	25	120	100	230	170	150	120	300	220	750	500
M_R (Nm)	5		10		10		20		20		30	

All forces and torques relate to the following:

existing values / table values

$$\frac{Fy}{Fy_{dyn}} + \frac{Fz}{Fz_{dyn}} + \frac{Mx}{Mx_{dyn}} + \frac{My}{My_{dyn}} + \frac{Mz}{Mz_{dyn}} \leq 1$$

No-load torque						
Nm	0,7	0,9	0,9	1,1	1,2	1,5
Stiction torque M_R (Nm)	0,2	0,4	0,5	0,6	0,7	0,8
Speed						
(m/s) max	4	5	7	6	8	8
Tensile force						
permanent (N)	390	900	900	1900	1900	4000
0,2 s (N)	480	1000	1000	2090	2090	4300
Geometrical moments of inertia of aluminium profile						
I_x mm⁴	1,32x10⁵	6,79x10⁵	6,79x10⁵	18,99x10⁵	18,99x10⁵	44,4x10⁵
I_y mm⁴	1,34x10⁵	6,97x10⁵	6,97x10⁵	18,97x10⁵	18,97x10⁵	44,8x10⁵
E-Modulus N/mm²	70000	70000	70000	70000	70000	70000

For life-time calculation of rollers use our homepage.


Driving torque:

$$M_a = \frac{F * P * S_i}{2000 * \pi} + M_n$$

$$P_a = \frac{M_a * n}{9550}$$

F = force (N)
P = pulley action perimeter (mm)
Si = safety factor 1,2 ... 2
M_n = no-load torque (Nm)
n = rpm pulley (min^{-1})
M_a = driving torque (Nm)
P_a = motor power (KW)

Deflection:





$$f = \frac{F * L^3}{E * I * 192}$$

f = deflection (mm)
F = load (N)
L = free length (mm)
E = elastic modulus 70000 (N/mm^2)
I = second moment of area (mm^4)

Positioning system ELSD 40, 60, 60S, 80, 80S, 100

Dimensions (mm)





Shaft (drive end)			Shaft (load end)		
Size ❒	Shaft ø h6 x length (V)	Key (U)	Shaft ø h6 x length (V)	Key (U)	Thread (W)
40	10 x 20	3x3x10	12 x 20	4x4x10	M 6 x 12
60 (S)	14 x 25	5x5x20	17 x 25	5x5x20	M 8 x 20
80 (S)	18 x 30	6x6x20	20 x 30	6x6x20	M 10 x 20
100	22 x 35	6x6x30	25 x 35	8x7x30	M 12 x 25

Increasing the carriage length will increase the basic length by the same amount.

*For slide nuts refer to chapter 2.2 page 2

Size ❒	Basic length L	A	B	C	D -0,05	E1	E2	F	G	H	I	J	K	M	MM for	N	NN for	OO for	P	Q	T	X	Basic weight	Weight per 100 mm
ELSD 40	260	100	20	58	37	25	66	32	65	60	-	35	6,5	47	-	110	M 6	M 6	25	142	M 5	-	2,4 kg	0,40 kg
ELSD 60	320	144	30	82	47	30	96	42	80	80	-	49	8,5	69	-	130	M 8	M 8	35	168	M 6	-	5,9 kg	0,87 kg
ELSD 60S	345	170	30	82	47	30	108	42	80	80	-	53	8,5	69	-	130	M 8	M 8	35	194	M 6	-	6,9 kg	0,87 kg
ELSD 80	415	170	39	102	68	40	117	60	100	100	30	70	8,5	88	M 6	180	M 10	M 10	45	214	M 8	10	12,5 kg	1,30 kg
ELSD 80S	415	190	39	102	68	40	126	60	100	100	30	71	8,5	88	M 6	180	M 10	M 8	45	214	M 8	12,5	14,0 kg	1,30 kg
ELSD 100	585	230	60	130	90	50	155	80	130	130	29	89	10,5	112	M10	270	M 10	M 10	55	310	M 10	-	27,0 kg	1,70 kg

0 **Choice of guide body profile:**
(0) Standard **(2)** corrosion-protected guide rods and screws
(4) expanded corrosion-protected version (depending on the availability of components)

0 **Choice of carriages:**

(0)



(1)



(2)



(3)




Size	Version 1		Version 2		Version 3	
	Q	L	Q	L	Q	L
40	237	355	160	276	253	371
60	303	453	184	336	319	469
60S	329	469	214	365	349	489
80	379	575	230	431	395	591
80S	399	595	245	450	419	615
100	535	810	326	601	551	826

0 **Drive version:**

0





The standard version is supplied without shaft. A shaft can be retrofitted by inserting it into the pulley bore and securing it with 2 locking rings or tension sets (size 100).

Version 9 is the same as 0,
but with double sided coupling claw.

Belt table

Code No.		Size	Belt	mm/rev.	Number of teeth
0	**3**	**40**	5M15	100	20
0	**4**	**60 (S)**	5M25	130	26
0	**7**	**80 (S)**	8M30	192	24
0	**9**	**100**	8M50	256	32

Shaft dimensions / Coupling claw

Size	Shaft ø h6 x length	Key	Coupling
40	10 x 27	3x3x25	9
60 (S)	14 x 35	5x5x28	14
80 (S)	18 x 45	6x6x40	19
100	22 x 45	6x6x40	24

Basic length + stroke = total length


ELSD	60	0	0	0	0	0	4	1	01500
Pos.		1	2	3	4	5	6	7	


For combination kits and connecting elements refer to chapter 2.2

Sample ordering code:
ELSD 60 with standard body profile, standard carriage and coupling claw on one side, 1180 mm stroke

Positioning system ELSD 40, 60, 60S, 80, 80S, 100

Belt drive with widened belt and rotary shaft **Specifications**






Function:
Same as ELSZ, but with an additional rotary shaft, fitted within the aluminium body. One end can be driven by any suitable motor, and the other end is provided with a shaft with feather key and an axial tapped hole for fitting grippers or other components.

Fitting position: As required. Max. length 2.000 mm.
Carriage mounting: By T-slots.
Unit mounting: By T-slots or tapped holes in the bearing blocks, mounting sets.
Belt type: HTD with steel reinforcement, no backlash when changing direction, repeatability ± 0,1 mm.

Forces and torques



Size	ELSD 40		ELSD 60		ELSD 60 S		ELSD 80		ELSD 80 S		ELSD 100	
Forces/Torques	static	dynamic	static	dynamic	static	dynamic	static	dynamic	static	dynamic	static	dynamic
F_x (N)	894	800	1900	1800	1900	1800	4000	3800	4000	3800	5900	5750
F_y (N)	1200	700	3000	2000	4100	3100	3000	2000	4600	3600	8000	6500
F_z (N)	900	650	1700	1100	2160	1600	1700	1100	3000	1800	3600	2200
F_D (N)	50		150		150		250		250		400	
M_x (Nm)	25	20	67	43	88	65	90	55	170	140	300	230
M_y (Nm)	32	18	90	70	190	140	110	80	270	230	400	270
M_z (Nm)	35	25	120	100	230	170	150	120	300	220	750	500
M_R (Nm)	5		10		10		20		20		30	
All forces and torques relate to the following: existing values / table values	$\frac{Fy}{Fy_{dyn}} + \frac{Fz}{Fz_{dyn}} + \frac{Mx}{Mx_{dyn}} + \frac{My}{My_{dyn}} + \frac{Mz}{Mz_{dyn}} \leq 1$											
No-load torque												
Nm	0,7		0,9		0,9		1,1		1,2		1,5	
Stiction torque M_x (Nm)	0,2		0,4		0,5		0,6		0,7		0,8	
Speed												
(m/s) max	4		5		7		6		8		8	
Tensile force												
permanent (N)	900		1900		1900		4000		4000		5900	
0,2 s (N)	1000		2090		2090		4300		4300		6350	
Geometrical moments of inertia of aluminium profile												
I_x mm⁴	1,32x10⁵		6,79x10⁵		6,79x10⁵		18,99x10⁵		18,99x10⁵		44,4x10⁵	
I_y mm⁴	1,34x10⁵		6,97x10⁵		6,97x10⁵		18,97x10⁵		18,97x10⁵		44,8x10⁵	
E-Modulus N/mm²	70000		70000		70000		70000		70000		70000	

For life-time calculation of rollers use our homepage.

Driving torque:


$$M_a = \frac{F * P * S_i}{2000 * \pi} + M_n$$

$$P_a = \frac{M_a * n}{9550}$$

F = force (N)
P = pulley action perimeter (mm)
Si = safety factor 1,2 ... 2
M_n = no-load torque (Nm)
n = rpm pulley (min^{-1})
M_a = driving torque (Nm)
P_a = motor power (KW)

Deflection:


$$f = \frac{F * L^3}{E * I * 192}$$




f = deflection (mm)
F = load (N)
L = free length (mm)
E = elastic modulus 70000 (N/mm^2)
I = second moment of area (mm^4)

Positioning system ELSD 40, 60, 60S, 80, 80S, 100

Dimensions (mm)





Shaft (drive end)			Shaft (load end)		
Size ❒	Shaft ø h6 x length (V)	Key (U)	Shaft ø h6 x length (V)	Key (U)	Thread (W)
40	10 x 20	3x3x10	12 x 20	4x4x10	M 6 x 12
60 (S)	14 x 25	5x5x20	17 x 25	5x5x20	M 8 x 20
80 (S)	18 x 30	6x6x20	20 x 30	6x6x20	M 10 x 20
100	22 x 35	6x6x30	25 x 35	8x7x30	M 12 x 25

Increasing the carriage length will increase the basic length by the same amount.

*For slide-nuts refer to chapter 2.2 page 2

Size ❒	Basic length L	A	B	C	D -0,05	E1	E2	F	G	H	I	J	K	M	MM for	N	NN for	OO for	P	Q	T	X	Basic weight	Weight per 100 mm
ELSD 40	286	100	30	58	47	25	66	42	83	80	-	35	6,5	47	-	130	M 6	M 6	25	164	M 6	-	2,7 kg	0,40 kg
ELSD 60	395	144	39	82	68	30	96	60	105	100	-	49	8,5	69	-	180	M 8	M 8	35	214	M 8	-	6,5 kg	0,87 kg
ELSD 60S	395	170	39	82	68	30	108	60	105	100	-	53	8,5	69	-	180	M 8	M 8	35	214	M 8	-	7,5 kg	0,87 kg
ELSD 80	510	170	60	102	90	40	117	80	140	130	30	70	8,5	88	M 6	270	M 10	M 10	45	304	M 10	10	13,7 kg	1,30 kg
ELSD 80S	510	190	60	102	90	40	126	80	140	130	30	71	8,5	88	M 6	270	M 10	M 8	45	304	M 10	12,5	15,2 kg	1,30 kg
ELSD 100	625	230	62	130	110	50	155	100	143	160	29	89	10,5	112	M10	310	M 10	M 10	55	350	M 10	-	33,4 kg	1,70 kg

0 **Choice of guide body profile:**
(0) Standard **(2)** corrosion-protected guide rods and screws
(4) expanded corrosion-protected version (depending on the availability of components)

0 **Choice of carriages:**

(0)



(1)



(2)



(3)




Size	Version 1		Version 2		Version 3	
	Q	L	Q	L	Q	L
40	257	381	180	302	273	397
60	353	534	230	411	369	550
60S	379	560	234	415	399	580
80	469	675	320	526	485	691
80S	489	695	324	530	509	715
100	575	850	366	641	591	866

0 **Drive version:**

0





The standard version is supplied without shaft. A shaft can be retrofitted by inserting it into the pulley bore and securing it with 2 locking rings or tension sets (size 80 + 100).

Version 9 is the same as 0,
but with double sided coupling claw.

Belt table

Code No.		Size	Belt	mm/rev.	Number of teeth
0	**4**	**40**	5M25	130	26
0	**7**	**60 (S)**	8M30	192	24
0	**9**	**80 (S)**	8M50	256	32
1	**0**	**100**	8M70	304	38

Shaft dimensions / Coupling claw

Size	Shaft ø h6 x length	Key	Coupling
40	14 x 35	5x5x28	14
60 (S)	18 x 45	6x6x40	19
80 (S)	22 x 45	6x6x40	24
100	30 x 55	8x7x40	28

Basic length + stroke = total length

ELSD	60	0	0	0	0	0	7	1	01500
Pos.		1	2	3	4	5	6	7	


For combination kits and connecting elements refer to chapter 2.2

Sample ordering code:
ELSD 60 with standard body profile, standard carriage and coupling claw on one side, 1146 mm stroke

Positioning system ELZT 40, 60, 60S, 80, 80S, 100

Telescopic belt drive


Specifications



Function:
This unit consists of an aluminium square profile with integrated, hardened steel guide rods. Two carriages, which have internal linear ball bearings that can be adjusted free of play, are driven along the guide rods in opposite directions by 2 belts. The pulleys include maintenance-free ball bearings. One belt is tensioned by a tensioning device within the carriage. The other timing belt is tensioned by a tensioning device within the bearing block. The carriage with the drive block (with motor) is screwed to the crosshead. A T-slot profile is screwed to the carriage as an extension arm which can be adjusted to any length (see functional diagram on page 3/20).

Fitting position: As required. Max. length 3.000 mm.
Unit mounting: By T-slots in the carriage, extension arm
Belt type: HTD with steel reinforcement, no backlash when changing direction, repeatability ± 0,1 mm.

Forces and torques



Size	ELZT 40		ELZT 60		ELZT 60 S		ELZT 80		ELZT 80 S		ELZT 100	
Forces/torques	static	dynamic	static	dynamic	static	dynamic	static	dynamic	static	dynamic	static	dynamic
F_x (N)	360	300	580	470	580	470	1800	1570	1800	1570	4000	3500
F_y (N)	1200	700	3000	2000	4100	3100	3000	2000	4600	3600	8000	6500
F_z (N)	900	650	1700	1100	2160	1600	1700	1100	3000	1800	3600	2200
M_x (Nm)	25	20	67	43	88	65	90	55	170	140	300	230
M_y (Nm)	32	18	90	70	190	140	110	80	270	230	400	270
M_z (Nm)	35	25	120	100	230	170	150	120	370	310	750	500

All forces and torques relate to the following:

existing values / table values

$$\frac{Fy}{Fy_{dyn}} + \frac{Fz}{Fz_{dyn}} + \frac{Mx}{Mx_{dyn}} + \frac{My}{My_{dyn}} + \frac{Mz}{Mz_{dyn}} \leq 1$$

No-load torque						
Nm	0,9	1,1	1,1	1,3	1,2	2,4
Speed						
(m/s) max	4	5	7	6	8	8
Tensile force						
permanent (N)	360	580	580	1800	1800	4000
0,2 s (N)	450	700	700	2200	2200	4300
Geometrical moments of inertia of aluminium profile						
I_x mm⁴	1,32x10⁵	6,79x10⁵	6,79x10⁵	18,99x10⁵	18,99x10⁵	44,4x10⁵
I_y mm⁴	1,34x10⁵	6,97x10⁵	6,97x10⁵	18,97x10⁵	18,97x10⁵	44,8x10⁵
E-Modulus N/mm²	70000	70000	70000	70000	70000	70000

For life-time calculation of rollers use our homepage.

Driving torque:


$$M_a = \frac{F * P * S_i}{2000 * \pi} + M_n$$

$$P_a = \frac{M_a * n}{9550}$$

F = force (N)
P = pulley action perimeter (mm)
Si = safety factor 1,2 ... 2
M_n = no-load torque (Nm)
n = rpm pulley (min^{-1})
M_a = driving torque (Nm)
P_a = motor power (KW)

Deflection:


$$f = \frac{F * L^3}{E * I * 192}$$



f = deflection (mm)
F = load (N)
L = free length (mm)
E = elastic modulus 70000 (N/mm^2)
I = second moment of area (mm^4)

Positioning system ELZT 40, 60, 60S, 80, 80S, 100

Dimensions (mm)



Functional principle
on page 3.1 | 29

*For slide nuts refer to chapter 2.2 page 2

Increasing the carriage length will increase the basic length by the same amount.

Size ❐	Basic length L	A	B	C	D - 0,05	F	G	H	I	J	MM for	N	OO for	P	Q	T	V	Basic weight	Weight per 100 mm
ELZT 40	265	100	30	58	47	42	83	80	-	70	-	130	M 6	49	164	M 6	-	3,6 kg	0,31 kg
ELZT 60	345	144	39	80	68	60	105	100	-	98	-	180	M 8	59	218	M 8	-	9,1 kg	0,73 kg
ELZT 60S	370	170	39	80	68	60	105	100	-	106	-	180	M 8	59	220	M 8	-	10,1 kg	0,73 kg
ELZT 80	494	170	60	100	90	80	140	130	30	140	M 6	270	M 10	90	304	M 10	10	24,0 kg	1,14 kg
ELZT 80S	494	190	60	100	90	80	140	130	30	142	M 6	270	M 8	90	304	M 10	12,5	26,0 Kg	1,14 kg
ELZT 100	570	230	62	130	110	100	143	160	29	178	M 10	310	M 10	110	350	M 10	-	40,6 kg	1,95 kg

0 **Choice of guide body profile:**
(0) Standard **(2)** corrosion-protected guide rods and screws
(4) expanded corrosion-protected version (depending on the availability of components)

0 **Choice of carriages:**

(0)



(1)



(3)




Size	Version 1		Version 3	
	Q	L	Q	L
40	257	360	257	360
60	353	480	353	480
60S	379	506	379	506
80	469	659	469	659
80S	489	679	489	679
100	575	795	575	795

0 **Drive version:**

0



0 1 2 3 4 5 6 7 8 9



The standard version is supplied without shaft. A shaft can be retrofitted by inserting it into the pulley bore and securing it with 2 locking rings or tension sets (size 80 + 100).

Version 9 is the same as 0, but with double sided coupling claw.

Belt table

Code No.		Size	Belt	mm/rev.	Number of teeth
0	**4**	**40**	5M25	130	26
0	**7**	**60 (S)**	8M30	192	24
0	**9**	**80 (S)**	8M50	256	32
1	**0**	**100**	8M70	304	38

Shaft dimensions / Coupling Claw

Size	Shaft ø h6 x length	Key	Coupling
40	14 x 35	5x5x28	14
60 (S)	18 x 45	6x6x40	19
80 (S)	22 x 45	6x6x40	24
100	30 x 55	8x7x40	28

ELZT	60	6	0	0	0	0	4	1	01500
Pos.	1	2	3	4	5	6	7		


Basic length + 1/2stroke = total length

For combination kits and connecting elements refer to chapter 2.2

Sample ordering code:
ELZT 60 with standard body profile, standard carriage and coupling claw on one side, 2310 mm stroke

Positioning system ELHZ 60, 60S, 80, 80S, 100, 125

Internal belt drive **Specifications**




Fraunhofer IPA TESTED DEVICE Lineareinheit ELHZ 60 Report No. BA 9807-151

Function:
This linear unit consists of an aluminium square profile with integrated, hardened steel guide rods. The carriage, which has internal linear ball bearings that can be adjusted free of play, is driven along the guide rods by a timing belt. Toothed pulley has maintenance-free ball bearings. Belt tension can be readjusted by a simple screw adjustment device in the carriage. This device can also be used for symmetrical adjustment of two or more linear units running parallel.
This linear unit is suitable for application in clean rooms of clean-room classification 1.000 (corresponding to US Fed. Standard 209 E).

Fitting position: As required. Max. length 3.000 mm without joints.
Carriage mounting: By T-slots.
Unit mounting: By tapped holes or tapped holes in the bearing block, mounting sets.
Belt type: HTD with steel reinforcement, no backlash when changing direction, repeatability ± 0,1 mm.

Forces and torques



Size	ELHZ 60		ELHZ 60 S		ELHZ 80		ELHZ 80 S		ELHZ 100		ELHZ 125	
Forces/Torques	static	dynamic	static	dynamic	static	dynamic	static	dynamic	static	dynamic	static	dynamic
F_x (N)	700	580	700	580	1000	840	1000	840	3100	2600	5000	4950
F_y (N)	3000	2000	4100	3100	3000	2000	4600	3600	8000	6500	12000	9000
F_z (N)	1700	1100	2160	1600	1700	1100	3000	1800	3600	2200	6000	4500
M_x (Nm)	67	43	88	65	90	55	170	140	300	230	600	450
M_y (Nm)	90	70	190	140	110	80	270	230	400	270	750	600
M_z (Nm)	120	100	230	170	150	120	300	220	750	500	1350	1150

All forces and torques relate to the following:

existing values / table values

$$\frac{Fy}{Fy_{dyn}} + \frac{Fz}{Fz_{dyn}} + \frac{Mx}{Mx_{dyn}} + \frac{My}{My_{dyn}} + \frac{Mz}{Mz_{dyn}} \leq 1$$

No-load torque						
Nm	0,5	0,5	0,8	1,2	1,2	1,6
Speed						
(m/s) max	3	4	4	4	5	6
Tensile force						
permanent (N)	700	700	1000	1000	3100	5000
0,2 s (N)	800	800	1150	1150	3400	5450
Geometrical moments of inertia of aluminium profile						
I_x mm^4	6,79x10^5	6,79x10^5	18,99x10^5	18,99x10^5	44,4x10^5	101,5x10^5
I_y mm^4	6,97x10^5	6,97x10^5	18,97x10^5	18,97x10^5	44,8x10^5	101,5x10^5
E-Modulus N/mm^2	70000	70000	70000	70000	70000	70000

For life-time calculation of rollers use our homepage.


Driving torque:

$$M_a = \frac{F * P * S_i}{2000 * \pi} + M_n$$

$$P_a = \frac{M_a * n}{9550}$$

F = force (N)
P = pulley action perimeter (mm)
Si = safety factor 1,2 ... 2
M_n = no-load torque (Nm)
n = rpm pulley (min^{-1})
M_a = driving torque (Nm)
P_a = motor power (KW)

Deflection:




$$f = \frac{F * L^3}{E * I * 192}$$

f = deflection (mm)
F = load (N)
L = free length (mm)
E = elastic modulus 70000 (N/mm^2)
I = second moment of area (mm^4)

BAHR Modultechnik

Positioning system ELHZ 60, 60S, 80, 80S, 100, 125

Dimensions (mm)



*For slide nuts refer to chapter 2.2 page 2

Increasing the carriage length will increase the basic length by the same amount.


Size ❒	Basic length L	A	B	C	D ± 0,05	E	F	G	H	J	K	MM for	NN for	OO for	P	Q	T	U	V -0,05	W¹	X	Y	Z	Basic weight	Weight per 100 mm
ELHZ 60	290	144	96	82	62x1	30	69	--	-	49	90	-	M 8	M 8	59	168	8,5	23	37	14	30	36	M 6	4,8 kg	0,62 kg
ELHZ 60S	315	170	108	82	62x1	30	69	--	-	53	94	-	M 8	M 8	59	194	8,5	23	37	14	30	36	M 6	5,8 kg	0,62 kg
ELHZ 80	375	170	117	102	80x1	40	88	10	30	70	121	M 6	M10	M10	90	194	8,5	38	47	18	40	50	M 8	10,0 kg	1,00 kg
ELHZ 80S	395	190	126	102	80x1	40	88	12,5	30	71	122	M 6	M10	M 8	90	214	8,5	38	47	18	40	50	M 8	11,0 kg	1,00 kg
ELHZ 100	530	230	155	130	110x1	50	112	-	29	89	154	M10	M10	M10	110	300	10,5	45	68	19	50	64	M10	24,0 kg	1,60 kg
ELHZ 125	630	295	200	165	130x2	60	142	-	30	107,5	190	M10	M10	M12	132	365	13,0	58	90	35	60	85	M10	37,0 kg	2,10 kg

W¹ = standard shaft

0 **Choice of guide body profile:**
(0) Standard **(2)** corrosion-protected guide rods and screws
(4) expanded corrosion-protected version (depending on the availability of components)

0 **Choice of carriages:**

(0)




(1)



Size	Version 1	
	Q	L
60	184	306
60S	214	336
80	210	391
80S	234	415
100	316	546
125	389	649

0 **Drive version:**



The standard version 0 is supplied with 4 flush mounted shafts.

Belt table

Code No.		Size	Belt	mm/rev.	Number of teeth
0	**4**	**60 (S)**	5M 25	80	16
0	**4**	**80 (S)**	5M 25	110	22
0	**9**	**100**	8M 48	144	18
0	**9**	**125**	8M 50	192	24

Shaft dimensions

Size	Shaft ø h6 x length	Key
60 (S)	14 x 35	5x5x28
80 (S)	18 x 45	6x6x40
100	22 x 45	6x6x40
125	30 x 55	8x7x50

Basic length + stroke = total length


ELHZ	60	0	0	0	0	0	4	1	01500
Pos.		1	2	3	4	5	6	7	

For combination kits and connecting elements refer to chapter 2.2

Sample ordering code:
ELHZ 60, with standard body profile, standard carriage and 4 flush mounted shafts, 1210 mm stroke.

Positioning system ELVZ 60, 60S, 80, 80S, 100, 125

Internal belt drive **Specifications**




Fraunhofer IPA TESTED DEVICE Linearreinheit ELVZ 60

Function:
This linear unit consists of an aluminium square profile with integrated, hardened steel guide rods. The carriage, which has internal linear ball bearings that can be adjusted free of play, is driven along the guide rods by a toothed belt. Toothed pulley has maintenance-free ball bearings. Belt tension can be readjusted by a simple screw adjustment device in the carriage. This device can also be used for symmetrical adjustment of two or more linear units running parallel.
This linear unit is suitable for application in clean rooms of clean-room classification 1.000 (corresponding to US Fed. Standard 209 E).

Fitting position: As required. Max. length 3.000 mm without joints.
Carriage mounting: By T-slots.
Unit mounting: By tapped holes or tapped holes in the bearing block, mounting sets.
Belt type: HTD with steel reinforcement, no backlash when changing direction, repeatability ± 0,1 mm.

Forces and torques



Size	ELVZ 60		ELVZ 60 S		ELVZ 80		ELVZ 80 S		ELVZ 100		ELVZ 125	
Forces/Torques	static	dynamic	static	dynamic	static	dynamic	static	dynamic	static	dynamic	static	dynamic
F_x (N)	700	580	700	580	1000	840	1000	840	3100	2600	5000	4950
F_y (N)	3000	2000	4100	3100	3000	2000	4600	3600	8000	6500	12000	9000
F_z (N)	1700	1100	2160	1600	1700	1100	3000	1800	3600	2200	6000	4500
M_x (Nm)	67	43	88	65	90	55	170	140	300	230	600	450
M_y (Nm)	90	70	190	140	110	80	270	230	400	270	750	600
M_z (Nm)	120	100	230	170	150	120	300	220	750	500	1350	1150

All forces and torques relate to the following:
existing values / table values

$$\frac{Fy}{Fy_{dyn}} + \frac{Fz}{Fz_{dyn}} + \frac{Mx}{Mx_{dyn}} + \frac{My}{My_{dyn}} + \frac{Mz}{Mz_{dyn}} \leq 1$$

No-load torque					
Nm	0,5	0,5	0,8	1,2	1,2	1,6
Speed					
(m/s) max	3	4	4	4	5	6
Tensile force					
permanent (N)	700	700	1000	1000	3100	5000
0,2 s (N)	800	800	1150	1150	3400	5450
Geometrical moments of inertia of aluminium profile					
I_x mm⁴	6,79x10⁵	6,79x10⁵	18,99x10⁵	18,99x10⁵	44,4x10⁵	101,5x10⁵
I_y mm⁴	6,97x10⁵	6,97x10⁵	18,97x10⁵	18,97x10⁵	44,8x10⁵	101,5x10⁵
E-Modulus N/mm²	70000	70000	70000	70000	70000	70000

For life-time calculation of rollers use our homepage.


Driving torque:

$$M_a = \frac{F * P * S_i}{2000 * \pi} + M_n$$

$$P_a = \frac{M_a * n}{9550}$$

F = force (N)
P = pulley action perimeter (mm)
Si = safety factor 1,2 ... 2
M_n = no-load torque (Nm)
n = rpm pulley (min^{-1})
M_a = driving torque (Nm)
P_a = motor power (KW)

Deflection:




$$f = \frac{F * L^3}{E * I * 192}$$


f = deflection (mm)
F = load (N)
L = free length (mm)
E = elastic modulus 70000 (N/mm^2)
I = second moment of area (mm^4)


BAHR Modultechnik

Positioning system ELVZ 60, 60S, 80, 80S, 100, 125

Dimensions (mm)









*For slide nuts refer to chapter 2.2 page 2

Increasing the carriage length will increase the basic length by the same amount.


Size ❒	Basic length L	A	B	C	D ± 0,05	E	F	G	H	J	K	MM for	NN for	OO for	P	Q	T	U	V - 0,05	W¹	X	Y	Z	Basic weight	Weight per 100 mm
ELVZ 60	290	144	96	82	62x1	30	69	–	-	49	90	-	M 8	M 8	59	168	8,5	23	37	14	30	36	M 6	4,8 kg	0,62 kg
ELVZ 60S	315	170	108	82	62x1	30	69	–	-	53	94	-	M 8	M 8	59	194	8,5	23	37	14	30	36	M 6	5,8 kg	0,62 kg
ELVZ 80	375	170	117	102	80x1	40	88	10	30	70	121	M 6	M10	M10	90	194	8,5	38	47	18	40	50	M 8	10,0 kg	1,00 kg
ELVZ 80S	395	190	126	102	80x1	40	88	12,5	30	71	122	M 6	M10	M 8	90	214	8,5	38	47	18	40	50	M 8	11,0 kg	1,00 kg
ELVZ 100	530	230	155	130	110x1	50	112	-	29	89	154	M10	M10	M10	110	300	10,5	45	68	19	50	64	M10	24,0 kg	1,60 kg
ELVZ 125	630	295	200	165	130x2	60	142	-	30	107,5	190	M10	M10	M12	130	365	13	58	90	35	60	85	M10	37,0 kg	2,10 kg

W¹ = standard shaft

1 **(1)** Belt connection right  **(2)** Belt connection left 

0 **Choice of guide body profile:**
(0) Standard **(2)** corrosion-protected guide rods and screws
(4) expanded corrosion-protected version (depending on the availability of components)


0 **Choice of carriages:**

(0) 

(1) 

Size	Version 1	
	Q	L
60	184	306
60S	214	336
80	210	391
80S	234	415
100	316	546
125	389	649

0 **Drive version:**



The standard version 0 is supplied with 4 flush mounted shafts.

Belt table

Code No.		Size	Belt	mm/rev.	Number of teeth
0	**4**	**60 (S)**	5M 25	80	16
0	**4**	**80 (S)**	5M 25	110	22
0	**9**	**100**	8M 48	144	18
0	**9**	**125**	8M 50	192	24

Shaft dimensions

Size	Shaft ø h6 x length	Key
60 (S)	14 x 35	5x5x28
80 (S)	18 x 45	6x6x40
100	22 x 45	6x6x40
125	30 x 55	8x7x50

Basic length + stroke = total length

ELVZ	60	1	0	0	0	0	4	1	01500
Pos.		1	2	3	4	5	6	7	


For combination kits and connecting elements refer to chapter 2.2


Sample ordering code:
ELVZ 60 with belt connection right, standard body profile, standard carriage and 4 flush mounted shafts, 1210 mm stroke


Positioning system ELVZ 60, 60S, 80, 80S, 100, 125

Internal belt drive with two carriages moving in opposite directions

Dimensions (mm)








*For slide nuts refer to chapter 2.2 page 2

Increasing the carriage length will increase the basic length by the same amount

Size ❒	Basic length L	A	B	C	D ± 0,05	E	F	G	H	J	K	MM for	NN for	OO for	P	Q	T	U	V - 0,05	W¹	X	Y	Z	Basic weight	Weight per 100 mm
ELVZ 60	460	144	96	82	62x1	30	69	–	–	49	90	–	M 8	M 8	59	168	8,5	23	37	14	30	36	M 6	6,5 kg	0,62 kg
ELVZ 60S	510	170	108	82	62x1	30	69	–	–	53	94	–	M 8	M 8	59	194	8,5	23	37	14	30	36	M 6	8,5 kg	0,62 kg
ELVZ 80	570	170	117	102	80x1	40	88	10	30	70	121	M 6	M10	M10	90	194	8,5	38	47	18	40	50	M 8	13,0 kg	1,00 kg
ELVZ 80S	610	190	123	102	80x1	40	88	12,5	30	71	122	M 6	M10	M 8	90	214	8,5	38	47	18	40	50	M 8	15,0 kg	1,00 kg
ELVZ 100	830	230	155	130	110x1	50	112	–	29	89	154	M10	M10	M10	110	300	10,5	45	68	19	50	64	M10	31,0 kg	1,60 kg
ELVZ 125	990	295	200	165	130x2	60	142	–	30	107,5	190	M10	M10	M12	130	365	13	58	90	35	60	85	M10	50,5 kg	2,10 kg

W¹ = standard shaft

7 **(7)** Belt connection right  **(8)** Belt connection left 

0 **Choice of guide body profile:**
(0) Standard **(2)** corrosion-protected guide rods and screws
(4) expanded corrosion-protected version (depending on the availability of components)


0 **Choice of carriages:**

(0) 

(1) 

Size	Version 1	
	Q	L
60	184	492
60S	214	542
80	210	602
80S	234	650
100	316	862
125	389	1038

0 **Drive version:**



The standard version 0 is supplied with 4 flush mounted shafts.

Belt table

Code No.		Size	Belt	mm/rev.	Number of teeth
0	**4**	**60 (S)**	5M 25	80	16
0	**4**	**80 (S)**	5M 25	110	22
0	**9**	**100**	8M 48	144	18
0	**9**	**125**	8M 50	192	24

Shaft dimensions

Size	Shaft ø h6 x length	Key
60 (S)	14 x 35	5x5x28
80 (S)	18 x 45	6x6x40
100	22 x 45	6x6x40
125	30 x 55	8x7x50

Basic length + stroke = total length


ELVZ	60	7	0	0	0	0	4	1	01500
Pos.		1	2	3	4	5	6	7	

For combination kits and connecting elements refer to chapter 2.2

Sample ordering code:
ELVZ 60 right-/left-hand with belt connection right, standard body profile, standard carriage and 4 flush mounted shafts, 1040 mm stroke


Function and possibilities of variation

ELZT belt drive unit



Positioning system ELFZ 60S, 80S, 100, 125


Specifications



Function:
This special lifting unit consists of an aluminium square profile with hardened steel guide rods. The carriages, which have internal linear ball bearings that can be adjusted free of play, are driven along the guide rods by a timing belt. The rotating timing belt pulleys have maintenance-free ball bearings. One rotation of the drive pulley complies with 1/2 linear circumference of the drive pulley. Belt tension can be readjusted by a simple tensioning device in one of the carriages. This device can also be used for symmetrical adjustment of two or more linear units running parallel.

Fitting position: As required. Max. length without joints 6.000 mm.
Carriage mounting: By T-slots.
Unit mounting: By T-slots or tapped holes in the bearing blocks, or mounting sets.
Belt type: HTD with steel reinforcement, no backlash when changing direction, repeatability ± 0,1 mm.

Forces and torques



Size	ELFZ 60S		ELFZ 80S		ELFZ 100		ELFZ 125	
Forces/Torques	static	dynamic	static	dynamic	static	dynamic	static	dynamic
F_x (N)	3600	3200	6200	5400	8700	7600	12000	10400
F_y (N)	8200	6200	9200	7200	16000	13000	24000	18000
F_z (N)	4320	3200	6000	3600	7200	4400	12000	9000
M_x (Nm)	176	130	340	280	600	460	1200	900
M_y (Nm)	380	280	540	460	800	540	1500	1200
M_z (Nm)	460	340	600	440	1500	1000	2700	2300
All forces and torques relate to the following: existing values / table values: $\frac{Fy}{Fy_{dyn}} + \frac{Fz}{Fz_{dyn}} + \frac{Mx}{Mx_{dyn}} + \frac{My}{My_{dyn}} + \frac{Mz}{Mz_{dyn}} \leq 1$								
No-load torque								
Nm	1,3		1,5		2		2	
Speed								
(m/s) max	4		4		4		4	
Drive torque								
max (Nm)	48		120		386		500	
Geometrical moments of inertia of aluminium profile								
I_x mm^4	6,79x10^5		1,89x10^6		4,44x10^6		10,15x10^6	
I_y mm^4	6,9710^5		1,8910^6		4,48x10^6		10,15x10^6	
E-Modulus N/mm^2	70000		70000		70000		70000	

For life-time calculation of rollers use our homepage.

Driving torque:


$$M_a = \frac{F * P * S_i}{2000 * \pi * 2} + M_n$$

$$P_a = \frac{M_a * n}{9550}$$

F = force (N)
P = pulley action perimeter (mm)
Si = safety factor 1,2 ... 2
M_n = no-load torque (Nm)
n = rpm pulley (min^{-1})
M_a = driving torque (Nm)
P_a = motor power (KW)

Deflection:


$$f = \frac{F * L^3}{E * I * 192}$$




f = deflection (mm)
F = load (N)
L = free length (mm)
E = elastic modulus 70000 (N/mm^2)
I = second moment of area (mm^4)


Positioning system ELFZ 60S, 80S, 100, 125

Dimensions (mm)





Functional principle on page 3.1 | 40



*For slide nuts refer to chapter 2.2 page 2

Increasing the carriage length will increase the basic length by the same amount.

Size ❐	Basic length L	A	B	C	D - 0,05	E	F	G	H	I	J	K	MM for	M	N	OO for	P	Q	R	S	T	U	V	Basic weight	Weight per 100 mm
ELFZ 60S	410	170	38	108	68	97	60	102	100	-	53	106	-	M8	180	M8	97	214	6x6x40	18x45	M8	97	60	23,1 kg	0,64 kg
ELFZ 80S	580	190	60	154	90	135	80	139	130	12,5	71	142	M6	M10	270	M 8	130	315	8x7x40	30x45	M10	130	70	51 kg	1,20 kg
ELFZ 100	530	230	62	170	110	150	100	143	160	29	89	178	M10	M10	310	M10	77	365	12x8x50	40x55	M10	150	80	69 kg	1,80 kg
ELFZ 125	560	295	62	200	110	180	100	139	180	30	107,5	218	M10	M12	310	M12	92	365	12x8x50	40x55	M10	186	89	87,5 kg	2,70 kg

0 **Choice of guide body profile:**
(0) Standard **(2)** corrosion-protected guide rods and screws
(4) expanded corrosion-protected version (depending on the availability of components)

0 **Choice of carriages:**

(0)




(1)



Size	Version 1	
	Q	L
60S	380	580
80S	489	750
100	575	740
125	640	830

1 **Drive version:**



Belt table

Code No.		Size	Belt	mm/rev. ≈ linear	Number of teeth
0	**3**	**60S**	8M30	192 ≈ 96	24
0	**4**	**80S**	8M50	256 ≈128	32
0	**7**	**100**	8M70	304 ≈152	38
0	**9**	**125**	8M100	304 ≈152	38

Shaft dimensions

Size	Shaft ø h6 x length	Key
60S	18 x 45	6x6x40
80S	30 x 45	8x7x40
100	40 x 55	12x8x50
125	40 x 55	12x8x50

Basic length + stroke = total length

ELFZ	125	0	0	0	1	0	9	1	01500
Pos.	1	2	3	4	5	6	7		


For combination kits and connecting elements refer to chapter 2.2

Sample ordering code:
ELFZ 125 with standard body profile, standard carriage, shaft Pos. 1, 940 mm stroke

Positioning system ELFZ Ex 60S, 80S, 100, 125

Specifications

ATEX 2014/34/EU
Ex II 2G Ex h IIB T4 Gb
Ex II 3D Ex h IIIB T125 °C Dc




Function:
Like ELFZ. The positioning system is suitable for use according to the intended purpose in potentially explosive areas (see ATEX 95 marking). An operating manual is included in the scope of delivery. The system is certified for the following areas:

ATEX 2014/34/EU II 2G Ex h IIB T4 Gb:
All application areas except for underground mining. Gas atmosphere category 2, explosion protection category: protection due to secure construction (design security). Equipment group IIB. Temperature class T4=135 °C

ATEX 2014/34/EU II 3D Ex h IIIB T125 °C Dc:
All application areas except for underground mining. Dust atmosphere category 3. Maximum permissible surface temperature: 125 °C.

Fitting position: As required. Max. length without joints 3.000 mm.
Carriage mounting: By T-slots.
Unit mounting: By T-slots or tapped holes in the bearing blocks, or mounting sets.
Belt type: HTD with steel reinforcement, no backlash when changing direction, repeatability ± 0,1 mm.

Forces and torques



Size	ELFZex 60S		ELFZex 80S		ELFZex 100		ELFZex 125	
Forces/Torques	static	dynamic	static	dynamic	static	dynamic	static	dynamic
F_x (N)	1800	1550	3000	2600	4200	3650	6000	5200
F_y (N)	3820	3056	4438	3550	6200	4960	9960	7968
F_z (N)	1870	1496	1052	842	1292	1043	2190	1752
M_x (Nm)	104	82	134	108	202	162	440	352
M_y (Nm)	132	106	154	140	272	218	560	448
M_z (Nm)	274	220	364	292	652	520	1272	1018
All forces and torques relate to the following: existing values / table values $\frac{Fy}{Fy_{dyn}} + \frac{Fz}{Fz_{dyn}} + \frac{Mx}{Mx_{dyn}} + \frac{My}{My_{dyn}} + \frac{Mz}{Mz_{dyn}} \leq 1$								
No-load torque								
Nm	1,2		1,5		2		2	
Speed								
(m/s) max	1		1		1		1	
Drive torque								
max (Nm)	27		62		101		145	
Geometrical moments of inertia of aluminium profile								
I_x mm⁴	6,79x10⁵		1,89x10⁶		4,44x10⁶		10,15x10⁶	
I_y mm⁴	6,97x10⁵		1,89x10⁶		4,48x10⁶		10,15x10⁶	
E-Modulus N/mm²	70000		70000		70000		70000	

For life-time calculation of rollers use our homepage.


Driving torque:

$$M_a = \frac{F * P * S_i}{2000 * \pi * 2} + M_n$$

$$P_a = \frac{M_a * n}{9550}$$

F = force (N)
P = pulley action perimeter (mm)
Si = safety factor 1,2 ... 2
M_n = no-load torque (Nm)
n = rpm pulley (min^{-1})
M_a = driving torque (Nm)
P_a = motor power (KW)

Deflection:





$$f = \frac{F * L^3}{E * I * 192}$$

f = deflection (mm)
F = load (N)
L = free length (mm)
E = elastic modulus 70000 (N/mm^2)
I = second moment of area (mm^4)


Positioning system ELFZ Ex 60S, 80S, 100, 125

Dimensions (mm)





ATEX 2014/34/EU
Ⓔx II 2G Ex h IIB T4 Gb
Ⓔx II 3D Ex h IIIB T125 °C Dc



3.1

*For slide nuts refer to chapter 2.2 page 2

Increasing the carriage length will increase the basic length by the same amount.

Size ❒	Basic length L	A	B	C	D - 0,05	E	F	G	H	I	J	K	MM for	M	N	OO for	P	Q	R	S	T	U	V	Basic weight	Weight per 100 mm
ELFZex 60S	430	170	38	108	68	97	60	102	100	-	53	106	-	M8	180	M8	97	214	6x6x40	18x45	M8	97	60	23,2 kg	0,64 kg
ELFZex 80S	600	190	60	154	90	135	80	139	130	12,5	71	142	M6	M10	270	M 8	130	315	8x7x40	30x45	M10	130	70	51 kg	1,20 kg
ELFZex 100	560	230	62	170	110	150	100	143	160	29	89	178	M10	M10	310	M10	77	365	12x8x50	40x55	M10	150	80	69 kg	1,80 kg
ELFZex 125	590	295	62	200	110	180	100	139	180	30	107,5	218	M10	M12	310	M12	92	365	12x8x50	40x55	M10	186	89	87,5 kg	2,70 kg

0 **Choice of guide body profile:**
(0) Standard **(2)** corrosion-protected guide rods and screws

0 **Choice of carriages:**

(0)




(1)



Size	Version 1	
	Q	L
60S	380	600
80S	489	770
100	575	770
125	640	860

1 **Drive version:**



Belt table

Code No.		Size	Belt	mm/rev. ≈ linear	Number of teeth
0	**3**	**60S**	8M30	192 ≈ 96	24
0	**4**	**80S**	8M50	256 ≈ 128	32
0	**7**	**100**	8M70	304 ≈ 152	38
0	**9**	**125**	8M100	304 ≈ 152	38

Shaft dimensions

Size	Shaft ø h6 x length	Key
60S	18 x 45	6x6x40
80S	30 x 45	8x7x40
100	40 x 55	12x8x50
125	40 x 55	12x8x50

Basic length + stroke = total length


ELFZex	125	0	0	0	1	0	9	1	01500
Pos.		1	2	3	4	5	6	7	

For combination kits and connecting elements refer to chapter 2.2


Sample ordering code:
ELFZ 125 with standard body profile, standard carriage, shaft Pos. 1, 910 mm stroke

Positioning system ELZU 30, 40, 60, 60S, 80, 80S, 100

Surface portal **Specifications**



Function:
Surface portal, consisting of 2 Y-axes and 1 X-axis, driven by one rotating belt. This belt runs around different deflection pulleys. Positioning is achieved by two motors. The coordinate is diagonal to the deflection points of the Y-axis.
Advantage: Only small weights are moved, thus enabling high accelerations to be achieved.



Forces and torques

Fitting position: As required. Max. length and width 3.000 mm.
Carriage mounting: By T-slots.
Unit mounting: By T-slots or tapped holes in the bearing block, mounting sets.
Belt type: HTD with steel reinforcement, no backlash when changing direction, repeatability: ± 0,1 mm.

Size	ELZU 30		ELZU 40		ELZU 60		ELZU 60 S		ELZU 80		ELZU 80 S		ELZU 100	
Forces/Torques	static	dynamic	static	dynamic	static	dynamic	static	dynamic	static	dynamic	static	dynamic	static	dynamic
F_x (N)	200	180	390	350	894	800	894	800	1900	1800	1900	1800	4000	3800
F_y (N)	90	60	1200	700	3000	2000	4100	3100	3000	2000	4600	3600	8000	6500
F_z (N)	90	60	900	650	1700	1100	2160	1600	1700	1100	3000	1800	3600	2200
M_x (Nm)	10	5	25	20	67	43	88	65	90	55	170	140	300	230
M_y (Nm)	13	6	32	18	90	70	190	140	110	80	270	230	400	270
M_z (Nm)	14	7	35	25	120	100	230	170	150	120	300	220	750	500
All forces and torques relate to the following: existing values / table values $\frac{Fy}{Fy_{dyn}} + \frac{Fz}{Fz_{dyn}} + \frac{Mx}{Mx_{dyn}} + \frac{My}{My_{dyn}} + \frac{Mz}{Mz_{dyn}} \leq 1$														
No-load torqe														
Nm	0,2		0,6		1,2		1,2		1,8		1,8		2,6	
Speed														
(m/s) max	2		4		5		5		6		6		8	
Tensile force														
permanent (N)	200		390		900		900		1900		1900		3600	
0,2 s (N)	280		480		1000		1000		2090		2090		4000	
Geometrical moments of inertia of aluminium profile														
I_x mm⁴	4,09x10⁴		1,32x10⁵		6,79x10⁵		6,79x10⁵		18,99x10⁵		18,99x10⁵		44,4x10⁵	
I_y mm⁴	4,00x10⁴		1,34x10⁵		6,97x10⁵		6,97x10⁵		18,97x10⁵		18,97x10⁵		44,8x10⁵	
E-Modulus N/mm²	70000		70000		70000		70000		70000		70000		70000	

For life-time calculation of rollers use our homepage.

Driving torque:


$$M_a = \frac{F * P * S_i}{2000 * \pi} + M_n$$

$$P_a = \frac{M_a * n}{9550}$$

F = force (N)
P = pulley action perimeter (mm)
Si = safety factor 1,2 ... 2
M_n = no-load torque (Nm)
n = rpm pulley (min^{-1})
M_a = driving torque (Nm)
P_a = motor power (KW)

Deflection:


$$f = \frac{F * L^3}{E * I * 192}$$



f = deflection (mm)
F = load (N)
L = free length (mm)
E = elastic modulus 70000 (N/mm^2)
I = second moment of area (mm^4)

Positioning system ELZU 30, 40, 60, 60S, 80, 80S, 100

Dimensions (mm)





*For slide nuts refer to chapter 2.2 page 2

Size ❒	Basic length		A	B	C	D - 0,05	E	F	G	H	I	J	K	MM for	N for	OO for	P	Qx	Qy	T	V	X	Y	Basic weight	Weight per 100 mm
	Lx	Ly																							
ELZU 30	240	210	70	56	42	28	13	25	-	-	27	44	47	-	M 5	M 6	36	82	126	M 5	74	16	16	6,3 kg	0,13 kg
ELZU 40	304	250	100	66	58	37	18	32	-	-	26	58	64	-	M 6	M 6	49	122	147	M 5	90	20,5	20,5	6,8 kg	0,24 kg
ELZU 60	426	330	144	96	80	47	30	42	-	-	33	82	90	-	M 8	M 8	59	168	210	M 6	123	27	26	14,7 kg	0,62 kg
ELZU 60S	450	330	170	108	80	47	30	42	-	-	33	82	94	-	M 8	M 8	59	194	210	M 6	127	27	26	17,7 kg	0,62 kg
ELZU 80	535	435	170	117	100	68	40	60	10	30	44	110	121	M 6	M10	M10	90	194	244	M 8	165	39	38	31,0 kg	1,00 kg
ELZU 80S	555	455	190	126	100	68	40	60	12,5	30	44	110	122	M6	M10	M 8	90	214	264	M 8	166	39	38	32,0 kg	1,00 kg
ELZU 100	758	590	230	155	130	90	50	80	-	29	69	135	154	M10	M12	M10	110	300	360	M10	223	50	50	47,3 kg	1,40 kg

0 **Choice of guide body profile:**
(0) Standard **(2)** corrosion-protected guide rods and screws
(4) expanded corrosion-protected version (depending on the availability of components)

0 **Choice of carriages:**

(0)



(1)



(2)




Size	Version 1				Version 2			
	Qx	Lx	Qy	Ly	Qx	Lx	Qy	Ly
30	94	252	126	210	94	252	138	222
40	138	320	147	250	138	320	163	266
60	184	442	210	330	184	442	226	346
60S	214	468	210	330	214	468	230	350
80	210	551	244	435	210	551	260	451
80S	234	575	264	455	234	575	284	475
100	316	774	360	590	316	774	376	606

0 **Drive version:**


(0)



(1)



(2)



The standard version is supplied without shaft. A shaft can be retrofitted by inserting it into the pulley bore and securing it with 2 locking rings.

Belt table

Code No.		Size	Belt	mm/rev.	Number of teeth
0	**1**	**30**	3M12	75	25
0	**3**	**40**	5M15	100	20
0	**4**	**60 (S)**	5M25	130	26
0	**7**	**80 (S)**	8M30	192	24
0	**9**	**100**	8M50	256	32

Shaft dimensions / Coupling claw

Size	Shaft ø h6 x length	Key	Coupling
30	6 x 15	2x2x12	7
40	10 x 27	3x3x25	9
60 (S)	14 x 35	5x5x28	14
80 (S)	18 x 45	6x6x40	19
100	22 x 45	6x6x40	24

ELZU	**60**	**7**	**0**	**0**	**0**	**0**	**4**	**1**	**01500**
ELZU	**60**	**8**	**0**	**0**	**0**	**0**	**4**	**1**	**00700**
Pos.	1	2	3	4	5	6	7		


X-Axis Basic length + stroke = total length
Y-Axes Basic length + stroke = total length

For combination kits and connecting elements refer to chapter 2.2

Sample ordering code:
ELZU 60 with standard body profile, standard carriage, coupling claw on one side, stroke X = 1074 / Y = 370 mm

Positioning system ELZU 60 (S) W


Surface portal



Function:
Surface gantry consisting of two Y axes and one X axis. The unit is driven by a rotating belt, which remains connected through various deflection points. Due to the rectangular profile high torques and loads can be taken up. In addition, a very high stability and low deflection are ensured for long axis systems. The belt tension can be easily readjusted via a tensioning device within the carriage. The movement is realised by two motors. The coordinate lies diagonal to the deflection points of the X axis. Advantage: Only small masses are moved and thus it is possible to achieve high accelerations.

Fitting position: As required. Max. length and width 3.000 mm.
Carriage mounting: By T-slots.
Unit mounting: By T-slots or tapped holes in the bearing block, mounting sets.
Belt type: HTD with steel reinforcement, no backlash when changing direction, repeatability: ± 0,1 mm.

Forces and torques



Size	60		60 S	
Forces/Torques	static	dynamic	static	dynamic
F_x (N)	894	800	894	800
F_y (N)	3000	2000	4100	3100
F_z (N)	1700	1100	2160	1600
M_x (Nm)	67	43	88	65
M_y (Nm)	90	70	190	140
M_z (Nm)	120	100	230	170
All forces and torques relate to the following: existing values / table values $\frac{Fy}{Fy_{dyn}} + \frac{Fz}{Fz_{dyn}} + \frac{Mx}{Mx_{dyn}} + \frac{My}{My_{dyn}} + \frac{Mz}{Mz_{dyn}} \leq 1$				
No-load torqe				
Nm	1,2		1,2	
Speed				
(m/s) max	5		5	
Tensile force				
permanent (N)	900		900	
0,2 s (N)	1000		1000	
Geometrical moments of inertia of aluminium profile - Y-Axis				
I_x mm⁴	6,79x10⁵		6,79x10⁵	
I_y mm⁴	6,97x10⁵		6,97x10⁵	
E-Modul N/mm²	70000		70000	
Geometrical moments of inertia of aluminium profile - X-Axis				
I_x mm⁴	2,8 x 10⁶		2,8 x 10⁶	
I_y mm⁴	9,6 x 10⁵		9,6 x 10⁵	
E-Modulus N/mm²	70000		70000	

For life-time calculation of rollers use our homepage.

Driving torque:


$$M_a = \frac{F * P * S_i}{2000 * \pi} + M_n$$

$$P_a = \frac{M_a * n}{9550}$$

F = force (N)
P = pulley action perimeter (mm)
Si = safety factor 1,2 ... 2
M_n = no-load torque (Nm)
n = rpm pulley (min^{-1})
M_a = driving torque (Nm)
P_a = motor power (KW)

Deflection:


$$f = \frac{F * L^3}{E * I * 192}$$



f = deflection (mm)
F = load (N)
L = free length (mm)
E = elastic modulus 70000 (N/mm²)
I = second moment of area (mm⁴)

Positioning system ELZU 60 (S) W

Dimensions (mm)





*For slide nuts refer to chapter 2.2 page 2

Size	Basic length		A	B	C	D - 0,05	E	F	G	H	I	J	K	MM for	N for	OO for	P	Qx	Qy	T	V	X	Y	Basic weight	Weight per 100 mm
	Lx	Ly																							
60 **W**	424	400	70	56	80	47	30	42	-	-	33	82	90	-	M 8	M 8	59	168	279	123	27	26	16	14,9 kg	0,9 kg
60(S) **W**	450	400	100	66	80	47	30	42	-	-	33	82	94	-	M 8	M 8	59	218	279	127	27	26	20,5	17,9 kg	0,9 kg

0 **Choice of guide body profile:**
(0) Standard **(2)** corrosion-protected guide rods and screws
(4) expanded corrosion-protected version (depending on the availability of components)

0 **Choice of carriages:**

(0)



(1)



(2)




Size	Version 1				Version 2			
	Qx	Lx	Qy	Ly	Qx	Lx	Qy	Ly
60	192	446	279	397	192	478	226	346
60 (S)	218	472	279	397	218	496	299	417

0 **Drive version:**


(0)



(1)



(2)



The standard version is supplied without shaft. A shaft can be retrofitted by inserting it into the pulley bore and securing it with 2 locking rings.

Belt table

Code No.		Size	Belt	mm/rev.	Number of teeth
0	**4**	**60 (S)**	5M25	130	26

Shaft dimensions / Coupling claw

Size	Shaft ø h6 x length	Key	Coupling
60 (S)	14 x 35	5x5x28	14


ELZU	**60 W**	**7**	**0**	**0**	**0**	**0**	**4**	**1**	**01500**
ELZU	**60 W**	**8**	**0**	**0**	**0**	**0**	**4**	**1**	**00700**
	Pos.	1	2	3	4	5	6	7	

X-Axis Basic length + stroke = total length
Y-Axes Basic length + stroke = total length

For combination kits and connecting elements refer to chapter 2.2

Sample ordering code:
ELZU 60 W, standard body profile, standard carriage, coupling claw on one side, stroke X = 1074 / Y = 370 mm


Positioning system ELZI 30, 40, 60



Function:
X/Z gantry consisting of a double guide in the horizontal X level and a vertical Z axis. The belt is fixed and tensioned at the load end. The unit is driven by a rotating belt, which remains connected through various deflection points. The movement is realised by two motors. The coordinate lies diagonal to the deflection points of the X axes and the Z axis.
Advantage: Only small masses are moved and thus it is possible to achieve high accelerations.

Fitting position: As required, max. length for x-axes 2000mm, for z-axis 1000mm
Unit mounting: By tapped holes in the bearing block, mounting sets.
Belt type: HTD with steel reinforcement, no backlash when changing direction, repeatability: ± 0,1 mm.

Forces and torques



Size	ELZI 30		ELZI 40		ELZI 60	
Forces/torques	static	dynam.	static	dynam.	static	dynam.
F_x (N)	390	350	894	800	1900	1800
F_z (N)	180	160	1200	900	1600	1200
M_x (Nm)	15	9	25	20	67	43
M_y (Nm)	20	13	32	22	90	70
M_z (Nm)	23	18	35	25	120	100
All forces and torques relate to the following: existing values / table values $\frac{Fy}{Fy_{dyn}} + \frac{Fz}{Fz_{dyn}} + \frac{Mx}{Mx_{dyn}} + \frac{My}{My_{dyn}} + \frac{Mz}{Mz_{dyn}} \leq 1$						
No-load torque horizontal movement						
Nm	2 x 0,4		2 x 0,6		2 x 1,1	
Speed						
(m/s) max	2		4		5	
Tensile force (please use necessarily the Mulco life-time calculation, see Chapter 4.2						
permanent (N)	390		894		1900	
0,2 s (N)	480		1000		2090	
Geometrical moments of inertia of aluminium profile						
I_x mm⁴ (X-/Z-Achse)	0,31x10⁵ / 0,41x10⁵		1,12x10⁵ / 1,32x10⁵		4,06x10⁵ / 6,79x10⁵	
I_y mm⁴ (X-/Z-Achse)	1,70x10⁵ / 0,40x10⁵		7,20x10⁵ / 1,34x10⁵		24,3x10⁵ / 6,97x10⁵	
E-Modulus N/mm²	70000		70000		70000	

For life-time calculation of rollers use our homepage.

Driving torque:


$$M_a = \frac{F * P * S_i}{2000 * \pi} + M_n$$

$$P_a = \frac{M_a * n}{9550}$$

F = force (N)
P = pulley action perimeter (mm)
Si = safety factor 1,2 ... 2
M_n = no-load torque (Nm)
n = rpm pulley (min^{-1})
M_a = driving torque (Nm)
P_a = motor power (KW)

Deflection:


$$f = \frac{F * L^3}{E * I * 192}$$




f = deflection (mm)
F = load (N)
L = free length (mm)
E = elastic modulus 70000 (N/mm^2)
I = second moment of area (mm^4)


Positioning system ELZI 30, 40, 60

Dimensions (mm)





Endpiece for gripper




Size	X-Axie		Z-Axis	
	Profile	moving mass	Profile	moving mass
30	2 x UL40	4,5 kg	EL30	1,0 kg
40	2 x UL60	7,0 kg	EL40	2,4 kg
60	2 X UL80	19,0 kg	EL60	6,5 kg

Size ❒	Basic legth		A	B	C	D -0,05	E	F	G	H	I	J	K	MM for	ø N	OO for	P	Qz	R for	S	T	U	V	X	Y	Z	Basic weight	Weight per 100 mm X-/Z-axis
	Lx	Lz																									
ELZI 30	290	245	137	70	51	47	52	42	42	35	15	114	40	M6	4,2	M6	55	144	M6	60	-	40	112	26,5	62,5	35	5,20 kg	0,32/0,18 kg
ELZI 40	380	290	187	100	70	55	70	55	58	47	20	125	60	M6	6,6	M6	70	165	M8	70	18	60	122	33	80	50	11,5 kg	0,68/0,3 kg
ELZI 60	525	425	262	144	110	90	100	80	82	68	20	192	80	M10	8,5	M8	110	235	M10	100	30	80	198	50	120	80	33,0 kg	1,13/0,67 kg

0 **Choice of guide body profile:**
(0) Standard **(2)** corrosion-protected guide rods and screws
(4) expanded corrosion-protected version (depending on the availability of components)

0 **Drive version:**

(0) **(0)** **(1)** **(2)** **(3)** **(4)**



Belt table

Code No.		Size	Belt	mm/rev.	Number of teeth
0	**3**	**30**	5M15	120	24
0	**4**	**40**	5M25	160	32
0	**6**	**60**	8M30	224	28

Shaft dimensions / Coupling claw

Size	Shaft ø h6 x length	Key	Coupling
30	10x27	3x3x25	9
40	14x35	5x5x28	14
60	22x45	6x6x35	24

X-Axis Basic length + stroke = total length
Y-Axes Basic length + stroke = total length


ELZI	40	0	0	0	0	0	4	1	01500

ELZI	40	1	0	0	0	0	4	1	00700


Pos. 1 2 3 4 5 6 7


Sample ordering code:
ELZI 40, with standard body profile, coupling claw on one side, stroke X = 1120 / Z = 410mm

Possible mounting styles



Operational principle ELFZ





Rack and pinion driven positioning systems ELZA, ELDZA, ELZQ

Positioning system ELZA 40 / ELDZA 60, 60S, 80, 80S, 100


Rack and pinion drive **Specifications**



ELZA 40



ELDZA
60, 60S, 80, 80S, 100




We have been implementing comprehensive model improvement measures so that we are able to offer our products in the segment of toothed rack drives in a more cost-effective and application-oriented way.
New innovative guiding profiles ELDZA have been developed, which can be used effectively in combination with standardized toothed racks. Depending on the specific task (e. g. load, mounting position, service life or cost) it is possible to use different material combinations.

Function:
This unit consists of an aluminium square profile with integrated, hardened steel guide rods. The carriage, which has internal linear ball bearings that can be adjusted free of play, is driven by a rack and pinion. The pinion is equipped with maintenance-free ball bearings.

Fitting position: As required. Max. length without joints 6.000 mm.
Carriage mounting: By T-slots.
Unit mounting: By T-slots and holes in the bearing blocks, mounting sets.
Rack: C45,Steel 1.4305 or plastic (PA 6) possible. Repeatability: ± 0,2 mm.

Forces and torques



Size	ELZA 40		ELDZA 60		ELDZA 60 S		ELDZA 80		ELDZA 80 S		ELDZA 100	
Forces/Torques	static	dynamic	static	dynamic	static	dynamic	static	dynamic	static	dynamic	static	dynamic
F_x (N)	900	750	1500 *	1200 *	1500 *	1200 *	2200 *	1800 *	2200 *	1800 *	2900 *	2500 *
F_y (N)	1200	700	3000	2000	4100	3100	3000	2000	4600	3600	8000	6500
F_z (N)	900	650	1700	1100	2160	1600	1700	1100	3000	1800	3600	2200
M_x (Nm)	25	20	67	43	88	65	90	55	170	140	300	230
M_y (Nm)	32	18	90	70	190	140	110	80	270	230	400	270
M_z (Nm)	35	25	120	100	230	170	150	120	300	220	750	500
All forces and torques related to the following: existing values / table values: $\frac{Fy}{Fy_{dyn}} + \frac{Fz}{Fz_{dyn}} + \frac{Mx}{Mx_{dyn}} + \frac{My}{My_{dyn}} + \frac{Mz}{Mz_{dyn}} \leq 1$												
Speed												
(m/s) max	2		2,5		2,5		3		3		3	
Geometrical moments of inertia of aluminium profile												
I_x mm⁴	1,32x10⁵		4,86x10⁵		4,86x10⁵		18,99x10⁵		18,99x10⁵		44,4x10⁵	
I_y mm⁴	1,34x10⁵		4,87x10⁵		4,87x10⁵		18,97x10⁵		18,97x10⁵		44,8x10⁵	
E-Modulus N/mm²	70000		70000		70000		70000		70000		70000	

** = Depending on materialcombinations (see page 3) Fx values could be different!*
For life-time calculation of rollers use our homepage.


Driving torque:

$$M_a = \frac{F * P * S_i}{2000 * \pi} + M_n$$

$$P_a = \frac{M_a * n}{9550}$$

F = force (N)
P = pulley action perimeter (mm)
Si = safety factor 1,2 ... 2
M_n = no-load torque (Nm)
n = rpm pulley (min^{-1})
M_a = driving torque (Nm)
P_a = motor power (KW)

Deflection:





$$f = \frac{F * L^3}{E * I * 192}$$

f = deflection (mm)
F = load (N)
L = free length (mm)
E = elastic modulus 70000 (N/mm^2)
I = second moment of area (mm^4)

Positioning system ELZA 40 / ELDZA 60, 60S, 80, 80S, 100

Dimensions (mm)





*For slide nuts refer to chapter 2.2 page 2

Increasing the carriage length will increase the basic length by the same amount.

Size ❐	Basic length L	A	B	C	D -0,05	E	F	G	H	I	J	K	KK for	M	MM for	N	NN for	OO for	P	Q	T	V	Basic weight
ELZA 40	150	100	21,5	58	37	18	32	60	56	-	35	6,5	-	47	-	100	M 6	M 6	12	122	M 6	-	2,0 kg
ELDZA 60	205	144	28,0	82	47	30	42	75	63	-	49	8,5	M 6	69	-	130	M 8	M 8	16	168	M 6	-	4,7 kg
ELDZA 60S	230	170	34,5	82	47	30	42	92	63	-	53	8,5	M 6	69	-	150	M 8	M 8	16	194	M 6	10	7,2 kg
ELDZA 80	240	170	39,0	102	68	40	60	105	100	30	70	8,5	-	88	M 6	170	M 10	M 10	20	194	M 8	10	11,9 kg
ELDZA 80S	260	190	39,0	102	68	40	60	105	100	30	71	8,5	-	88	M 6	170	M 10	M 8	20	214	M 8	12,5	12,9 kg
ELDZA 100	360	230	55,3	130	90	50	80	155	120	29	89	10,5	-	112	M 10	240	M 10	M 10	30	300	M 10	-	24,0 kg

0 **Choice of guide body profile:**

(0) Standard

(2) corrosion-protected guide rods and screws *(Version 0 and 2)*

(4) expanded corrosion-protected version *(Version 1 and 3)*
(depending on the availability of components)

ELZA 40		0,35 kg / 100 mm
ELDZA 60	Polyamide rack	0,56 kg / 100 mm
ELDZA 60	Steel rack	0,78 kg / 100 mm
ELDZA 80	Polyamide rack	0,95 kg / 100 mm
ELDZA 80	Steel rack	1,48 kg / 100 mm
ELDZA 100	Polyamide rack	1,48 kg / 100 mm
ELDZA 100	Steel rack	1,99 kg / 100 mm

0 **Choice of carriages:**

(0)



(1)



(2)




(3)



Size	Version 1		Version 2		Version 3	
	Q	L	Q	L	Q	L
40	227	255	138	166	243	271
60	303	340	184	221	319	356
60S	349	386	214	251	369	406
80	369	415	210	256	385	431
80S	389	435	234	280	409	455
100	505	565	316	376	521	581

1 **Drive version:**



Size ❐	Shaft ø h6 x length	Key	Pinion	
			mm/rev.	Modul
40	14 x 30	5x5x28	188,5	1,5
60	18 x 30	6x6x28	251,3	2
60 S	18 x 30	6x6x28	314,2	2
80 (S)	28 x 40	8x7x35	358,0	3
100	28 x 40	8x7x35	508,9	3

0 **Rack/Pinion Version: (ONLY for ELDZA)**

Version	0	1	2	3
Material Rack/Pinion	Steel/Plastic (Standard)	Stainless steel/Plastic	Plastic/Steel	Plastic/Stainless steel

Version 0/1



Version 2/3



ELDZA	60	0	0	0	1	0	3	0	01500
Pos.		1	2	3	4	5	6	7	


1500 Basic length + stroke = total length

For combination kits and connecting elements refer to chapter 2.2

Sample ordering code:
ELDZA 60 with standard body profile, standard carriage, standard shaft , steelpinion, 1295 mm stroke

Positioning system ELZQ 60, 80, 80S


Rack and pinion drive



Function:
This unit consists of an aluminium square profile with integrated, hardened steel guide rods. The carriage, which has internal linear ball bearings that can be adjusted free of play, is driven along the guide rods by a high precision rack. The rack and pinion system is suitable for highly dynamic servo operation and ideal for lifting movements. The pinion has maintenance-free ball bearings. The rack is lubricated by a toothed felt wheel.

Fitting position: As required. Max. length without joints 6.000 mm.
Carriage mounting: By T-slots.
Unit mounting: By T-slots and holes in the bearing block, mounting sets.
Rack: Cf53; h6= hardened and ground; h7 = finely toothed. Repeatability: ± 0,1 mm.

Forces and torques



Size	ELZQ 60 h6		ELZQ 60 h7		ELZQ 80 h6		ELZQ 80 h7		ELZQ 80S h6		ELZQ 80S h7	
Forces/Torques	static	dynamic	static	dynamic	static	dynamic	static	dynamic	static	dynamic	static	dynamic
F_x (N)	1800	1400	940	780	1800	1400	940	780	1800	1400	940	780
F_y (N)	3000	2000	3000	2000	3000	2000	3000	2000	4600	3600	4600	3600
F_z (N)	1700	1100	1700	1100	1700	1100	1700	1100	3000	1800	3000	1800
M_x (Nm)	67	43	67	43	90	55	90	55	170	140	170	140
M_y (Nm)	90	70	90	70	110	80	110	80	270	230	270	230
M_z (Nm)	120	100	120	100	150	120	150	120	300	220	300	220

All forces and torques related to the following:

existing values / table values

$$\frac{Fy}{Fy_{dyn}} + \frac{Fz}{Fz_{dyn}} + \frac{Mx}{Mx_{dyn}} + \frac{My}{My_{dyn}} + \frac{Mz}{Mz_{dyn}} \leq 1$$

Speed						
(m/s) max	4	4	4	4	4	4
Geometrical moments of inertia of aluminium profile						
I_x mm⁴	6,79x10⁵	6,79x10⁵	18,99x10⁵	18,99x10⁵	18,99x10⁵	18,99x10⁵
I_y mm⁴	6,97x10⁵	6,97x10⁵	18,97x10⁵	18,97x10⁵	18,97x10⁵	18,97x10⁵
E-Modulus N/mm²	70000	70000	70000	70000	70000	70000

For life-time calculation of rollers use our homepage.


Driving torque:

$$M_a = \frac{F * P * S_i}{2000 * \pi} + M_n$$

$$P_a = \frac{M_a * n}{9550}$$

F = force (N)
P = pulley action perimeter (mm)
Si = safety factor 1,2 ... 2
M_n = no-load torque (Nm)
n = rpm pulley (min^{-1})
M_a = driving torque (Nm)
P_a = motor power (KW)


Deflection:



$$f = \frac{F * L^3}{E * I * 192}$$

f = deflection (mm)
F = load (N)
L = free length (mm)
E = elastic modulus 70000 (N/mm^2)
I = second moment of area (mm^4)

Positioning system ELZQ 60, 80, 80S



Size 60 with mounting plate on carriage.

*For slide nuts refer to chapter 2.2 page 2

Increasing the carriage length will increase the basic length by the same amount.

Size ❒	Basic length L	A	B	C	D Ø ±0,05	E	G	H	J	K	M	N	NN for	OO for	P	Q	T	Basic weight	Weight per 100 mm
ELZQ 60	230	144	25,5	82	62	30	71,5	42	49	8,5	69	19	M 8	M 8	16	194	M 10	5,0 kg	0,68 kg
ELZQ 80	260	170	25,5	102	80	40	60,5	31	70	8,5	88	25	M 10	M 10	20	214	M 10	11,0 kg	1,19 kg
ELZQ 80S	280	190	25,5	102	80	40	60,5	31	71	8,5	88	13	M 10	M 8	20	234	M 10	12,0 Kg	1,19 kg

0 **Choice of guide body profile:**
(0) Standard **(2)** corrosion-protected guide rods and screws
(4) expanded corrosion-protected version (depending on the availability of components)

0 **Choice of carriages:**

(0)



(1)



(2)




(3)



Size	Version 1		Version 2		Version 3	
	Q	L	Q	L	Q	L
60	338	374	210	246	354	390
80	384	430	230	276	400	446
80S	404	450	254	300	420	466

1 **Drive version:**



Size ❒	Shaft ø h6 x length	Key	Pinion	
			mm/rev.	Modul
60	20 x 29,5	6x6x25	100	1,6
80 (S)	20 x 29,5	6x6x25	100	1,6

0 **Rack and pinion accuracy:**
(0) h7 (standard) **(1)** h6 (hardened and ground, finely toothed)


1500 Basic length + stroke = total length


ELZQ	60	0	0	0	1	0	2	0	01500
Pos.	1		2	3	4	5	6	7	


For combination kits and connecting elements refer to chapter 2.2

Sample ordering code:
ELZQ 60 with standard body profile, standard carriage, position of drive 1, rack and pinion accuracy class h7, 1270 mm stroke

Example for ELZA









ML - Belt driven positioning systems

Positioning system MLZ 60, 60S, 80, 80S, 100

Belt drive






Function:
This linear unit consists of an aluminium square profile with integrated, hardened steel guide rods. The carriage, which has internal linear ball bearings, that can be adjusted free of play, is driven along the guide rods by a timing belt. The advantage of this system is that the belt is guided within the profile, ensuring that the belt is always tight and thus enabling the system to be operated e.g. when lying on its side. The pulleys have maintenance-free ball bearings. Belt tension can be readjusted by a simple screw adjustment device in the carriage. This device can also be used for symmetrical adjustment of two or more linear units running parallel.

Fitting position: As required, max. length 6.000 mm without joints.
Carriage mounting: By T-slots.
Unit mounting: By T-slots or tapped holes in the bearing block, mounting sets.
Belt type: HTD with steel reinforcement, no backlash when changing direction, repeatability: ± 0,1 mm.

Forces and torques



Size	MLZ 60		MLZ 60 S		MLZ 80		MLZ 80 S		MLZ 100	
Forces/Torques	static	dynamic	static	dynamic	static	dynamic	static	dynamic	static	dynamic
F_x (N)	894	800	894	800	1900	1800	1900	1800	4000	3800
F_y (N)	3000	2000	4100	3100	3000	2000	4600	3600	8000	6500
F_z (N)	1700	1100	2160	1600	1700	1100	3000	1800	3600	2200
M_x (Nm)	67	43	88	65	90	55	170	140	300	230
M_y (Nm)	90	70	190	140	110	80	270	230	400	270
M_z (Nm)	120	100	230	170	150	120	300	220	750	500

All forces and torques relate to the following:

existing values / table values

$$\frac{Fy}{Fy_{dyn}} + \frac{Fz}{Fz_{dyn}} + \frac{Mx}{Mx_{dyn}} + \frac{My}{My_{dyn}} + \frac{Mz}{Mz_{dyn}} \leq 1$$

No-load torque					
Nm	0,6	0,7	0,9	1,2	1,4
Speed					
(m/s) max	5	7	6	8	10
Tensile force					
permanent (N)	900	900	1900	1900	4000
0,2 s (N)	1000	1000	2090	2090	4300
Geometrical moments of inertia of aluminium profile					
I_x mm⁴	$4,83x10^5$	$4,83x10^5$	$17,49x10^5$	$17,49x10^5$	$39,4x10^5$
I_y mm⁴	$5,03x10^5$	$5,03x10^5$	$18,02x10^5$	$18,02x10^5$	$43,5x10^5$
E-Modulus N/mm²	70000	70000	70000	70000	70000

For life-time calculation of rollers use our homepage.


Driving torque:

$$M_a = \frac{F * P * S_i}{2000 * \pi} + M_n$$

$$P_a = \frac{M_a * n}{9550}$$

F = force (N)
P = pulley action perimeter (mm)
Si = safety factor 1,2 ... 2
M_n = no-load torque (Nm)
n = rpm pulley (min^{-1})
M_a = driving torque (Nm)
P_a = motor power (KW)

Deflection:




$$f = \frac{F * L^3}{E * I * 192}$$

f = deflection (mm)
F = load (N)
L = free length (mm)
E = elastic modulus 70000 (N/mm^2)
I = second moment of area (mm^4)

Positioning system MLZ 60, 60S, 80, 80S, 100

Dimensions (mm)



*For slide nuts refer to chapter 2.2 page 2


Increasing the carriage length will increase the basic length by the same amount.

Size ❒	Basic length L	A	B	C	D -0,05	E	F	G	H	J	K	MM for	N	OO for	P	Q	T	U	W	X	Y	Basic weight	Weight per 100 mm
MLZ 60	290	144	96	80	47	30	42	-	-	63	79	-	M 8	M 8	59	168	M 6	29,5	36	27	26	4,7 kg	0,6 kg
MLZ 60S	315	170	108	80	47	30	42	-	-	63	83	-	M 8	M 8	59	194	M 6	29,5	30	27	26	5,7 kg	0,6 kg
MLZ 80	375	170	117	100	68	40	60	10	30	93	110	M 6	M 10	M 10	90	194	M 8	47,5	40	45	40	9,6 kg	1,0 kg
MLZ 80 S	395	190	126	100	68	40	60	12,5	30	93	111	M 6	M 10	M 8	90	214	M 8	47,5	40	45	40	10,8 kg	1,0 kg
MLZ 100	530	230	155	130	90	50	80	-	29	110	139	M10	M 12	M10	110	300	M 10	55	50	49	50	22,5 kg	1,55 kg

0 **Choice of guide body profile:**
(0) Standard **(2)** corrosion-protected guide rods and screws
(4) expanded corrosion-protected version (depending on the availability of components)

0 **Choice of carriages:**

(0)




(1)



Size	Version 1	
	Q	L
60	184	306
60S	214	336
80	210	391
80S	234	415
100	316	546

0 **Drive version:**



Version 9 is the same as 0, but with double sided coupling claw.

The standard version is supplied without shaft.

Belt table

Code No.		Size	Belt	mm/rev.	Number of teeth
0	**4**	**60 (S)**	5M25	130	26
0	**7**	**80 (S)**	8M30	176	22
0	**9**	**100**	8M50	224	28

Shaft dimensions / Coupling claw

Size	Shaft ø h6 x length	Key	Coupling
60 (S)	14 x 35	5x5x28	14
80 (S)	18 x 45	6x6x40	19
100	22 x 45	6x6x40	24

Basic length + stroke = total length


MLZ	60	1	0	0	0	0	4	1	01500
	Pos.	1	2	3	4	5	6	7	

For combination kits and connecting elements refer to chapter 2.2

Sample ordering code:
MLZ 60 with standard body profile, standard carriage, coupling claw on one side, 1210 mm stroke.

Positioning system MLN 60, 60S

Nubbed belt drive




5.1

Function:
The guide body consists of an aluminium square profile with lateral, parallel, form-fit, internal hardened steel rods. The guide carriage, which is driven along the shafts by a nobbed belt, moves on the guide body with internal linear ball bearings that are adjustable free of play. The advantage of this system: The belt is guided within the profile, so that the system is independent of the mounting position. The nobbed belt is self-tracking and has a very low operating noise level thanks to its nobs being offset by 45°. Furthermore, it is almost vibration-free in the transition sections.

Fitting position: As required, max. length 6.000 mm without joints.
Carriage mounting: By T-slots.
Unit mounting: By T-slots or tapped holes in the bearing block, mounting sets.
Belt type: N10 with steel reinforcement, no backlash when changing direction, repeatability: ± 0,1 mm.

Forces and torques



Size	60		60 S	
Forces/Torques	static	dynamic	static	dynamic
F_x (N)	1950	1300	1950	1300
F_y (N)	3000	2000	4100	3100
F_z (N)	1700	1100	2160	1600
M_x (Nm)	67	43	88	65
M_y (Nm)	90	70	190	140
M_z (Nm)	120	100	230	170
All forces and torques relate to the following: existing values / table values: $\frac{Fy}{Fy_{dyn}} + \frac{Fz}{Fz_{dyn}} + \frac{Mx}{Mx_{dyn}} + \frac{My}{My_{dyn}} + \frac{Mz}{Mz_{dyn}} \leq 1$				
No-load torque				
Nm	0,6		0,7	
Speed				
(m/s) max	5		7	
Tensile force				
permanent (N)	1050		1050	
0,2 s (N)	1150		1150	
Geometrical moments of inertia of aluminium profile				
I_x mm^4	4,67x10^5		4,67x10^5	
I_y mm^4	5,21x10^5		5,21x10^5	
E-Modulus N/mm^2	70000		70000	

For life-time calculation of rollers use our homepage.

Driving torque:


$$M_a = \frac{F * P * S_i}{2000 * \pi} + M_n$$

$$P_a = \frac{M_a * n}{9550}$$

F	= force	(N)
P	= pulley action perimeter	(mm)
Si	= safety factor 1,2 ... 2	
M_n	= no-load torque	(Nm)
n	= rpm pulley	(min^{-1})
M_a	= driving torque	(Nm)
P_a	= motor power	(KW)


Deflection:

$$f = \frac{F * L^3}{E * I * 192}$$



f = deflection	(mm)
F = load	(N)
L = free length	(mm)
E = elastic modulus 70000	(N/mm^2)
I = second moment of area	(mm^4)

Positioning system MLN 60, 60S



*For slide nuts refer to chapter 2.2 page 2


Increasing the carriage length will increase the basic length by the same amount.

Size ❒	Basic length L	A	B	C	D -0,05	E	F	J	K	N	OO for	P	Q	T	U	W	X	Y	Basic weight	Weight per 100 mm
MLN 60	290	144	96	80	47	30	42	63	79	M 8	M 8	59	168	M 6	29,5	30	27	26	4,7 kg	0,6 kg
MLN 60S	315	170	108	80	47	30	42	63	83	M 8	M 8	59	194	M 6	29,5	30	27	26	5,7 kg	0,6 kg

0 **Choice of guide body profile:**
(0) Standard **(2)** corrosion-protected guide rods and screws
(4) expanded corrosion-protected version (depending on the availability of components)

0 **Choice of carriages:**

(0)




(1)



Size	Version 1	
	Q	L
60	184	306
60S	214	336

0 **Drive version:**



Version 9 is the same as 0, but with double sided coupling claw.

The standard version is supplied without shaft.

Belt table

Code No.		Size	Belt	mm/rev.	Number of teeth
0	**8**	**60 (S)**	Nobbed belt N10	130	13/3

Shaft dimensions / Coupling claw

Size	Shaft ø h6 x length	Key	Coupling
60 (S)	14 x 35	5x5x28	14

MLN	60	1	0	0	0	0	8	1	01500
Pos.	1	2	3	4	5	6	7		


Basic length + stroke = total length

For combination kits and connecting elements refer to chapter 2.2

Sample ordering code:
MLN 60, standard body profile, standard carriage, drive version 0, knobbelt belt, 1210 mm stroke

Positioning system MLZ 60 (S) W

Belt drive




5.1

Function:
The guide body consists of an aluminium square profile with lateral, parallel, form-fit, internal hardened steel rods. The guide carriage, which is driven along the shafts by a timing belt, moves on the guide body with internal linear ball bearings that are adjustable free of play. The advantage of this system: The timing belt is guided within the profile, so that the system is independent of the mounting position. Due to the rectangular profile high torques and loads can be taken up. In addition, a very high stability and low deflection are ensured for long axis systems. The belt tension can be easily readjusted via a tensioning device within the carriage. This device also helps to adjust the symmetry of the carriages in applications where two parallel linear units are used.

Fitting position: As required, max. length 6.000 mm without joints.
Carriage mounting: By T-slots.
Unit mounting: By T-slots or tapped holes in the bearing block, mounting sets.
Belt type: HTD with steel reinforcement, no backlash when changing direction, repeatability: ± 0,1 mm.

Forces and torques



Size	60		60 S	
Forces/Torques	static	dynamic	static	dynamic
F_x (N)	894	800	894	800
F_y (N)	3000	2000	4100	3100
F_z (N)	1700	1100	2160	1600
M_x (Nm)	67	43	88	65
M_y (Nm)	90	70	190	140
M_z (Nm)	120	100	230	170
All forces and torques relate to the following: existing values / table values $\frac{Fy}{Fy_{dyn}} + \frac{Fz}{Fz_{dyn}} + \frac{Mx}{Mx_{dyn}} + \frac{My}{My_{dyn}} + \frac{Mz}{Mz_{dyn}} \leq 1$				
No-load torque				
Nm	0,6		0,7	
Speed				
(m/s) max	5		7	
Tensile force				
permanent (N)	900		900	
0,2 s (N)	1000		1000	
Geometrical moments of inertia of aluminium profile				
I_x mm⁴	2,8 x 10⁶		2,8 x 10⁶	
I_y mm⁴	9,6 x 10⁵		9,6 x 10⁵	
E-Modulus N/mm²	70000		70000	

For life-time calculation of rollers use our homepage.

Driving torque:


$$M_a = \frac{F * P * S_i}{2000 * \pi} + M_n$$

$$P_a = \frac{M_a * n}{9550}$$

F = force (N)
P = pulley action perimeter (mm)
Si = safety factor 1,2 ... 2
M_n = no-load torque (Nm)
n = rpm pulley (min^{-1})
M_a = driving torque (Nm)
P_a = motor power (KW)

Deflection:


$$f = \frac{F * L^3}{E * I * 192}$$



f = deflection (mm)
F = load (N)
L = free length (mm)
E = elastic modulus 70000 (N/mm²)
I = second moment of area (mm⁴)

Positioning system MLZ 60 (S) W

Dimensions (mm)



*For slide nuts refer to chapter 2.2 page 2


Increasing the carriage length will increase the basic length by the same amount.

Size	Basic length L	A	B	C	D -0,05	E	F	G	H	J	K	M	N	OO for	P	Q	T	U	W	X	Y	Z	Basic weight	Weight per 100 mm
MLZ 60 **W**	290	144	96	80	47	30	42	60	139	79	48	71	M 8	M 8	59	168	M 6	29,5	60	27	26	55	5,2 kg	0,8 kg
MLZ 60S **W**	315	170	108	80	47	30	42	60	143	83	52	71	M 8	M 8	59	194	M 6	29,5	60	27	26	55	6,2 kg	0,8 kg


0 **Choice of guide body profile:**
(0) Standard **(2)** corrosion-protected guide rods and screws
(4) expanded corrosion-protected version (depending on the availability of components)

0 **Choice of carriages:**

(0)



(1)




Size	Version 1	
	Q	L
60	184	306
60 S	214	336

0 **Drive version:**

0





Version 9 is the same as 0, but with double sided coupling claw.

The standard version is supplied without shaft.

Belt table

Code No.		Size	Belt	mm/rev.	Number of teeth
0	**4**	**60 (S)**	5M25	130	26

Shaft dimensions / Coupling claw

Size	Shaft ø h6 x length	Key	Coupling
60 (S)	14 x 35	5x5x28	14

MLZ	60 W	1	0	0	0	0	4	1	01500
Pos.		1	2	3	4	5	6	7	


Basic length + stroke = total length


For combination kits and connecting elements refer to chapter 2.2

Sample ordering code:
MLZ 60 W, standard body profile, standard carriage, coupling claw on one side, 1210 mm stroke

Positioning system MLZD 60 (S) W

Belt drive






The carriages can be moved independently of one another.

5.1

Function:
The guide body consists of an aluminium square profile with lateral, parallel, form-fit, internal hardened steel rods. Two guide carriages, each with its own drive, move along the guide body. The timing belt is guided within the profile, so that it is independent of the mounting position. Due to the high rectangular profile high torques and loads can be taken up. In addition, a very high stability is ensured for long axis systems. The toothed pulleys have maintenance-free ball bearings. The belt tension can be easily readjusted via a tensioning device within the carriage. This device also helps to adjust the symmetry of the carriages in applications where two parallel linear units are used.

Fitting position: As required, max. length 6.000 mm without joints.
Carriage mounting: By T-slots.
Unit mounting: By T-slots or tapped holes in the bearing block, mounting sets.
Belt type: HTD with steel reinforcement, no backlash when changing direction, repeatability: ± 0,1 mm.

Forces and torques



Size	60		60 S	
Forces/Torques	static	dynamic	static	dynamic
F_x (N)	894	800	894	800
F_y (N)	3000	2000	4100	3100
F_z (N)	1700	1100	2160	1600
M_x (Nm)	67	43	88	65
M_y (Nm)	90	70	190	140
M_z (Nm)	120	100	230	170
All forces and torques relate to the following: existing values / table values	$\frac{Fy}{Fy_{dyn}} + \frac{Fz}{Fz_{dyn}} + \frac{Mx}{Mx_{dyn}} + \frac{My}{My_{dyn}} + \frac{Mz}{Mz_{dyn}} \leq 1$			
No-load torque				
Nm	0,6		0,7	
Speed				
(m/s) max	5		7	
Tensile force				
permanent (N)	900		900	
0,2 s (N)	1000		1000	
Geometrical moments of inertia of aluminium profile				
I_x mm⁴	2,8 x 10⁶		2,8 x 10⁶	
I_y mm⁴	9,6 x 10⁵		9,6 x 10⁵	
E-Modulus N/mm²	70000		70000	

For life-time calculation of rollers use our homepage.

Driving torque:


$$M_a = \frac{F * P * S_i}{2000 * \pi} + M_n$$

$$P_a = \frac{M_a * n}{9550}$$

F = force (N)
P = pulley action perimeter (mm)
Si = safety factor 1,2 ... 2
M_n = no-load torque (Nm)
n = rpm pulley (min^{-1})
M_a = driving torque (Nm)
P_a = motor power (KW)

Deflection:


$$f = \frac{F * L^3}{E * I * 192}$$





f = deflection (mm)
F = load (N)
L = free length (mm)
E = elastic modulus 70000 (N/mm²)
I = second moment of area (mm⁴)

Positioning system MLZD 60 (S) W

Dimensions (mm)







*For slide nuts refer to chapter 2.2 page 2

Increasing the carriage length will increase the basic length by the same amount.

Size	Basic length L	A	B	C	D - 0,05	F	H	J	K	M	N	OO for	P	Q	T	X	Y	Basic weight	Weight per 100 mm
MLZD 60 **W**	290	144	96	80	47	42	158	79	48	71	M 8	M 8	59	168	M 6	27	26	9,3 kg	1,0 kg
MLZD 60S **W**	315	170	108	80	47	42	166	83	52	71	M 8	M 8	59	194	M 6	27	26	11,3 kg	1,0 kg

0 **Choice of guide body profile:**
(0) Standard **(2)** corrosion-protected guide rods and screws
(4) expanded corrosion-protected version (depending on the availability of components)

0 **Choice of carriages:**


(0)




0 **Drive version:**

(0)






Top drive version:
Version 9 is the same as 0, but with double sided coupling claw.



Mirror plane
Drive version
(top and bottom identical)

(0)





Bottom drive version:
Version 9 is the same as 0, but with double sided coupling claw.

Belt table

Code No.		Size	Belt	mm/rev.	Number of teeth
0	4	**60 (S)**	5M25	130	26

Shaft dimensions / Coupling claw

Size	Shaft ø h6 x length	Key	Coupling
60 (S)	14 x 35	5x5x28	14

MLZD	60 W	1	0	0	0	0	4	1	01500
Pos.		1	2	3	4	5	6	7	

Basic length + stroke = total length


For combination kits and connecting elements refer to chapter 2.2

Sample ordering code:
MLZD 60 W, standard body profile, standard carriage, coupling claw on one side, 1210 mm stroke


Possible mounting styles



MLZ 60W



MLZ 80S



Roller guide positioning systems QL

Positioning system QLZ 60, 80, 100

Belt drive




Fraunhofer IPA TESTED DEVICE Lineareinheit QLZ 80 Report No. BA 0005-171

Function:
This unit consists of a square aluminium profile with an integrated roller guide. The carriage is driven by a timing belt. Each standard pulley includes one coupling claw on one side. Belt tension can be readjusted by a simple screw adjustment device in the carriage. This device can also be used for symmetrical adjustment of two or more linear units running parallel.
This linear unit is suitable for application in clean rooms of clean-room classification 1.000 (corresponding to US Fed. Standard 209 E).

6.1

Fitting position: As required. Max. length 6.000 mm without joints.
Carriage mounting: By T-slots.
Unit mounting: By T-slots and mounting sets. The linear axis can be combined with any T-slot profile.
Belt performance: HTD with steel reinforcement, no backlash when changing direction, repeatability ± 0,1 mm.
Carriage support: In the standard version, the carriage runs on 4 rollers which can be adjusted and serviced at a central servicing position. For longer carriages the number of rollers can be increased.

Forces and torques



Size	60		80		100	
Forces/Torques	static	dynamic	static	dynamic	static	dynamic
F_x (N)	894	800	1900	1800	4000	3800
F_y (N)	600	500	1600	1240	1900	1500
F_z (N)	900	650	1500	1200	2100	1700
M_x (Nm)	15	10	50	40	85	60
M_y (Nm)	60	50	100	80	140	110
M_z (Nm)	40	30	75	60	110	90
All forces and torques related to the following: existing values / table values	$\frac{Fy}{Fy_{dyn}} + \frac{Fz}{Fz_{dyn}} + \frac{Mx}{Mx_{dyn}} + \frac{My}{My_{dyn}} + \frac{Mz}{Mz_{dyn}} \leq 1$					
No-load torque						
Nm	0,6		0,8		1,2	
Speed						
(m/s) max	4		6		7	
Tensile force						
permanent (N)	900		1900		4000	
0,2 s (N)	1000		2090		4300	
Geometrical moments of inertia of aluminium profile						
I_x mm⁴	$4,3x10^5$		$16,5x10^5$		$43,0x10^5$	
I_y mm⁴	$4,8x10^5$		$18,7x10^5$		$48,8x10^5$	
Elastic modulus N/mm²	70000		70000		70000	

For life-time calculation of rollers use our homepage.

Driving torque:


$$M_a = \frac{F * P * S_i}{2000 * \pi} + M_n$$

$$P_a = \frac{M_a * n}{9550}$$

F = force (N)
P = pulley action perimeter (mm)
Si = safety factor 1,2 ... 2
M_n = no-load torque (Nm)
n = rpm pulley (min^{-1})
M_a = driving torque (Nm)
P_a = motor power (KW)

Deflection:

$$f = \frac{F * L^3}{E * I * 192}$$





f = deflection (mm)
F = load (N)
L = free length (mm)
E = elastic modulus 70000 (N/mm^2)
I = second moment of area (mm^4)

BAHR Modultechnik

Positioning system QLZ 60, 80, 100

Dimensions (mm)





*For slide nuts refer to chapter 2.2 page 2

V = Q + 100 mm W = servicing position

Increasing the carriage length will increase the basic length by the same amount.

6.1


Size ❐	Basic length L	A	B	C	D -0,05	E	F	G	H	J	K	N for	M for	P	Q	T	X	Y	Basic weight	Weight per 100 mm
QLZ 60	280	80	60	36	47	63	42	79	29,5	30	M 8	M 5	M 6	59	152	M 6	27	26	3,2 Kg	0,39 kg
QLZ 80	390	100	80	50	68	93	60	106	47,5	40	M 10	M 6	M 8	90	196	M 8	45	40	9,6 Kg	0,86 Kg
QLZ 100	490	130	100	66	90	110	80	129	55	50	M 12	M 10	M 10	110	260	M 10	49	50	15,8 kg	1,23 Kg

0 **Choice of guide body profile:**

(0) Standard **(2)** corrosion-protected guide rods and screws


(4) expanded corrosion-protected version (depending on the availability of components)

0 **Choice of carriages:**



Size	Version 1		Version 2		Version 3	
	Q	L	Q	L	Q	L
60	192	320	>232	>360	>232	>360
80	246	440	>296	>490	>296	>490
100	320	550	>388	>610	>388	>610

0 **Drive version:**



Size	Shaft ø h6 x length	Key
60	14 x 35	5x5x28
80	18 x 45	6x6x40
100	22 x 45	6x6x40

9 is as 0, but with coupling claws on both sides. The standard version is supplied without shaft. A shaft can be retrofitted by inserting it into the pulley bore and securing it with 2 locking rings or tension sets (size 100).

Belt table / Coupling claw

Code No.		Size	Belt	Pulley		Coupling
				mm/rev.	Number of teeth	
0	**3**	60	5M25	130	26	14
0	**4**	80	8M30	176	22	19
0	**7**	100	8M50	224	28	24

QLZ	80	1	0	0	0	0	4	1	01500
	Pos.	1	2	3	4	5	6	7	


Basic length + stroke = total length

For additional accessories refer to chapter 2.2 – 3.2

Sample ordering code:
QLZ80, standard body profile, standard carriage, coupling claw on one side, 1110 mm stroke

Positioning system QLR 60, 80, 100

Roller guide




6.1

Function:
This unit consists of a square aluminium profile with an integrated roller guide. The carriage, which has internal linear ball bearings that can be adjusted free of play, moves along the guide body. This roller guide can be driven by a pneumatic cylinder or other additional drives or it serves as a load carrying slide unit.

Fitting position: As required. Max. length 6.000 mm without joints.
Carriage mounting: By T-slots.
Unit mounting: By T-slots and mounting sets. The linear axis can be combined with any T-slot profile.
Carriage support: In the standard version, the carriage runs on 4 rollers which can be adjusted and serviced at a central servicing position. For longer carriages the number of rollers can be increased.

Forces and torques




Size	60		80		100	
Forces/torques	static	dynamic	static	dynamic	static	dynamic
F_x (N)	-	-	-	-	-	-
F_y (N)	600	500	1600	1240	1900	1500
F_z (N)	900	650	1500	1200	2100	1700
M_x (Nm)	15	10	50	40	85	60
M_y (Nm)	60	50	100	80	140	110
M_z (Nm)	40	30	75	60	110	90
All forces and torques related to the following:						
existing values / table values	$\frac{Fy}{Fy_{dyn}} + \frac{Fz}{Fz_{dyn}} + \frac{Mx}{Mx_{dyn}} + \frac{My}{My_{dyn}} + \frac{Mz}{Mz_{dyn}} \leq 1$					
Speed						
(m/s) max	4		6		7	
Geometrical moments of inertia of aluminium profile						
I_x mm^4	4,3x10^5		16,5x10^5		43,0x10^5	
I_y mm^4	4,8x10^5		18,7x10^5		48,8x10^5	
Elastic modulus N/mm^2	70000		70000		70000	

For life-time calculation of rollers use our homepage.

Deflection:


$$f = \frac{F * L^3}{E * I * 192}$$



f = deflection (mm)
F = load (N)
L = free length (mm)
E = elastic modulus 70000 (N/mm^2)
I = second moment of area (mm^4)

Positioning system QLR 60, 80, 100

Dimensions (mm)



*For slide nuts refer to chapter 2.2 page 2

V = Q + 100 mm W = servicing position


Increasing the carriage length will increase the basic length by the same amount.

Size ❒	Basic length L	A	B	C	E	G	N for	M for	P	Q	Basic weight	Weight per 100 mm
QLR 60	180	80	60	36	60	79	M 5	M 6	12	152	1,45 kg	0,37 kg
QLR 80	240	100	80	50	93	106	M 6	M 8	17	196	4,2 kg	0,82 kg
QLR 100	310	130	100	66	110	129	M 10	M 10	20	260	7,2 kg	1,17 kg


0 **Choice of guide body profile:**
(0) Standard **(2)** corrosion-protected guide rods and screws
(4) expanded corrosion-protected version (depending on the availability of components)

0 **Choice of carriages:**


(0)




(1)



(2)



(3)



Size	Version 0		Version 1		Version 2		Version 3	
	Q	L	Q	L	Q	L	Q	L
60	152	180	192	220	>232	>260	>232	>260
80	196	240	246	290	>296	>340	>296	>340
100	260	310	320	370	>388	>430	>388	>430


1500 Basic length + stroke = total length

For additional accessories refer to chapter 2.2 – 3.2

QLR	80	0	0	0	0	0	0	0	01500
Pos.		1	2	3	4	5	6	7	


Sample ordering code:
QLR80 with standard body profile, standard carriage and 1260 mm stroke

Possible mounting styles










Rail guide
positioning systems QS

Positioning system QSZ 60, 80, 100, 125

Belt drive




Fraunhofer TESTED® DEVICE IPA
Bahr Modultechnik GmbH
Linear unit QSZ 80
Report No. BA 1611-858

Function:
This unit consists of a square aluminium profile with an integrated ball rail. The carriage is moved by a belt drive. Each standard pulley includes one coupling claw on one side. Belt tension can be readjusted by a simple screw adjustment device in the carriage. This device can also be used for symmetrical adjustment of two or more linear units running parallel.

Fitting position: As required. Max. length 6.000 mm without joints.
Carriage mounting: By T-slots.
Unit mounting: By T-slots and mounting sets. The linear axis can be combined with any T-slot profile.
Belt performance: HTD with steel reinforcement, no backlash when changing direction, repeatability ± 0,1 mm.
Carriage support: In the standard version, the carriage runs on two runner blocks which can be adjusted and serviced at a central servicing position. For longer carriages the number of runner blocks can be increased.

Forces and torques



Size	60		80		100		125	
permitted dyn. forces*	5000 km	10000 km	5000 km	10000 km	5000 km	10000 km	5000 km	10000 km
F_x (N)	894	800	1900	1800	4000	3800	5900	5750
F_y (N)	1410	990	3570	2550	4080	2900	6892	5470
F_z (N)	3520	2500	8500	6050	10300	7270	17205	13659
M_x (Nm)	33	23	107	75	142	101	288	228
M_y (Nm)	104	73	310	222	439	311	1110	881
M_z (Nm)	100	70	296	210	412	292	1012	803
All forces and torques related to the following: existing values / table values $\frac{Fy}{Fy_{dyn}} + \frac{Fz}{Fz_{dyn}} + \frac{Mx}{Mx_{dyn}} + \frac{My}{My_{dyn}} + \frac{Mz}{Mz_{dyn}} \leq 1$								
No-load torque								
Nm	1,0		1,4		1,8			
Speed								
(m/s) max	5		5		5		5	
Tensile force								
permanent (N)	900		1900		4000		5900	
0,2 s (N)	1000		2090		4300		6350	
Geometrical moments of inertia of aluminium profile								
I_x mm⁴	$4,3x10^5$		$16,5x10^5$		$43,0x10^5$		$74,9x10^5$	
I_y mm⁴	$4,8x10^5$		$18,7x10^5$		$48,8x10^5$		$106,5x10^5$	
Elastic modulus N/mm²	70000		70000		70000		70000	

** referred to lifetime*

Driving torque:


$$M_a = \frac{F*P*S_i}{2000*\pi} + M_n$$

$$P_a = \frac{M_a*n}{9550}$$

F = force (N)
P = pulley action perimeter (mm)
Si = safety factor 1,2 ... 2
M_n = no-load torque (Nm)
n = rpm pulley (min^{-1})
M_a = driving torque (Nm)
P_a = motor power (KW)

Deflection:

$$f = \frac{F*L^3}{E*I*192}$$





f = deflection (mm)
F = load (N)
L = free length (mm)
E = elastic modulus 70000 (N/mm²)
I = second moment of area (mm⁴)

BAHR Modultechnik


Positioning system QSZ 60, 80, 100, 125


Dimensions (mm)






QSZ 125







*For slide nuts refer to chapter 2.2 page 2

Increasing the carriage length will increase the basic length by the same amount.

Size ❐	Basic length L	A	B	C	D -0,05	E	F	G	H	J	K	N for	M for	P	Q	T	X	Y	Basic weight	Weight per 100 mm
QSZ 60	300	80	60	36	47	63	42	79	29,5	30	M 8	M 5	M 6	59	177	M 6	27	26	3,5 kg	0,55 kg
QSZ 80	430	100	80	50	68	93	60	106	47,5	40	M 10	M 6	M 8	90	232	M 8	45	40	10,4 kg	0,96 kg
QSZ 100	510	130	100	66	90	110	80	129	55	50	M 12	M 10	M 10	110	268	M 10	49	50	15,9 kg	1,47 kg
QSZ 125	570	160	125	82	110	134,5	100	157,5	65	60	M 12	M 10	M 12	130	300	M 10	60	60	30,5 kg	2,21 kg

V = Q + 100 mm
W = servicing position

0 **Choice of guide body profile:**
(0) Standard **(1)** corrosion-protected screws
(4) expanded corrosion-protected version (depending on the availability of components)


0 **Choice of carriages:**

(0) **(1)** **(2)** **(3)** **(4)**



Size	Version 0		Version 1		Version 2		Version 3		Version 4	
	Q	L	Q	L	Q	L	Q	L	Q	L
60	177	300	152	280	242	370	302	430		
80	232	430	196	390	312	510	390	585		
100	268	510	260	500	362	610	448	690	628	860
125	300	570	260	530	365	635	467	740		

0 **Drive version:**



Size	Shaft ø h6 x length	Key
60	14 x 35	5x5x28
80	18 x 45	6x6x40
100	22 x 45	6x6x40
125	30 x 55	8x7x50

9 is as 0, but with coupling claws on both sides. The standard version is supplied without shaft. A shaft can be retrofitted by inserting it into the pulley bore and securing it with 2 locking rings or clamping sets (Size 100 + 125).

Belt table / Coupling claw

Code No.		Size	Belt	Pulley		Coupling
				mm/rev.	Number of teeth	
0	**3**	**60**	5M25	130	26	14
0	**4**	**80**	8M30	176	22	19
0	**7**	**100**	8M50	224	28	24
0	**9**	**125**	8M70	288	36	28

QSZ	80	1	0	0	0	0	4	1	01500
Pos.	1	2	3	4	5	6	7		

— Basic length + stroke = total length


For additional accessories refer to chapter 2.2 – 3.2

Sample ordering code:
QSZ80 with standard body profile, standard carriage, coupling claw on one side, 1070 mm stroke

Positioning system QSSZ 60, 80

Belt drive






Function:
This linear unit consists of a square aluminium profile with integrated rail guidance. The carriage, which has runner blocks, is driven by a timing belt. Each standard pulley includes a coupling claw on one side and is equipped with maintenance-free ball bearings. Belt tension can be readjusted by a simple screw adjustment device in the carriage. This device can also be used for symmetrical adjustment of two or more linear units running parallel.

Fitting position: As required. Max. length 3.000 mm without joints.
Carriage mounting: By T-slots.
Unit mounting: By T-slots and mounting sets. The linear axis can be combined with any T-slot profile.
Belt performance: HTD with steel reinforcement, no backlash when changing direction, repeatability ± 0,1 mm.
Carriage support: In the standard version, the carriage runs on 2 runner blocks which can be serviced at a central servicing position. For longer carriages the number of runner blocks can be increased.

Forces and torques



Size	60		80	
permitted dyn. forces*	5000 km	10000 km	5000 km	10000 km
F_x (N)	97	87	223	200
F_y (N)	350	240	890	630
F_z (N)	880	625	2100	1500
M_x (Nm)	8	6	26	18
M_y (Nm)	26	18	77	55
M_z (Nm)	25	17	74	52
All forces and torques related to the following: existing values / table values $\frac{Fy}{Fy_{dyn}} + \frac{Fz}{Fz_{dyn}} + \frac{Mx}{Mx_{dyn}} + \frac{My}{My_{dyn}} + \frac{Mz}{Mz_{dyn}} \leq 1$				
No-load torque				
Nm	1,0		1,4	
Speed				
(m/s) max	3		3	
Tensile force				
permanent (N)	Lifetime calculation see the internet			
Geometrical moments of inertia of aluminium profile				
I_x mm⁴			16,5x10⁵	
I_y mm⁴			18,7x10⁵	
Elastic modulus N/mm²			70000	

** referred to life-time*

Driving torque:


$$M_a = \frac{F * P * S_i}{2000 * \pi} + M_n$$

$$P_a = \frac{M_a * n}{9550}$$

F = force (N)
P = pulley action perimeter (mm)
Si = safety factor 1,2 ... 2
M_n = no-load torque (Nm)
n = rpm pulley (min^{-1})
M_a = driving torque (Nm)
P_a = motor power (KW)


Deflection:

$$f = \frac{F * L^3}{E * I * 192}$$



f = deflection (mm)
F = load (N)
L = free length (mm)
E = elastic modulus 70000 (N/mm^2)
I = second moment of area (mm^4)

Positioning system QSSZ 60, 80



*For slide nuts refer to chapter 2.2 page 2 V = Q + 100 mm W = servicing position


Size ❒	Basic length L	A	B	C1	C2	D -0,05	E	F	G	J	K	N for	P	Q	T	X	Y	Basic weight	Weight per 100 mm
QSSZ 60	168	60	60	28	48	37	60	32	65	7,50	134,5	M 5	20	124	M 5	110	20	3,30 kg	0,47 kg
QSSZ 80	200	106	80	38	62	47	80	42	80	8	169	M 6	24	144	M 6	130	30	5,90 kg	1,02 kg

0 **Choice of guide body profile:**
(0) Standard **(1)** corrosion-protected screws
(4) expanded corrosion-protected version
(depending on the availability of components)


Size	H1	H2	H3	H4	M1	M2	M3
QSSZ 60	–	–	60	45	–	M6	M8
QSSZ 80	97	104	–	–	M6	M8	–

0 **Choice of carriages:**

(0)



0 **Drive version:**



Size	Shaft ø h6 x length	Key
60	10 x 27	3x3x25
80	14 x 35	5x5x28

8 is as 0, but with coupling claws on both sides. The standard version is supplied without shaft. A shaft can be retrofitted by inserting it into the pulley bore and securing it with 2 locking rings.

Belt table / Coupling claw

Code No.		Size	Belt	Pulley		Coupling
				mm/rev.	Number of teeth	
0	**3**	**60**	5M15	100	20	9
0	**7**	**80**	5M25	130	26	14

Basic length + stroke = total length

For additional accessories refer to chapter 2.2 – 3.2

QSSZ	80	1	0	0	0	0	7	1	01500
	Pos.	1	2	3	4	5	6	7	

Sample ordering code:
QSSZ80, standard body profile, standard carriage, coupling claw on one side, 1300 mm stroke

Positioning system QST/K 60, 80, 100

Spindle drives




Fraunhofer TESTED DEVICE IPA
Bahr Modultechnik GmbH Positioningsystem QSK 80 Report No. BA 0610-367

Function:
This unit consists of a square aluminium profile with an integrated ball rail. The carriage is driven by means of a rotating spindle with leading nut. The openings of the guide body are sealed by a stainless steel cover band to protect the drive from splash water and dust.

7.1

Fitting position: As required, max. length 3000mm
Carriage connection: By T-slots
Unit mounting: By half round slots and tapped holes in the bearing blocks, mounting sets.

Forces and torques



Size	QST/K 60		QST/K 80		QST/K 100	
permitted dyn. forces*	5000 km	10000 km	5000 km	10000 km	5000 km	10000 km
F_x (N)	900	800	2500	2000	5000	4000
F_y (N)	1415	1010	3570	2542	4082	2910
F_z (N)	3525	2510	8500	6050	10300	7360
M_x (Nm)	33	23	107	76	142	101
M_y (Nm)	190	143	604	430	838	597
M_z (Nm)	176	125	550	392	745	532
All forces and torques related to the following: existing values / table values $\frac{Fy}{Fy_{dyn}} + \frac{Fz}{Fz_{dyn}} + \frac{Mx}{Mx_{dyn}} + \frac{My}{My_{dyn}} + \frac{Mz}{Mz_{dyn}} \leq 1$						
No-load torque						
Trapezoidal	18x4/18x8		24x5/24x10		32x6/32x12	
Nm	0,6/0,7		0,6/0,8		1,5/1,7	
Ballscrew	16x5/16x10		25x5/20x20/25x10		32x5/32x10	
Nm	0,4/0,6		0,4/0,7/0,6		1,3/1,6	
Geometrical moments of inertia of aluminium profile						
I_x mm^4	$4,3x10^5$		$14,0x10^5$		$43,0x10^5$	
I_y mm^4	$4,8x10^5$		$16,6x10^5$		$48,8x10^5$	
E-Modulus N/mm^2	70000		70000		70000	

** referred to life-time*

Driving torque:

$$M_a = \frac{F * P * S_i}{2000 * \pi * \mu} + M_n$$

$$P_a = \frac{M_a * n}{9550}$$


F	= force	(N)
P	= thread pitch	(mm)
Si	= safety factor 1,2 ... 2	
M_n	= no-load torque	(Nm)
n	= rpm of screw	(min^{-1})
M_a	= driving torque	(Nm)
μ	= screw efficiency	
P_a	= motor power	(KW)

Efficiency of lead screws:

All ballscrew		0,900
Tr	18x4	0,399
Tr	18x8	0,565
Tr	24x5	0,384
Tr	24x10	0,550
Tr	32x6	0,360
Tr	32x12	0,524

Deflection:

$$f = \frac{F * L^3}{E * I * 192}$$




f	= deflection	(mm)
F	= load	(N)
L	= free length	(mm)
E	= elastic modulus 70000	(N/mm^2)
I	= second moment of area	(mm^4)


For the diagram for critical speeds of lead screws refer to chapter 4.2


BAHR Modultechnik

Positioning system QST/K 60, 80, 100

Dimensions (mm)







V = Q + 100 mm
W = servicing position

*For slide nuts refer to main catalog chapter 2.2 page 2

Increasing the carriage length will increase the basic length by the same amount.


Size ❒	Basic length L	A	B	C	D -0,05	E	F ❒	G	H	J	K	M for	P	Q	Shaft R Key	Shaft S Ø h6 x length	T for	U	Basic weight	Weight per 100 mm
QST/K 60	270	60	36	45	37	67	32	79	19	18	M6	M6	38	188	3x3x25	10 x 27	M5	60	4,1 kg	0,5 kg
QST/K 80	350	80	50	62	47	89	42	106	22,5	40	M10	M8	45	250	5x5x28	14 x 35	M6	80	7,5 kg	0,9 kg
QST/K 100	410	100	66	75	68	112	60	129	28,5	50	M10	M10	57	288	6x6x40	22 x 45	M8	100	14,8 kg	1,3 kg

7.1

K **Spindle:**
(T) Trapezoidal thread **(K)** Ballscrew

1 **Selection of screw:**
(1) right hand (Standard) **(2)** left hand (Ballscrew by inquiry)

0 **Choice of carriage:**



Size	Carriage version 1	
	Q	Basic length L
60	255	350
80	336	436
100	383	510

0 **Drive version:**
(0) one shaft (locating bearing side) **(1)** one shaft (non-locating bearing side) **(2)** shaft on both sides

0 **Selection of screw:**

Size	Standard	Multistart screw	Standard	Multistart screw		
	Trapezoidal thread		Ballscrew			
60	**(0)** Tr 18x4	**(1)** Tr 18x8	**(0)** Kg 16x5	**(1)** Kg 16x10	**(2)** Kg 16x16	
80	**(0)** Tr 24x5	**(1)** Tr 24x10	**(0)** Kg 25x5	**(1)** Kg 20x20	**(2)** Kg 25x10	**(3)** Kg 25x25***
100	**(0)** Tr 32x6	**(1)** Tr 32x12	**(0)** Kg 32x5	**(1)** Kg 32x10	**(2)** Kg 32x32 *	**(3)** Kg 32x20**

** = Basic and carriage length (L and Q) increase over 47 mm*
***= Basic and carriage length (L and Q) increase over 11 mm*
**** = Basic and carriage length (L and Q) increase over 42 mm*

0 **Choice of guide body profile:**
(0) Standard **(1)** corrosion-protected screws

0 **Ballscrew pitch accuracy:**
(0) 0,05 mm / 300 mm (Standard) **(2)** 0,025 mm / 300 mm

0 **End play of ball nut:**
(0) 0,04 mm (Standard) **(1)** < 0,02 mm **(2)** 2% apply prestress


1500 Basic length + stroke = total length


QS	K	80	1	0	0	0	0	0	0	01500
		Pos.	1	2	3	4	5	6	7	


Sample ordering code:
QSK80, ballscrew right hand thread, standard carriage, one shaft (locating bearing side), spindle 25x5, 1150 mm stroke.


Positioning system QST/K 60, 80, 100

Dimensions (mm)









*For slide nuts refer to main catalog chapter 2.2 page 2

Increasing the carriage length will increase the basic length by the same amount.

Size ❒	Basic length L selection of screw		A	B	C	D -0,05	E	F ❒	G	H	J	K	M for	P	Q	Shaft		T for	U	Basic weight	Weight per 100 mm
	3	4														R Key	S ∅ h6 x length				
QST/K 60	460	500	60	36	45	37	67	32	79	19	18	M6	M6	38	188	3x3x25	10 x 27	M5	60	5,4 kg	0,5 kg
QST/K 80	600	640	80	50	62	47	89	42	106	22,5	40	M10	M8	45	250	5x5x28	14 x 35	M6	80	9,8 kg	0,9 kg
QST/K 100	700	740	100	66	75	68	112	60	129	28,5	50	M10	M10	57	288	6x6x40	22 x 45	M8	100	18,6 kg	1,3 kg


V = Q + 100 mm
W = servicing position

Size	Carriage version 1		
	Q	Basic length L selection of spindle	
		3	4
60	255	590	630
80	336	770	810
100	383	890	930

K **Spindle:**
(T) Trapezoidal thread **(K)** Ballscrew

3 **Selection of screw:**
(3) right - left hand **(4)** divided spindle

0 **Choice of carriage:**



0 **Drive version:**
(0) shaft right hand thread **(1)** shaft left hand thread **(2)** shaft on both sides

0 **Selection of screw:**

	Size	Standard	Multistart screw	
Ballscrew right hand	60	**(0)** 16x5	**(1)** 16x10*	**(2)** 16x16*
	80	**(0)** 25x5	**(1)** 20x20*	**(2)** 25x10*
	100	**(0)** 32x5	**(1)** 32x10*	**(2)** 32x32**
Ballscrew left hand	upon request			
Trapezoidal right hand thread	60	**(0)** 18x4	**(1)** 18x8	
	80	**(0)** 24x5	**(1)** 24x10	
	100	**(0)** 32x6	**(1)** 32x12	
Trapezoidal left hand thread	60	**(0)** 18x4	**(1)** 18x8	
	80	**(0)** 24x5	**(1)** 24x10	
	100	**(0)** 32x6	**(1)** 32x12	

* = only for selection of divided spindle,
** = only for selection of divided spindle, Basic and carriage length (L and Q) increase over 94 mm

0 **Choice of guide body profile:**
(0) Standard **(1)** corrosion-protected screws
(4) expanded corrosion-protected version (depending on the availability of components)

0 **Ballscrew pitch accuracy:**
(0) 0,05 mm / 300 mm (Standard) **(2)** 0,025 mm / 300 mm


0 **End play of ball nut:**
(0) 0,04 mm (Standard) **(1)** < 0,02 mm **(2)** 2% apply prestress

QS	K	80	3	0	0	0	0	0	0	01500	1500
		Pos.	1	2	3	4	5	6	7		


Basic length + stroke = total length

Sample ordering code:
QSK80, ballscrew right - left hand thread, standard carriage, shaft on right hand thread, spindle 25x5, 860 mm stroke.

Possible combinations and mounting styles



Q-Portal



Combination
QS 60 with DS 120

Positioning system QSR 60, 80, 100, 125


Rail guide



Function:
This unit consists of a square aluminium profile with an integrated ball rail. This unit can be driven by a pneumatic cylinder or other additional drives or it serves as a load carrying slide unit.

Fitting position: As required. Max. length 6.000 mm without joints.
Carriage mounting: By T-slots.
Unit mounting: By T-slots and mounting sets. The linear axis can be combined with any T-slot profile.
Carriage support: In the standard version, the carriage runs on two runner blocks which can be adjusted and serviced at a central servicing position. For longer carriages the number of runner blocks can be increased.

Forces and torques




Size	60		80		100		125	
permitted dyn. forces*	5000 km	10000 km	5000 km	10000 km	5000 km	10000 km	5000 km	10000 km
F_x (N)	-	-	-	-	-	-	-	-
F_y (N)	1410	990	3570	2550	4080	2900	6892	5470
F_z (N)	3520	2500	8500	6050	10300	7270	17205	13659
M_x (Nm)	33	23	107	75	142	101	288	228
M_y (Nm)	104	73	310	222	439	311	1110	881
M_z (Nm)	100	70	296	210	412	292	1012	803
All forces and torques related to the following: existing values / table values $\frac{Fy}{Fy_{dyn}} + \frac{Fz}{Fz_{dyn}} + \frac{Mx}{Mx_{dyn}} + \frac{My}{My_{dyn}} + \frac{Mz}{Mz_{dyn}} \leq 1$								
Speed								
(m/s) max	5		5		5		5	
Geometrical moments of inertia of aluminium profile								
I_x mm^4	$4{,}3 \times 10^5$		$16{,}5 \times 10^5$		$43{,}0 \times 10^5$		$74{,}9 \times 10^5$	
I_y mm^4	$4{,}8 \times 10^5$		$18{,}7 \times 10^5$		$48{,}8 \times 10^5$		$106{,}5 \times 10^5$	
Elastic modulus N/mm^2	70000		70000		70000		70000	

** referred to life-time*

Deflection:


$$f = \frac{F * L^3}{E * I * 192}$$




f = deflection (mm)
F = load (N)
L = free length (mm)
E = elastic modulus 70000 (N/mm^2)
I = second moment of area (mm^4)


Positioning system QSR 60, 80, 100, 125

Dimensions (mm)










QSR 125



V = Q + 100 mm
W = servicing position

*For slide nuts refer to chapter 2.2 page 2


Increasing the carriage length will increase the basic length by the same amount.

Size ❐	Basic length L	A	B	C	E	G	N for	M for	P	Q	Basic weight	Weight per 100 mm
QSR 60	205	80	60	36	60	79	M 5	M 6	12	177	1,8 kg	0,53 kg
QSR 80	270	100	80	50	93	106	M 6	M 8	17	232	4,9 kg	0,92 kg
QSR 100	315	130	100	66	110	129	M 10	M 10	20	268	8,2 kg	1,41 kg
QSR 125	360	160	125	82	134,5	157,5	M 10	M 12	25	300	15,1 kg	2,12 kg


0 **Choice of guide body profile:**
(0) Standard **(1)** corrosion-protected screws
(4) expanded corrosion-protected version (depending on the availability of components)

0 **Choice of carriages:**

(0)



(1)



Size	Version 0		Version 1	
	Q	L	Q	L
60	177	205	152	180
80	232	270	196	240
100	268	315	260	310
125	300	360	260	320

1500 Basic length + stroke = total length

For additional accessories refer to chapter 2.2 – 3.2

QSR	80	0	0	0	0	0	0	0	01500
	Pos.	1	2	3	4	5	6	7	

Sample ordering code:
QSR80 with standard body profile, standard carriage and 1230 mm stroke

Positioning system QSSR 60, 80, 100


Rail guide



Function:
This unit consists of a square aluminium profile with an integrated ball rail. The carriage is with leading nut and without drive. The openings of the guide body are covered by a stainless steel cover band to protect the system from splash water and dust.

Fitting position: As required, max. length 6.000mm
Carriage connection: By T-slots
Unit mounting: By half round slots and tapped holes in the bearing blocks, mounting sets.

Forces and torques



Size	QSSR 60		QSSR 80		QSSR 100	
permitted dyn. forces*	5000 km	10000 km	5000 km	10000 km	5000 km	10000 km
F_y (N)	1410	990	3570	2550	4080	2900
F_z (N)	3520	2500	8500	6050	10300	7270
M_x (Nm)	33	23	107	75	142	101
M_y (Nm)	190	143	604	430	838	597
M_z (Nm)	176	125	550	392	745	532

All forces and torques related to the following:

existing values / table values


$$\frac{Fy}{Fy_{dyn}} + \frac{Fz}{Fz_{dyn}} + \frac{Mx}{Mx_{dyn}} + \frac{My}{My_{dyn}} + \frac{Mz}{Mz_{dyn}} \leq 1$$

Geometrical moments of inertia of aluminium profile			
I_x mm^4	$4{,}3 \times 10^5$	$14{,}0 \times 10^5$	$43{,}0 \times 10^5$
I_y mm^4	$4{,}8 \times 10^5$	$16{,}6 \times 10^5$	$48{,}8 \times 10^5$
E-Modulus N/mm^2	70000	70000	70000

** referred to life-time*

Deflection:


$$f = \frac{F * L^3}{E * I * 192}$$





f = deflection (mm)
F = load (N)
L = free length (mm)
E = elastic modulus 70000 (N/mm^2)
I = second moment of area (mm^4)

Positioning system QSSR 60, 80, 100

Dimensions (mm)







V = Q + 100 mm
W = servicing position

*For slide nuts refer to chapter 2.2 page 2

Increasing the carriage length will increase the basic length by the same amount.


Size ❒	Basic length L	A	B	C	D -0,05	E	F ❒	G	H	J	K	M for	P	Q	T for	U	Basic weight	Weight per 100 mm
QSSR 60	270	60	36	45	37	67	32	79	19	18	M6	M6	38	188	M5	60	3,1 kg	0,3 kg
QSSR 80	350	80	50	62	47	89	42	106	22,5	40	M10	M8	45	250	M6	80	5,7 kg	0,8 kg
QSSR 100	410	100	66	75	68	112	60	129	28,5	50	M10	M10	57	288	M8	100	10,2 kg	1,2 kg

7.1


0 **Choice of guide body profile:**
(0) Standard **(1)** corrosion-protected screws
(4) expanded corrosion-protected version (depending on the availability of components)

0 **Choice of carriage:**

(0)



(1)



Size	Carriage version 1	
	Q	Basic length L
60	255	350
80	336	436
100	383	510


1500 Basic length + stroke = total length

QSSR	80	0	0	0	0	0	0	0	01500
	Pos. 1	2	3	4	5	6	7		

Sample ordering code:
QSSR80 with standard body profile, standard carriage, 1150 mm stroke.

Positioning system QSRZ 60, 80, 100, 125


Rail guide



Function:
This unit consists of a square aluminium profile with an integrated ball rail. The carriage is with leading nut and without drive.

Fitting position: As required, max. length 6.000mm
Carriage connection: By T-slots
Unit mounting: By half round slots and tapped holes in the bearing blocks, mounting sets.

Forces and torques



Size	QSRZ 60		QSRZ 80		QSRZ 100		QSRZ 125	
permitted dyn. forces*	5000 km	10000 km	5000 km	10000 km	5000 km	10000 km	5000 km	10000 km
F_y (N)	1410	990	3570	2550	4080	2900	6892	5470
F_z (N)	3520	2500	8500	6050	10300	7270	17205	13659
M_x (Nm)	33	23	107	75	142	101	288	228
M_y (Nm)	104	73	310	222	439	311	1110	881
M_z (Nm)	100	70	296	210	412	292	1012	803

All forces and torques related to the following:

existing values / table values


$$\frac{Fy}{Fy_{dyn}} + \frac{Fz}{Fz_{dyn}} + \frac{Mx}{Mx_{dyn}} + \frac{My}{My_{dyn}} + \frac{Mz}{Mz_{dyn}} \leq 1$$

Geometrical moments of inertia of aluminium profile				
I_x mm^4	4,3x10^5	16,5x10^5	43,0x10^5	74,9x10^5
I_y mm^4	4,8x10^5	18,7x10^5	48,8x10^5	106,5x10^5
E-Modulus N/mm^2	70000	70000	70000	70000

** referred to life-time*

Deflection:


$$f = \frac{F * L^3}{E * I * 192}$$




f = deflection (mm)
F = load (N)
L = free length (mm)
E = elastic modulus 70000 (N/mm^2)
I = second moment of area (mm^4)


Positioning system QSRZ 60, 80, 100, 125

Dimensions (mm)










QSRZ125



V = Q + 100 mm
W = servicing position

*For slide nuts refer to chapter 2.2 page 2

Increasing the carriage length will increase the basic length by the same amount.

Size ❒	Basic length L	A	B	C	E	G	H	J	K	N for	M for	P	Q	Basic weight	Weight per 100 mm
QSRZ 60	300	80	60	36	63	79	29,5	30	M 8	M 5	M 6	59	177	3,5 kg	0,55 kg
QSRZ 80	430	100	80	50	93	106	47,5	40	M 10	M 6	M 8	90	232	10,4 kg	0,96 kg
QSRZ 100	510	130	100	66	110	129	55	50	M 12	M 10	M 10	110	268	15,9 kg	1,47 kg
QSRZ 125	570	160	125	82	134,5	157,5	65	60	M 12	M 10	M 12	130	300	30,5 kg	2,21 kg

0 **Choice of guide body profile:**
(0) Standard **(1)** corrosion-protected screws
(4) expanded corrosion-protected version (depending on the availability of components)

0 **Choice of carriages:**

Size	Version 0		Version 1		Version 2		Version 3	
	Q	L	Q	L	Q	L	Q	L
60	177	300	152	280	242	370	302	430
80	232	430	196	390	312	510	390	585
100	268	510	260	500	362	610	448	690
125	300	570	260	530	365	635	467	740


Basic length + stroke = total length


For additional accessories refer to chapter 2.2 – 3.2


QSRZ	80	0	0	0	0	0	0	0	01500
	Pos.	1	2	3	4	5	6	7	

Sample ordering code:
QSRZ80 with standard body profile, standard carriage, coupling claw on one side, 1070 mm stroke

Possible mounting styles








Roller guide positioning systems DL

Positioning system DLT/DLK 120, 160, 200

Spindle drives






Function:
This unit consists of a rectangular aluminium profile with 2 integrated roller guides. The carriage is driven by means of a rotating spindle with leading nut. Where two parallel linear units are used or where two carriages are mounted on one unit, the leading-nut receiver can be used to adjust the symmetry of the carriages. The openings of the guide body are sealed with 3 stainless steel cover bands to protect the drive from splash water and dust.

Fitting position: As required. Max. length 3.000 mm without joints.
Carriage mounting: By T-slots.
Unit mounting: By T-slots and mounting sets. The linear axis can be combined with any T-slot profile.
Carriage support: In the standard version, the carriage runs on 8 rollers which can be adjusted and serviced at a central servicing position. For longer carriages the number of rollers can be increased. Repeatability ballscrew ± 0,025 mm, trapezoidal thread ± 0,2 mm.

8.1

Forces and torques



Size	120		160		200	
Forces/Torques	static	dynamic	static	dynamic	static	dynamic
F_x (N)	900	800	5000	4000	10000	8000
F_y (N)	1100	900	3000	2000	4400	3100
F_z (N)	1250	1000	3500	2800	4900	4400
M_x (Nm)	150	125	400	320	600	510
M_y (Nm)	140	120	360	300	560	480
M_z (Nm)	100	90	180	150	310	275
All forces and torques related to the following:						
existing values / table values	$\frac{Fy}{Fy_{dyn}} + \frac{Fz}{Fz_{dyn}} + \frac{Mx}{Mx_{dyn}} + \frac{My}{My_{dyn}} + \frac{Mz}{Mz_{dyn}} \leq 1$					
No-load torque						
Trapezoidal thread	18 x 4	18 x 8	24 x 5	24 x 10	32 x 6	32 x 12
(Nm)	0,6	0,9	0,6	0,9	0,9	1,1
Ballscrew	16 x 5	16 x 10	25 x 5	20 x 20	32 x 5	32 x 10
(Nm)	0,5	0,8	0,5	0,8	0,7	0,9
Geometrical moments of inertia of aluminium profile						
I_x mm^4	$6{,}6 \times 10^5$		$22{,}2 \times 10^5$		$63{,}8 \times 10^5$	
I_y mm^4	$38{,}6 \times 10^5$		$122{,}0 \times 10^5$		$335{,}0 \times 10^5$	
Elastic modulus N/mm^2	70000		70000		70000	

For life-time calculation of rollers use our homepage.

Driving torque:

$$M_a = \frac{F * P * S_i * w}{2000 * \pi * \mu} + M_n$$

$$P_a = \frac{M_a * n}{9550}$$


F	= force	(N)
P	= thread pitch	(mm)
Si	= safety factor 1,2 ... 2	
M_n	= no-load torque	(Nm)
n	= rpm of screw	(min^{-1})
M_a	= driving torque	(Nm)
μ	= screw efficiency	
w	= friction coefficient	~1,22
P_a	= motor power	(KW)

Efficiency of lead screws:

All ballscrew		0,900
Tr	18x4	0,399
Tr	18x8	0,565
Tr	24x5	0,384
Tr	24x10	0,550
Tr	32x6	0,360
Tr	32x12	0,524

Deflection:

$$f = \frac{F * L^3}{E * I * 192}$$





f = deflection	(mm)
F = load	(N)
L = free length	(mm)
E = elastic modulus 70000	(N/mm^2)
I = second moment of area	(mm^4)

For the diagram for critical speeds of lead screws refer to chapter 4.2

Positioning system DLT/DLK 120, 160, 200

Dimensions (mm)





V = Q + 100 mm
W = servicing position

*For slide nuts refer to chapter 2.2 page 2

Increasing the carriage length will increase the basic length by the same amount.


Size	Basic length L	A	B	C	D +0,1 +0,05	E	F	G	H	J	K	M for	N for	O for	P	Q	Shaft R Key	Shaft S Ø h6 x length	T	U	Basic weight	Weight per 100 mm
DL 120	200	120	96	39	47	78	42	42	10	68	79	M 5	M 6	M 6	15	156	3x3x25	10 x 27	M 6	60	3,9 kg	0,92 kg
DL 160	260	160	130	53	62	90	50	60	11	90	106	M 6	M 8	M 8	20	200	5x5x28	14 x 35	M 8	80	8,2 kg	1,96 kg
DL 200	320	200	160	66	68	140	60	60	15	110	129	M 8	M10	M10	20	270	6x6x40	22 x 45	M 8	100	19,6 kg	2,82 kg

T **Spindle:**
(T) Trapezoidal thread **(K)** Ballscrew

1 **Selection of screw:**
(1) right hand **(2)** left hand (Ballscrew by inquiry)

0 **Choice of guide body profile:**

(0)



internal profile
with cover bands

(3)




with bellows


Stainless versions upon request.

0 **Choice of carriages:**


(0)



(2)



(3)



Size	Version 0 Q	Version 0 L	Version 2 Q	Version 2 L	Version 3 Q	Version 3 L
120	156	200	196	240	>236	>280
160	200	260	250	310	>300	>360
200	270	320	330	380	>410	>460

0 **Drive version:**
(0) one shaft (locating bearing side) **(1)** one shaft (non-locating bearing side) **(2)** shaft on both sides

0 **Selection of screw:**

	Size	Standard	Multistart screw
Ballscrew right hand	120	**(0)** 16x5	**(1)** 16x10 **(2)** 16x16 **(3)** 20x20 **(4)** 25x5 **(5)** 25x10
	160	**(0)** 25x5	**(1)** 20x20 **(2)** 25x10 **(3)** 25x25
	200	**(0)** 32x5	**(1)** 32x10 **(2)** 32x20 **(3)** 32x32
Ballscrew left hand	upon request		
Trapezoidal right hand thread	120	**(0)** 18x4	**(1)** 18x8
	160	**(0)** 24x5	**(1)** 24x10
	200	**(0)** 32x6	**(1)** 32x12
Trapezoidal left hand thread	120	**(0)** 18x4	**(1)** 18x8
	160	**(0)** 24x5	**(1)** 24x10
	200	**(0)** 32x6	**(1)** 32x12

0 **Ballscrew pitch accuracy:**
(0) 0,05 mm / 300 mm (Standard) **(2)** 0,025 mm / 300 mm

0 **End play of ball nut:**
(0) 0,04 mm (Standard), **(1)** < 0,02 mm, **(2)** 2% apply prestress

1500 Basic length + stroke = total length

Repeatability:
± 0,2 mm Trapezoidal
± 0,025 mm Ballscrew


DL	T	160	1	0	0	0	0	0	01500
	Pos.		1	2	3	4	5	6	7

Sample ordering code:
DLT160, trapezoidal right hand thread, with internal profile and cover bands, standard carriage, one shaft (locating bearing side), spindle 24x5, 1240 mm stroke.


Positioning system DLT/DLK 120, 160, 200

Dimensions (mm)

with trapezoidal thread or ballscrew, right-hand and left-hand thread or divided spindles







V = Q + 100 mm
W = servicing position

*For slide nuts refer to chapter 2.2 page 2

Increasing the carriage length will increase the basic length by the same amount.


Size	Basic length L	A	B	C	D +0,1 +0,05	E	F	G	H	J	K	M for	N for	O for	P	Q	Shaft R Key	Shaft S Ø h6 x length	T	U	Basic weight	Weight per 100 mm
DL 120	360	120	96	39	47	78	42	42	10	68	79	M 5	M 6	M 6	15	156	3x3x25	10 x 27	M 6	60	5,1 kg	0,92 kg
DL 160	470	160	130	53	62	90	50	60	11	90	106	M 6	M 8	M 8	20	200	5x5x28	14 x 35	M 8	80	12,0 kg	1,96 kg
DL 200	590	200	160	66	68	140	60	60	15	110	129	M 8	M10	M10	20	270	6x6x40	22 x 45	M 8	100	27,1 kg	2,82 kg

T **Spindle:**
(T) Trapezoidal thread **(K)** Ballscrew

3 **Selection of screw:**
(3) right - left hand **(4)** divided spindle

0 **Choice of guide body profile:**

(0)



internal profile
with cover bands

(3)




with bellows


Stainless versions upon request.

0 **Choice of carriages:**


(0)



(2)



(3)



Size	Version 0 Q	Version 0 L	Version 2 Q	Version 2 L	Version 3 Q	Version 3 L
120	156	360	196	440	>236	>530
160	200	470	250	570	>300	>670
200	270	600	330	720	>410	>880

0 **Drive version:**
(0) shaft right hand thread **(1)** shaft left hand thread **(2)** shaft on both sides

0 **Selection of screw:**

	Size	Standard	Multistart screw
Ballscrew right hand	120	**(0)** 16x5	**(1)** 16x10* **(2)** 16x16* **(3)** 20x20* **(4)** 25x5* **(5)** 25x10*
	160	**(0)** 25x5	**(1)** 20x20* **(2)** 25x10* **(3)** 25x25*
	200	**(0)** 32x5	**(1)** 32x10* **(2)** 32x20* **(3)** 32x32*
Ballscrew left hand	upon request		
Trapezoidal right hand thread	120	**(0)** 18x4	**(1)** 18x8
	160	**(0)** 24x5	**(1)** 24x10
	200	**(0)** 32x6	**(1)** 32x12
Trapezoidal left hand thread	120	**(0)** 18x4	**(1)** 18x8
	160	**(0)** 24x5	**(1)** 24x10
	200	**(0)** 32x6	**(1)** 32x12

* = only for selection of divided spindle

0 **Ballscrew pitch accuracy:**
(0) 0,05 mm / 300 mm (Standard) **(2)** 0,025 mm / 300 mm

0 **End play of ball nut:**
(0) 0,04 mm (Standard), **(1)** < 0,02 mm, **(2)** 2% apply prestress


Repeatability:
± 0,2 mm Trapezoidal
± 0,025 mm Ballscrew

1500 Basic length + stroke = total length

DL	T	160	3	0	0	0	0	0	0	01500
		Pos.	1	2	3	4	5	6	7	


Sample ordering code:
DLT160, trapezoidal right - left hand thread, with internal profile and cover bands, standard carriage, shaft on the right hand side, spindle 24x5, 1030 mm stroke

Possible mounting styles



Positioning system DLT/DLK 120 P, 160 P, 200 P

Spindle drive






Function:
This unit consists of a rectangular aluminium profile with 2 integrated roller guides. The carriage is driven by means of a rotating spindle with leading nut. Where two parallel linear units are used or where two carriages are mounted on one unit, the leading-nut receiver can be used to adjust the symmetry of the carriages. A special curved aluminium sheet is covering the carriage side. There is only a small gap between carriage and aluminium sheet.

Fitting position: As required. Max. length DLT/K 120P / 1600mm, DLT/K 160P / 1800mm, DLT/K 200P / 2000mm
Carriage mounting: By tapped holes in the carriage.
Unit mounting: By T-slots and mounting sets. The linear axis can be combined with any T-slot profile.
Carriage support: In the standard version, the carriage runs on 8 rollers which can be adjusted and serviced at a central servicing position. For longer carriages the number of rollers can be increased. Repeatability ballscrew ± 0,025 mm, trapezoidal thread ± 0,2 mm.

Forces and torques



Size	120		160		200	
Forces/Torques	static	dynamic	static	dynamic	static	dynamic
F_x (N)	900	800	5000	4000	10000	8000
F_y (N)	1100	900	3000	2000	4400	3100
F_z (N)	1250	1000	3500	2800	4900	4400
M_x (Nm)	150	125	400	320	600	510
M_y (Nm)	140	120	360	300	560	480
M_z (Nm)	100	90	180	150	310	275
All forces and torques related to the following:						
existing values / table values	$\frac{Fy}{Fy_{dyn}} + \frac{Fz}{Fz_{dyn}} + \frac{Mx}{Mx_{dyn}} + \frac{My}{My_{dyn}} + \frac{Mz}{Mz_{dyn}} \leq 1$					
No-load torque						
Trapezoidal thread	18 x 4	18 x 8	24 x 5	24 x 10	32 x 6	32 x 12
(Nm)	0,6	0,9	0,6	0,9	0,9	1,1
Ballscrew	16 x 5	16 x 10	25 x 5	20 x 20	32 x 5	32 x 10
(Nm)	0,5	0,8	0,5	0,8	0,7	0,9
Geometrical moments of inertia of aluminium profile						
I_x mm^4	$6{,}6 \times 10^5$		$22{,}2 \times 10^5$		$63{,}8 \times 10^5$	
I_y mm^4	$38{,}6 \times 10^5$		$122{,}0 \times 10^5$		$335{,}0 \times 10^5$	
Elastic modulus N/mm^2	70000		70000		70000	

For life-time calculation of rollers use our homepage.

Driving torque:

$$M_a = \frac{F * P * S_i * w}{2000 * \pi * \mu} + M_n$$

$$P_a = \frac{M_a * n}{9550}$$


F	= force	(N)
P	= thread pitch	(mm)
Si	= safety factor 1,2 ... 2	
M_n	= no-load torque	(Nm)
n	= rpm of screw	(min^{-1})
M_a	= driving torque	(Nm)
μ	= screw efficiency	
w	= friction coefficient	~1,22
P_a	= motor power	(KW)

Efficiency of lead screws:

All ballscrew		0,900
Tr	18x4	0,399
Tr	18x8	0,565
Tr	24x5	0,384
Tr	24x10	0,550
Tr	32x6	0,360
Tr	32x12	0,524

Deflection:


$$f = \frac{F * L^3}{E * I * 192}$$





f = deflection	(mm)
F = load	(N)
L = free length	(mm)
E = elastic modulus 70000	(N/mm^2)
I = second moment of area	(mm^4)

Drehzahldiagramm für Spindelachsen siehe Katalog - Kapitel 4.2

Positioning system DLT/DLK 120 P, 160 P, 200 P







*For slide nuts refer to chapter 2.2 page 2
Increasing the carriage length will increase the basic length by the same amount.

DL 120 M1 = M6 x 8 only 8 threaded holes in the carriage
DL 160 M1 = M8 x 12 **DL 200** M1 = M10 x 12
V = Q + 100 mm W = servicing position


Size	Basic length L	A	C	D +0,1 +0,05	E	F	G	H	I	J	K	M for	N for	P	Q	Shaft R Key	Shaft S Ø h6 x length	T	U	X	Y	Z	Basic weight	Weight per 100 mm
DL 120	220	120	39	47	78	42	42	10	67	82	79	M5	M6	12	152	3x3x25	10 x 27	M6	120	106	40	11,5	4,20 kg	1,16 kg
DL 160	277	160	53	62	90	50	60	11	89	109	106	M6	M8	20	196	5x5x28	14 x 35	M8	160	144	80	15	9,70 kg	1,98 kg
DL 200	340	200	66	68	140	60	60	15	110	133	129	M8	M10	20	256	6x6x40	22 x 45	M8	200	180	100	17	18,70 kg	3,16 kg

T **Spindle:** **(T)** Trapezoidal thread **(K)** Ballscrew

1 **Selection of screw:** **(1)** right hand *(Standard)* **(2)** left hand *(Ballscrew by inquiry)*


0 **Choice of guide body profile:** Stainless versions upon request.

(0)



with cover profile

(1)




without cover profile


Size	Version 0 Q	Version 0 L	Version 2 Q	Version 2 L	Version 3 Q	Version 3 L
120	152	220	192	260	>240	>308
160	196	277	250	331	>300	>381
200	256	340	330	414	>410	>494

0 **Choice of carriages::**


(0)



(2)



(3)



0 **Drive version:**
(0) right (locating bearing side) **(1)** left (non-locating bearing side) **(2)** shaft on both sides

0

Selection of screw:	Size	Standard	Multistart screw				
Ballscrew right hand	120	**(0)** 16x5	**(1)** 16x10	**(2)** 16x16	**(3)** 20x20*	**(4)** 25x5*	**(5)** 25x10*
	160	**(0)** 25x5	**(1)** 20x20	**(2)** 25x10	**(3)** 25x25		
	200	**(0)** 32x5	**(1)** 32x10	**(2)** 32x20	**(3)** 32x32		
Ballscrew left hand			upon request				
Trapezoidal right hand thread	120	**(0)** 18x4	**(1)** 18x8				
	160	**(0)** 24x5	**(1)** 24x10				
	200	**(0)** 32x6	**(1)** 32x12				
Trapezoidal left hand thread	120	**(0)** 18x4	**(1)** 18x8				
	160	**(0)** 24x5	**(1)** 24x10				
	200	**(0)** 32x6	**(1)** 32x12		* by inquiry		

0 **Ballscrew pitch accuracy:**
(0) 0,05 mm / 300 mm *(Standard)* **(2)** 0,025 mm / 300 mm

0 **End play of ball nut:**
(0) 0,04 mm *(Standard)*, **(1)** < 0,02 mm, **(2)** 2% apply prestress

DL	T	160 P	1	0	0	0	0	0	0	01500	1500
		Pos.	1	2	3	4	5	6	7		

Basic length + stroke = total length

Sample ordering code:
DLT 160 P, trapezoidal right hand thread, with cover profile, standard carriage (0), right (locating bearing side), spindle (standard), 1220 mm stroke.

Positioning system DLZ 120, 160, 200

Belt drive




COLANDIS
the clean air company

Function:
This unit consists of a rectangular aluminium profile with 2 integrated roller guides. The carriage is moved by a belt drive. Each standard pulley has got one coupling claw on one side. Belt tension can be readjusted by a simple screw adjustment device in the carriage. This device can also be used for symmetrical adjustment of two or more linear units running parallel. The openings of the guide body are sealed with 3 stainless steel cover bands to protect the guide from splash water and dust. Alternatively, the opening can also be covered with a bellow or can be delivered without cover bands.

Fitting position: As required. Max. length 6.000 mm without joints.
Carriage mounting: By T-slots.
Unit mounting: By T-slots and mounting sets. The linear axis can be combined with any T-slot profile.
Belt type: HTD with steel reinforcement, no backlash when changing direction, repeatability ± 0,1 mm.
Carriage support: In the standard version, the carriage runs on 8 rollers which can be adjusted and serviced at a central servicing position. For longer carriages the number of rollers can be increased.

Forces and torques



Size	120		160		200	
Forces/Torques	static	dynamic	static	dynamic	static	dynamic.
F_x (N)	894	800	1900	1800	4000	3800
F_y (N)	1100	900	3000	2000	4400	3100
F_z (N)	1250	1000	3500	2800	4900	4400
M_x (Nm)	150	125	400	320	600	510
M_y (Nm)	140	120	360	300	560	480
M_z (Nm)	100	90	180	150	310	275
All forces and torques related to the following: existing values / table values $\frac{Fy}{Fy_{dyn}} + \frac{Fz}{Fz_{dyn}} + \frac{Mx}{Mx_{dyn}} + \frac{My}{My_{dyn}} + \frac{Mz}{Mz_{dyn}} \leq 1$						
No-load torque						
Nm without cover bands	1,2		1,5		1,8	
Nm with cover bands	1,6		2,1		4	
Speed						
(m/s) max	4		6		8	
Tensile force						
permanent (N)	900		1900		4000	
0,2 s (N)	1000		2090		4300	
Geometrical moments of inertia of aluminium profile						
I_x mm^4	6,6x10^5		22,2x10^5		63,8x10^5	
I_y mm^4	38,6x10^5		122,0x10^5		335x10^5	
Elastic modulus N/mm^2	70000		70000		70000	

For life-time calculation of rollers use our homepage.


Driving torque:

$$M_a = \frac{F * P * S_i}{2000 * \pi} + M_n$$

$$P_a = \frac{M_a * n}{9550}$$

F = force (N)
P = pulley action perimeter (mm)
Si = safety factor 1,2 ... 2
M_n = no-load torque (Nm)
n = rpm pulley (min^{-1})
M_a = driving torque (Nm)
P_a = motor power (KW)

Deflection:




$$f = \frac{F * L^3}{E * I * 192}$$

f = deflection (mm)
F = load (N)
L = free length (mm)
E = elastic modulus 70000 (N/mm^2)
I = second moment of area (mm^4)

BAHR Modultechnik

Positioning system DLZ 120, 160, 200

Dimensions (mm)



V = Q + 100 mm
W = servicing position


*For slide nuts refer to chapter 2.2 page 2


Increasing the carriage length will increase the basic length by the same amount.


Size	Basic length L	A	B	C	D -0,05	E	F	G	H	I	J	K	M for	N for	O for	P	Q	T	U	X	Y	Basic weight	Weight per 100 mm
DLZ 120	330	120	96	80	47	78	42	58	10	10	68	79	M 5	M 6	M 6	70	156	M 6	60	28	35	5,1 Kg	0,85 Kg
DLZ 160	440	160	130	100	68	90	60	78	11	12	90	106	M 6	M 8	M 8	95	200	M 8	80	39	45	13,0 kg	1,69 kg
DLZ 200	530	200	160	130	90	140	80	97	15	15	110	129	M 8	M10	M10	110	270	M10	100	49	50	23,4 kg	2,33 kg

8.1

0 Choice of guide body profile:

(0)

internal profile with cover bands

(1)

internal profile without cover bands


(2)

without internal profile and cover bands


(3)


with bellows

Stainless versions upon request.

0 Choice of carriage:


(0)


(2)


(3)


Size	Version 0		Version 2		Version 3	
	Q	L	Q	L	Q	L
120	156	330	196	370	>236	>410
160	200	440	250	490	>300	>540
200	270	530	330	600	>410	>680

0 Drive version:



9 is as 0, but with coupling claws on both sides.
The standard version is supplied without shaft. A shaft can be retrofitted by inserting it into the pulley bore and securing it with 2 locking rings or tension sets (size 200).

Belt table

Code No.		Size	Belt	mm/rev.	Number of teeth
0	**4**	120	5M25	130	26
0	**7**	160	8M30	176	22
0	**9**	160	8M50	176	22
0	**9**	200	8M50	224	28
1	**0**	200	8M70	224	28

Shaft dimensions / Coupling claw

Size	Shaft ø h6 x length	Key	Coupling
120 (5M25)	14 x 35	5x5x28	14
160 (8M30)	18 x 45	6x6x40	19
160 (8M50)	25 x 35	8x7x32	— *
200 (8M50)	22 x 45	6x6x40	24
200 (8M70)	30 x 55	8x7x50	— *

DLZ	160	1	0	0	0	0	7	1	01500
	Pos.	1	2	3	4	5	6	7	


Basic length + stroke = total length

* Coupling claw not possible with belt widening.

Sample ordering code:
DLZ160 with internal profile and cover bands, standard carriage, coupling claw on one side, 1060 mm stroke.

Positioning system DLZZ 160, 200


Belt drive with two separately driven carriages



Function:
This unit consists of a rectangular aluminium profile with 2 integrated roller guides. The carriage is moved by a belt drive. Each carriage can be moved separately by its own drive. This unit has twin pulleys, which run on separate bearings, and two independent, parallel drive belts, one for each carriage. The openings of the guide body are sealed with 3 stainless steel cover bands to protect the guide from splash water and dust.

Fitting position: As required. Max. length 4.000 mm without joints.
Carriage mounting: By T-slots
Unit mounting: By T-slots and mounting sets. The linear axis can be combined with any T-slot profile.
Belt type: HTD with steel reinforcement, no backlash when changing direction, repeatability ± 0,1 mm.
Carriage support: In the standard version, the carriage runs on 8 rollers which can be adjusted and serviced at a central servicing position. For longer carriages the number of rollers can be increased.

Forces and torques



Size	120		160		200	
Forces/Torques	static	dynamic.	static	dynamic.	static	dynamic.
F_x (N)			1210	1100	1900	1800
F_y (N)			3000	2000	4400	3100
F_z (N)			3500	2800	4900	4400
M_x (Nm)			400	320	600	510
M_y (Nm)			360	300	560	480
M_z (Nm)			180	150	310	275
All forces and torques related to the following: existing values / table values $\frac{Fy}{Fy_{dyn}} + \frac{Fz}{Fz_{dyn}} + \frac{Mx}{Mx_{dyn}} + \frac{My}{My_{dyn}} + \frac{Mz}{Mz_{dyn}} \leq 1$						
No-load torque						
Nm without cover bands			1,5		1,8	
Nm with cover bands			2,1		4	
Speed						
(m/s) max			6		8	
Tensile force						
permanent (N)			1900		4000	
0,2 s (N)			2090		4300	
Geometrical moments of inertia of aluminium profile						
I_x mm⁴			22,2x10⁵		63,8x10⁵	
I_y mm⁴			122,0x10⁵		335x10⁵	
Elastic modulus N/mm²			70000		70000	

For life-time calculation of rollers use our homepage.

Driving torque:


$$M_a = \frac{F * P * S_i}{2000 * \pi} + M_n$$

$$P_a = \frac{M_a * n}{9550}$$

F = force (N)
P = pulley action perimeter (mm)
Si = safety factor 1,2 ... 2
M_n = no-load torque (Nm)
n = rpm pulley (min^{-1})
M_a = driving torque (Nm)
P_a = motor power (KW)

Deflection:


$$f = \frac{F * L^3}{E * I * 192}$$




f = deflection (mm)
F = load (N)
L = free length (mm)
E = elastic modulus 70000 (N/mm²)
I = second moment of area (mm⁴)

Positioning system DLZZ 160, 200







V = Q + 100 mm W = servicing position

*For slide nuts refer to chapter 2.2 page 2


Increasing the carriage length will increase the basic length by the same amount.

Size	Basic length L	A	B	C	D	E	F	G	H	I	J	K	M for	N for	O for	P	Q	T	X	Y	Basic weight	Weight per 100 mm
DLZZ 160	615	160	130	100	68	90	60	78	11	12	90	106	M6	M8	M8	95	200	M8	39	45	16,0 kg	1,69 kg
DLZZ 200	790	200	160	150	90	140	80	97	15	15	110	129	M8	M10	M10	110	270	M10	49	50	28,50 kg	2,33 kg

8.1


0 **Choice of guide body profile:** Stainless versions upon request.

(0)




internal profile with cover bands

(1)



internal profile without cover bands


(2)




without internal profile and cover bands

0 **Choice of carriage:**


(0)



(2)




(3)



Size	Version 0		Version 2		Version 3	
	Q	L	Q	L	Q	L
160	200	615	250	715	300	830
200	270	790	330	910	410	1070

0 **Drive version:**



Belt table:

Code No.		Size	Belt	mm/rev.	Number of teeth
0	6	**160**	8M 20	176	22
0	7	**200**	8M 30	224	28

Shaft dimensions / Coupling claw:

Size	Shaft ø h6 x length	Key	Coupling
DLZZ 160 1	Ø 18 x 45	6x6x35	19
DLZZ 160 2	Ø 14 x 35	5x5xx28	19
DLZZ 200 1	Ø 22 x 45	6x6x40	24
DLZZ 200 2	Ø 18 x 45	6x6x40	24


DLZZ	200	4	0	0	2	0	7	1	01500
Pos.		1	2	3	4	5	6	7	

Basic length + stroke = total length


Sample ordering code:
DLZZ 200 with internal profile and cover bands, carriage version 0, drive version 2, 710 mm stroke.

Positioning system DLZPVI 120, 160, 200

Belt drive




Size	A1	□ B1	Ø TK	Ø C1 +0,1 +0,05	D1	E1	F1
DLZPVI 120	57	48,1	68	60	48	16	M5
DLZPVI 160	46,5	60,1	85	70	56	22	M6
DLZPVI 200	69,5	84,9	120	90	88	32	M8



Function:
This unit consists of a rectangular aluminium profile with 2 integrated roller guides. The carriage is moved by a belt drive. On the drive side the pulley is beared on the shaft of a planetary gear. Belt tension can be readjusted by a simple screw adjustment at the opposite side of the drive. A special curved aluminium sheet is covering the carriage side. There is only a small gap between carriage and aluminium sheet. Because of its special design it is possible to drive the carriage over the pulley areas. This fact is making the unit very compact. The cover profile can be adjusted according to the mounting position.

Fitting position: As required, max. length DLZPVI 120 / 1600mm, DLZPVI 160 / 1800mm, DLZPVI 200 / 2000mm
Carriage mounting: By tapped holes.
Unit mounting: T-slots
Belt type: HTD with steel reinforcement, no backlash when changing direction, repeatability ± 0,1 mm.
Carriage support: In the standard version, the carriage runs on 4 runner blocks which can be serviced at a central servicing position. For longer carriages the number of runner blocks can be increased.

Forces and torques



Size	120		160		200	
Forces/Torques	static	dynamic	static	dynamic	static	dynamic.
F_x (N)	894	800	1900	1800	4000	3800
F_y (N)	1100	900	3000	2000	4400	3100
F_z (N)	1250	1000	3500	2800	4900	4400
M_x (Nm)	150	125	400	320	600	510
M_y (Nm)	140	120	360	300	560	480
M_z (Nm)	100	90	180	150	310	275
All forces and torques related to the following: existing values / table values $\frac{Fy}{Fy_{dyn}} + \frac{Fz}{Fz_{dyn}} + \frac{Mx}{Mx_{dyn}} + \frac{My}{My_{dyn}} + \frac{Mz}{Mz_{dyn}} \leq 1$						
No-load torque						
Nm	1,2		1,5		1,8	
Speed						
(m/s) max	4		6		8	
Tensile force						
permanent (N)	900		1900		4000	
0,2 s (N)	1000		2090		4300	
Geometrical moments of inertia of aluminium profile						
I_x mm⁴	6,6 x 10⁵		22,2 x 10⁵		57,2 x 10⁵	
I_y mm⁴	38,6 x 10⁵		122,0 x 10⁵		310 x 10⁵	
Elastic modulus N/mm²	70000		70000		70000	

For life-time calculation of rollers use our homepage.


Driving torque:

$$M_a = \frac{F * P * S_i}{2000 * \pi} + M_n$$

$$P_a = \frac{M_a * n}{9550}$$

F = force (N)
P = pulley action perimeter (mm)
Si = safety factor 1,2 ... 2
M_n = no-load torque (Nm)
n = rpm pulley (min^{-1})
M_a = driving torque (Nm)
P_a = motor power (KW)

Deflection:




$$f = \frac{F * L^3}{E * I * 192}$$

f = deflection (mm)
F = load (N)
L = free length (mm)
E = elastic modulus 70000 (N/mm^2)
I = second moment of area (mm^4)

Positioning system DLZPVI 120, 160, 200


Dimensions (mm)






Optionally available with angular planetary gearbox

Increasing the carriage length will increase the basic length by the same amount.






*slide nuts


DLZPVI 120 M1 = M6 x 8 only 8 threaded holes in the carriage
DLZPVI 160 M1 = M8 x 12 **DLZPVI 200** M1 = M10 x 12


V = Q + 100
W = servicing position

Size	Basic length L	A	C	D	G	I	K	M for	N for	O	P1	P2	Q	R	S	T	U	Basic weight *without gearbox*	Weight per 100 mm
DLZPVI 120	225	120	78	169	82,5	60	79	M6	M5	78	2	35	152	11,5	106	40	120	3,74 kg	0,65 kg
DLZPVI 160	285	160	90	217,5	108,5	80	106	M8	M6	104	3	52,5	196	15	144	80	160	10,42 kg	1,26 kg
DLZPVI 200	350	200	140	251	132,5	100	129	M10	M8	128	3	62,5	256	17	180	100	200	17,44 kg	2,18 kg

0 **Choice of guide body profile:** *Stainless versions upon request.*


(0)  with cover profile


(1)  without cover profile




belt connection

0 **Choice of carriages:**


(0) 


(2) 


(3) 

Size	Version 2		Version 3	
	Q	L	Q	L
120	192	265	232	305
160	246	335	296	385
200	320	420	400	500

0 **Drive version:**

(0) 

(1) 

(2) 

(0) planetary gearbox
(1) angular planetary gearbox
(2) without gearbox

Belt table:

Code-No.		Size	Belt	mm/rev.	Number of teeth
0	**4**	**120**	5M25	130	26
0	**7**	**160**	8M30	176	22
0	**9**	**200**	8M50	224	28

Gearbox variants:

Gearbox		DLZPVI 120	DLZPVI 160	DLZPVI 200
Neugart	(0)	PLN 70	PLN 90	PLN 115
	(1)	WPLN 70	WPLN 90	WPLN 115
SEW	(0)	PSKC 221	PSKC 321	PSKC 521
Wittenstein	(0)	SP+060	SP+075	SP+100
	(1)	SK+060	SK+075	SK+100


DLZPVI	160	1	0	0	0	0	7	1	01500
	Pos.	1	2	3	4	5	6	7	

Basic length + stroke = total length

Sample ordering code:
DLZPVI 160 with cover profile, standard carriage, with planetary gearbox, 1202 mm stoke.

Positioning system DLZA 120, 160, 200


Rack and pinion drive



Function:
This unit consists of a rectangular aluminium profile with 2 integrated roller guides. The carriage, which has internal linear ball bearings that can be adjusted free of play, is driven along the guide rods by a high precision rack. The rack and pinion system is suitable for highly dynamic servo operation and ideal for lifting movements. The pinion is equipped with maintenance-free ball bearings. The rack is lubricated by a toothed felt wheel.

Fitting position: As required. Max. length 6.000 mm without joints.
Carriage mounting: By T-slots.
Unit mounting: By T-slots and mounting sets. The linear axis can be combined with any T-slot profile.
Rack: 6h23 Modul 2 (hardened and ground), repeatability ± 0,1 mm.
Carriage support: In the standard version, the carriage runs on 8 rollers which can be adjusted and serviced at a central servicing position. For longer carriages the number of rollers can be increased.

Forces and torques



Size	160		200	
Forces/Torques	static	dynam.	static	dynam.
F_x (N)	1900	1800	4000	3800
F_y (N)	3000	2000	4400	3100
F_z (N)	3500	2800	4900	4400
M_x (Nm)	400	320	600	510
M_y (Nm)	360	300	560	480
M_z (Nm)	180	150	310	275
All forces and torques related to the following: existing values / table values: $\frac{Fy}{Fy_{dyn}} + \frac{Fz}{Fz_{dyn}} + \frac{Mx}{Mx_{dyn}} + \frac{My}{My_{dyn}} + \frac{Mz}{Mz_{dyn}} \leq 1$				
No-load torque				
Nm	1,5		2,6	
Speed				
(m/s) max	3		5,0	
Tensile force				
permanent (N)	1900		3000	
Geometrical moments of inertia of aluminium profile				
I_x mm^4	22,2x10^5		63,8x10^5	
I_y mm^4	122,0x10^5		335x10^5	
Elastic modulus N/mm^2	70000		70000	

For life-time calculation of rollers use our homepage.

Driving torque:


$$M_a = \frac{F * P * S_i}{2000 * \pi} + M_n$$

$$P_a = \frac{M_a * n}{9550}$$

F	= force	(N)
P	= pulley action perimeter	(mm)
Si	= safety factor 1,2 ... 2	
M_n	= no-load torque	(Nm)
n	= rpm pulley	(min^{-1})
M_a	= driving torque	(Nm)
P_a	= motor power	(KW)

Deflection:


$$f = \frac{F * L^3}{E * I * 192}$$





f = deflection	(mm)
F = load	(N)
L = free length	(mm)
E = elastic modulus 70000	(N/mm^2)
I = second moment of area	(mm^4)

Positioning system DLZA 120, 160, 200

Dimensions (mm)







V = Q + 100 mm
W = servicing position

*For slide nuts refer to chapter 2.2 page 2

Increasing the carriage length will increase the basic length by the same amount.

Size	Basic length L	A	B	C	D ±0,05	E	F	G	H	J	K	M	N	O for	Ox for	Oy for	P	Q	T for	U	X	Basic weight	Weight per 100 mm
DLZA 160	240	160	130	100	68	90	16,5	56,5	11	90	106	60	59	M 8	M 8	M 6	12	200	M 8	80	8,5	13,0 kg	2,10 kg
DLZA 200	320	200	160	120	90	140	20	45	15	110	129	80	95	M 10	M 10	M 8	15	270	M 8	100	5	28,9 kg	6,15 kg

8.1

0 Choice of guide body profile:


(0) internal profile with cover bands

(1) internal profile without cover bands

(3) with bellows


Stainless versions upon request.

0 Choice of carriage:



Size	Version 0		Version 1		Version 2		Version 3	
	Q	L	Q	L	Q	L	Q	L
160	200	240	250	290	>300	>340	-	-
200	270	320	330	380	>410	>460	>535	>580

1 Drive version:



Shaft dimensions

Size	Shaft ø h6 x length	Key	Pinion	
	S	R	mm/rev.	Modul
160	20 x 40	6x6x35	100,53	2
200	18 x 25	6x6x20	94,25	2


DLZA	160	1	0	0	1	0	0	1	01500
Pos.		1	2	3	4	5	6	7	

Basic length + stroke = total length

Sample ordering code:
DLZA160 with internal profile and cover bands, standard carriage,1260 mm stroke.

Positioning system DLSZ 120, 160, 200


Belt drive



Function:
This linear unit consists of a rectangular aluminium profile with integrated, hardened steel guide rods. The carriage, which has linear ball bearings that can be adjusted free of play, is driven along the guide rods by a timing belt. Each standard pulley includes a coupling claw on one side and is equipped with maintenance-free ball bearings. Belt tension can be readjusted by a simple screw adjustment device in the carriage. This device can also be used for symmetrical adjustment of two or more linear units running parallel.

Fitting position: As required. Max. length 6.000 mm without joints.
Carriage mounting: By T-slots.
Unit mounting: By T-slots and mounting sets. The linear axis can be combined with any T-slot profile.
Belt performance: HTD with steel reinforcement, no backlash when changing direction, repeatability ± 0,1 mm.
Carriage support: In the standard version, the carriage runs on 8 rollers which can be adjusted and serviced at a central servicing position. For longer carriages the number of rollers can be increased.

Forces and torques



Size	120		160		200	
Forces/Torques	static	dynamic	static	dynamic	static	dynamic
F_x (N)	1900	1800	4000	3800	5900	5750
F_y (N)	1100	900	3000	2000	4400	3100
F_z (N)	1250	1000	3500	2800	4900	4400
M_x (Nm)	150	125	400	320	600	510
M_y (Nm)	140	120	360	300	560	480
M_z (Nm)	100	90	180	150	310	275
All forces and torques related to the following: existing values / table values	$\frac{Fy}{Fy_{dyn}} + \frac{Fz}{Fz_{dyn}} + \frac{Mx}{Mx_{dyn}} + \frac{My}{My_{dyn}} + \frac{Mz}{Mz_{dyn}} \leq 1$					
No-load torque						
Nm	1,1		1,5		1,8	
Speed						
(m/s) max	4		6		8	
Tensile force						
permanent (N)	1900		4000		5900	
0,2 s (N)	2090		4300		6350	
Geometrical moments of inertia of aluminium profile						
I_x mm^4	6,6x10^5		2,22x10^6		6,38x10^6	
I_y mm^4	38,6x10^5		12,20x10^6		33,5x10^6	
Elastic modulus N/mm^2	70000		70000		70000	

For life-time calculation of rollers use our homepage.


Driving torque:

$$M_a = \frac{F * P * S_i}{2000 * \pi} + M_n$$

$$P_a = \frac{M_a * n}{9550}$$

F = force (N)
P = pulley action perimeter (mm)
Si = safety factor 1,2 ... 2
M_n = no-load torque (Nm)
n = rpm pulley (min^{-1})
M_a = driving torque (Nm)
P_a = motor power (KW)

Deflection:





$$f = \frac{F * L^3}{E * I * 192}$$


f = deflection (mm)
F = load (N)
L = free length (mm)
E = elastic modulus 70000 (N/mm^2)
I = second moment of area (mm^4)

Positioning system DLSZ 120, 160, 200

Dimensions (mm)







V = Q + 100 mm
W = servicing position

*For slide nuts refer to chapter 2.2 page 2

Increasing the carriage length will increase the basic length by the same amount.

Size	Basic length L	A	B	C	D -0,05	E	F	G	H	J	K	I for	M for	N for	O for	P	Q	R	S	T	U	X	Y	Basic weight	Weight per 100 mm
DLSZ 120	230	120	96	100	68	78	60	100	10	68	79	M 6	M 5	M 6	M 6	10	200	39	42	M 8	60	180	39	12,0 kg	1,2 kg
DLSZ 160	330	160	130	130	90	90	80	130	11	105	106	M 8	M 6	M 8	M 8	12	290	53	60	M 10	80	270	60	27,0 kg	1,8 kg
DLSZ 200	380	200	160	160	110	140	100	145	15	128	129	M 10	M 8	M 10	M 10	15	340	69	95	M 10	100	310	62	53,0 kg	2,6 kg

1 **Choice of guide body profile:**


(1) internal profile without cover bands

(2) without internal profile and cover bands

(3) with bellows


Stainless versions upon request.

0 **Choice of carriages:**



Size	Version 0		Version 1		Version 2	
	Q	L	Q	L	Q	L
120	200	230	>280	>310	>360	>390
160	290	330	>390	>430	>490	>530
200	340	380	>480	>520	>610	>650

0 **Drive version:**



8 is as 0, but with coupling claws on both sides. The standard version is supplied without shaft. A shaft can be retrofitted by inserting it into the pulley bore and securing it with 2 locking rings or tension sets (size 160 and 200).

Belt table

Code No.		Size	Belt	mm/rev.	Number of teeth
0	**7**	**120**	8M30	192	24
0	**9**	**160**	8M50	256	32
1	**0**	**200**	8M70	304	38

Shaft dimensions / Coupling claw

Size	Shaft ø h6 x length	Key	Coupling
120	18 x 45	6x6x40	19
160	22 x 45	6x6x40	24
200	30 x 55	8x7x50	28


Basic length + stroke = total length

DLSZ	120	1	1	0	0	0	7	2	01500
	Pos.	1	2	3	4	5	6	7	

Sample ordering code:
DLSZ120, body profile with internal profile without cover bands, standard carriage, coupling claws on one side, 1270 mm stroke

Positioning system DLVZ 120, 160


Internal belt drive



Function:
This unit consists of a rectangular aluminium profile with 2 integrated roller guides. The carriage is moved by a belt drive. Belt tension can be readjusted by a simple screw adjustment device in the carriage. This device can also be used for symmetrical adjustment of two or more linear units running parallel. The openings of the guide body are sealed with 3 stainless steel cover bands to protect the guide from splash water and dust. Alternatively, the opening can also be covered with a bellow or can be delivered without cover bands.

Fitting position: As required. Max. length 3.000 mm without joints.
Carriage mounting: By T-slots.
Unit mounting: By T-slots and mounting sets. The linear axis can be combined with any T-slot profile.
Belt type: HTD with steel reinforcement, no backlash when changing direction, repeatability ± 0,1 mm.
Carriage support: In the standard version, the carriage runs on 8 rollers which can be adjusted and serviced at a central servicing position. For longer carriages the number of rollers can be increased.

Forces and torques



Size	DLVZ 120		DLVZ 160		DLVZ 200	
Forces/Torques	static	dynamic	static	dynamic	static	dynamic
F_x (N)	894	800	1000	840		
F_y (N)	1100	900	3000	2000		
F_z (N)	1250	1000	3500	2800		
M_x (Nm)	150	125	400	320		
M_y (Nm)	140	120	360	300		
M_z (Nm)	100	90	180	150		
All forces and torques relate to the following: existing values / table values: $\frac{Fy}{Fy_{dyn}} + \frac{Fz}{Fz_{dyn}} + \frac{Mx}{Mx_{dyn}} + \frac{My}{My_{dyn}} + \frac{Mz}{Mz_{dyn}} \leq 1$						
No-load torque						
Nm	1,4		1,8			
Speed						
(m/s) max	3		4			
Tensile force						
permanent (N)	900		1000			
0,2 s (N)	1000		1150			
Geometrical moments of inertia of aluminium profile						
I_x mm^4	6,6x10^5		22,2x10^5			
I_y mm^4	38,6x10^5		122,0x10^5			
E-Modulus N/mm^2	70000		70000			

For life-time calculation of rollers use our homepage.

Driving torque:


$$M_a = \frac{F * P * S_i}{2000 * \pi} + M_n$$

$$P_a = \frac{M_a * n}{9550}$$

F = force (N)
P = pulley action perimeter (mm)
Si = safety factor 1,2 ... 2
M_n = no-load torque (Nm)
n = rpm pulley (min^{-1})
M_a = driving torque (Nm)
P_a = motor power (KW)

Deflection:


$$f = \frac{F * L^3}{E * I * 192}$$





f = deflection (mm)
F = load (N)
L = free length (mm)
E = elastic modulus 70000 (N/mm^2)
I = second moment of area (mm^4)

Positioning system DLVZ 120, 160

Dimensions (mm)








V = Q + 100 mm
W = servicing position


*For slide nuts refer to chapter 2.2 page 2


Increasing the carriage length will increase the basic length by the same amount


Size	Basic length L	A	B	C	D -0,05	E	F	G	H	I	J	K	M for	N for	O for	P	Q	R	S	T	U	X	Y	Basic weight	Weight per 100 mm
DLVZ 120	300	120	96	56	37	78	30	36	10	10	68	79	M5	M6	M6	56	156	2,5	82	M6	60	28	24	4,62 kg	0,82 kg
DLVZ 160	410	160	130	74	47	90	40	50	11	12	90	106	M6	M8	M8	76	200	8,5	102	M 8	80	37	35	11,23 kg	1,76 kg
DLVZ 200																									

1 **(1)** Belt connection right  **(2)** Belt connection left 

0 **Choice of guide body profile:**

(0)

internal profile with cover bands

(1)

internal profile without cover bands



(2)

without internal profile and cover bands


(3)

with bellows

Stainless versions upon request.


0 **Choice of carriages:**

(0)  **(2)** 

(3) 

Size	Version 0		Version 2		Version 3	
	Q	L	Q	L	Q	L
120	156	300	196	340	236	380
160	200	410	250	460	>300	>510
200						

0 **Drive version:**



The standard version 0 is supplied with 4 flush mounted shafts.

Belt table

Code No.		Size	Belt	mm/rev.	Number of teeth
0	**4**	**120**	5M25	80	16
0	**4**	**160**	5M25	110	22
0	**9**	**200**			

Shaft dimensions

Size	Shaft ø h6 x length	Key
120	14 x 35	5x5x28
160	18 x 45	6x6x40
200		

Basic length + stroke = total length


DLVZ	160	1	0	0	0	0	4	1	01500
	Pos.	1	2	3	4	5	6	7	

For combination kits and connecting elements refer to chapter 2.2

Sample ordering code:
DLVZ 160 with belt connection right, internal profile with cover bands, standard carriage and 4 flush mounted shafts, 1090 mm stroke

Positioning system DLR 120, 160, 200


Roller unit without drive



Function:
This unit consists of a rectangular aluminium profile with 2 integrated roller guides. The openings of the guide body are sealed with 3 stainless steel cover bands to protect the guide from splash water and dust. Alternatively, the opening can also be covered with a bellow or can be delivered without cover bands. The roller guide can be either driven by an internal pneumatic cylinder or other additional drives or it serves as load carrying linear slide.

Fitting position: As required. Max. length 6.000 mm without joints.
Carriage mounting: By T-slots.
Unit mounting: By T-slots and mounting sets. The linear axis can be combined with any T-slot profile.
Carriage support: In the standard version, the carriage runs on 8 rollers which can be adjusted and serviced at a central servicing position. For longer carriages the number of rollers can be increased.

Forces and torques




Size	120		160		200	
Forces/Torques	static	dynamic	statisch	dynam.	statisch	dynam.
F_x (N)	-	-	-	-	-	-
F_y (N)	1100	900	3000	2000	4400	3100
F_z (N)	1250	1000	3500	2800	4900	4400
M_x (Nm)	150	125	400	320	600	510
M_y (Nm)	140	120	360	300	560	480
M_z (Nm)	100	90	180	150	310	275
All forces and torques related to the following:						
existing values / table values	$\frac{Fy}{Fy_{dyn}} + \frac{Fz}{Fz_{dyn}} + \frac{Mx}{Mx_{dyn}} + \frac{My}{My_{dyn}} + \frac{Mz}{Mz_{dyn}} \leq 1$					
Speed						
(m/s) max	4		6		8	
Geometrical moments of inertia of aluminium profile						
I_x mm^4	$6{,}6 \times 10^5$		$22{,}2 \times 10^5$		$63{,}8 \times 10^5$	
I_y mm^4	$38{,}6 \times 10^5$		$122{,}0 \times 10^5$		$335{,}0 \times 10^5$	
Elastic modulus N/mm²	70000		70000		70000	

For life-time calculation of rollers use our homepage.

Deflection:


$$f = \frac{F * L^3}{E * I * 192}$$





f = deflection (mm)
F = load (N)
L = free length (mm)
E = elastic modulus 70000 (N/mm²)
I = second moment of area (mm⁴)

Positioning system DLR 120, 160, 200

Dimensions (mm)







V = Q + 100 mm
W = servicing position

*For slide nuts refer to chapter 2.2 page 2


Increasing the carriage length will increase the basic length by the same amount.

Size	Basic length L	A	B	E	H	J	K	M for	N for	O for	P	Q	U	Basic weight	Weight per 100 mm
DLR 120	200	120	96	78	10	68	79	M 5	M 6	M 6	10	156	60	3,2 kg	0,71 kg
DLR 160	240	160	130	90	11	90	106	M 6	M 8	M 8	12	200	80	6,9 kg	1,42 kg
DLR 200	320	200	160	140	15	110	129	M 8	M 10	M 10	15	270	100	11,4 kg	2,30 kg

8.1


0 **Choice of guide body profile:**

(0)




internal profile
with cover bands

(1)




internal profile
without cover bands

(2)



without internal profile
and cover bands

(3)




with bellows


Stainless versions upon request.

0 **Choice of carriages:**


(0)



(2)



(3)



Size	Version 0		Version 2		Version 3	
	Q	L	Q	L	Q	L
120	156	200	196	240	>236	>280
160	200	240	250	290	>300	>340
200	270	320	330	380	>410	>470


1500 Basic length + stroke = total length

DLR	**160**	**0**	**0**	**0**	**0**	**0**	**0**	**01500**
Pos.		1	2	3	4	5	6	7

Sample ordering code:
DLR160, with internal profile and cover bands, standard rollers, 1260 mm stroke.


Dust sealing D 160, 200 Systems

Without cable chain
Code-No.: 028x0



Function:
The dust seal consists of a specially formed aluminium sheet which is provided with a smooth running brush and is available either with or without energy chain take-up. This cover makes it possible to retrofit existing D 160, 200 positioning systems with a sealing.

With cable chain
Code-No.:028x1




*For slide nuts refer to carriage profile QL/QS chapter 2.2 page 2

Code-No.	for Size	Basic length L	A	B	C	D	E	F	G	H	J	K	MM for	Basic weight	Weight per 100 mm
02830	**D** 120	**													
02831	**D** 120	**													
02840	**D** 160	**	176	143	-	78	119	80	50	23	-	-	M 8	** kg	0,40 kg
02841	**D** 160	**	176	143	228	78	119	80	50	23	27	50	M 8	** kg	0,54 kg
02850	**D** 200	**	216	163	-	80	139	100	66	26	-	-	M 10	** kg	0,46 kg
02851	**D** 200	**	216	163	248	80	139	100	66	26	27	50	M 10	** kg	0,60 kg


** System dependent

02851	**2000**

Sample ordering code:
D200 Dust sealing with cable chain, 2000 mm length








Rail guide
positioning systems DS

Positioning system DST/DSK 120, 160, 200


Spindle drives



Function:
This unit consists of a rectangular aluminium profile with 2 integrated rail guides. The carriage is driven by means of a rotating spindle with leading nut. Where two parallel linear units are used or where two carriages are mounted on one unit, the leading-nut receiver can be used to adjust the symmetry of the carriages. The openings of the guide body are sealed with 3 stainless steel cover bands to protect the drive from splash water and dust. Another option is to cover the opening with a bellows.

Fitting position: As required. Max. length 3.000 mm without joints.
Carriage mounting: By T-slots.
Unit mounting: By T-slots and mounting sets. The linear axis can be combined with any T-slot profile.
Carriage support: In the standard version, the carriage runs on 4 runner blocks which can be serviced at a central servicing position. For longer carriages the number of runner blocks can be increased.
Repeatability: Ballscrew ± 0,025 mm, trapezoidal thread ± 0,2 mm.

Forces and torques



Size	120		160		200			
permitted dyn. Forces*	5000 km	10000 km	5000 km	10000 km	5000 km		10000 km	
F_x (N)	900	800	5000	4000	10000		8000	
F_y (N)	1776	1405	5570	3900	15600		11080	
F_z (N)	2090	1650	7050	5020	20600		14600	
M_x (Nm)	81	64	358	255	1285		915	
M_y (Nm)	97	77	369	262	1375		980	
M_z (Nm)	96	76	364	258	1345		960	
All forces and torques related to the following: existing values / table values $\frac{Fy}{Fy_{dyn}} + \frac{Fz}{Fz_{dyn}} + \frac{Mx}{Mx_{dyn}} + \frac{My}{My_{dyn}} + \frac{Mz}{Mz_{dyn}} \leq 1$								
No-load torque								
Trapezoidal thread	18 x 4	18 x 8	24 x5	24 x 10	32 x 6	32 x 12		
(Nm)	0,8	1,1	1,0	1,3	1,5	1,7		
Ballscrew	16 x 5	16 x 10	25 x 5	20 x 20	32 x 5	32 x 10	32 x 20	32 x 32
(Nm)	0,7	1,0	1,0	1,2	1,3	1,6	1,7	1,7
Geometrical moments of inertia of aluminium profile								
I_x mm⁴	5,61x10⁵		2,13x10⁶		4,81 x10⁶			
I_y mm⁴	34,19x10⁵		12,33x10⁶		26,0 x10⁶			
Elastic modulus N/mm²	70000		70000		70000			

** referred to life-time*

Driving torque:

$$M_a = \frac{F * P * S_i}{2000 * \pi * \mu} + M_n$$

$$P_a = \frac{M_a * n}{9550}$$

F = force (N)
P = thread pitch (mm)
Si = safety factor 1,2 ... 2
M_n = no-load torque (Nm)
n = rpm of screw (min^{-1})
M_a = driving torque (Nm)
μ = screw efficiency
P_a = motor power (KW)


Efficiency of lead screws:

All ballscrew 0,900

Tr 24x5 0,384
Tr 24x10 0,550
Tr 32x6 0,360
Tr 32x12 0,524

Deflection:

$$f = \frac{F * L^3}{E * I * 192}$$





f = deflection (mm)
F = load (N)
L = free length (mm)
E = elastic modulus 70000 (N/mm^2)
I = second moment of area (mm^4)


For the diagram for critical speeds of lead screws refer to chapter 4.2

Positioning system DST/DSK 120, 160, 200

Dimensions (mm)







V = Q + 100 mm
W = servicing position

*For slide nuts refer to chapter 2.2 page 2

Increasing the carriage length will increase the basic length by the same amount.


Size	Basic length L	A	B	C	D +0,1 +0,05	E	F	G	H	J	K	M for	N for	O for	P	Q	Shaft R Key	Shaft S Ø h6 x length	T	U	Basic weight	Weight per 100 mm
DS 120	200	120	96	39	47	78	42	42	10	68	79	M 5	M 6	M 6	15	156	3x3x25	10 x 27	M 6	60	3,9 kg	0,92 kg
DS 160	260	160	130	53	62	90	50	60	11	90	106	M 6	M 8	M 8	20	200	5x5x28	14 x 35	M 8	80	7,2 kg	2,1 kg
DS 200	320	200	160	66	68	140	60	60	15	110	129	M 8	M 10	M 10	20	270	6x6x40	22 x 45	M 8	100	19,4 kg	3,5 kg

T **Spindle:**
(T) Trapezoidal thread **(K)** Ballscrew

1 **Selection of screw:**
(1) right hand **(2)** left hand (Ballscrew by inquiry)

0 **Choice of guide body profile:**

(0)



internal profile
with cover bands

(3)




with bellows


Stainless versions upon request.

0 **Choice of carriages:**

(0)



(1)



Size	Version 0		Version 1	
	Q	L	Q	L
120	156	200	156	200
160	200	260	>230	>290
200	270	320	>310	>360

0 **Drive version:**
(0) one shaft (locating bearing side) **(1)** one shaft (non-locating bearing side) **(2)** shaft on both sides

0

Selection of screw:	Size	Standard	Multistart screw			
Ballscrew right hand	120	**(0)** 16x5	**(1)** 16x10	**(2)** 16x16	**(3)** 20x20	**(4)** 25x5	**(5)** 25x10
	160	**(0)** 25x5	**(1)** 20x20	**(2)** 25x10	**(3)** 25x25		
	200	**(0)** 32x5	**(1)** 32x10	**(2)** 32x20	**(3)** 32x32		
Ballscrew left hand		upon request					
Trapezoidal right hand thread	120	**(0)** 18x4	**(1)** 18x8				
	160	**(0)** 24x5	**(1)** 24x10				
	200	**(0)** 32x6	**(1)** 32x12				
Trapezoidal left hand thread	120	**(0)** 18x4	**(1)** 18x8				
	160	**(0)** 24x5	**(1)** 24x10				
	200	**(0)** 32x6	**(1)** 32x12				

0 **Ballscrew pitch accuracy:**
(0) 0,05 mm / 300 mm (Standard) **(2)** 0,025 mm / 300 mm

0 **End play of ball nut:**
(0) 0,04 mm (Standard) **(1)** < 0,02 mm **(2)** 2% apply prestress

1500 Basic length + stroke = total length

DS	T	160	1	0	0	0	0	0	0	01500
		Pos.	1	2	3	4	5	6	7	


Sample ordering code:
DST160, trapezoidal right hand thread, with internal profile and cover bands, standard carriage, one shaft (locating bearing side), spindle 24x5, 1240 mm stroke.

9.1


Positioning system DST/DSK 120, 160, 200

Dimensions (mm)

with trapezoidal thread or ballscrew, right-hand and left-hand thread or divided spindles







V = Q + 100 mm
W = servicing position
*For slide nuts refer to chapter 2.2 page 2

Increasing the carriage length will increase the basic length by the same amount.


Size	Basic length L	A	B	C	D +0,1 +0,05	E	F	G	H	J	K	M for	N for	O for	P	Q	Shaft R Key	Shaft S Ø h6 x length	T	U	Basic weight	Weight per 100 mm
DS 120	360	120	96	39	47	78	42	42	10	68	79	M 5	M 6	M 6	15	156	3x3x25	10 x 27	M 6	60	5,1 kg	0,92 kg
DS 160	470	160	130	53	62	90	50	60	11	90	106	M 6	M 8	M 8	20	200	5x5x28	14 x 35	M 8	80	10,1 kg	2,1 kg
DS 200	590	200	160	66	68	140	60	60	15	110	129	M 8	M 10	M 10	20	270	6x6x40	22 x 45	M 8	100	35,9 kg	3,5 kg

T **Spindle:**
(T) Trapezoidal thread **(K)** Ballscrew

3 **Selection of screw:**
(3) right - left hand (ballscrew by inquiry) **(4)** divided spindle

0 **Choice of guide body profile:**

(0)



internal profile
with cover bands

(3)




with bellows


Stainless versions upon request.

0 **Choice of carriages:**

(0)



(1)



Size	Version 0 Q	Version 0 L	Version 1 Q	Version 1 L
120	156	360	156	360
160	200	470	>230	>530
200	270	590	>310	>680

0 **Drive version:**
(0) shaft right hand thread **(1)** shaft left hand thread **(2)** shaft on both sides

0

Selection of screw::	Size	Standard	Multistart screw			
Ballscrew right hand	120	**(0)** 16x5	**(1)** 16x10*	**(2)** 16x16*	**(3)** 20x20*	**(4)** 25x5	**(5)** 25x10*
	160	**(0)** 25x5	**(1)** 20x20*	**(2)** 25x10*	**(3)** 25x25*		
	200	**(0)** 32x5	**(1)** 32x10*	**(2)** 32x20*	**(3)** 32x32*		
Ballscrew left hand		upon request					
Trapezoidal right hand thread	120	**(0)** 18x4	**(1)** 18x8				
	160	**(0)** 24x5	**(1)** 24x10				
	200	**(0)** 32x6	**(1)** 32x12				
Trapezoidal left hand thread	120	**(0)** 18x4	**(1)** 18x8				
	160	**(0)** 24x5	**(1)** 24x10				
	200	**(0)** 32x6	**(1)** 32x12				

** = only for selection of divided spindle*

0 **Ballscrew pitch accuracy:**
(0) 0,05 mm / 300 mm (Standard) **(2)** 0,025 mm / 300 mm

0 **End play of ball nut:**
(0) 0,04 mm (Standard) **(1)** < 0,02 mm **(2)** 2% apply prestress

1500 Basic length + stroke = total length

DS	T	160	3	0	0	0	0	0	01500
	Pos.	1	2	3	4	5	6	7	

Sample ordering code:
DST160, trapezoidal right - left hand thread, with internal profile and cover bands, standard carriage, shaft on right hand thread, spindle 24x5,1030 mm stroke.

Possible mounting styles



QSZ 80 - DSZ 160 - QSK 80




DSZPVI 120

Positioning system DST/DSK 120 P, 160 P, 200 P

Spindle drives






Function:
This unit consists of a rectangular aluminium profile with 2 integrated rail guides. The carriage is driven by means of a rotating spindle with leading nut. Where two parallel linear units are used or where two carriages are mounted on one unit, the leading-nut receiver can be used to adjust the symmetry of the carriages. A special curved aluminium sheet is covering the carriage side. There is only a small gap between carriage and aluminium sheet. The cover profile can be adjusted according to the mounting position.

Fitting position: As required, max. length DST/K 120P / 1600mm, DST/K 160P / 1800mm, DST/K 200P / 2000mm
Carriage mounting: By tapped holes.
Unit mounting: T-slots
Carriage support: In the standard version, the carriage runs on 4 runner blocks which can be serviced at a central servicing position. For longer carriages the number of runner blocks can be increased.
Repeatability: Ballscrew ± 0,025 mm, trapezoidal thread ± 0,2 mm.

9.1

Forces and torques



Size	120		160		200	
permitted dyn. Forces*	5000 km	10000 km	5000 km	10000 km	5000 km	10000 km
F_x (N)	900	800	5000	4000	10000	8000
F_y (N)	1776	1405	5570	3900	15600	11080
F_z (N)	2090	1650	7050	5020	20600	14600
M_x (Nm)	81	64	358	255	1285	915
M_y (Nm)	97	77	369	262	1375	980
M_z (Nm)	96	76	364	258	1345	960

All forces and torques related to the following:

existing values / table values

$$\frac{Fy}{Fy_{dyn}} + \frac{Fz}{Fz_{dyn}} + \frac{Mx}{Mx_{dyn}} + \frac{My}{My_{dyn}} + \frac{Mz}{Mz_{dyn}} \leq 1$$

No-load torque								
Trapezoidal thread	18 x 4	18 x 8	24 x5	24 x 10	32 x 6	32 x 12	--	--
(Nm)	0,8	1,1	1,0	1,3	1,5	1,7	--	--
Ballscrew	16 x 5	16 x 10	25 x 5	20 x 20	32 x 5	32 x 10	32 x 20	32 x 32
(Nm)	0,7	1,0	1,0	1,2	1,3	1,6	1,7	1,7
Geometrical moments of inertia of aluminium profile								
I_x mm⁴	5,61x10⁵		2,13x10⁶		4,81 x10⁶			
I_y mm⁴	34,19x10⁵		12,33x10⁶		26,0 x10⁶			
Elastic modulus N/mm²	70000		70000		70000			

** referred to life-time*

Driving torque:

$$M_a = \frac{F * P * S_i}{2000 * \pi * \mu} + M_n$$

$$P_a = \frac{M_a * n}{9550}$$

F = force (N)
P = thread pitch (mm)
Si = safety factor 1,2 ... 2
M_n = no-load torque (Nm)
n = rpm of screw (min^{-1})
M_a = driving torque (Nm)
μ = screw efficiency
P_a = motor power (KW)


Efficiency of lead screws:

All ballscrew 0,900

Tr 24x5 0,384
Tr 24x10 0,550
Tr 32x6 0,360
Tr 32x12 0,524

Deflection:

$$f = \frac{F * L^3}{E * I * 192}$$





f = deflection (mm)
F = load (N)
L = free length (mm)
E = elastic modulus 70000 (N/mm^2)
I = second moment of area (mm^4)


For the diagram for critical speeds of lead screws refer to catalog - chapter 4.2

Positioning system DST/DSK 120 P, 160 P, 200 P

Dimensions (mm)







*For slide nuts refer to chapter 2.2 page 2
Increasing the carriage length will increase the basic length by the same amount.

DS 120 M1 = M6 x 8 only 8 threaded holes in the carriage
DS 160 M1 = M8 x 12 **DS 200** M1 = M10 x 12
V = Q + 100 mm W = servicing position


Size	Basic length L	A	C	D +0,1 +0,05	E	F	G	H	I	J	K	M for	N for	P	Q	Shaft R Key	Shaft S Ø h6 x length	T	U	X	Y	Z	Basic weight	Weight per 100 mm
DS 120	225	120	39	47	78	42	42	10	67	82	79	M5	M6	12	152	3x3x25	10 x 27	M6	120	106	40	11,5	3,67 kg	1,05 kg
DS 160	285	160	53	62	90	50	60	11	89	109	106	M6	M8	20	196	5x5x28	14 x 35	M8	160	144	80	15	9,45 kg	2,71 kg
DS 200	340	200	66	68	140	60	60	15	100	133	129	M8	M10	20	256	6x6x40	22 x 45	M8	200	180	100	17	17,43 kg	3,43 kg

T **Spindle:** **(T)** Trapezoidal thread **(K)** Ballscrew

1 **Selection of screw:** **(1)** right hand *(Standard)* **(2)** left hand *(Ballscrew by inquiry)*


0 **Choice of guide body profile:**

(0)



with cover profile

(1)




without cover profile

Stainless versions upon request.


Size	Version 1 Q	Version 1 L
120	>152	>225
160	>228	>330
200	>296	>384

0 **Choice of carriages:**

(0)



(1)



0 **Drive version:**
(0) one shaft (locating bearing side) **(1)** one shaft (non-locating bearing side) **(2)** shaft on both sides

0

Selection of screw::	Size	Standard	Multistart screw			
Ballscrew right hand	120	**(0)** 16x5	**(1)** 16x10	**(2)** 16x16	**(3)** 20x20*	**(4)** 25x5* **(5)** 25x10*
	160	**(0)** 25x5	**(1)** 20x20	**(2)** 25x10	**(3)** 25x25	
	200	**(0)** 32x5	**(1)** 32x10	**(2)** 32x20	**(3)** 32x32	
Ballscrew left hand		upon request				
Trapezoidal right hand thread	120	**(0)** 18x4	**(1)** 18x8			
	160	**(0)** 24x5	**(1)** 24x10			
	200	**(0)** 32x6	**(1)** 32x12			
Trapezoidal left hand thread	120	**(0)** 18x4	**(1)** 18x8			
	160	**(0)** 24x5	**(1)** 24x10			
	200	**(0)** 32x6	**(1)** 32x12			* by inquiry

0 **Ballscrew pitch accuracy:**
(0) 0,05 mm / 300 mm *(Standard)* **(2)** 0,025 mm / 300 mm

0 **End play of ball nut:**
(0) 0,04 mm *(Standard)* **(1)** < 0,02 mm **(2)** 2% apply prestress

DS	T	160 P	1	0	0	0	0	0	0	01500	1500
		Pos.	1	2	3	4	5	6	7		

Basic length + stroke = total length

Sample ordering code:
DST 160 P, trapezoidal right hand thread, with cover profile, standard carriage, one shaft (locating bearing side), spindle 24x5, 1215 mm stroke.

Positioning system DSZ 120, 160, 200


Belt drive



Function:
This unit consists of a rectangular aluminium profile with 2 integrated rail guidess. The carriage is moved by a belt drive. Each standard pulley has got one coupling claw on one side. Belt tension can be readjusted by a simple screw adjustment device in the carriage. This device can also be used for symmetrical adjustment of two or more linear units running parallel. The openings of the guide body are sealed with 3 stainless steel cover bands to protect the guide from splash water and dust. Alternatively, the opening can also be covered with a bellow or can be delivered without cover bands.

Fitting position: As required. Max. length 6.000 mm without joints.
Carriage mounting: By T-slots.
Unit mounting: By T-slots and mounting sets. The linear axis can be combined with any T-slot profile.
Belt type: HTD with steel reinforcement, no backlash when changing direction, repeatability ± 0,1 mm.
Carriage support: In the standard version, the carriage runs on 4 runner blocks which can be serviced at a central servicing position. For longer carriages the number of runner blocks can be increased.

Forces and torques



Size	120		160		200	
permitted dyn. Forces*	5000 km	10000 km	5000 km	10000 km	5000 km	10000 km
F_x (N)	894	800	1900	1800	4000	3800
F_y (N)	1776	1405	5570	3900	15600	11080
F_z (N)	2090	1650	7050	5020	20600	14600
M_x (Nm)	81	64	358	255	1285	915
M_y (Nm)	97	77	369	262	1375	980
M_z (Nm)	96	76	364	258	1345	960
All forces and torques related to the following: existing values / table values: $\frac{Fy}{Fy_{dyn}} + \frac{Fz}{Fz_{dyn}} + \frac{Mx}{Mx_{dyn}} + \frac{My}{My_{dyn}} + \frac{Mz}{Mz_{dyn}} \leq 1$						
No-load torque						
Nm without cover bands	1,2		1,5		2,0	
Nm with cover bands	1,6		2,1		4	
Speed						
(m/s) max	5		5		5	
Tensile force						
permanent (N)	900		1900		4000	
0,2 s (N)	1000		2090		4300	
Geometrical moments of inertia of aluminium profile						
I_x mm^4	5,61x10^5		2,13x10^6		4,81 x10^6	
I_y mm^4	34,19x10^5		12,33x10^6		26,0 x10^6	
Elastic modulus N/mm^2	70000		70000		70000	

** referred to life-time*

Driving torque:


$$M_a = \frac{F * P * S_i}{2000 * \pi} + M_n$$

$$P_a = \frac{M_a * n}{9550}$$

F = force (N)
P = pulley action perimeter (mm)
Si = safety factor 1,2 ... 2
M_n = no-load torque (Nm)
n = rpm pulley (min^{-1})
M_a = driving torque (Nm)
P_a = motor power (KW)

Deflection:


$$f = \frac{F * L^3}{E * I * 192}$$





f = deflection (mm)
F = load (N)
L = free length (mm)
E = elastic modulus 70000 (N/mm^2)
I = second moment of area (mm^4)

Positioning system DSZ 120, 160, 200

Dimensions (mm)








V = Q + 100 mm
W = servicing position


*For slide nuts refer to chapter 2.2 page 2


Increasing the carriage length will increase the basic length by the same amount.


Size	Basic length L	A	B	C	D -0,05	E	F	G	H	I	J	K	M for	N for	O for	P	Q	T	U	X	Y	Basic weight	Weight per 100 mm
DSZ 120	330	120	96	80	47	78	42	58	10	10	68	79	M 5	M 6	M 6	70	156	M 6	60	28	35	5,1 Kg	0,85 Kg
DSZ 160	440	160	130	100	68	90	60	78	11	12	90	106	M 6	M 8	M 8	95	200	M 8	80	39	45	12,0 kg	1,9 kg
DSZ 200	530	200	160	130	90	140	80	97	15	15	110	129	M 8	M 10	M 10	110	270	M 10	100	49	50	21,3 kg	2,9 kg

0 **Choice of guide body profile:**

(0)

internal profile with cover bands


(1)

internal profile without cover bands


(2)

without internal profile and cover bands

(3)

with bellows

Stainless versions upon request.


0 **Choice of carriages:**

(0)


(1)


Size	Version 0		Version 1	
	Q	L	Q	L
120	156	330	156	330
160	200	440	>230	>470
200	270	530	>310	>570

0 **Drive version:**



9 is as 0, but with coupling claws on both sides.
The standard version is supplied without shaft. A shaft can be retrofitted by inserting it into the pulley bore and securing it with 2 locking rings or tension sets (size 200).

Belt table

Code No.		Size	Belt	mm/rev.	Number of teeth
0	**4**	**120**	5M25	130	26
0	**7**	**160**	8M30	176	22
0	**9**	**160**	8M50	176	22
0	**9**	**200**	8M50	224	28
1	**0**	**200**	8M70	224	28

Shaft dimensions / Coupling

Size	Shaft ø h6 x length	Key	Coupling
120 (5M25)	14 x 35	5x5x28	14
160 (8M30)	18 x 45	6x6x40	19
160 (8M50)	25 x 35	8x7x32	– *
200 (8M50)	22 x 45	6x6x40	24
200 (8M70)	30 x 55	8x7x50	– *

* Coupling claw not possible with belt widening.


DSZ	160	1	0	0	0	0	7	1	01500
	Pos.	1	2	3	4	5	6	7	

Basic length + stroke = total length

Sample ordering code:
DSZ160 with internal profile and cover bands, standard carriage, coupling claw on one side, 1060 mm stroke.

Positioning system DSZA 160, 200


Rack and pinion drive



Function:
This unit consists of a rectangular aluminium profile with 2 integrated rail guides. The carriage is driven by a pinion on a high precision rack. The rack and pinion system is suitable for highly dynamic servo operation and ideal for lifting movements. The pinion is equipped with maintenance-free ball bearings. The rack is lubricated by a toothed felt wheel.

Fitting position: As required. Max. length 6.000 mm without joints.
Carriage mounting: By T-slots.
Unit mounting: By T-slots and mounting sets. The linear axis can be combined with any T-slot profile.
Rack: 6h23 Modul 2 (hardened and ground), repeatability ± 0,1 mm.
Carriage support: In the standard version, the carriage runs on 4 runner blocks which can be serviced at a central servicing position. For longer carriages the number of runner blocks can be increased.

Forces and torques



Size	120		160		200	
permitted dyn. Forces*	5000 km	10000 km	5000 km	10000 km	5000 km	10000 km
F_x (N)	894	800	1900	1800	4000	3800
F_y (N)	1776	1405	5570	3900	15600	11080
F_z (N)	2090	1650	7050	5020	20600	14600
M_x (Nm)	81	64	358	255	1285	915
M_y (Nm)	97	77	369	262	1375	980
M_z (Nm)	96	76	364	258	1345	960
All forces and torques related to the following: existing values / table values: $\frac{Fy}{Fy_{dyn}} + \frac{Fz}{Fz_{dyn}} + \frac{Mx}{Mx_{dyn}} + \frac{My}{My_{dyn}} + \frac{Mz}{Mz_{dyn}} \leq 1$						
No-load torque						
Nm without cover bands	1,2		1,5		2,0	
Nm with cover bands	1,6		2,1		4	
Speed						
(m/s) max	5		5		5	
Tensile force						
permanent (N)	900		1900		4000	
0,2 s (N)	1000		2090		4300	
Geometrical moments of inertia of aluminium profile						
I_x mm^4	5,61x10^5		2,13x10^6		4,81 x10^6	
I_y mm^4	34,19x10^5		12,33x10^6		26,0 x10^6	
Elastic modulus N/mm^2	70000		70000		70000	

** referred to life-time*


Driving torque:

$$M_a = \frac{F * P * S_i}{2000 * \pi} + M_n$$

$$P_a = \frac{M_a * n}{9550}$$

F = force (N)
P = pulley action perimeter (mm)
Si = safety factor 1,2 ... 2
M_n = no-load torque (Nm)
n = rpm pulley (min^{-1})
M_a = driving torque (Nm)
P_a = motor power (KW)


Deflection:





$$f = \frac{F * L^3}{E * I * 192}$$

f = deflection (mm)
F = load (N)
L = free length (mm)
E = elastic modulus 70000 (N/mm^2)
I = second moment of area (mm^4)

Positioning system DSZA 160, 200







V = Q + 100 mm
W = servicing position


*For slide nuts refer to chapter 2.2 page 2


Increasing the carriage length will increase the basic length by the same amount.


Size	Basic length L	A	B	C	D ±0,05	E	F	G	H	J	K	M	N	O for	Ox for	Oy for	P	Q	T for	U	X	Basic weight	Weight per 100 mm
DSZA 160	250	160	130	100	68	90	16,5	56,5	11	90	106	60	62	M 8	M 8	M 6	12	224	M 8	80	8,5	9,4 kg	2,15 kg
DSZA 200	320	200	160	120	90	140	20	45	15	110	129	80	95	M 10	M 10	M 8	15	270	M 8	100	9	28,9 kg	7,10 kg

9.1

0 **Choice of guide body profile:**


(0)

internal profile with cover bands


(1)

internal profile without cover bands

(3)

with bellows

Stainless versions upon request.


0 **Choice of carriage:**

(0)


(1)


Size	Version 0		Version 1	
	Q	L	Q	L
160	224	250	360	390
200	270	320	320	360

1 **Drive version:**



Shaft dimensions:

Size	Shaft ø h6 x length	Key	Pinion	
	S	R	mm/U	Modul
160	20 x 40	6x6x35	100,53	2
200	18 x 26	6x6x20	94,25	2


DSZA	160	1	0	0	1	0	0	1	01500
	Pos.	1	2	3	4	5	6	7	

Basic length + stroke = total length


Sample ordering code:
DSZA 160 with internal profile and cover bands, standard carriage, 1250mm stroke.

Positioning system DSZPVI 120, 160, 200

Belt drive



Size	A1	□ B1	Ø TK	Ø C1 +0,1 +0,05	D1	E1	F1
DSZPVI 120	57	48,1	68	60	48	16	M5
DSZPVI 160	46,5	60,1	85	70	56	22	M6
DSZPVI 200	69,5	84,9	120	90	88	32	M8




Function:

This unit consists of a rectangular aluminium profile with 2 integrated rail guides. The carriage is moved by a belt drive. On the drive side the pulley is beared on the shaft of a planetary gear. Belt tension can be readjusted by a simple screw adjustment at the opposite side of the drive. A special curved aluminium sheet is covering the carriage side. There is only a small gap between carriage and aluminium sheet. Because of its special design it is possible to drive the carriage over the pulley areas. This fact is making the unit very compact.

Fitting position: As required, max. length DSZPVI 120 / 1600mm, DSZPVI 160 / 1800mm, DSZPVI 200 / 2000mm
Carriage mounting: By tapped holes.
Unit mounting: T-slots
Belt type: HTD with steel reinforcement, no backlash when changing direction, repeatability ± 0,1 mm.
Carriage support: In the standard version, the carriage runs on 4 runner blocks which can be serviced at a central servicing position. For longer carriages the number of runner blocks can be increased.

9.1

Forces and torques



Size	120		160		200	
permitted dyn. Forces*	5000 km	10000 km	5000 km	10000 km	5000 km	10000 km
F_x (N)	894	800	1900	1800	4000	3800
F_y (N)	1776	1405	5570	3900	15600	11080
F_z (N)	2090	1650	7050	5020	20600	14600
M_x (Nm)	81	64	358	255	1285	915
M_y (Nm)	97	77	369	262	1375	980
M_z (Nm)	96	76	364	258	1345	960
All forces and torques related to the following: existing values / table values $\frac{Fy}{Fy_{dyn}} + \frac{Fz}{Fz_{dyn}} + \frac{Mx}{Mx_{dyn}} + \frac{My}{My_{dyn}} + \frac{Mz}{Mz_{dyn}} \leq 1$						
No-load torque						
Nm without cover bands	1,2		1,5		2,0	
Speed						
(m/s) max	5		5		5	
Tensile force						
permanent (N)	900		1900		4000	
0,2 s (N)	1000		2090		4300	
Geometrical moments of inertia of aluminium profile						
I_x mm⁴	5,61x10⁵		2,32 x 10⁵		48,07 x 10⁵	
I_y mm⁴	34,19x10⁵		123,36 x 10⁵		259,99 x 10⁵	
Elastic modulus N/mm²	70000		70000		70000	

* referred to life-time


Driving torque:

$$M_a = \frac{F * P * S_i}{2000 * \pi} + M_n$$

$$P_a = \frac{M_a * n}{9550}$$

F = force (N)
P = pulley action perimeter (mm)
Si = safety factor 1,2 ... 2
M_n = no-load torque (Nm)
n = rpm pulley (min^{-1})
M_a = driving torque (Nm)
P_a = motor power (KW)

Deflection:




$$f = \frac{F * L^3}{E * I * 192}$$

f = deflection (mm)
F = load (N)
L = free length (mm)
E = elastic modulus 70000 (N/mm²)
I = second moment of area (mm⁴)

Positioning system DSZPVI 120, 160, 200


Dimensions (mm)




Increasing the carriage length will increase the basic length by the same amount.



Optionally available with angular planetary gearbox





*For slide nuts refer to chapter 2.2 page 2

DSZPVI 120 M1 = M6 x 8 only 8 threaded holes in the carriage
DSZPVI 160 M1 = M8 x 12 **DSZPVI 200** M1 = M10 x 12


V = Q + 100
W = servicing position

Size	Basic length L	A	C	D	G	I	K	M for	N for	O	P1	P2	Q	R	S	T	U	Basic weight *without gearbox*	Weight per 100 mm
DSZPVI 120	225	120	78	169	82,5	60	79,5	M6	M5	78	2	35	152	11,5	106	40	120	3,45 kg	0,87 kg
DSZPVI 160	285	160	90	217,5	108,5	80	106	M8	M6	104	3	52,5	196	15	144	80	160	10,27 kg	2,24 kg
DSZPVI 200	350	200	140	251	132,5	100	129	M10	M8	128	3	62,5	248	17	180	100	200	18,20 kg	3,15 kg

9.1


0 **Choice of guide body profile:**

(0)




with cover profile

(1)



without cover profile


Stainless versions upon request.




belt connection

0 **Choice of carriages:**

(0)




(1)




Size	Version 1	
	Q	L
120	>152	>225
160	>228	>330
200	>290	>430

0 **Drive version:**


(0)



(1)



(2)



(0) planetary gearbox
(1) angular planetary gearbox
(2) without gearbox

Belt table:

Code-No.		Size	Belt	mm/rev.	Number of teeth
0	**4**	**120**	5M25	130	26
0	**7**	**160**	8M30	176	22
0	**9**	**200**	8M50	224	28

Gearbox variants:

Gearbox		DSZPVI 120	DSZPVI 160	DSZPVI 200
Neugart	(0)	PLN 70	PLN 90	PLN 115
	(1)	WPLN 70	WPLN 90	WPLN 115
SEW	(0)	PSKC 221	PSKC 321	PSKC 521
Wittenstein	(0)	SP+060	SP+075	SP+100
	(1)	SK+060	SK+075	SK+100

DSZPVI	160	1	0	0	0	0	7	1	01500
	Pos.	1	2	3	4	5	6	7	


Basic length + stroke = total length

Sample ordering code:
DSZPVI 160 with cover profile, standard carriage, with planetary gearbox, 1202 mm stoke.


Positioning system DSZPVI 120, 160, 200

Dimensions (mm)


Belt drive, with two driven carriages




Increasing the carriage length will increase the basic length by the same amount.



Optionally available with angular planetary gearbox





*For slide nuts refer to chapter 2.2 page 2

DSZPVI 120 M1 = M6 x 8 only 8 threaded holes in the carriage

DSZPVI 160 M1 = M8 x 12 **DSZPVI 200** M1 = M10 x 12


V = Q + 100

W = servicing position

Size	Basic length L	A	C	D	G	I	K	M for	N for	O	P1	P2	Q	R	S	T	U	Basic weight *without gearbox*	Weight per 100 mm
DSZPVI 120	380	120	78	169	82,5	60	79	M6	M5	78	2	35	152	11,5	106	40	120	4,3 kg	0,9 kg
DSZPVI 160	485	160	90	217,5	108,5	80	106	M8	M6	104	3	52,5	196	15	144	80	160	12,1 kg	2,3 kg
DSZPVI 200	600	200	140	251	132,5	100	129	M10	M8	128	3	62,5	248	17	180	100	200	22,1 kg	3,2 kg


0 **Choice of guide body profile:** *Stainless versions upon request.*

(0)




with cover profile

(1)



without cover profile


Baugröße	Ausführung 1	
	Q	L
120	>152	>380
160	>228	>549
200	>290	>684




belt connection

0 **Choice of carriages:**

(0)




(1)




0 **Drive version:**


(0)



(1)



(2)



(0) planetary gearbox
(1) angular planetary gearbox
(2) without gearbox

Belt table:

Code-No.		Size	Belt	mm/rev.	Number of teeth
0	**4**	**120**	5M25	130	26
0	**7**	**160**	8M30	176	22
0	**9**	**200**	8M50	224	28

Gearbox variants:

Gearbox		DSZPVI 120	DSZPVI 160	DSZPVI 200
Neugart	(0)	PLN 70	PLN 90	PLN 115
	(1)	WPLN 70	WPLN 90	WPLN 115
SEW	(0)	PSKC 221	PSKC 321	PSKC 521
Wittenstein	(0)	SP+060	SP+075	SP+100
	(1)	SK+060	SK+075	SK+100

DSZPVI	160	1	0	0	0	0	7	1	01500
	Pos.	1	2	3	4	5	6	7	

Basic length + stroke = total length

Sample ordering code:
DSZPVI 160, right - left version, with cover profile, standard carriage, with planetary gearbox, 1015 mm stoke




DSZS 120 P



DSZS 120 P

Positioning system DSSZ 120, 160, 200


Belt drive



Function:
This linear unit consists of a rectangular aluminium profile with integrated rail guides . The carriage, which has runner blocks, is driven by a timing belt. Each standard pulley includes a coupling claw on one side and is equipped with maintenance-free ball bearings. Belt tension can be readjusted by a simple screw adjustment device in the carriage. This device can also be used for symmetrical adjustment of two or more linear units running parallel.

Fitting position: As required. Max. length 6.000 mm without joints.
Carriage mounting: By T-slots.
Unit mounting: By T-slots and mounting sets. The linear axis can be combined with any T-slot profile.
Belt performance: HTD with steel reinforcement, no backlash when changing direction, repeatability ± 0,1 mm.
Carriage support: In the standard version, the carriage runs on 4 runner blocks which can be serviced at a central servicing position. For longer carriages the number of runner blocks can be increased.

Forces and torques



Size	120		160		200	
permitted dyn. Forces*	5000 km	10000 km	5000 km	10000 km	5000 km	10000 km
F_x (N)	1900	1800	4000	3800	5900	5750
F_y (N)	1776	1405	5570	3900	15600	11080
F_z (N)	2090	1650	7050	5020	20600	14600
M_x (Nm)	81	64	358	255	1285	915
M_y (Nm)	97	77	369	262	1375	980
M_z (Nm)	96	76	364	258	1345	960
All forces and torques related to the following: existing values / table values $\frac{Fy}{Fy_{dyn}} + \frac{Fz}{Fz_{dyn}} + \frac{Mx}{Mx_{dyn}} + \frac{My}{My_{dyn}} + \frac{Mz}{Mz_{dyn}} \leq 1$						
No-load torque						
(Nm)	1,4		1,8		2,2	
Speed						
(m/s) max	5		5		5	
Tensile force						
permanent (N)	1900		4000		5900	
0,2 s (N)	2090		4300		6350	
Geometrical moments of inertia of aluminium profile						
I_x mm^4	5,61x10^5		2,13x10^6		48,07 x10^5	
I_y mm^4	34,19x10^5		12,33x10^6		259,99 x10^5	
Elastic modulus N/mm^2	70000		70000		70000	

** referred to life-time*


Driving torque:

$$M_a = \frac{F * P * S_i}{2000 * \pi} + M_n$$

$$P_a = \frac{M_a * n}{9550}$$

F = force (N)
P = pulley action perimeter (mm)
Si = safety factor 1,2 ... 2
M_n = no-load torque (Nm)
n = rpm pulley (min^{-1})
M_a = driving torque (Nm)
P_a = motor power (KW)


Deflection:



$$f = \frac{F * L^3}{E * I * 192}$$

f = deflection (mm)
F = load (N)
L = free length (mm)
E = elastic modulus 70000 (N/mm^2)
I = second moment of area (mm^4)

Positioning system DSSZ 120, 160, 200




V = Q + 100 mm
W = servicing position

*For slide nuts refer to chapter 2.2 page 2

Increasing the carriage length will increase the basic length by the same amount.

Size	Basic length L	A	B	C	D -0,05	E	F	G	H	J	K	I for	M for	N for	O for	P	Q	R	S □	T	U	X	Y	Basic weight	Weight per 100 mm
DSSZ 120	230	120	96	100	68	78	60	100	10	68	79	M 6	M 5	M 6	M 6	10	200	39	42	M 8	60	180	39	12,0 kg	1,2 kg
DSSZ 160	330	160	130	130	90	90	80	130	11	105	106	M 8	M 6	M 8	M 8	12	290	53	60	M 10	80	270	60	27,8 kg	1,8 kg
DSSZ 200	380	200	160	160	110	140	100	145	15	128	129	M 10	M 8	M 10	M 10	15	340	62,5	95	M 10	100	310	62	53,0 kg	2,6 kg

1 **Choice of guide body profile:**




(1) internal profile without cover bands

(2) without internal profile and cover bands

(3) with bellows


Stainless versions upon request.

0 **Choice of carriages:**



Size	Version 0		Version 1	
	Q	L	Q	L
120	200	230	200	230
160	290	330	290	330
200	340	380	340	380

0 **Drive version:**



8 is as 0, but with coupling claws on both sides.The standard version is supplied without shaft. A shaft can be retrofitted by inserting it into the pulley bore and securing it with 2 locking rings or tension sets (size 200).

Belt table

Code No.		Size	Belt	mm/rev.	Number of teeth
0	**7**	**120**	8M30	192	24
0	**9**	**160**	8M50	256	32
1	**0**	**200**	8M70	304	38

Shaft dimensions

Size	Shaft ø h6 x length	Key
120	18 x 45	6x6x40
160	22 x 45	6x6x40
200	30 x 55	8x7x50

DSSZ	160	1	1	0	0	0	9	1	01500
Pos.		1	2	3	4	5	6	7	

Basic length + stroke = total length

Sample ordering code:
DSSZ160, body profile with internal profile without cover bands, standard carriage, coupling claws on one side, 1170 mm stroke

Positioning system DSR 120, 160, 200


Roller unit without drive



Function:
This unit consists of a rectangular aluminium profile with 2 integrated rail guidess. The openings of the guide body are sealed with 3 stainless steel cover bands to protect the guide from splash water and dust. Alternatively, the opening can also be covered with a bellow or can be delivered without cover bands. The positioning system can be either driven by an internal pneumatic cylinder or other additional drives or it serves as load carrying linear slide.

Fitting position: As required. Max. length 6.000 mm without joints.
Carriage mounting: By T-slots.
Unit mounting: By T-slots and mounting sets. The linear axis can be combined with any T-slot profile.
Carriage support: In the standard version, the carriage runs on 4 runner blocks which can be adjusted and serviced at a central servicing position. For longer carriages the number of runner blocks can be increased.

Forces and torques




Size	120		160		200	
permitted dyn. Forces*	5000 km	10000 km	5000 km	10000 km	5000 km	10000 km
F_y (N)	1776	1405	5570	3900	15600	11080
F_z (N)	2090	1650	7050	5020	20600	14600
M_x (Nm)	81	64	358	255	1285	915
M_y (Nm)	97	77	369	262	1375	980
M_z (Nm)	96	76	364	258	1345	960
All forces and torques related to the following: existing values / table values $\frac{Fy}{Fy_{dyn}} + \frac{Fz}{Fz_{dyn}} + \frac{Mx}{Mx_{dyn}} + \frac{My}{My_{dyn}} + \frac{Mz}{Mz_{dyn}} \leq 1$						
Speed						
(m/s) max	5		5		5	
Geometrical moments of inertia of aluminium profile						
I_x mm^4	5,61x10^5		2,13x10^6		4,81 x10^6	
I_y mm^4	34,19x10^5		12,33x10^6		26,0 x10^6	
Elastic modulus N/mm^2	70000		70000		70000	

** referred to life-time*

Deflection:


$$f = \frac{F * L^3}{E * I * 192}$$




f = deflection (mm)
F = load (N)
L = free length (mm)
E = elastic modulus 70000 (N/mm^2)
I = second moment of area (mm^4)

Positioning system DSR 120, 160, 200

Dimensions (mm)





V = Q + 100 mm
W = servicing position


*For slide nuts refer to chapter 2.2 page 2

Increasing the carriage length will increase the basic length by the same amount.

Size	Basic length L	A	B	E	H	J	K	M for	N for	O for	P	Q	U	Basic weight	Weight per 100 mm
DSR 120	200	120	96	78	10	68	79	M 5	M 6	M 6	10	156	60	3,2 kg	0,71 kg
DSR 160	240	160	130	90	11	90	106	M 6	M 8	M 8	12	200	80	7,0 kg	1,5 kg
DSR 200	320	200	160	140	15	110	129	M 8	M 10	M 10	15	270	100	15,0 kg	2,9 kg


0 **Choice of guide body profile:**

(0)




internal profile
with cover bands

(1)



internal profile
without cover bands

(2)



without internal profile
and cover bands

(3)




with bellows


Stainless versions upon request.

0 **Choice of carriages:**

(0)



(1)



Size	Version 0		Version 1	
	Q	L	Q	L
120	156	200	156	200
160	200	240	>230	>270
200	270	320	>310	>360


1500 Basic length + stroke = total length

DSR	160	0	0	0	0	0	0	0	01500
	Pos.	1	2	3	4	5	6	7	

Sample ordering code:
DSR160, with internal profile and cover bands, standard runner blocks, 1260 mm stroke.

Positioning system DSZS 160, 200


Belt drive



Function:
This unit consists of a rectangular aluminium profile with 2 integrated rail guidess. The carriage is moved by a belt drive. An innovation is that the toothed belt is diverted within a drive block positioned centrically. The result is an enormous compactness with regard to the overall system length. The toothed drive pulley has a coupling claw in the standard version. Belt tension can be readjusted by a simple screw adjustment device in the carriage. This device can also be used for symmetrical adjustment of two or more linear units running parallel. The openings of the guide body are sealed with 3 stainless steel cover bands to protect the guide from splash water and dust. Alternatively, the opening can also delivered without cover bands.

Fitting position: As required. Max. length 6.000 mm without joints.
Carriage mounting: By T-slots.
Unit mounting: By T-slots and mounting sets. The linear axis can be combined with any T-slot profile.
Belt type: HTD with steel reinforcement, no backlash when changing direction, repeatability ± 0,1 mm.
Carriage support: In the standard version, the carriage runs on 4 runner blocks which can be serviced at a central servicing position. For longer carriages the number of runner blocks can be increased.

Forces and torques



Size	160		200	
permitted dyn. Forces*	5000 km	10000 km	5000 km	10000 km
F_x (N)	1900	1800	4000	3800
F_y (N)	5570	3900	15600	11080
F_z (N)	7050	5020	20600	14600
M_x (Nm)	358	255	1285	915
M_y (Nm)	369	262	1375	980
M_z (Nm)	364	258	1345	960
All forces and torques related to the following: existing values / table values $\frac{Fy}{Fy_{dyn}} + \frac{Fz}{Fz_{dyn}} + \frac{Mx}{Mx_{dyn}} + \frac{My}{My_{dyn}} + \frac{Mz}{Mz_{dyn}} \leq 1$				
No-load torque				
Nm without cover bands	1,5		2,0	
Nm with cover bands	2,1		4	
Speed				
(m/s) max	5		5	
Tensile force				
permanent (N)	1900		4000	
0,2 s (N)	2090		4300	
Geometrical moments of inertia of aluminium profile				
I_x mm⁴	$21,32 \times 10^5$		$4,81 \times 10^6$	
I_y mm⁴	$123,36 \times 10^5$		$26,0 \times 10^6$	
Elastic modulus N/mm²	70000		70000	

** referred to life-time*

Driving torque:


$$M_a = \frac{F * P * S_i}{2000 * \pi} + M_n$$

$$P_a = \frac{M_a * n}{9550}$$

F = force (N)
P = pulley action perimeter (mm)
Si = safety factor 1,2 ... 2
M_n = no-load torque (Nm)
n = rpm pulley (min^{-1})
M_a = driving torque (Nm)
P_a = motor power (KW)

Deflection:


$$f = \frac{F * L^3}{E * I * 192}$$



f = deflection (mm)
F = load (N)
L = free length (mm)
E = elastic modulus 70000 (N/mm^2)
I = second moment of area (mm^4)

Positioning system DSZS 160, 200

Dimensions (mm)



V = Q + 100 mm
W = servicing position


*For slide nuts refer to chapter 2.2 page 2

Increasing the carriage length will increase the basic length by the same amount.

Size	Basic length L	A	B	C	D -0,05	E	F	G	H	I	J	K	M for	N for	O for	P	Q	T	U	X	Y	Basic weight	Weight per 100 mm
DSZS 160	310	160	130	100	68	90	60	107	11	39	90	213	M 6	M 8	M 8	12	280	M 8	80	180	39	23,0 kg	1,9 kg
DSZS 200	380	200	160	130	90	140	80	146	15	48,5	110	275	M8	M10	M10	15	340	M10	100	270	60	33,0 kg	2,4 kg


0 **Choice of guide body profile:**

(0)



internal profile
with cover bands

(1)




internal profile
without cover bands


Stainless versions upon request.

0 **Choice of carriages:**

(0)



(1)




Size	Version 0		Version 1	
	Q	L	Q	L
160	280	310	280	310
200	340	380	380	420

0 **Drive version:**

0



0 1 3 4 5



5 is as 0, but with coupling claws on both sides.
The standard version is supplied without shaft. A shaft can be retrofitted by inserting it into the pulley bore and securing it with 2 locking rings or tension sets (size 200).

Belt table

Code No.		Size	Belt	mm/rev.	Number of teeth
0	**7**	**160**	8M30	192	24
0	**9**	**200**	8M50	256	32

Shaft dimensions / Coupling claw

Size	Shaft ø h6 x length	Key	Coupling
160	18 x 45	6x6x40	19
200	22 x 45	6x6x40	24


DSZS	**160**	**1**	**0**	**0**	**0**	**0**	**7**	**1**	**01500**
	Pos.	1	2	3	4	5	6	7	


Basic length + stroke = total length


Sample ordering code:
DSZS160 with internal profile and cover bands, standard carriage, coupling claw on one side, 1190 mm stroke.

Positioning system DSZS 120 P

Belt drive








Function:
The guide body consists of a rectangular aluminium profile with two integrated rail guides. The carriage, which is running on four runner blocks, is driven by a revolving timing belt. The novelty is that the timing belt is diverted into a drive block positioned centrically. This results in an extraordinary compactness with regard to the overall length of the system. The driving toothed pulley is provided with a coupling claw as a standard. The belt tension can be easily readjusted via a tensioning device within the bearing block. The openings in the guide body are closed by an aluminium profile, leaving only small slits open on the sides. The cover profile can be adjusted according to the mounting position.

The advantages compared to the DSZS positioning system are: The number of components prone to wear such as cover bands and sliding blocks is reduced and the fact that there is no friction makes it possible to use smaller motors. In addition, the cover profile, which is fixed with only a few screws, improves the serviceability and maintainability.

Einbaulage: As required. Max. length DSZS 120P / 1600mm, DSZS 160P / 1800mm, DSZS 200P / 2000mm
Führungsschlittenanschluss: By tapped holes.
Befestigung: By T-slots and mounting sets. The linear axis can be combined with any T-slot profile.
Zahnriemenausführung: HTD with steel reinforcement, no backlash when changing direction, repeatability ± 0,1 mm.
Schlittenlagerung: In the standard version, the carriage runs on 4 runner blocks which can be serviced at a central servicing position. For longer carriages the number of runner blocks can be increased.

Forces and torques



Size	120	
permitted dyn. Forces*	5000 km	10000 km
F_x (N)	894	800
F_y (N)	1776	1405
F_z (N)	2090	1650
M_x (Nm)	81	64
M_y (Nm)	97	77
M_z (Nm)	96	76
All forces and torques related to the following: existing values / table values	$\frac{Fy}{Fy_{dyn}} + \frac{Fz}{Fz_{dyn}} + \frac{Mx}{Mx_{dyn}} + \frac{My}{My_{dyn}} + \frac{Mz}{Mz_{dyn}} \leq 1$	
No-load torque		
Nm without cover bands	1,2	
Nm with cover bands	1,6	
Speed		
(m/s) max	5	
Tensile force		
permanent (N)	900	
0,2 s (N)	1000	
Geometrical moments of inertia of aluminium profile		
I_x mm⁴	5,61 x 10⁵	
I_y mm⁴	34,19 x 10⁵	
Elastic modulus N/mm²	70.000	

** referred to life-time*

Driving torque:


$$M_a = \frac{F * P * S_i}{2000 * \pi} + M_n$$

$$P_a = \frac{M_a * n}{9550}$$

F	= force	(N)
P	= pulley action perimeter	(mm)
Si	= safety factor 1,2 ... 2	
M_n	= no-load torque	(Nm)
n	= rpm pulley	(min^{-1})
M_a	= driving torque	(Nm)
P_a	= motor power	(KW)

Deflection:


$$f = \frac{F * L^3}{E * I * 192}$$



f = deflection	(mm)
F = load	(N)
L = free length	(mm)
E = elastic modulus 70000	(N/mm²)
I = second moment of area	(mm⁴)

Positioning system DSZS 120 P

Dimensions (mm)





V = Q + 100 mm
W = servicing position

*For slide nuts refer to chapter 2.2 page 2


Increasing the carriage length will increase the basic length by the same amount.

Size	A	B	C	D	E ∅	F □	G	H	I	K	M	N	O	P1	R	S	T	U	X	Y	Z	Basic weight	Weight per 100 mm
DSZS 120 **P**	120	78	80	169	47	42	82,5	10	60	79	M5	85,5	M6	6	11,5	106	40	120	130	30	116	5,4 kg	0,87 kg

0 **Choice of guide body profile:** *Stainless versions upon request.*


DS 120 M1 = M6 x 8
only 8 threaded holes in the carriage
DS 160 M1 = M8 x 12 **DS 200** M1 = M10 x 12

(0)



with cover profile


(1)




without cover profile

0 **Choice of carriages:**

(0)



(1)




Size	Version 0		Version 1	
	Q	L	Q	L
120	152	192	>152	>192

0 **Drive version:**

0



0 1 3 4 5



5 is as 0, but with coupling claws on both sides.
The standard version is supplied without shaft. A shaft can be retrofitted by inserting it into the pulley bore and securing it with 2 locking rings or tension sets (size 200).

Belt table

Code No.		Size	Belt	mm/rev.	Number of teeth
0	**4**	**120**	5M 25	130	26

Shaft dimensions / Coupling claw


Size	Shaft ø h6 x length	Key	Coupling
120	14 x 35	5 x 5 x 28	14

DSZS	**120 P**	**1**	**0**	**0**	**0**	**0**	**4**	**1**	**1500**
	Pos.	1	2	3	4	5	6	7	


Basic length + stroke = total length

Sample ordering code:
DSZS120 P with cover profile, standard carriage, coupling claw on one side, 1308 mm stroke.

Possible mounting styles








Roller guide positioning systems DLM, DLVM

Rail guide positioning system DSM, DSB, DSM P

Positioning system DLM 120, 160, 200


Linear motor drive



Function:
This unit consists of a rectangular aluminium profile with 2 integrated roller guides. The linear motor DLM unit is based on the principle of a linear, synchronous AC motor.
The guiding profile is fitted with permanent magnets as stator (secondary part). The carriage is fitted with the actuator (primary part). The magnetic attraction causes a force between carriage and guiding profile also in the absence of current. This force can be used for the initial tension of the bearings. Several carriages (primary parts) can be driven independently on one guiding profile.

Fitting position: As required. Max. length 6.000 mm without joints.
Carriage mounting: By T-slots.
Unit mounting: By T-slots and mounting sets. The linear axis can be combined with any T-slot profile.
Carriage support: In the standard version, the carriage runs on 10 or 12 rollers which can be adjusted and serviced at a central servicing position. For longer carriages the number of rollers can be increased.
Repeatability ± 0,05 mm. Repeated accuracy max. ± 0,05 bis 4.000 mm, ± 0,1 >4.000 mm.

Forces and torques




F_z = external force by load
F_a = magnetic attraction force
F_{zm} = maximum force in consideration of motor power
$F_{zm} = F_z + F_a$

Size	120			160			200		
Motor size	1	2	3	1	2	3	1	2	3
Forces/Torques $_{dyn}$									
F_a (N)	600	1200	1800	1200	1800	5500	3600	5500	11000
F_{zm} (N)	820	1640	2460	1590	8800	7030	5000	7500	13800
F_y (N)	700	700	470	1500	1000	450	3300	2200	1200
M_x (Nm)	180	90	60	280	190	130	600	400	220
M_y (Nm)	50	100	70	320	210	140	640	420	230
M_z (Nm)	22	33	50	90	100	120	200	170	210
Number of rollers	10	12	12	12	12	12	12	12	12
All forces and torques related to the following: existing values / table values $\frac{Fy}{Fy_{dyn}} + \frac{Fzm}{Fzm_{dyn}} + \frac{Mx}{Mx_{dyn}} + \frac{My}{My_{dyn}} + \frac{Mz}{Mz_{dyn}} \leq 1{,}5$									
Motor specifications Fx									
Motor size	1	2	3	1	2	3	1	2	3
Carriage weight (kg)	1,7	2,5	3,1	5,1	4,7	5,4	9,4	10,5	12,7
Weight primary part (kg)	0,7	1,4	2,0	1,4	3,7	5,2	4,5	6,4	8,4
permanent (N)	61	115	173	115	271	406	383	574	766
Max. (N) (1s)	162	323	485	323	607	911	868	1301	1735
Moving force without current									
N	3	5	6	5	8	9	7	11	12
Speed									
(m/s) max	4			6			6		
Geometrical moments of inertia of aluminium profile									
I_x mm^4	$6{,}6 \times 10^5$			$22{,}2 \times 10^5$			$63{,}8 \times 10^5$		
I_y mm^4	$38{,}6 \times 10^5$			$122{,}0 \times 10^5$			$335{,}0 \times 10^5$		
Elastic modulus N/mm²	70000			70000			70000		

Deflection:


$$f = \frac{F * L^3}{E * I * 192}$$



f = deflection (mm)
F = load (N)
L = free length (mm)
E = elastic modulus 70000 (N/mm²)
I = second moment of area (mm⁴)

Positioning system DLM 120, 160, 200

Dimensions (mm)





V = Q + 100 mm
W = servicing position


*For slide nuts refer to chapter 2.2 page 2

Increasing the carriage length will increase the basic length by the same amount.

Size ❒	Basic length L	A	B	E	H	J	K	M for	N for	O for	P	U	Basic weight Motor size 1/2/3	Weight per 100 mm Motor size 1/2/3
DLM 120	Q + 30	120	96	78	10	68	79	M 5	M 6	M 6	10	60	5,2/7,2/9,2 Kg	1,0/1,0/1,0 Kg
DLM 160	Q + 30	160	130	90	11	90	106	M 6	M 8	M 8	12	80	12,6/15,6/20,7 Kg	1,6/2,0/2,0 Kg
DLM 200	Q + 35	200	160	140	15	110	129	M 8	M 10	M 10	15	100	26,9/30,5/37,9 Kg	2,6/2,6/2,6 Kg


0 **Choice of guide body profile:**

(0)



without internal profile and cover bands

(3)



with bellows

Stainless version upon request.

1 **Measurement system:**

(1) Measurement system LE100 5V Resolution 0.05 **(2)** Measurement system LE100 10,5-30V Resolution 0.05 **(3)** Hall sensor **(4)** Measurement system provided by customer

1 **Plug:**

(1) Plug Pos. 1 **(2)** Plug Pos. 2 **(3)** open unconnected cable end







1 **Motor size:**

(1) Motor size 1 with Q_1 **(2)** Motor size 2 with Q_2 **(3)** Motor size 3 with Q_3
(4) Supply with Q_1* **(5)** Supply with Q_2* **(6)** Supply with Q_3*
* = provided by customer

Dimensioning criteria for motor output						
	l_p ❒	b_p ❒	h_{ps} ❒	Q_1	Q_2	Q_3
120	**Q - 70**	**55**	**38**	**196**	**276**	**372**
160	**Q - 70**	**71**	**50**	**316**	**360**	**461**
200	**Q - 70**	**85**	**62**	**410**	**444**	**610**

l_p = length primary part; b_p = width primary part;
h_{ps} = height primary part + height secondary part + interspaces primary-/secondary part

For standard carriage length see 'Q' in table.
For linear encoder refer to chapter 9.1.

1500 Basic length + stroke = total length

DLM	**160**	**0**	**0**	**1**	**1**	**0**	**0**	**1**	**01500**
Pos.		1	2	3	4	5	6	7	

Sample ordering code:
DLM160, Bahr Modultechnik Linearmotor, standard body profile, Measurement system LE100 5V, Plug Pos. 1, motor size 1, 1154 mm stroke.

10.1

Positioning system DLVM 200


Linear motor drive



Function:
This unit consists of a rectangular aluminium profile with 2 integrated roller guides. The linear motor DLVM unit is based on the principle of a linear, synchronous AC motor.
The guiding profile is fitted with permanent magnets as stator (secondary part). The carriage is fitted with the actuator (primary part). The magnetic attraction causes a force between carriage and guiding profile also in the absence of current. This force can be used for the initial tension of the bearings. Several carriages (primary parts) can be driven independently on one guiding profile.

Fitting position: As required. Max. length 6.000 mm without joints.
Carriage mounting: By T-slots.
Unit mounting: By T-slots and mounting sets. The linear axis can be combined with any T-slot profile.
Carriage support: In the standard version, the carriage runs on 8 rollers which can be adjusted and serviced at a central servicing position. For longer carriages the number of rollers can be increased.
Repeatability ± 0,05 mm. Repeated accuracy max. ± 0,05 bis 4.000 mm, ± 0,1 >4.000 mm.

Forces and torques




F_z = external force by load
F_a = magnetic attraction force
F_{zm} = maximum force in consideration of motor power
$F_{zm} = F_z + F_a$

Size	200
Motor size	3
Forces/Torques $_{dyn}$	
F_a (N)	11000
F_{zm} (N)	13800
F_y (N)	1200
M_x (Nm)	220
M_y (Nm)	230
M_z (Nm)	210
Number of rollers	12
All forces and torques related to the following:	
existing values / table values	$\frac{Fy}{Fy_{dyn}} + \frac{Fzm}{Fzm_{dyn}} + \frac{Mx}{Mx_{dyn}} + \frac{My}{My_{dyn}} + \frac{Mz}{Mz_{dyn}} \leq 1{,}5$
Motor specifications Fx	
Motor size	3
Carriage weight (kg)	12,7
Weight primary part (kg)	8,4
permanent (N)	766
Max. (N) (1s)	1735
Moving force without current	
N	12
Speed	
(m/s) max	6
Geometrical moments of inertia of aluminium profile	
I_x mm^4	6,38x10^6
I_y mm^4	33,5x10^6
Elastic modulus N/mm^2	70000

For life-time calculation of rollers use our homepage.

Deflection:


$$f = \frac{F * L^3}{E * I * 192}$$





f = deflection (mm)
F = load (N)
L = free length (mm)
E = elastic modulus 70000 (N/mm^2)
I = second moment of area (mm^4)

Positioning system DLVM 200

Dimensions (mm)







*For slide nuts refer to chapter 2.2 page 2

Increasing the carriage length will increase the basic length by the same amount.

Size ❒	Basic length L	A	B	C	D	E	F	G	H	J	K	M for	N for	P	Q	R	S	T for	U	Basic weight	Weight per 100 mm
DLVM 200	602	197	205	140	15	224,5	50,5	42,5	15	15,5	54,5	M 8	M10	15	260	240	25	M8	198,5	39,4 kg	2,8 kg

10.1

1500	Basic length + stroke = total length

DLVM	**200**	**0**	**0**	**0**	**0**	**0**	**0**	**1**	**01500**
	Pos.	1	2	3	4	5	6	7	

Sample ordering code:
DLVM200, 898 mm stroke.

Positioning system DSM 120, 160, 200

Linear motor drive




Function:

This unit consists of a rectangular aluminium profile with 2 integrated rail guidance. The linear motor DSM unit is based on the principle of a linear, synchronous AC motor.

The guiding profile is fitted with permanent magnets as stator (secondary part). The carriage is fitted with the actuator (primary part). The magnetic attraction causes a force between carriage and guiding profile also in the absence of current. This force can be used for the initial tension of the bearings. Several carriages (primary parts) can be driven independently on one guiding profile.

Fitting position: As required. Max. length 6.000 mm without joints.
Carriage mounting: By T-slots.
Unit mounting: By T-slots and mounting sets. The linear axis can be combined with any T-slot profile.
Carriage support: In the standard version, the carriage runs on 4 runner blocks which can be serviced at a central servicing position. For longer carriages the number of runner blocks can be increased.
Repeatability ± 0,05mm mm. Repeated accuracy max. ± 0,05mm bis 4.000 mm, ± 0,1 >4.000 mm.

Forces and torques




F_z = external force by load
F_a = magnetic attraction force
F_{zm} = maximum force in consideration of motor power
$F_{zm} = F_z + F_a$

Size	120		160			200		
Motor size	1	2	1	2	3	1	2	3
permitted dyn.Forces*	10000 km		10000 km			10000 km		
F_a (N)	600	1200	1200	1800	5500	3600	5500	11000
F_{zm} (N)	820	1640	1590	2800	7030	4990	7640	13860
F_z (N)	650	500	1775	1775	3550	4092	4092	8184
M_x (Nm)	35	32	160	128	153	357	231	462
M_y (Nm)	40	58	373	351	532	769	556	1540
M_z (Nm)	40	57	222	261	328	585	654	906
Number of runner blocks	6	8	4	4	8	4	4	8
All forces and torques related to the following: existing values / table values $\frac{Fy}{Fy_{dyn}} + \frac{Fzm}{Fzm_{dyn}} + \frac{Mx}{Mx_{dyn}} + \frac{My}{My_{dyn}} + \frac{Mz}{Mz_{dyn}} \leq 1,5$								
Motor specifications Fx								
Motor size	1	2	1	2	3	1	2	3
Carriage weight (kg)	1,4	2,7	4,8	5,3	7,1	10,9	11,4	16,9
Weight primary part (kg)	0,7	1,4	1,4	3,7	5,2	4,5	6,4	8,4
permanent (N)	61	115	115	271	406	383	574	766
Max. (N) 1s	162	323	323	607	911	868	1301	1735
Moving force without current								
N	15	15	30	30	60	40	40	80
Geometrical moments of inertia of aluminium profile								
I_x mm⁴	5,60 x10⁵		2,13 x10⁶			4,81 x10⁶		
I_y mm⁴	34,19 x10⁵		12,3 x10⁶			26,0 x10⁶		
Elastic modulus N/mm²	70000		70000			70000		

* referred to life-time

Deflection:


$$f = \frac{F * L^3}{E * I * 192}$$




f = deflection (mm)
F = load (N)
L = free length (mm)
E = elastic modulus 70000 (N/mm²)
I = second moment of area (mm⁴)

Positioning system DSM 120, 160, 200

Dimensions (mm)





V = Q + 100 mm
W = servicing position


*For slide nuts refer to chapter 2.2 page 2

Increasing the carriage length will increase the basic length by the same amount.

Size ❒	Basic length L	A	B	E	H	J	K	M for	N for	O for	P	U	Basic weight Motor size 1/2/3	Weight per 100 mm Motor size 1/2/3
DSM 120	Q + 30	120	96	78	10	68	79	M 5	M 6	M 6	10	60	4,8/6,9 kg	1,0/1,0
DSM 160	Q + 30	160	130	90	11	90	106	M 6	M 8	M 8	12	80	12,4/16,7/22,6 kg	1,7/2,0/2,0 kg
DSM 200	Q + 35	200	160	140	15	110	129	M 8	M 10	M 10	15	100	30,0 /33,0 /44,2kg	3,1/3,1/3,1 kg


0 **Choice of guide body profile:**

(0)



without internal profile and cover bands

(3)



with bellows

Stainless version upon request.

1 **Measurement system:**

(1) Measurement system LE100 5V Resolution 0.05 **(2)** Measurement system LE100 10,5-30V Resolution 0.05 **(3)** Hall sensor **(4)** Measurement system provided by customer

1 **Plug:**

(1) Plug Pos. 1



(2) Plug Pos. 2



(3) open unconnected cable end



1 **Motor size:**

(1) Motor size 1 with Q_1 **(2)** Motor size 2 with Q_2 **(3)** Motor size 3 with Q_3
(4) Supply with Q_1* **(5)** Supply with Q_2* **(6)** Supply with Q_3*
* = provided by customer

Dimensioning criteria for motor output						
	l_p ❒	b_p ❒	h_{ps} ❒	Q_1	Q_2	Q_3
120	Q - 70	55	38	196	276	-
160	Q - 70	71	50	316	360	461
200	Q - 70	85	62	410	444	610

l_p = length primary part; b_p = width primary part;
h_{ps} = height primary part + height secondary part + interspaces primary-/secondary part

For standard carriage length see 'Q' in table.
The carriages can be delivered in any non-standard length upon request; the longer the carriage, the greater the load capacity. For linear encoder refer to chapter 9.1.

1500 Basic length + stroke = total length

DSM	160	0	0	1	1	0	0	1	01500
Pos.		1	2	3	4	5	6	7	

Sample ordering code:
DSM160, Bahr Modultechnik Linear motor, standard body profile, Measurement system LE100 5V, Plug Pos. 1, motor size 1, 1154 mm stroke

Positioning system DSM 160P, 200P


Linear motor drive



Function:
This unit consists of a rectangular aluminium profile with 2 integrated rail guidance. The linear motor DSM unit is based on the principle of a linear, synchronous AC motor.
The guiding profile is fitted with permanent magnets as stator (secondary part). The carriage is fitted with the actuator (primary part). The magnetic attraction causes a force between carriage and guiding profile also in the absence of current. This force can be used for the initial tension of the bearings. Several carriages (primary parts) can be driven independently on one guiding profile. A special design of the carriage geometry results in the guiding profile being covered. This prevents small parts from falling into the system, so that clean-room applications are possible.

Fitting position: As required. Max. length 3.000 mm without joints.
Carriage mounting: By threaded holes.
Unit mounting: By T-slots and mounting sets. The linear axis can be combined with any T-slot profile.
Carriage support: In the standard version, the carriage runs on 4 runner blocks which can be serviced at a central servicing position. For longer carriages the number of runner blocks can be increased.
Repeatability ± 0,05mm mm. Repeated accuracy max. ± 0,05mm up to 3.000 mm

Forces and torques




F_z = external force by load
F_a = magnetic attraction force
F_{zm} = maximum force in consideration of motor power
$F_{zm} = F_z + F_a$

Size	160			200		
Motor size	1	2	3	1	2	3
permitted dyn.Forces*	10000 km			10000 km		
F_a (N)	1200	1800	5500	3600	5500	11000
F_{zm} (N)	1590	2800	7030	4990	7640	13860
F_z (N)	1775	1775	3550	4092	4092	8184
M_x (Nm)	160	128	153	357	231	462
M_y (Nm)	373	351	532	769	556	1540
M_z (Nm)	222	261	328	585	654	906
Number of runner blocks	4	4	8	4	4	8
All forces and torques related to the following: existing values / table values $\frac{Fy}{Fy_{dyn}} + \frac{Fzm}{Fzm_{dyn}} + \frac{Mx}{Mx_{dyn}} + \frac{My}{My_{dyn}} + \frac{Mz}{Mz_{dyn}} \leq 1{,}5$						
Motor specifications Fx						
Motor size	1	2	3	1	2	3
Carriage weight (kg)	4,8	5,3	7,1	10,9	11,4	16,9
Weight primary part (kg)	1,4	3,7	5,2	4,5	6,4	8,4
permanent (N)	115	271	406	383	574	766
Max. (N) 1s	323	607	911	868	1301	1735
Moving force without current						
N	30	30	60	40	40	80
Geometrical moments of inertia of aluminium profile						
I_x mm⁴	2,13 x10⁶			4,81 x10⁶		
I_y mm⁴	12,3 x10⁶			26,0 x10⁶		
Elastic modulus N/mm²	70000			70000		

* referred to life-time

Deflection:




$f = \frac{F * L^3}{E * I * 192}$

f = deflection (mm)
F = load (N)
L = free length (mm)
E = elastic modulus 70000 (N/mm²)
I = second moment of area (mm⁴)

Positioning system DSM 160P, 200P

Dimensions (mm)



V = Q + 100 mm
W = servicing position


*For slide nuts refer to chapter 2.2 page 2

Increasing the carriage length will increase the basic length by the same amount.

Size ❒	Basic length L	A	B	C	E	F	G	H	J	K	M for	N for	O for	R	P1	P2	U	Basic weight Motor size 1/2/3	Weight per 100mm Motor size 1/2/3
DSM 160P	Q + 108	160	144	76	90	76	106	11	104	106	M 6	M 8	M 8	107	9	57	80	12,1/15/20	1,7/2,1/2,1
DSM 200P	Q + 126	200	182	76	140	96	126	15	128	129	M 8	M 10	M 10	130	10	62	100	26,1/29,6/36,8	2,8/2,8/2,8


0 **Choice of guide body profile:**

(0)



without internal profile
and cover bands

(1)



without internal profile
without cover bands

Stainless version upon request.

1 **Measurement system:**


(1) Measurement system LE100/1 5V Resolution 0.05 **(2)** Measurement system LE100/1 10,5-30V Resolution 0.05 **(3)** Hall sensor **(4)** Measurement system provided by customer

1 **Plug:**

(1) Plug Pos. 1



(2) Plug Pos. 2



(3) open unconnected cable end



1 **Motor size:**

(1) Motor size 1 with Q_1 **(2)** Motor size 2 with Q_2 **(3)** Motor size 3 with Q_3
(4) Supply with Q_1* **(5)** Supply with Q_2* **(6)** Supply with Q_3*
* = provided by customer

Dimensioning criteria for motor output						
	l_p ❒	b_p ❒	h_{ps} ❒	Q_1	Q_2	Q_3
160	Q-70	71	50	316	360	461
200	Q-70	85	62	410	444	610

l_p = length primary part; b_p = width primary part;
h_{ps} = height primary part + height secondary part
+ interspaces primary-/secondary part

For standard carriage length see 'Q' in table.
The carriages can be delivered in any non-standard length upon request; the longer the carriage, the greater the load capacity. For linear encoder refer to chapter 9.1.

1500 Basic length + stroke = total length

DSM	160P	0	0	1	1	0	0	1	01500
Pos.		1	2	3	4	5	6	7	

Sample ordering code:
DSM160P, Bahr Modultechnik Linear motor, standard body profile, Measurement system LE100/1 5V, Plug Pos. 1, motor size 1, 1094mm stroke

Magnetic Sensor LE100/1 und Magnetic Band MB100



Specifications:

+ Supply voltage	10,5 - 30 VDC; 5 VDC +/- 5% optional 5 V DC +/- 5%
+ Power consumption	<25 mA @ 24VDC; <50mA @ 5VDC
+ Protection	reverse battery protection
+ Connection	flying leads
+ Material of casing	metal
+ Output signals	sinusA, B, phase-shifted by 90°
+ Output current	I out max. 5 mA per signal path
+ Signal size	approx. 1 Vss
+ Travel speed	max. 10 m/s
+ System accuracy	depending on interpolation electronics
+ Gap strip/sensor	0,1 - 0,4 mm (without cover strip)
+ Working temperature	-10....+70 °C
+ Storage temperature	-30....+80°C
+ Interference protection class	3, accord. to ICE 801
+ Test mark	CE
+ System of protection	IP 67 reading S

Magnetic Sensor LE100/1

Contactlessly measuring scanning unit with integrated analog signal output (sine 1 Vss). Together with the magnetic scale MB100 and a follower interpolation electronics unit, the LE100/1 forms an open linear measuring system.


Features:
+ Easy mounting
+ LED status display
+ Signal period 1000 µm (analog)
+ Scale MB100
+ Reference signal (option)
+ Insensitive to dust, shavings, humidity

Magnetic Band MB100


The magnetic band consists of a magnetic tape magnetized at regular distances and firmly joind with the carrier strip. For mounting a special adhesive tape is pre-mounted

Features:
+ Easy mounting by glueing
+ Insensitive to dust, shavings, humidity...
+ accuracy class 50 µm/1000 mm

Options
+ Stainless stell strip



Example DLM 160




Belt driven positioning systems LL

Positioning system LLZ 60, 80

Belt drive



pulley block




Size	X1	X2	X3
LL 60	M8	29,5	30
LL 80	M10	47,5	40

Function:
The guide body consists of an aluminium square profile, with an integrated roller guide. The carriage is moved by means of an internal rotating toothed belt. On one end there is a pulley block with coupling claws on both sides (standard version). On the opposite end there is a plate with a retensioning device for the toothed belt.

Fitting position: As required. Max. length 6.000 mm without joints.
Carriage mounting: By tapped holes.
Unit mounting: By T-slots and mounting sets. The linear axis can be combined with any T-slot profile.
Belt performance: HTD with steel reinforcement, no backlash when changing direction, repeatability ± 0,1 mm.
Carriage support: The carriage runs on 5 rollers which can be adjusted and serviced at each central servicing position. Two grease nipples at the carriage enable relubrication of the positioning system.

Forces and torques



Size	60		80	
Forces/Torques	static	dynamic	static	dynamic
F_x (N)	1073	960	1900	1800
F_y (N)	780	650	1900	1500
F_z (N)	1170	845	2100	1700
M_x (Nm)	20	13	85	60
M_y (Nm)	78	65	140	110
M_z (Nm)	52	39	110	90
All forces and torques related to the following:				
existing values / table values	$\frac{Fy}{Fy_{dyn}} + \frac{Fz}{Fz_{dyn}} + \frac{Mx}{Mx_{dyn}} + \frac{My}{My_{dyn}} + \frac{Mz}{Mz_{dyn}} \leq 1$			
No-load torque				
Nm	0,6		0,8	
Speed				
(m/s) max	6		10	
Tensile force				
permanent (N)	1050		1900	
0,2 s (N)	1150		2090	
Geometrical moments of inertia of aluminium profile				
I_x mm⁴	4,47x10⁵		15,83x10⁵	
I_y mm⁴	5,59x10⁵		20,68x10⁵	
Elastic modulus N/mm²	70000		70000	

For life-time calculation of rollers use our homepage · www.bahr-modultechnik.com

Driving torque:


$$M_a = \frac{F * P * S_i}{2000 * \pi} + M_n$$

$$P_a = \frac{M_a * n}{9550}$$

F = force (N)
P = pulley action perimeter (mm)
Si = safety factor 1,2 ... 2
M_n = no-load torque (Nm)
n = rpm pulley (min^{-1})
M_a = driving torque (Nm)
P_a = motor power (KW)

Deflection:


$$f = \frac{F * L^3}{E * I * 192}$$




f = deflection (mm)
F = load (N)
L = free length (mm)
E = elastic modulus 70000 (N/mm²)
I = second moment of area (mm⁴)

Positioning system LLZ 60, 80


Dimensions (mm)



2 cupped-type lubricating nipples for each carriage



Hose connections available on request.



*For slide nuts refer to chapter 2.2 page 2

Size ❐	Basic length L	A	AB ❐	B	C1	C2	C3	D -0,05	E	F	G	M	N for	P1	P2	P3	T	X	Y	Basic weight	Weight per 100 mm
LLZ 60	330	80	60	25	18	24	20	47	63	42	62	M6x6	M5	59	6	55	M6	27	26	2,75 kg	0,41 kg
LLZ 80	495	100	80	25	18	30	22	68	93	60	83	M6x10	M6	90	9	84	M8	45	40	8,45 kg	0,90 kg

11.1


0 **Choice of guide body profile:**

(0) Standard **(2)** corrosion-protected guide rods and screws


(4) expanded corrosion-protected version (depending on the availability of components)

0 **Choice of carriages:**

(0)




(1)




Carriage	L	Q1	Q2	H1	H2	H3	H4
LLZ 60 Vers. (0)	330	215	175	31	93	155	161,5
LLZ 60 Vers. (1)	299	184	144	62	---	124	130,5
LLZ 80 Vers. (0)	495	320	251	30	90	150	228
LLZ 80 Vers. (1)	435	260	191	40	---	120	168

0 **Drive version:**


0




1



2



6



Belt table:

Code No.		Size	Belt	mm/rev.	Number of teeth
0	3	**60**	5M30	130	26
0	7	**80**	8M 30	176	22

Shaft dimensions / Coupling claw:

Size	Shaft	Feather key	Coupling
60	14 h6 x 35	5x5x28	14
80	18 h6 x 45	6x6x40	19


LLZ	60	1	0	0	0	0	3	1	01500
Pos.		1	2	3	4	5	6	7	

Basic length + stroke = total length

Sample ordering code:
LLZ60, standard body profile, double-sided coupling claw, 1170 mm stroke

Positioning system LLR 60, 80


Roller guide without drive



Function:
The guide body consists of an aluminium square profile, with an integrated roller guide. This roller guide can be driven by a pneumatic cylinder or other additional drives or it serves as a load carrying slide unit.

Fitting position: As required. Max. length 6.000 mm without joints.
Carriage mounting: By tapped holes.
Unit mounting: By T-slots and mounting sets. The linear axis can be combined with any T-slot profile.
Belt performance: HTD with steel reinforcement, no backlash when changing direction, repeatability ± 0,1 mm.
Carriage support: The carriage runs on 5 rollers which can be adjusted and serviced at each central servicing position. Two grease nipples at the carriage enable relubrication of the positioning system.

Forces and torques




Size	60		80	
Forces/Torques	static	dynamic	static	dynamic
F_x (N)	–	–	–	–
F_y (N)	780	650	1900	1500
F_z (N)	1170	845	2100	1700
M_x (Nm)	20	13	85	60
M_y (Nm)	78	65	140	110
M_z (Nm)	52	39	110	90
All forces and torques related to the following: existing values / table values $\frac{Fy}{Fy_{dyn}} + \frac{Fz}{Fz_{dyn}} + \frac{Mx}{Mx_{dyn}} + \frac{My}{My_{dyn}} + \frac{Mz}{Mz_{dyn}} \leq 1$				
No-load torque				
Nm	0,6		0,8	
Speed				
(m/s) max	6		10	
Tensile force				
permanent (N)	1050		1900	
0,2 s (N)	1150		2090	
Geometrical moments of inertia of aluminium profile				
I_x mm^4	4,47x10^5		15,83x10^5	
I_y mm^4	5,59x10^5		20,68x10^5	
Elastic modulus N/mm^2	70000		70000	

For life-time calculation of rollers use our homepage.

Deflection:


$$f = \frac{F * L^3}{E * I * 192}$$




f = deflection (mm)
F = load (N)
L = free length (mm)
E = elastic modulus 70000 (N/mm^2)
I = second moment of area (mm^4)


Positioning system LLR 60, 80

Dimensions (mm)






2 cupped-type lubricating nipples for each carriage



Hose connections available on request.



*For slide nuts refer to chapter 2.2 page 2


Size ❒	Basic lenght L	A ❒	B	C1	C2	C3	G	H1	H2	H4	Mxl	N for	P2	Q	Basic weight	Weight per 100 mm
LLR 60	187	60	25	18	24	20	62	31	93	161,5	M6	M5	6	175	1,145 kg	0,377 kg
LLR 80	287	80	25	18	30	22	83	40	120	---	M6	M6	9	260	4,006 kg	0,730 kg

0 **Choice of guide body profile:**

(0) Standard **(2)** corrosion-protected guide rods and screws

(4) expanded corrosion-protected version (depending on the availability of components)

0 **Choice of carriages:**



Size	Carriage	L	Q	H1	H2	H3	H4
60	**Version (0)**	187	175	31	93	155	161,5
60	**Version (1)**	158	144	62	---	124	130,5
80	**Version (0)**	---	---	---	---	---	---
80	**Version (1)**	278	260	40	120	---	---

LLR	60	0	0	0	0	0	0	0	01500
	Pos.	1	2	3	4	5	6	7	

Basic length + stroke = total length

Sample ordering code:
LLR60, standard body profile, carriage (0), 1312 mm stroke

11.1

Application example



LLZ 60 - DLZ 120




LLZ 60 - DLZ 120



Belt driven positioning systems LS

Positioning system LSZ 60, 80

Belt drive




Fraunhofer IPA TESTED DEVICE
Lineareinheit LSZ 80
Report No. BA 1610-848

Function:
The guide body consists of an aluminium square profile with an integrated rail guide. The carriage is moved by means of a revolving interior timing belt. At the front face there is a timing belt deflection unit with integrated coupling claws integrated on two sides. The opposite front face is provided with a plate containing a tensioning device for the timing belt.

Mounting position: Variable, max. one-piece-length: 6.000 mm.
Carriage connection: By threaded holes.
Fixation: By T-slots and mounting sets. The linear axis can be combined with any T-slot profile.
Timing belt: HTD with reinforcing steel mesh, no backlash when changing direction, repeatability ± 0.1 mm.
Carriage support: In the standard version the carriage is positioned on two runner blocks which can be readjusted and maintained at each central servicing position. Two grease nipples at the carriage enable relubrication of the positioning system.

Forces and torques



Size	60		80	
permitted dyn. Forces*	5000 km	10000 km	5000 km	10000 km
F_x (N)	1073	960	1900	1800
F_y (N)	1410	990	3570	2550
F_z (N)	3520	2500	8500	6050
M_x (Nm)	33	23	107	75
M_y (Nm)	104	73	310	222
M_z (Nm)	100	70	296	210
All forces and torques related to the following: existing values / table values $\frac{Fy}{Fy_{dyn}} + \frac{Fz}{Fz_{dyn}} + \frac{Mx}{Mx_{dyn}} + \frac{My}{My_{dyn}} + \frac{Mz}{Mz_{dyn}} \leq 1$				
No-load torque				
Nm	0,6		1,0	
Speed				
(m/s) max	5		5	
Tensile force				
Dauer (N)	1050		1900	
0,2 s (N)	1150		2090	
Geometrical moments of inertia of aluminium profile				
I_x mm⁴	4,37x10⁵		14,6x10⁵	
I_y mm⁴	5,78x10⁵		17,1x10⁵	
Elastic modulus N/mm²	70000		70000	

** referred to lifetime*


Driving torque:

$$M_a = \frac{F * P * S_i}{2000 * \pi} + M_n$$

$$P_a = \frac{M_a * n}{9550}$$

F = force (N)
P = pulley action perimeter (mm)
Si = safety factor 1,2 ... 2
M_n = no-load torque (Nm)
n = rpm pulley (min^{-1})
M_a = driving torque (Nm)
P_a = motor power (KW)

Deflection:




$$f = \frac{F * L^3}{E * I * 192}$$


f = deflection (mm)
F = load (N)
L = free length (mm)
E = elastic modulus 70000 (N/mm²)
I = second moment of area (mm⁴)

Positioning system LSZ 60, 80

Dimensions (mm)




2 cupped-type lubricating nipples for each carriage





Hose connections available on request.



*For slide nuts refer to chapter 2.2 page 2

Size ❐	A	AB ❐	B	C1	C2	C3	D -0,05	E	F ❐	G	Mxl	N for	P1	P2	P3	T	X	Y	a	b	c	Weight per 100 mm
LSZ 60	80	60	25	18	24	20	47	63	42	62	M6x10	M5	59	6	55	M6	27	26	29,5	30	M8	0,53 kg
LSZ 80	100	80	25	18	30	22	68	93	60	83	M6x12	M6	90	8	73	M8	45	40	47,5	40	M10	0,87 kg

0 **Choice of guide body profile:**


(0) Standard **(1)** corrosion-protected screws

(4) expanded corrosion-protected version (depending on the availability of components)


Carriage		L	Q	Q2	H1	H2	H4	Basic weight System
LS 60	Version (0)	274	160	116	31	93	106	3,06 kg
	Version (1)	254	140	96	32	84	10	2,62 kg
	Version (2)	214	100	56	31	-	48	2,07 kg
LS 80	Version (0)	382	219	149	40	120	133	7,69 kg
	Version (1)	367	204	134	40	120	125	7,41 kg
	Version (2)	310	147	77	40	-	60,5	6,39 kg

0 **Choice of carriages:**


(0)



(1)




(2)




0 **Drive version:**

0



1 2 6



Belt table:

Code No.		Size	Belt	mm/rev.	Number of teeth
0	**3**	**60**	5M 30	130	26
0	**7**	**80**	8M 30	176	22

Shaft dimensions / Coupling claw:

Size	Shaft Ø h6 x length	Feather key	Coupling
60	14 x 35	5x5x28	14
80	18 x 45	6x6x40	19

LSZ	60	1	0	0	0	0	3	1	01500
Pos.		1	2	3	4	5	6	7	


Basic length + stroke = total length

Sample ordering code:
LSZ60, standard body profile, standard carriage , double-sided coupling claw, 1226 mm stroke

12.1

Positioning system LSN 60


Belt drive



Function:
The guide body consists of an aluminium square profile with an integrated rail guide. The carriage is moved by a revolving interior nobbed belt. The advantage of this system: The belt is guided within the profile, so that the system is independent of the mounting position. The nobbed belt is self-tracking and has a very low operating noise level thanks to its nobs being offset by 45°. Furthermore, it is almost vibration-free in the transition sections. At the front face there is a timing belt deflection unit containing a toothed pulley with two coupling claws in the standard version. On the opposite side there is a bearing piece plate containing a tensioning device for the timing belt.

Mounting position: Variable, max. one-piece-length: 6.000 mm.
Carriage connection: By threaded holes.
Fixation: By T-slots and mounting sets. The linear axis can be combined with any T-slot profile.
Timing belt: N10 with reinforcing steel mesh, no backlash when changing direction, repeatability ± 0.1 mm.
Carriage support: In the standard version the carriage is positioned on two runner blocks which can be readjusted and maintained at each central servicing position. Two grease nipples at the carriage enable relubrication of the positioning system.

Forces and torques



Size	60	
permitted dyn. Forces*	5000 km	10000 km
F_x (N)	1170	1040
F_y (N)	1410	990
F_z (N)	3520	2500
M_x (Nm)	33	23
M_y (Nm)	104	73
M_z (Nm)	100	70
All forces and torques related to the following: existing values / table values	$\frac{Fy}{Fy_{dyn}} + \frac{Fz}{Fz_{dyn}} + \frac{Mx}{Mx_{dyn}} + \frac{My}{My_{dyn}} + \frac{Mz}{Mz_{dyn}} \leq 1$	
No-load torque		
Nm	0,6	
Speed		
(m/s) max	5	
Tensile force		
Dauer (N)	1170	
0,2 s (N)	1300	
Geometrical moments of inertia of aluminium profile		
I_x mm⁴	$4{,}37 \times 10^5$	
I_y mm⁴	$5{,}78 \times 10^5$	
E-Modul N/mm²	70000	

** referred to lifetime*


Driving torque:

$$M_a = \frac{F * P * S_i}{2000 * \pi} + M_n$$

$$P_a = \frac{M_a * n}{9550}$$

F = force (N)
P = pulley action perimeter (mm)
Si = safety factor 1,2 ... 2
M_n = no-load torque (Nm)
n = rpm pulley (min^{-1})
M_a = driving torque (Nm)
P_a = motor power (KW)

Deflection:




$$f = \frac{F * L^3}{E * I * 192}$$


f = deflection (mm)
F = load (N)
L = free length (mm)
E = elastic modulus 70000 (N/mm^2)
I = second moment of area (mm^4)

Positioning system LSN 60

Dimensions (mm)




2 cupped-type lubricating nipples for each carriage





Hose connections available on request.



*For slide nuts refer to chapter 2.2 page 2


Size ❐	A	AB ❐	B	C1	C2	C3	D -0,05	E	F ❐	G	Mxl	N for	P1	P2	P3	T	X	Y	a	b	c	Weight per 100 mm
LSN 60	80	60	25	18	24	20	47	63	42	62	M6x10	M5	59	6	55	M6	27	26	29,5	30	M8	0,53 kg

0 **Choice of guide body profile:**
(0) Standard **(1)** corrosion-protected screws

Carriage		L	Q	Q2	H1	H2	H4	Basic weight System
LS 60	Version (0)	274	160	116	31	93	106	3,06 kg
	Version (1)	254	140	96	32	84	10	2,62 kg
	Version (2)	214	100	56	31	–	48	2,07 kg


0 **Choice of carriages:**

(0) **(1)** **(2)**



0 **Drive version:**

0 1 2 6



Belt table:

Code No.		Size	Belt	mm/rev.	Number of teeth
0	**8**	**60**	Nubbed belt	130	13/3

Shaft dimensions / Coupling claw:

Size	Shaft Ø h6 x length	Feather key	Coupling
60	14 x 35	5x5x28	14

LSN	60	1	0	0	0	0	8	1	01500
Pos.		1	2	3	4	5	6	7	

—— Basic length + stroke = total length


Sample ordering code:
LSN60, standard body profile, standard carriage , nubbed belt, double-sided coupling claw, 1226 mm stroke


12.1

Positioning system LSZ 60 HP

Belt drive

Positioning system with very high accuracy





Milling on these surfaces.


Function:

The guide body consists of an aluminium square profile which is surface-milled before assembly (marked red in the picture). The eloxal is removed in these areas. Thanks to these machining operations we achieve the highest level of accuracy for the positioning systems and are able to remove fine unevennesses and deviations.

The guide body consists of an aluminium square profile with an integrated rail guide. The carriage is moved by means of a revolving interior timing belt. At the front face there is a timing belt deflection unit with integrated coupling claws integrated on two sides. The opposite front face is provided with a plate containing a tensioning device for the timing belt.

Mounting position: Variable, max. one-piece-length: 2.000 mm.
Carriage connection: By threaded holes.
Fixation: By T-slots and mounting sets. The linear axis can be combined with any T-slot profile.
Timing belt: HTD with reinforcing steel mesh, no backlash when changing direction, repeatability ± 0.1 mm.
Carriage support: In the standard version the carriage is positioned on two runner blocks which can be readjusted and maintained at each central servicing position. Two grease nipples at the carriage enable relubrication of the positioning system.

Forces and torques



Size	60	
permitted dyn. Forces*	5000 km	10000 km
F_x (N)	1073	960
F_y (N)	1410	990
F_z (N)	3520	2500
M_x (Nm)	33	23
M_y (Nm)	104	73
M_z (Nm)	100	70
All forces and torques related to the following: existing values / table values $\frac{Fy}{Fy_{dyn}} + \frac{Fz}{Fz_{dyn}} + \frac{Mx}{Mx_{dyn}} + \frac{My}{My_{dyn}} + \frac{Mz}{Mz_{dyn}} \leq 1$		
No-load torque		
Nm	0,6	
Speed		
(m/s) max	5	
Tensile force		
permanent (N)	1050	
0,2 s (N)	1150	
Geometrical moments of inertia of aluminium profile		
I_x mm^4	4,37x10^5	
I_y mm^4	5,78x10^5	
Elastic modulus N/mm^2	70000	

** referred to lifetime*

Driving torque:


$$M_a = \frac{F * P * S_i}{2000 * \pi} + M_n$$

$$P_a = \frac{M_a * n}{9550}$$

F = force (N)
P = pulley action perimeter (mm)
Si = safety factor 1,2 ... 2
M_n = no-load torque (Nm)
n = rpm pulley (min^{-1})
M_a = driving torque (Nm)
P_a = motor power (KW)

Deflection:


$$f = \frac{F * L^3}{E * I * 192}$$




f = deflection (mm)
F = load (N)
L = free length (mm)
E = elastic modulus 70000 (N/mm^2)
I = second moment of area (mm^4)

Positioning system LSZ 60 HP

Dimensions (mm)



2 cupped-type lubricating nipples for each carriage





Hose connections available on request.

*For slide nuts refer to chapter 2.2 page 2

All milled surfaces without anodizing.

Size ❐	A	AB	B	C1	C2	C3	D -0,05	E	F ❐	G	Mxl	N for	P1	P2	P3	T	X	Y	a	b	c	Basic weight	Weight per 100 mm
LSZ 60 **HP**	80	60	25	18	24	19,5	47	63	42	61	M6x10	M5	59	6	55	M6	27	26	29,5	30	M8	2,67 kg	0,46 kg

0 **Choice of guide body profile:**

(0) Standard


Carriage	L	Q	Q2	H1	H2	H4
Version (0)	274	160	116	31	93	106
Version (1)	254	140	96	32	84	10
Version (2)	214	100	56	31	-	48

0 **Choice of carriages:**


(0)



(1)




(2)




0 **Drive version:**

0



1 2 6



Belt table:

Code No.		Size	Belt	mm/rev.	Number of teeth
0	3	**60**	5M 30	130	26

Shaft dimensions / Coupling claw:

Size	Shaft	Feather key	Coupling
60	14 h6 x 35	5x5x28	14


LSZ	60 HP	1	0	0	0	0	3	1	01500
Pos.		1	2	3	4	5	6	7	

Basic length + stroke = total length

Sample ordering code:
LSZ60HP, standard body profile, standard carriage , double-sided coupling claw, 1226 mm stroke

Positioning system LSR 60, 80


Rail guide without drive



Function:
The guide body consists of an aluminium square profile, with an integrated rail guide. This rail guide can be driven by a pneumatic cylinder or other additional drives or it serves as a load carrying slide unit.

Fitting position: As required. Max. length 6.000 mm without joints.
Carriage mounting: By tapped holes.
Unit mounting: By T-slots and mounting sets. The linear axis can be combined with any T-slot profile.
Belt performance: HTD with steel reinforcement, no backlash when changing direction, repeatability ± 0,1 mm.
Carriage support: In the standard version the carriage is positioned on two runner blocks which can be readjusted and maintained at each central servicing position. Two grease nipples at the carriage enable relubrication of the positioning system.

Forces and torques




Size	60		80	
permitted dyn. Forces*	5000 km	10000 km	5000 km	10000 km
F_x (N)	–	–	–	–
F_y (N)	1410	990	3570	2550
F_z (N)	3520	2500	8500	6050
M_x (Nm)	33	23	107	75
M_y (Nm)	104	73	310	222
M_z (Nm)	100	70	296	210
All forces and torques related to the following: existing values / table values $\frac{Fy}{Fy_{dyn}} + \frac{Fz}{Fz_{dyn}} + \frac{Mx}{Mx_{dyn}} + \frac{My}{My_{dyn}} + \frac{Mz}{Mz_{dyn}} \leq 1$				
No-load torque				
Nm	0,6		1,0	
Speed				
(m/s) max	5		5	
Tensile force				
Dauer (N)	1050		1900	
0,2 s (N)	1150		2090	
Geometrical moments of inertia of aluminium profile				
I_x mm⁴	$4,37x10^5$		$14,6x10^5$	
I_y mm⁴	$5,78x10^5$		$17,1x10^5$	
Elastic modulus N/mm²	70000		70000	

** referred to lifetime*

Deflection:


$$f = \frac{F * L^3}{E * I * 192}$$




f = deflection (mm)
F = load (N)
L = free length (mm)
E = elastic modulus 70000 (N/mm²)
I = second moment of area (mm⁴)

Positioning system LSR 60, 80


Dimensions (mm)



2 cupped-type lubricating nipples for each carriage



Hose connections available on request.




*For slide nuts refer to chapter 2.2 page 2

Size□	Basic lenght L	A □	B	C1	C2	C3	G	H1	H2	H4	Mxl	N for	P2	Q	Basic weight	Weight per 100 mm
LSR 60	162	60	25	18	24	20	62	31	93	106	M6 x 11	M5	6	116	1,54 kg	0,43 kg
LSR 80	166	80	25	18	30	22	83	40	120	133	M6 x 12	M6	8	149	2,19 kg	0,88 kg

0 **Choice of guide body profile:**
(0) Standard **(1)** corrosion-protected screws
(4) expanded corrosion-protected version
(depending on the availability of components)

0 **Choice of carriages:**

(0)



LSR	60	0	0	0	0	0	0	0	01500
	Pos.	1	2	3	4	5	6	7	

Basic length + stroke = total length


Sample ordering code:
LSR60, standard body profile, standard carriage, 1338 mm stroke

12.1

Application examples








CLLZ - CLLT/K
Belt and spindle driven positioning systems

Positioning system CLLZ 60

Belt drive

Special positioning system for building
3D printers and tripods.






Function:
The guide body consists of an aluminium profile with elegantly rounded outer edges, with a roller guide integrated into it. The carriage is moved by means of a revolving interior timing belt. At the front face there is a timing belt deflection unit with integrated coupling claws on two sides. The opposite front face is provided with a plate containing a tensioning device for the timing belt.

Fitting position: As required. Max. length 6.000 mm without joints.
Carriage mounting: By tapped holes.
Belt performance: HTD with steel reinforcement, no backlash when changing direction, repeatability ± 0,1 mm.
Carriage support: The carriage runs on 5 rollers which can be adjusted and serviced at each central servicing position. Two grease nipples at the carriage enable relubrication of the positioning system.

Forces and torques



Size	60	
Forces/Torques	static	dynamic
F_x (N)	1073	960
F_y (N)	780	650
F_z (N)	1170	845
M_x (Nm)	20	13
M_y (Nm)	78	65
M_z (Nm)	52	39
All forces and torques related to the following: existing values / table values	$\frac{Fy}{Fy_{dyn}} + \frac{Fz}{Fz_{dyn}} + \frac{Mx}{Mx_{dyn}} + \frac{My}{My_{dyn}} + \frac{Mz}{Mz_{dyn}} \leq 1$	
No-load torque		
Nm	0,6	
Speed		
(m/s) max	4	
Tensile force		
permanent (N)	1050	
0,2 s (N)	1150	
Geometrical moments of inertia of aluminium profile		
I_x mm^4	4,47x10^5	
I_y mm^4	5,59x10^5	
Elastic modulus N/mm^2	70000	

For life-time calculation of rollers use our homepage · www.bahr-modultechnik.com

Driving torque:


$$M_a = \frac{F * P * S_i}{2000 * \pi} + M_n$$

$$P_a = \frac{M_a * n}{9550}$$

F	= force	(N)
P	= pulley action perimeter	(mm)
Si	= safety factor 1,2 ... 2	
M_n	= no-load torque	(Nm)
n	= rpm pulley	(min^{-1})
M_a	= driving torque	(Nm)
P_a	= motor power	(KW)


Deflection:

$$f = \frac{F * L^3}{E * I * 192}$$



f = deflection	(mm)
F = load	(N)
L = free length	(mm)
E = elastic modulus 70000	(N/mm^2)
I = second moment of area	(mm^4)

Positioning system CLLZ 60



Size	X1	X2	X3
CLLZ 60	M8	29,5	30


Size	Basic length L	A	B	C	C1	D	E	F Ø	G	H1	H2	H3	H4	Mxl	P1	P2	P3	Q1	Q2	T	X	Y	Basic weight	Weight per 100 mm
CLLZ 60	329	97	80	25	18	47	63	42	70	31	93	155	161,5	M6x6	59	6	55	215	175	M6	27	26	2,65 kg	0,81 kg

0 **Choice of guide body profile:**

(0) Standard **(2)** corrosion-protected guide rods and screws


(4) expanded corrosion-protected version (depending on the availability of components)

0 **Choice of carriages:**



Carriage	L	Q1	Q2	H1	H2	H3	H4
60 Vers. (0)	330	215	175	31	93	155	161,5
60 Vers. (1)	299	184	144	62	---	124	130,5

0 **Drive version:**



Belt table:

Code No.		Size	Belt	mm/rev.	Number of teeth
0	3	60	5M 30	130	26

Shaft dimensions / Coupling claw:

Size	Shaft	Feather key	Coupling
60	14 h6 x 35	5x5x28	14

CLLZ	60	1	0	0	0	0	3	1	01500
Pos.		1	2	3	4	5	6	7	


Basic length + stroke = total length

Sample ordering code:
CLLZ60, standard body profile, double-sided coupling claw, 1329 mm stroke

Positioning system CLLT/K 60

Belt drive

Special positioning system for building 3D printers and tripods.




Function:

The guide body consists of an aluminium profile with elegantly rounded outer edges. The carriage is moved by a rotating threaded spindle provided with a follower nut. The spindle nuts move along the profile axes through a roller guide system to ensure a smooth, synchronous run. Additional grooves integrated in the profile facilitate the optional fixation of various side frame covers made of glass, plexiglass, aluminium or composite materials.

Fitting position: As required. Max. length 6.000 mm without joints.
Spindle version: Trapezoidal or ball screw spindle, max. length 3000 mm
Carriage support: The carriage runs on 5 rollers which can be adjusted and serviced at each central servicing position. Two grease nipples at the carriage enable relubrication of the positioning system.

Forces and torques



Size	60	
Forces / Torques	static	dynamic
F_x (N)	900	800
F_y (N)	390	325
F_z (N)	1170	845
M_x (Nm)	10	6,5
M_y (Nm)	78	65
M_z (Nm)	52	39
All forces and torques relate to the following:		
existing values / table values	$\frac{Fy}{Fy_{dyn}} + \frac{Fz}{Fz_{dyn}} + \frac{Mx}{Mx_{dyn}} + \frac{My}{My_{dyn}} + \frac{Mz}{Mz_{dyn}} \leq 1$	
No-load torque		
Trapezoidal thread	18 x 4	18 x 8
Nm	0,4	0,5
Ballscrew	16 x 5	16 x 16
Nm	0,2	0,4
Mass moments of inertia spindle		
Kg m²/ m	Tr 18x4 - $5{,}05 \times 10^{-5}$	
Kg m²/ m	Kg 16x5 - $4{,}1 \times 10^{-5}$	

For life-time calculation of rollers use our homepage · www.bahr-modultechnik.com

Driving torque:


$$M_a = \frac{F * P * S_i}{2000 * \pi} + M_n$$

$$P_a = \frac{M_a * n}{9550}$$

F	= force	(N)
P	= pulley action perimeter	(mm)
Si	= safety factor 1,2 ... 2	
M_n	= no-load torque	(Nm)
n	= rpm pulley	(min^{-1})
M_a	= driving torque	(Nm)
P_a	= motor power	(KW)

Deflection:


$$f = \frac{F * L^3}{E * I * 192}$$





f = deflection	(mm)
F = load	(N)
L = free length	(mm)
E = elastic modulus 70000	(N/mm^2)
I = second moment of area	(mm^4)

Positioning system CLLT/K 60

Dimensions (mm)







Size	Basic length L	A	B	D	E	G	H	J	K	M	Q	R	S	T	Basic weight	Weight per 100 mm
CLLT/K 60	269	95,6	58	18,6	6,3	variable*	71	48	131	256	144	93	106	18	3,2 kg	0,6 kg

*Motor space


K **Spindel:**
(T) Trapezoidal thread **(K)** Ballscrew

1 **Selection of screw:**
(1) right hand **(2)** left hand


0 **Choice of guide body profile:**
(0) Standard **(2)** corrosion-protected guide rods and screws

0 **Choice of carriages:**

(0)



(1)



Carriage	Q
Version (1)	184

0 **Drive version:**
(0) one shaft (locating bearing side) **(1)** one shaft (non-locating bearing side) **(2)** shaft on both sides

0 **Selection of screw:**

Size	Standard	Multistart screw	Standard	Multistart screw	
	Trapezoidal thread		Ballscrew		
60	**(0)** Tr 18x4	**(1)** Tr 18x8	**(0)** Kg 16x5	**(0)** Kg 16x10	**(0)** Kg 16x16

0 **Ballscrew pitch accuracy:**
(0) 0,05 mm / 300 mm (Standard) **(2)** 0,025 mm / 300 mm

0 **End play of ball nut:**
(0) 0,04 mm (Standard) **(1)** < 0,02 mm **(2)** 2% apply prestress


CLL	K	60	1	0	0	0	0	0	0	1500
		Pos.	1	2	3	4	5	6	7	

Basic length + stroke = total length

It is recommended to contact our sales department for any inquiries regarding this special system.


13.1

3D PRINTER CLLK 60









W - Positioning systems

Positioning system WGVZ | WKVZ 16


Belt drive



Function:
This positioning system is guided either by means of ball bushings (WKVZ) or sliding bushings (WGVZ). An HTD toothed belt is used as drive mechanism. The carriage is moved by means of a revolving vertical timing belt. Due to various threaded holes and a small installation height, this system can be integrated individually and easily into any application. Both bearing pieces offer the possibility to combine motors of any make, from either end by means of pivots or couplings. The open arrangement of the axes ensures that no dirt can accumulate in the interior parts. Optionally, the units are also available with two carriages, which can be driven in the same direction or in opposite directions.

Fitting position: As required. Max. length 2000 mm
Carriage mounting: By tapped holes in the carriage.
Unit mounting: By tapped holes in the bearing block.
Belt type: HTD with steel reinforcement, no backlash when changing direction, repeatability: ± 0,1 mm.

Forces and torques



Size	WGVZ 16		WKVZ 16	
Forces/Torques	static	dynamic	static	dynamic
F_x (N)	750	600	750	600
F_y (N)	90	60	90	60
F_z (N)	90	60	90	60
M_x (Nm)	10	5	12	10
M_y (Nm)	13	6	12	10
M_z (Nm)	14	7	15	12
All forces and torques relate to the following: existing values / table values $\frac{Fy}{Fy_{dyn}} + \frac{Fz}{Fz_{dyn}} + \frac{Mx}{Mx_{dyn}} + \frac{My}{My_{dyn}} + \frac{Mz}{Mz_{dyn}} \leq 1$				
No-load torque				
Nm	0,1		0,1	
Speed				
(m/s) max	1		3	
Tensile force				
permanent (N)	200		200	
0,2 s (N)	280		280	
Geometrical moments of inertia of aluminium profile				
I_x mm⁴	0,6434 x 10⁴		0,6434 x 10⁴	
I_y mm⁴	2,38 x 10⁵		2,38 x 10⁵	
E-Modulus N/mm²	2,1 x 10⁵		2,1 x 10⁵	

Driving torque:


$$M_a = \frac{F * P * S_i}{2000 * \pi} + M_n$$

$$P_a = \frac{M_a * n}{9550}$$

F = force (N)
P = pulley action perimeter (mm)
Si = safety factor 1,2 ... 2
M_n = no-load torque (Nm)
n = rpm pulley (min^{-1})
M_a = driving torque (Nm)
P_a = motor power (KW)

Deflection:


$$f = \frac{F * L^3}{E * I * 192}$$



f = deflection (mm)
F = load (N)
L = free length (mm)
E = elastic modulus 210.000 (N/mm²)
I = second moment of area (mm⁴)

14.1

Positioning system WGVZ | WKVZ 16



Size	Basic length L	A	B	C	D1 Ø - 0,05	D2	E1	E2	F Ø	G	H	J	K	N1	N2	M	O □	P	Q	R	S	Basic weight	Weight per 100 mm
W 16	162	80	54	31	28	28	39	41	16	45	10	M6	24	M4x8	M5x10	M5x7	25	28	70	68	56	1,78 kg	0,35 kg


Size	G1	G2	T1	T2
W 16	40	28	38	18

K **Version:**
(G) Slide bushing **(K)** Ball bushing

0 **Choice of guide body profile:**
(0) Standard

0 **Choice of carriages:**

(0)




0 **Drive version:**


(0)



(0)



(1)



Belt table

Code No.		Size	Belt	mm/rev.	Number of teeth
0	**1**	**16**	3M 12	60	20

Shaft dimensions / Coupling

Size	Hollow shaft	Coupling
16	Ø 8 H7	Rotex 9

W	K	VZ	16	1	0	0	0	0	1	0	1500
			Pos.	1	2	3	4	5	6	7	


Basic length + stroke = total length

Sample ordering code:
WKVZ 16 with ball bushings, standard body profile, carriage version 0, drive version 0, 1338 mm stroke

14.1

Positioning system WGVZ | WKVZ 16

Belt drive



Size	Basic length L	A	B	C	D2	E1	E2	F Ø	G	H	J	K	N1	N2	M	O □	P	Q	R	S	Basic weight	Weight per 100 mm
W 16	232	80	54	31	28	39	41	16	45	10	M6	24	M4x8	M5x10	M5x7	25	28	70	68	56	2,26 kg	0,35 kg


Size	G1	G2	T1	T2
W 16	40	28	38	18

K **Version:**
(G) Slide bushing **(K)** Ball bushing

0 **Choice of guide body profile:**
(0) Standard

0 **Choice of carriages:**

(0)




0 **Drive version:**


(0)



(0)



(1)



Belt table

Code No.		Size	Belt	mm/rev.	Number of teeth
0	**1**	**16**	3M 12	60	20

Shaft dimensions / Coupling

Size	Hollow shaft	Coupling
16	Ø 8 H7	Rotex 9

W	K	VZ	16	1	0	0	0	0	1	0	1500
			Pos.	1	2	3	4	5	6	7	

Basic length + stroke = total length

Sample ordering code:
WKVZ 16 with ball bushings, standard body profile, carriage version 0, drive version 0, 1268 mm stroke



WKVZ 16




WKT 16



WKT 16 R/L

Positioning system WGT/K | WKT/K 16


Spindle drive



Function:
This positioning system can be guided through either sliding bushings (WG) or ball bushings (WK). The carriage is moved by means of a rotating thread spindle with an assigned follower nut. Due to various threaded holes and a small installation height, this system can be integrated individually and easily into any application. Motors of any make can be connected by means of pivots. The open arrangement of the axes ensures that no dirt can accumulate in the interior parts. Optionally, the units are also available with two carriages, which can be driven in the same direction or in opposite directions.

Fitting position: As required. Max. length 2000 mm
Carriage mounting: By tapped holes in the carriage.
Unit mounting: By tapped holes in the bearing block.

Forces and torques



Size	WGT/K 16		WKT/K 16	
Forces / Torques	static	dynamic	static	dynamic
F_x (N)	750	600	750	600
F_y (N)	90	60	90	60
F_z (N)	90	60	90	60
M_x (Nm)	10	5	12	10
M_y (Nm)	13	6	12	10
M_z (Nm)	14	7	15	12
All forces and torques relate to the following:				
No-load torque				
Trapezoidal thread	10 x 3		10 x 3	
Nm	0,35		0,3	
Ballscrew	8 x 2,5		8 x 2,5	
Nm	0,20		0,15	
Geometrical moments of inertia of aluminium profile				
I_x mm⁴	0,6434 x 10⁴		0,6434 x 10⁴	
I_y mm⁴	2,38 x 10⁵		2,38 x 10⁵	
Elastic-modulus N/mm²	2,1 x 10⁵		2,1 x 10⁵	

Driving torque:

$$M_a = \frac{F * P * S_i}{2000 * \pi * \mu} + M_n$$

$$P_a = \frac{M_a * n}{9550}$$

F = force (N)
P = thread pitch (mm)
Si = safety factor 1,2 ... 2
M_n = no-load torque (Nm)
n = rpm of screw (min^{-1})
M_a = driving torque (Nm)
μ = screw efficiency
P_a = motor power (KW)


Efficiency of lead screws:

All ballscrew 0,900

Tr 10x3 0,375

Deflection:

$$f = \frac{F * L^3}{E * I * 192}$$




f = deflection (mm)
F = load (N)
L = free length (mm)
E = elastic modulus 70000 (N/mm^2)
I = second moment of area (mm^4)

For the diagram for critical speeds of lead screws refer to chapter 4.2

Positioning system WGT/K | WKT/K 16

Dimensions (mm)



Size	Basic length L	A	B	C □	D2	E1	E2	F ∅	H	J	K1	K2	N1	N2	M	O	P	Q	R1	R2	S	Basic weight	Weight per 100 mm
W 16	162	80	54	25	28	39	41	16	10	M6	24	70	M5	M4	M5	56	45	70	68	28	5	1,75 kg	0,37 kg

Size	G1	G2	T1	T2
W 16	40	28	38	18

K **Version:**
(G) Slide bushing **(K)** Ball bushing


T **Spindle:**
(T) Trapezoidal thread **(K)** Ballscrew

1 **Selection of screw:**
(1) right hand **(2)** left hand

0 **Choice of guide body profile:**
(0) Standard **(2)** corrosion-protected screws **(4)** expanded corrosion-protected version (depending on the availability of components)

0 **Choice of carriages:**

(0)



0 **Drive version:**
(0) right (locating bearing side) **(1)** left (non-locating bearing side) **(2)** shaft on both sides

0 **Selection of screw:** Tr = trapezoidal thread Kg = ballscrew

Size	Standard trapezoidal thread	Standard ballscrew
16	**(0)** Tr 10x3	**(0)** Kg 8x2,5

0 **Ballscrew pitch accuracy:** *(only ballscrew)*
(0) 0,05 mm / 300 mm **(2)** 0,025 mm / 300 mm

0 **End play of ball nut:** *(only ballscrew)*
(0) 0,04 mm *(Standard)*, **(1)** < 0,02 mm, **(2)** 2% apply prestress

W	K	T	16	1	0	0	0	0	1	1	1500
			Pos.	1	2	3	4	5	6	7	

Basic length + stroke = total length


Sample ordering code:
WKT 16 with ball bushings, trapezoidal thread right hand thread, standard body profile, carriage version 0, drive version 0, spindle Tr 10x3, 1338 mm stroke


14.1

Positioning system WGT/K | WKT/K 16

Dimensions (mm)

Spindle drive | right-hand and left-hand thread or divided spindles





Size	Basic length L	A	B	C □	D2	E1	E2	F ∅	H	J	K1	K2	N1	N2	M	O	P	Q	R1	R2	S	Basic weight	Weight per 100 mm
W 16	230	80	54	25	28	39	41	16	10	M6	24	70	M5	M4	M5	56	45	70	68	28	5	1,87 kg	0,37 kg

Size	G1	G2	T1	T2
W 16	40	28	38	18

K **Version:**
(G) Slide bushing **(K)** Ball bushing


0 **Spindle:**
(T) Trapezoidal thread **(K)** Ballscrew

0 **Selection of screw:**
(3) right - left hand

0 **Choice of guide body profile:**
(0) Standard **(2)** corrosion-protected screws **(4)** expanded corrosion-protected version (depending on the availability of components)

0 **Choice of carriages:**

(0)



0 **Drive version:**
(0) right (locating bearing side) **(1)** left (non-locating bearing side) **(2)** shaft on both sides

0 **Selection of screw:** Tr = trapezoidal thread Kg = ballscrew

Size	Standard trapezoidal thread	Standard ballscrew
16	**(0)** Tr 10x3	**(0)** Kg 8x2,5

0 **Ballscrew pitch accuracy:** *(only ballscrew)*
(0) 0,05 mm / 300 mm **(2)** 0,025 mm / 300 mm


0 **End play of ball nut:** *(only ballscrew)*
(0) 0,04 mm *(Standard)*, **(1)** < 0,02 mm, **(2)** 2% apply prestress

W	K	T	16	1	0	0	0	0	1	1	1500
			Pos.	1	2	3	4	5	6	7	

Basic length + stroke = total length

Sample ordering code:
WKT 16 with ball bushings, trapezoidal thread, standard body profile, carriage version 0, drive version 0, spindle Tr 10x3, 1268 mm stroke

14.1




QLZE, QSZE, QST/KE, LLZE, LSZE, DSZPVIE
Stainless steel positioning systems

Positioning system QLZE 60, 80, 100

Belt drive

product design award 2011




Fraunhofer IPA TESTED DEVICE Linearreinheit QLZ 80 Report No. BA 0005-171

Function:
This unit consists of a square aluminium profile with an integrated roller guide and is covered by a stainless steel sheet (thickness 0.37mm, material 1.4301). The carriage is driven by a timing belt. Belt tension can be readjusted by a simple screw adjustment device in the carriage. This device can also be used for symmetrical adjustment of two or more linear units running parallel. This linear unit is based on the QLZ and is suitable for application in clean rooms of clean-room classification 1000 (corresponding to US Fed. Standard 209 E).

Fitting position: As required. Max. length 3.000 mm without joints.
Carriage mounting: By T-nuts and bores through the cover.
Unit mounting: By T-nuts and bores through the cover.
Belt performance: HTD with kevlar reinforcement, no backlash when changing direction, repeatability ± 0,1 mm.
Carriage support: In the standard version, the carriage runs on 4 rollers which can be adjusted and serviced at a central servicing position. For longer carriages the number of rollers can be increased.

Forces and torques



Size	60		80		100	
Forces/Torques	static	dynamic	static	dynamic	static	dynamic
F_x (N)	894	800	1900	1800	4000	3800
F_y (N)	399	333	1065	825	1267	1000
F_z (N)	599	433	999	799	1400	1133
M_x (Nm)	10	7	33	26	128	40
M_y (Nm)	40	33	66	53	93	73
M_z (Nm)	26	20	50	40	73	60
All forces and torques related to the following: existing values / table values	$\frac{Fy}{Fy_{dyn}} + \frac{Fz}{Fz_{dyn}} + \frac{Mx}{Mx_{dyn}} + \frac{My}{My_{dyn}} + \frac{Mz}{Mz_{dyn}} \leq 1$					
No-load torque						
Nm	1,0		1,3		2,0	
Speed						
(m/s) max	4		6		7	
Tensile force						
permanent (N)	900		1900		4000	
0,2 s (N)	1000		2090		4300	
Geometrical moments of inertia of aluminium profile						
I_x mm^4	4,3x10^5		16,5x10^5		43,0x10^5	
I_y mm^4	4,8x10^5		18,7x10^5		48,8x10^5	
Elastic modulus N/mm^2	70000		70000		70000	

For life-time calculation of rollers use our homepage.

15.1

Driving torque:


$$M_a = \frac{F * P * S_i}{2000 * \pi} + M_n$$

$$P_a = \frac{M_a * n}{9550}$$

F = force (N)
P = pulley action perimeter (mm)
Si = safety factor 1,2 ... 2
M_n = no-load torque (Nm)
n = rpm pulley (min^{-1})
M_a = driving torque (Nm)
P_a = motor power (KW)

Deflection:

$$f = \frac{F * L^3}{E * I * 192}$$





f = deflection (mm)
F = load (N)
L = free length (mm)
E = elastic modulus 70000 (N/mm^2)
I = second moment of area (mm^4)


BAHR Modultechnik

Positioning system QLZE 60, 80, 100

Dimensions (mm)








V = Q + 100 mm
W = servicing position
*For slide nuts refer to chapter 2.2 page 2

Increasing the carriage length will increase the basic length by the same amount.

Size ❒	Basic length L	A	B	C	D -0,05	E	F/F2	G	N for	M for	P	Q	T	X	Y	Basic weight	Weight per 100 mm
QLZE 60	296	61	60	36	37	61	36/30	80	M 5	M 6	67	152	M 6	24,5	34	4,2 kg	0,48 kg
QLZE 80	400	81	80	50	55	81	50/50	107	M 6	M 8	95	196	M 8	32,5	47	10,6 kg	0,98 kg
QLZE 100	484	101	100	66	62	101	62/58	130	M 10	M 10	107	260	M 10	40	54	18,3 kg	1,37 kg


0 **Choice of guide body profile:**
(0) Version with corrosion-protected components

0 **Choice of carriages:**



Size	Version 0		Version 1		Version 2		Version 3	
	Q	L	Q	L	Q	L	Q	L
60	152	296	192	336	232	376	232	376
80	196	400	246	450	296	500	296	500
100	260	484	320	544	388	604	388	604

2 **Drive version:**



The standard version is supplied shaft pos. 2

Size	Shaft	
	R Key	S ø h6 x length
60	5x5x28	14 x 35
80	6x6x40	18 x 45
100	6x6x40	22 x 45

Belt table

Code No.		Size	Belt	Pulley	
				mm/rev.	Number of teeth
0	**3**	**60**	5M25	130	26
0	**4**	**80**	8M30	176	22
0	**7**	**100**	8M50	224	28

Basic length + stroke = total length

QLZE	80	1	0	0	2	0	4	1	01500
	Pos.	1	2	3	4	5	6	7	

For additional accessories refer to main catalogue chapter 2.2 – 3.2


Sample ordering code:
QLZE80, standard body profile, standard carriage, shaft pos.2, 1100 mm stroke

15.1

Positioning system QSZE 60, 80, 100

Belt drive


product design award 2011



Function:
This unit consists of a square aluminium profile with an integrated ball rail guide and is covered by a stainless steel sheet (thickness 0.37mm, material 1.4301). The carriage is moved by a belt drive. Belt tension can be readjusted by a simple screw adjustment device in the carriage. This device can also be used for symmetrical adjustment of two or more linear units running parallel.

Fitting position: As required. Max. length 3.000 mm without joints.
Carriage mounting: By T-nuts and bores through the cover.
Unit mounting: By T-nuts and bores through the cover.
Belt performance: HTD with kevlar reinforcement, no backlash when changing direction, repeatability ± 0,1 mm.
Carriage support: In the standard version, the carriage runs on two runner blocks which can be adjusted and serviced at a central servicing position. For longer carriages the number of runner blocks can be increased.

Forces and torques



Size	60		80		100	
permitted dyn. Forces*	5000 km	10000 km	5000 km	10000 km	5000 km	10000 km
F_x (N)	894	800	1900	1800	4000	3800
F_y (N)	1410	990	3570	2550	4080	2900
F_z (N)	3520	2500	8500	6050	10300	7270
M_x (Nm)	33	23	107	75	142	101
M_y (Nm)	104	73	310	222	439	311
M_z (Nm)	100	70	296	210	412	292
All forces and torques related to the following: existing values / table values $\frac{Fy}{Fy_{dyn}} + \frac{Fz}{Fz_{dyn}} + \frac{Mx}{Mx_{dyn}} + \frac{My}{My_{dyn}} + \frac{Mz}{Mz_{dyn}} \leq 1$						
No-load torque						
Nm	1,3		1,8		2,3	
Speed						
(m/s) max	5		5		5	
Tensile force						
permanent (N)	900		1900		4000	
0,2 s (N)	1000		2090		4300	
Geometrical moments of inertia of aluminium profile						
I_x mm^4	$4,3x10^5$		$16,5x10^5$		$43,0x10^5$	
I_y mm^4	$4,8x10^5$		$18,7x10^5$		$48,8x10^5$	
Elastic modulus N/mm^2	70000		70000		70000	

* referred to life-time

15.1

Driving torque:


$$M_a = \frac{F*P*S_i}{2000*\pi} + M_n$$

$$P_a = \frac{M_a*n}{9550}$$

F = force (N)
P = pulley action perimeter (mm)
Si = safety factor 1,2 ... 2
M_n = no-load torque (Nm)
n = rpm pulley (min^{-1})
M_a = driving torque (Nm)
P_a = motor power (KW)

Deflection:


$$f = \frac{F*L^3}{E*I*192}$$





f = deflection (mm)
F = load (N)
L = free length (mm)
E = elastic modulus 70000 (N/mm^2)
I = second moment of area (mm^4)

Positioning system QSZE 60, 80, 100

Dimensions (mm)







V = Q + 100 mm
W = servicing position
*For slide nuts refer to chapter 2.2 page 2


Increasing the carriage length will increase the basic length by the same amount.

Size ❒	Basic length L	A	B	C	D -0,05	E	F/F2	G	N for	M for	P	Q	T	X	Y	Basic weight	Weight per 100 mm
QSZE 60	316	61	60	36	37	61	36/30	80	M 5	M 6	67	177	M 6	24,5	34	4,2 Kg	0,64 kg
QSZE 80	440	81	80	50	55	81	50/50	107	M 6	M 8	95	232	M 8	32,5	47	10,6 Kg	1,08 Kg
QSZE 100	504	101	100	66	62	101	62/58	130	M 10	M 10	107	268	M 10	40	54	19,5 Kg	1,61 Kg


0 **Choice of guide body profile:**
(0) Version with corrosion-protected components
(1) Version 0 but with not corrosion-protected guidings

0 **Choice of carriages:**

(0)




(1)



Size	Version 0		Version 1	
	Q	L	Q	L
60	177	316	152	296
80	232	440	196	400
100	268	504	260	494

2 **Drive version:**



The standard version is supplied shaft pos. 2

Size	Shaft	
	R Key	S ø h6 x length
60	5x5x28	14 x 35
80	6x6x40	18 x 45
100	6x6x40	22 x 45

Belt table

Code No.		Size	Belt	Pulley	
				mm/rev.	Number of teeth
0	**3**	**60**	5M25	130	26
0	**4**	**80**	8M30	176	22
0	**7**	**100**	8M50	224	28

Basic length + stroke = total length

QSZE	80	1	0	0	2	0	4	1	01500
	Pos.	1	2	3	4	5	6	7	

For additional accessories refer to main catalogue chapter 2.2 – 3.2

Sample ordering code:
QSZE80, standard body profile, standard carriage, shaft pos2, 1060 mm stroke

15.1

Positioning system QST/KE 60, 80, 100

Spindle drives


product design award 2011



Function:
This unit consists of a square aluminium profile with an integrated ball rail and is covered by a stainless steel sheet (thickness 0.37mm, material 1.4301). The carriage is driven by means of a rotating spindle with leading nut. The openings of the guide body are sealed by a stainless steel cover band to protect the drive from splash water and dust.

Fitting position: As required, max. length 3000mm
Carriage connection: By T-nuts and bores through the cover.
Unit mounting: By the bearing blocks

Forces and torques



Size	QST/KE 60		QST/KE 80		QST/KE 100	
permitted dyn. Forces*	5000 km	10000 km	5000 km	10000 km	5000 km	10000 km
F_x (N)	900	800	2500	2000	5000	4000
F_y (N)	1415	1010	3570	2542	4082	2910
F_z (N)	3525	2510	8500	6050	10300	7360
M_x (Nm)	33	23	107	76	142	101
M_y (Nm)	190	143	604	430	838	597
M_z (Nm)	176	125	550	392	745	532
All forces and torques related to the following: existing values / table values $\frac{Fy}{Fy_{dyn}} + \frac{Fz}{Fz_{dyn}} + \frac{Mx}{Mx_{dyn}} + \frac{My}{My_{dyn}} + \frac{Mz}{Mz_{dyn}} \leq 1$						
No-load torque						
Trapezoidal	18x4/18x8		24x5/24x10		32x6/32x12	
Nm	0,8/0,9		0,8/1,0		2,0/2,2	
Ballscrew	16x5/16x10		25x5/20x20/25x10		32x5/32x10	
Nm	0,5/0,8		0,5/0,9/0,8		1,7/2,1	
Geometrical moments of inertia of aluminium profile						
I_x mm^4	$4,3x10^5$		$14,0x10^5$		$43,0x10^5$	
I_y mm^4	$4,8x10^5$		$16,6x10^5$		$48,8x10^5$	
E-Modulus N/mm^2	70000		70000		70000	

* referred to life-time

15.1

Driving torque:

$$M_a = \frac{F * P * S_i}{2000 * \pi * \mu} + M_n$$

$$P_a = \frac{M_a * n}{9550}$$


F	= force	(N)
P	= thread pitch	(mm)
Si	= safety factor 1,2 ... 2	
M_n	= no-load torque	(Nm)
n	= rpm of screw	(min^{-1})
M_a	= driving torque	(Nm)
μ	= screw efficiency	
P_a	= motor power	(KW)

Efficiency of lead screws:

All ballscrew		0,900
Tr	18x4	0,399
Tr	18x8	0,565
Tr	24x5	0,384
Tr	24x10	0,550
Tr	32x6	0,360
Tr	32x12	0,524

Deflection:

$$f = \frac{F * L^3}{E * I * 192}$$





f = deflection	(mm)
F = load	(N)
L = free length	(mm)
E = elastic modulus 70000	(N/mm^2)
I = second moment of area	(mm^4)


For the diagram for critical speeds of lead screws refer to the main catalog chapter 4.2

Positioning system QST/KE 60, 80, 100

Dimensions (mm)







V = Q + 100 mm
W = servicing position

*For slide nuts refer to chapter 2.2 page 2

Increasing the carriage length will increase the basic length by the same amount.


Size ❒	Basic length L	A	B	C	D -0,05	E	F ❒	G	H	J	K for	N for	P	Q	Shaft R Key	Shaft S Ø h6 x length	T for	U	Basic weight	Weight per 100 mm
QST/KE 60	270	61	36	45,5	37	67,5	32	80	19	18	M6	M6	38	188	3x3x25	10 x 27	M5	61	4,1 kg	0,5 kg
QST/KE 80	350	81	50	62,5	47	89,5	42	107	22,5	40	M10	M8	45	250	5x5x28	14 x 35	M6	81	7,5 kg	0,9 kg
QST/KE 100	410	101	66	75,5	68	112,5	60	130	28,5	50	M10	M10	57	288	6x6x40	22 x 45	M8	101	14,8 kg	1,3 kg

K **Spindle:**
(T) Trapezoidal thread **(K)** Ballscrew

1 **Selection of screw:**
(1) right hand (Standard) **(2)** left hand (Ballscrew by inquiry)

0 **Choice of guide body profile:**
(0) Version with corrosion-protected components
(1) Version 0 but with not corrosion-protected guidings

0 **Choice of carriage:**



Size	Carriage version 1	
	Q	Basic length L
60	255	350
80	336	436
100	383	510

0 **Drive version:**
(0) one shaft (locating bearing side) **(1)** one shaft (non-locating bearing side) **(2)** shaft on both sides

0 **Selection of screw:**

Size	Standard	Multistart screw	Standard	Multistart screw		
	trapezoidal thread standard		ballscrew standard			
60	**(0)** Tr 18x4	**(1)** Tr 18x8	**(0)** Kg 16x5	**(1)** Kg 16x10	**(2)** Kg 16x16	
80	**(0)** Tr 24x5	**(1)** Tr 24x10	**(0)** Kg 25x5	**(1)** Kg 20x20	**(2)** Kg 25x10	**(3)** Kg 25x25***
100	**(0)** Tr 32x6	**(1)** Tr 32x12	**(0)** Kg 32x5	**(1)** Kg 32x10	**(2)** Kg 32x32 *	**(3)** Kg 32x20**
	trapezoidal thread stainless		ballscrew stainless by inquiry			
60	**(4)** Tr 18x4	**(5)** Tr 18x8				
80	**(4)** Tr 24x5	**(5)** Tr 24x10				
100	**(4)** Tr 32x6	**(5)** Tr 32x12				

** Basic and carriage length (L and Q) increase by 47 mm* *** Basic and carriage length (L and Q) increase by 11 mm*
**** Basic and carriage length (L and Q) increase by 42 mm*

0 **Ballscrew pitch accuracy:**
(0) 0,05 mm / 300 mm (Standard) **(2)** 0,025 mm / 300 mm

0 **End play of ball nut:**
(0) 0,04 mm (Standard) **(1)** < 0,02 mm **(2)** 2% apply prestress

1500 Basic length + stroke = total length

QS	K	E	80	1	0	0	0	0	0	01500
			Pos.	1	2	3	4	5	6	7

Sample ordering code:
QSKE80, ballscrew right hand thread, full stainless version, standard carriage, one shaft (locating bearing side), spindle 25x5, 1150 mm stroke.

15.1

Positioning system LLZE 60


Belt drive



Function:
This unit consists of a square aluminium profile with an integrated roller guide and is covered by a stainless steel sheet (thickness 0.37mm, material 1.4301). The carriage is moved by means of an internal rotating toothed belt. On one end there is a pulley block with shaft(s). On the opposite end there is a plate with a retensioning device for the toothed belt.

Fitting position: As required. Max. length 3.000 mm without joints.
Carriage mounting: By tapped holes.
Unit mounting: By T-slots and mounting sets, bores through the cover. The linear axis can be combined with any T-slot profile.
Belt performance: HTD with steel reinforcement, no backlash when changing direction, repeatability ± 0,1 mm.
Carriage support: The carriage runs on 5 rollers which can be adjusted and serviced at each central servicing position. Two grease nipples at the carriage enable relubrication of the positioning system.

Forces and torques



Size	60	
Forces/Torques	static	dynamic
F_x (N)	1073	960
F_y (N)	780	650
F_z (N)	1170	845
M_x (Nm)	20	13
M_y (Nm)	78	65
M_z (Nm)	52	39
All forces and torques related to the following: existing values / table values $\frac{Fy}{Fy_{dyn}} + \frac{Fz}{Fz_{dyn}} + \frac{Mx}{Mx_{dyn}} + \frac{My}{My_{dyn}} + \frac{Mz}{Mz_{dyn}} \leq 1$		
No-load torque		
Nm	0,6	
Speed		
(m/s) max	4	
Tensile force		
permanent (N)	1050	
0,2 s (N)	1150	
Geometrical moments of inertia of aluminium profile		
I_x mm^4	4,47x10^5	
I_y mm^4	5,59x10^5	
Elastic modulus N/mm^2	70000	

For life-time calculation of rollers use our homepage.

Driving torque:


$$M_a = \frac{F * P * S_i}{2000 * \pi} + M_n$$

$$P_a = \frac{M_a * n}{9550}$$

F = force (N)
P = pulley action perimeter (mm)
Si = safety factor 1,2 ... 2
M_n = no-load torque (Nm)
n = rpm pulley (min^{-1})
M_a = driving torque (Nm)
P_a = motor power (KW)

Deflection:


$$f = \frac{F * L^3}{E * I * 192}$$




f = deflection (mm)
F = load (N)
L = free length (mm)
E = elastic modulus 70000 (N/mm^2)
I = second moment of area (mm^4)

Positioning system LLZE 60

Dimensions (mm)



2 cupped-type lubricating nipples for each carriage



Hose connections available on request.




*For slide nuts refer to chapter 2.2 page 2

Size ❐	Basic length L	A ❐	B	C	C1	D -0,05	F1	F2	G	H1	H2	H3	H4	M	P1	P2	P3	Q1	Q2	T	X	Y	Basic weight	Weight per 100 mm
LLZE 60	339	61	26	12,4	18	37	36	30	63	31	93	155	161,5	M6x6	67	7	56	215	175	M6	24,6	34	2,99 kg	0,49 kg


0 **Choice of guide body profile:**
(0) Version with corrosion-protected components

Choice of carriages:

(0)




(1)



Carriage	L	Q1	Q2	H1	H2	H3	H4
Version (0)	339	215	175	31	93	155	161,5
Version (1)	308	184	144	62	---	124	130,5

1 **Drive version:**

1 2 6



Size	Shaft	Feather key
60	Ø 14 h6 x 35	5x5x28

Belt table:

Code No.		Size	Belt	mm/rev.	Number of teeth
0	**3**	**60**	5M30	130	26

LLZE	**60**	**1**	**0**	**0**	**1**	**0**	**3**	**1**	**01500**
Pos.		1	2	3	4	5	6	7	

Basic length + stroke = total length

Sample ordering code:
LLZE60, standard body profile, drive version 1, 1161 mm stroke

Positioning system LSZE 60


Belt drive



Function:
This unit consists of a square aluminium profile with an integrated rail guide and is covered by a stainless steel sheet (thickness 0.37mm, material 1.4301). The carriage is moved by means of an internal rotating toothed belt. On one end there is a pulley block with shaft(s). The opposite front face is provided with a plate containing a tensioning device for the timing belt.

Fitting position: As required. Max. length 3.000 mm without joints.
Carriage mounting: By tapped holes.
Unit mounting: By T-slots and mounting sets, bores through the cover. The linear axis can be combined with any T-slot profile.
Belt performance: HTD with steel reinforcement, no backlash when changing direction, repeatability ± 0,1 mm.
Carriage support: In the standard version the carriage is positioned on two runner blocks which can be readjusted and maintained at each central servicing position. Two grease nipples at the carriage enable relubrication of the positioning system.

Forces and torques



Size	60	
permitted dyn. Forces*	5000 km	10000 km
F_x (N)	894	800
F_y (N)	1410	990
F_z (N)	3520	2500
M_x (Nm)	33	23
M_y (Nm)	104	73
M_z (Nm)	100	70
All forces and torques related to the following: existing values / table values $\frac{Fy}{Fy_{dyn}} + \frac{Fz}{Fz_{dyn}} + \frac{Mx}{Mx_{dyn}} + \frac{My}{My_{dyn}} + \frac{Mz}{Mz_{dyn}} \leq 1$		
No-load torque		
Nm	0,6	
Speed		
(m/s) max	5	
Tensile force		
permanent (N)	900	
0,2 s (N)	1000	
Geometrical moments of inertia of aluminium profile		
I_x mm^4	4,37x10^5	
I_y mm^4	5,78x10^5	
Elastic modulus N/mm^2	70000	

** referred to lifetime*

Driving torque:


$$M_a = \frac{F * P * S_i}{2000 * \pi} + M_n$$

$$P_a = \frac{M_a * n}{9550}$$

F = force (N)
P = pulley action perimeter (mm)
Si = safety factor 1,2 ... 2
M_n = no-load torque (Nm)
n = rpm pulley (min^{-1})
M_a = driving torque (Nm)
P_a = motor power (KW)


Deflection:


$$f = \frac{F * L^3}{E * I * 192}$$




f = deflection (mm)
F = load (N)
L = free length (mm)
E = elastic modulus 70000 (N/mm^2)
I = second moment of area (mm^4)


Positioning system LSZE 60








2 cupped-type lubricating nipples for each carriage



Hose connections available on request.





*For slide nuts refer to chapter 2.2 page 2


Size ❐	Basic lenght L	A ❐	B	C	C1	D Ø -0,05	F1	F2	G	H1	H2	H4	Mxl	P1	P2	P3	Q1	Q2	T	X	Y	Basic weight	Weight per 100 mm
LSZE 60	284	61	25	12,4	18	37	36	30	63	31	93	106	M6x10	67	7	56	160	116	M6	24,6	34	3,3 kg	0,55 kg

0 **Choice of guide body profile:**


(0) Version with corrosion-protected components

Carriage	Q1	L	Q2	H1	H2	H4
Version (0)	160	284	116	31	93	106
Version (1)	140	264	96	32	84	10
Version (2)	100	224	56	31	-	48

0 **Choice of carriages:**



1 **Drive version:**



Belt table:

Code No.		Size	Belt	mm/rev.	Number of teeth
0	**3**	**60**	5M30	130	26

Shaft dimensions:

Size	Shaft	Feather key
60	Ø 14 h6 x 35	5x5x28

LSZE	**60**	**1**	**0**	**0**	**1**	**0**	**3**	**1**	**01500**
Pos.		1	2	3	4	5	6	7	


Basic length + stroke = total length


Sample ordering code:
LSZE60, standard body profile, drive version 1, 1218 mm stroke

15.1

Positioning system DSZPVIE 160, 200

Belt drive






Size	A1	□B1	Ø TK	Ø C1 +0,1 +0,05	D1	E1	F1
DSZPVI 160	46,5	60,1	85	70	56	22	M6
DSZPVI 200	70,5	84,9	120	90	88	32	M8

Function:
This unit consists of a rectangular aluminium profile with 2 integrated rail guides and is covered by a stainless steel sheet (thickness 0.37mm, material 1.4301). The carriage is moved by a belt drive. On the drive side the pulley is beared on the shaft of a planetary gear. Belt tension can be readjusted by a simple screw adjustment at the opposite side of the drive. A special curved aluminium sheet is covering the carriage side. There is only a small gap between carriage and aluminium sheet. Because of its special design it is possible to drive the carriage over the pulley areas. This fact is making the unit very compact.

Fitting position: As required, max. length DSZPVIE 120 / 1600mm, DSZPVIE 160 / 1800mm, DSZPVIE 200 / 2000mm
Carriage mounting: By tapped holes
Unit mounting: By T-slots and mounting sets, bores through the cover.
Belt type: HTD with steel reinforcement, no backlash when changing direction, repeatability ± 0,1 mm.
Carriage support: In the standard version, the carriage runs on 4 runner blocks which can be serviced at a central servicing position. For longer carriages the number of runner blocks can be increased.

Forces and torques



Size	160		200	
permitted dyn. Forces*	5000 km	10000 km	5000 km	10000 km
F_x (N)	1900	1800	4000	3800
F_y (N)	5570	3900	15600	11080
F_z (N)	7050	5020	20600	14600
M_x (Nm)	358	255	1285	915
M_y (Nm)	369	262	1375	980
M_z (Nm)	364	258	1345	960
All forces and torques related to the following: existing values / table values: $\frac{Fy}{Fy_{dyn}} + \frac{Fz}{Fz_{dyn}} + \frac{Mx}{Mx_{dyn}} + \frac{My}{My_{dyn}} + \frac{Mz}{Mz_{dyn}} \leq 1$				
No-load torque				
Nm without cover bands	1,5		2,0	
Nm with cover bands	2,1		2,9	
Speed				
(m/s) max	5		5	
Tensile force				
permanent (N)	1900		4000	
0,2 s (N)	2090		4300	
Geometrical moments of inertia of aluminium profile				
I_x mm⁴	21,32 x 10⁵		48,07 x 10⁵	
I_y mm⁴	123,36 x 10⁵		259,99 x 10⁵	
Elastic modulus N/mm²	70000		70000	

** referred to life-time*

Driving torque:


$$M_a = \frac{F * P * S_i}{2000 * \pi} + M_n$$

$$P_a = \frac{M_a * n}{9550}$$

F = force (N)
P = pulley action perimeter (mm)
Si = safety factor 1,2 ... 2
M_n = no-load torque (Nm)
n = rpm pulley (min^{-1})
M_a = driving torque (Nm)
P_a = motor power (KW)

Deflection:


$$f = \frac{F * L^3}{E * I * 192}$$



f = deflection (mm)
F = load (N)
L = free length (mm)
E = elastic modulus 70000 (N/mm²)
I = second moment of area (mm⁴)

Positioning system DSZPVIE 160, 200

Dimensions (mm)





V = Q + 100 mm
W = servicing position

DS 120 M = M6 x 8
only 8 threaded holes in the carriage
DS 160 M = M8 x 12
DS 200 M = M10 x 12



Optionally available with angular planetary gearbox







Increasing the carriage length will increase the basic length by the same amount.


Size	Basic length L	A	C	D	G	I	K	M for	N for	O	P1	P2	Q	R	S	T	U	Basic weight *without gearbox*	Weight per 100 mm
DSZPVI 160	288	160	90	217,5	108,5	80	107,5	M8	M6	104	3	52,5	188	15	144	80	160	9,83 kg	1,98 kg
DSZPVI 200	349	200	140	251	132,5	100	130,5	M10	M8	128	3	62,5	245	17	180	100	200	18,95 kg	3,71 kg

0 **Choice of guide body profile:**

(0) corrosion-protected components
(1) as above, but with standard components
(2) like version (0), but without cover profile
(3) as above (0), but with standard components


(0) | **(1)**  with cover profile


(2) | **(3)**  without cover profile




belt connection

0 **Choice of carriages:**


(0) 


(1) 

(2) 

Size	Version 1		Version 2	
	Q	L	Q	L
160	203	303	268	368
200	288	423	398	533

0 **Drive version:**

(0) 

(1) 

(2) 

(0) planetary gearbox
(1) angular planetary gearbox
(2) without gearbox

Belt table:

Code-No.		Size	Belt	mm/rev.	Number of teeth
0	**7**	**160**	8M 30	176	22
0	**9**	**200**	8M 50	224	28

DSZPVIE	**160**	**1**	**0**	**0**	**0**	**0**	**7**	**1**	**1500**	— Basic length + stroke = total length
Pos.		1	2	3	4	5	6	7		

Gearbox variants:

Gearbox		DSZPVIE 120	DSZPVIE 160	DSZPVIE 200
Neugart	(0)	PLN 70	PLN 90	PLN 115
	(1)	WPLN 70	WPLN 90	WPLN 115
SEW	(0)	PSKC 221	PSKC 321	PSKC 521
Wittenstein	(0)	SP+060	SP+075	SP+100
	(1)	SK+060	SK+075	SK+100


Sample ordering code:
DSZPVIE 160 with standard body profile, standard carriage, with planetary gearbox, 1211 mm stoke.

15.1

Positioning systems QSTE and DSZPVIE








Roller guide positioning systems
ALLM, ALLZ, ALLZQ, ALLR

Positioning system ALLM 203, 204

Linear motor drive




Function:

This unit consists of an aluminium profile with hardened steel spindles mounted on top of the profile. The carriage, which has internal linear ball bearings that can be adjusted free of play, moves along the unit. The linear-motor ALLM unit is based on the principle of a linear, synchronous AC motor.

The guiding profile is fitted with permanent magnets as stator. The carriage is fitted with the actuator. The magnetic attraction causes a force between carriage and guiding profile also in the absence of current. This force can be used for the initial tension of the bearings. Several carriages can be driven independently on one guiding profile.

Fitting position: As required. Max. length 6.400 mm without joints.
Carriage mounting: By tapped holes.
Unit mounting: By T-slots and mounting sets. The linear axis can be combined with any T-slot profile.
Carriage support: In the standard version, the carriage runs on 8 rollers which can be adjusted and serviced. For longer carriages the number of rollers can be increased. Repeatability ± 0,05 mm.

Forces and torques




Size	ALLM 203		ALLM 204	
Forces/Torques	static	dynamic	static	dynamic
F_y (N)	23000	18400	30000	24000
F_z (N)	11000	8800	16250	13000
M_x (Nm)	1200	950	1870	1500
M_y (Nm) Motor 1	3060	2450	5000	4000
M_z (Nm) Motor 1	6250	5100	9500	7600
M_y (Nm) Motor 2	4010	3210	6520	5220
M_z (Nm) Motor 2	8340	6670	12180	9750
All forces and torques related to the following: existing values / table values $\frac{Fy}{Fy_{dyn}} + \frac{Fz}{Fz_{dyn}} + \frac{Mx}{Mx_{dyn}} + \frac{My}{My_{dyn}} + \frac{Mz}{Mz_{dyn}} \leq 1$				
Transverse force without current				
N	35		45	
Moved mass (g) without motor	43	48	55	62
Speed				
Motor size / weight (kg)	1 / 17,2	2 / 25,5	1 / 17,2	2 / 25,5
(m/s) max	8	8	8	8
Thrust				
permanent (N)	2600	3900	2600	3900
Max. (N)	4000	6010	4000	6010
Geometrical moments of inertia of aluminium profile				
I_x mm^4	2,26 x 10^7		2,98 x 10^7	
I_y mm^4	8,75 x 10^7		10,22 x 10^7	
Elastic modulus N/mm^2	70000		70000	

For life-time calculation of rollers use our homepage.

Deflection:


$$f = \frac{F * L^3}{E * I * 192}$$




f = deflection (mm)
F = load (N)
L = free length (mm)
E = elastic modulus 70000 (N/mm^2)
I = second moment of area (mm^4)

Positioning system ALLM 203, 204

Dimensions (mm)







Increasing the carriage length will increase the basic length by the same amount.

Size	Basic length L motor size 1 / 2	A	B	Cx	Cy	D	F	G	H	K	N for	O	P	Q motor size 1 / 2	R	S	T	Basic weight motor size 1 / 2	Weight per 100 mm
ALLM 203	865/1050	432	88	200	97	260	139,6	210	180,5	200,5	M16	60	20	745/930	96	30	57	110 / 136 kg	5,6 kg
ALLM 204	925/1110	480	102,5	200	97	270	139,6	210	180,5	217,5	M16	60	20	805/990	96	30	57	136 / 163 kg	6,5 kg

3 **Guide rod size:**
(3) ∅=30 **(4)** ∅=40

0 **Choice of guide body profile:**
(0) Standard **(2)** corrosion-protected guide rods and screws
(4) expanded corrosion-protected version (depending on the availability of components)

1 **Measurement system:**
(1) Measurement system LE100 5V Resolution 0.05 **(2)** Measurement system LE100 10,5-30V Resolution 0.05 **(3)** Hall sensor **(4)** Measurement system provided by customer

0 **Motor size:**
(0) Motor size 1
(1) Motor size 2
(2) without Motor, for Motorsize 1
(3) without Motor, for Motorsize 2

Basic length + stroke = total length


ALLM 20	3	0	0	1	0	0	0	0	2000
Pos.		1	2	3	4	5	6	7	

Sample ordering code:
ALLM203, guide rods 30 mm, standard body profile, Measurement system LE100 5V, motor size 1, 1135 mm stroke.

16.1

Positioning system ALLZ 203, 204


Belt drive



Function:
This unit consists of an aluminium profile with hardened steel guide rods mounted on top of the profile. The carriage, which has internal linear ball bearings that can be adjusted free of play, is driven along the guide rods by a timing belt. The pulleys have maintenance-free ball bearings. Opposite the driven side there is an integrated timing-belt tensioner which can be readjusted by 2 screws.

Fitting position: As required. Max. length 6.400 mm without joints.
Carriage mounting: By tapped holes.
Unit mounting: By T-slots and mounting sets. The linear axis can be combined with any T-slot profile.
Carriage support: In the standard version, the carriage runs on 8 rollers which can be adjusted and serviced at a central servicing position. For longer carriages the number of rollers can be increased. Repeatability ± 0,1.
Belt type: HTD with steel reinforcement, no backlash when changing direction, repeatability: ± 0,1 mm.

Forces and torques



Size	ALLZ 203		ALLZ 204	
Forces/Torques	static	dynamic	static	dynamic
F_x (N)	-	5610	-	5610
F_y (N)	23000	18400	30000	24000
F_z (N)	11000	8800	16200	13000
M_x (Nm)	1180	950	1870	1500
M_y (Nm)	1870	1500	3000	2400
M_z (Nm)	3800	3100	5600	4500
All forces and torques related to the following:				
existing values / table values	$\frac{Fy}{Fy_{dyn}} + \frac{Fz}{Fz_{dyn}} + \frac{Mx}{Mx_{dyn}} + \frac{My}{My_{dyn}} + \frac{Mz}{Mz_{dyn}} \leq 1$			
No-load torque				
Nm	4		4	
Speed				
(m/s) max	8		8	
Geometrical moments of inertia of aluminium profile				
I_x mm⁴	2,26 x 10⁷		2,98 x 10⁷	
I_y mm⁴	8,75 x 10⁷		10,22 x 10⁷	
Elastic modulus N/mm²	70000		70000	

For life-time calculation of rollers use our homepage.

16.1


Driving torque:

$$M_a = \frac{F * P * S_i}{2000 * \pi} + M_n$$

$$P_a = \frac{M_a * n}{9550}$$

F = force (N)
P = pulley action perimeter (mm)
Si = safety factor 1,2 ... 2
M_n = no-load torque (Nm)
n = rpm pulley (min^{-1})
M_a = driving torque (Nm)
P_a = motor power (KW)

Deflection:





$$f = \frac{F * L^3}{E * I * 192}$$


f = deflection (mm)
F = load (N)
L = free length (mm)
E = elastic modulus 70000 (N/mm²)
I = second moment of area (mm⁴)

Positioning system ALLZ 203, 204


Dimensions (mm)







ALLZ 204




Increasing the carriage length will increase the basic length by the same amount.

Size	Basic length L	A	B	Cx	Cy	D	E	F	G	Hx	Hy	I	J	K	N for	O	P	Q	R	S	T	U -0,05	V	W	X	Y	Basic weight	Weight per 100 mm
ALLZ 203	792	432	88	200	97	260	300	140	200,5	180,5	124,5	20	14,5	154,5	M16	182	110	460	96	30	57	90	80	10	49,5	50	90 kg	4,0 kg
ALLZ 204	822	460	80	200	97	270	355	145	199	180,5	124,5	20	14,5	165	M16	182	110	490	96	30	57	90	80	10	49,5	50	92 kg	4,9 kg

3 **Guide rod size:**
(3) ∅=30 **(4)** ∅=40

0 **Choice of guide body profile:**
(0) Standard **(2)** corrosion-protected guide rods and screws
(4) expanded corrosion-protected version (depending on the availability of components)

0 **Drive version:**



9 is as 0, but with coupling claws on both sides.



Coupling claw on one side



Standard shaft

The standard version is supplied without shaft. A shaft can be retrofitted by inserting it into the pulley bore and securing it with 2 locking rings.

Belt table

Code No.		Belt	mm/rev.	Number of teeth
0	**7**	8M100	224	28

Shaft dimensions / Coupling claw

Size	Shaft ø h6 x length	Key	Coupling
203	30 x 55	8x7x50	24
204	30 x 55	8x7x50	24


ALLZ 20	3	0	0	0	0	0	7	0	2000
Pos.		1	2	3	4	5	6	7	

Basic length + stroke = total length

Sample ordering code:
ALLZ203, guide rods 30 mm, standard body profile, coupling claw on both side, toothed belt 8M100, 1208 mm stroke.

Positioning system ALLZQ 203


Rack and pinion drive



Function:
This unit consists of an aluminium profile with hardened steel guide rods mounted on top of the profile. The carriage, which has internal linear ball bearings that can be adjusted free of play, is driven along the guide rods by a high precision rack. The rack and pinion system is suitable for highly dynamic servo operation and ideal for lifting movements. The pinion has maintenance-free ball bearings. The rack is lubricated by a toothed felt wheel.

Fitting position: As required. Max. length 6.400 mm without joints.
Carriage mounting: By tapped holes.
Unit mounting: By T-slots and mounting sets. The linear axis can be combined with any T-slot profile.
Carriage support: In the standard version, the carriage runs on 8 rollers which can be adjusted and serviced at a central servicing position. For longer carriages the number of rollers can be increased. Repeatability ± 0,1.
Rack: 8e27 hardened and ground. Repeatability: ± 0,1 mm.

Forces and torques



existing values
table values

Size	ALLZQ 203
Forces/Torques	
F_x (N)	4610
F_y (N)	8700
F_z (N)	8300
M_x (Nm)	1050
M_y (Nm)	1240
M_z (Nm)	2600
All forces and torques related to the following: $\frac{Fy}{Fy_{dyn}} + \frac{Fz}{Fz_{dyn}} + \frac{Mx}{Mx_{dyn}} + \frac{My}{My_{dyn}} + \frac{Mz}{Mz_{dyn}} \leq 1$	
No-load torque	
Nm	3
Driving Tourque	
N	154
Geometrical moments of inertia of aluminium profile	
I_x mm^4	2,26x10^7
I_y mm^4	8,75x10^7
Elastic modulus N/mm^2	70000

For life-time calculation of rollers use our homepage.

16.1


Driving torque:

$$M_a = \frac{F * P * S_i}{2000 * \pi} + M_n$$

$$P_a = \frac{M_a * n}{9550}$$

F = force (N)
P = pulley action perimeter (mm)
Si = safety factor 1,2 ... 2
M_n = no-load torque (Nm)
n = rpm pulley (min^{-1})
M_a = driving torque (Nm)
P_a = motor power (KW)

Deflection:




$$f = \frac{F * L^3}{E * I * 192}$$

f = deflection (mm)
F = load (N)
L = free length (mm)
E = elastic modulus 70000 (N/mm^2)
I = second moment of area (mm^4)

Positioning system ALLZQ 203

Dimensions (mm)



Increasing the carriage length will increase the basic length by the same amount.

Size	Basic length L	A	B	Cx	Cy	D	E	F	G	H	J	K	N for	P	R	S	T	U ±0,05	V	W for	X	Y	Z	Basic weight	Weight per 100 mm
ALLZQ 203	670	432	88	200	97	40	300	139,6	154,6	260	30	200,6	M16	20	96	30	56,9	90	80	M10	120	100	55	71,9 kg	4,9 kg

3 **Guide rod size:**
(3) Ø=30

0 **Choice of guide body profile:**
(0) Standard **(2)** corrosion-protected guide rods and screws
(4) expanded corrosion-protected version (depending on the availability of components)

0 **Drive version:**

Size	Version (0) / (1) I	M	Q1	Q2	L	Version (2) / (3) I	M	Q2	L
203	172,75	516	626	460	670	172,75	294	510	560

Rack and pinion accuracy

Code No.	Modul	Quality	Rack accuracy	Material	Marks
0	3	10	0,091 mm/300 mm	C45	Hardened teeth
1	3	9	0,065 mm/300 mm	C45	Milled teeth
2	3	8	0,046 mm/300 mm	X8CrNiS18-9	Milled teeth

Shaft dimensions			
Shaft ø h6 x length	Key	Pinion mm/U	Pinion Modul
30 x 55	8x7x50	197,92	3

Basic length + stroke = total length


ALLZQ 20	3	0	0	0	0	0	0	0	2000
Pos.		1	2	3	4	5	6	7	

Sample ordering code:
ALLZQ203, guide rods 30 mm, standard body profile, coupling position 0, rack accuracy 0,091 mm/300 mm, 1330 mm stroke.

16.1

Positioning system ALLR 203, 204


Roller guide unit without drive



Function:
This unit consists of an aluminium profile with hardened steel spindles mounted on top of the profile. The carriage has internal linear ball bearings that can be adjusted free of play. The unit is without drive.

Fitting position: As required. Max. length 6.400 mm without joints.
Carriage mounting: By tapped holes.
Unit mounting: By T-slots and mounting sets. The linear axis can be combined with any T-slot profile.
Carriage support: In the standard version, the carriage runs on 8 rollers which can be adjusted and serviced at a central servicing position. For longer carriages the number of rollers can be increased.

Forces and torques




Size	ALLR 203		ALLR 204	
Forces/Torques	static	dynamic	static	dynamic
F_y (N)	23000	18400	30000	24000
F_z (N)	11000	8800	16250	13000
M_x (Nm)	1200	950	1870	1500
M_y (Nm)	1870	1500	3000	2400
M_z (Nm)	3800	3100	5600	4500
All forces and torques related to the following: existing values / table values $\frac{Fy}{Fy_{dyn}} + \frac{Fz}{Fz_{dyn}} + \frac{Mx}{Mx_{dyn}} + \frac{My}{My_{dyn}} + \frac{Mz}{Mz_{dyn}} \leq 1$				
Geometrical moments of inertia of aluminium profile				
I_x mm^4	2,26 x 10^7		2,98 x 10^7	
I_y mm^4	8,75 x 10^7		10,22 x 10^7	
Elastic modulus N/mm^2	70000		70000	

For life-time calculation of rollers use our homepage.

16.1

Deflection:


$$f = \frac{F * L^3}{E * I * 192}$$




f = deflection (mm)
F = load (N)
L = free length (mm)
E = elastic modulus 70000 (N/mm^2)
I = second moment of area (mm^4)

Positioning system ALLR 203, 204


Dimensions (mm)





ALLR 204





Increasing the carriage length will increase the basic length by the same amount.

Size	Basic length L	A	B	Cx	Cy	D	F	G	H	K	N for	O	P	Q	R	S	T	Basic weight	Weight per 100 mm
ALLR 203	580	432	88	200	97	260	139,6	200,5	180,5	154,5	M16	60	20	460	96	30	57	64 kg	3,9 kg
ALLR 204	610	460	80	200	97	270	139,6	199	180,5	165	M16	60	20	490	96	30	57	65 kg	4,8 kg

3 **Guide rod size**
(3) ∅=30 **(4)** ∅=40

0 **Choice of guide body profile:**
(0) Standard **(2)** corrosion-protected guide rods and screws
(4) expanded corrosion-protected version (depending on the availability of components)


Basic length + stroke = total length


ALLR20	3	0	0	0	0	0	0	0	2000
Pos.		1	2	3	4	5	6	7	

Sample ordering code:
ALLR203, guide rods 30 mm, standard body profile, 1420 mm stroke.

16.1


Positioning system ALLM/Z





SLTZA/SLTR heavy duty traverse with rack and pinion drive and without


Positioning system SLTZA 30, 50



Function:
The guide body consists of an aluminium square profile with a guide rod clamped into it on the upper side free of play. A roller pack containing 2 rollers moves along the guide body. The roller pack is secured against derailing by means of a lateral claw. The system is rack and pinion driven. The number of roller packs is limited due to the length. The system may be extended according to your needs by means of the connecting brackets available as accessories.

Fitting position: horizontal, any max. length
Unit mounting: by T-Nuts and mounting profiles at the side of the profile

Forces and torques



Size	SLTZA 30	SLTZA 50
Forces / Torques	static	static
F_z (N)	8400	17500
No-load torque		
Nm	3	4
Geometrical moments of inertia of aluminium profile		
I_x mm^4	2,10 x 10^7	8,70 x 10^7
I_y mm^4	3,00 x 10^7	10,80 x 10^7
Elastic modulus N/mm^2	70000	70000

17.1

Driving torque:


$$M_a = \frac{F * P * S_i}{2000 * \pi} + M_n$$

$$P_a = \frac{M_a * n}{9550}$$

F	= force	(N)
P	= pulley action perimeter	(mm)
Si	= safety factor 1,2 ... 2	
M_n	= no-load torque	(Nm)
n	= rpm pulley	(min^{-1})
M_a	= driving torque	(Nm)
P_a	= motor power	(KW)

Deflection:


$$f = \frac{F * L^3}{E * I * 192}$$




f = deflection	(mm)
F = load	(N)
L = free length	(mm)
E = elastic modulus 70000	(N/mm^2)
I = second moment of area	(mm^4)


Positioning system SLTZA 30, 50

Dimensions (mm)





Size ❐	Basic length L	B	C	CC	D -0,05	E	EE	F	G	J	O	P	Q	T	U	W	Basic weight	Weight per 100 mm
SLTZA 30	340	160	210	184	68	23	36	42	75	12	M10	25	290	M8	115	230	19,8 kg	2,00 kg
SLTZA 50	410	186	250	215	80	35	50	48	88	10	M12	30	350	M8	160	270	40,5 kg	4,00 kg



A	H	I	K	M	N	V	X	Y	Shaft ∅ h6 x length	Key	Pinion	
											mm/rev.	Modul
80	24	22	206	M8	28	188	40	56	22 x 35	6 x 6 x 30	201,1	2
120	30	30	277,5	M10	31,5	236,5	53,5	76	22 x 35	6 x 6 x 30	197,9	3

ZA **Drive variation:**
(ZA) rack and pinion driven

50 **Guide rod size / size**
∅=30 mm (SLTZA30), ∅=50 mm (SLTZA50)

0 **Choice of guide body profile:**
(0) Standard **(2)** corrosion-protected guide rods and screws **(4)** expanded corrosion-protected version (depending on the availability of components) **(9)** corrosion-protected guide rods, rollers, screws and rack

2 **Choice of carriage***
(0) without **(1)** 1 carriage **(2)** 2 carriages **(3)** 3 carriages **(4)** 4 carriages
*= each carriage has got 2 rollers

2 **Carriage drives**
(0) without **(1)** 1 drive **(2)** 2 drives **(3)** 3 drives **(4)** 4 drives

Rack and pinion accuracy


Code No.	Quality	Rack accuracy	Material	Marks
0	10	0,091 mm/300 mm	C45	Hardened teeth
1	9	0,065 mm/300 mm	C45	Milled teeth

910 Basic length + stroke = total length

SLT	ZA	50	0	0	2	2	0	0	0	00910
	Pos.	1	2	3	4	5	6	7		

Sample ordering code:
SLTZA 50, 50 mm guide rods, Standard profil, 2 carriages, 2 drives, rack and pinion accuracy 0,091 mm/300 mm, Stroke 500 mm


Positioning system SLTR 30, 50



Function:
The guide body consists of an aluminium square profile with a guide rod clamped into it on the upper side free of play. A roller pack containing 2 rollers moves along the guide body. The roller pack is secured against derailing by means of a lateral claw. The system is not driven. The number of roller packs is limited due to the length. The system may be extended according to your needs by means of the connecting brackets available as accessories.

Fitting position: horizontal, any max. length
Unit mounting: by T-Nuts and mounting profiles at the side of the profile

Forces and torques




Size	SLTR 30	SLTR 50
Forces / Torques	static	static
F_z (N)	8400	17500
Geometrical moments of inertia of aluminium profile		
I_x mm^4	2,10 x 10^7	8,70 x 10^7
I_y mm^4	3,00 x 10^7	10,80 x 10^7
Elastic modulus N/mm^2	70000	70000

17.1

Deflection:


$$f = \frac{F * L^3}{E * I * 192}$$




f = deflection (mm)
F = load (N)
L = free length (mm)
E = elastic modulus 70000 (N/mm^2)
I = second moment of area (mm^4)

Positioning system SLTR 30, 50

Dimensions (mm)



Size ❐	Basic length L	B	C	CC	E	EE	J	O	P	Q	U	W	Basic weight	Weight per 100 mm
SLTR 30	340	160	210	184	23	36	12	M10	25	290	115	230	14,5 kg	1,58 kg
SLTR 50	410	186	250	215	35	50	10	M12	30	350	160	270	33,0 kg	3,37 kg



Size ❐	A	H	I	K	M	N	X	Y
SLTR 30	80	24	22	206	M8	28	40	56
SLTR 50	120	30	30	277,5	M10	31,5	53,5	76

R **Drive variation:**
(R) without drive

50 **Guide rod size / size**
Ø=30 mm (SLTR30), Ø=50 mm (SLTR50)

0 **Choice of guide body profile:**
(0) Standard **(2)** corrosion-protected guide rods and screws
(4) expanded corrosion-protected version (depending on the availability of components)

2 **Choice of carriage***
(0) without **(1)** 1 carriage **(2)** 2 carriages **(3)** 3 carriages **(4)** 4 carriages
*= each carriage has got 2 rollers

910 Basic length + stroke = total length

SLT	R	50	0	0	2	0	0	0	0	00910
		Pos. 1	2	3	4	5	6	7		

Sample ordering code:
SLTR 50, 50 mm guide rods, Standard profil, 2 carriages, Stroke 500 mm

17.1

Combination of different systems



Jointing block SLTR/SLTZA




Code-No.	Type	A	B	C	D	E	H
030703	**SLT 30**	80	160	77	65	100	105
030705	**SLT 50**	120	200	93,5	79	135	145





Spare parts


Complete carriage EG



Additional complete carriage with V-slides and end plates.

Code-No.	Type	Q Standard	Q max.
04532	EG 30	82	1000
04542	EG 40	117	1000
04562	EG 60	165	1000
04582	EG 80	193	1000

Complete carriage EL/ML




Additional complete carriage with rollers, eccentrics and wiper end plates for free rolling.

	Code-No.	Type	Q Standard	Q max.
without Slider 2)	04531	EL 30	82	3000
	04541	EL 40	122	3000
	04561	EL/ML 60	168	3000
	04560	EL/ML 60S	194	3000
	04581	EL/ML 80	194	3000
	04580	EL/ML 80S	214	3000
	04511	EL/ML 100	300	2000
	04521	EL 125	365	2000

	Code-No.	Type	Q Standard	Q max.
with Slider 1)	045311	EL 30	82	3000
	045411	EL 40	122	3000
	045611	EL 60	168	3000
	045601	EL 60S	194	3000
	045811	EL 80	194	3000
	045801	EL 80S	214	3000
	045111	EL 100	300	2000
	045211	EL 125	365	2000

1) ELT/K, ELVZ, ELHZ
2) ELZ, ELZT, ELZU, ELZA, ELZQ, MLZ


Complete carriage UL



Carriage with rollers, eccentrics and end plates.

Code-No.	Type	A	Q
045471	UL 40	40	146
045472	UL 40	20	146
045671	UL 60	60	194
045672	UL 60	29	194
045871	UL 80	80	260
045872	UL 80	42	260


Complete carriage DL



Standardcarriage with 2x4 rollers, eccentrics and end plates.
Different versions by inquiry.

Code-No.	Type	Q Standard	Q max.
04591	DL 120	156	3000
04590	DL 160	200	3000
04592	DL 200	270	3000

Complete carriage DS




Carriage with four runner blocks and end plates.
Different versions by inquiry.

Code-No.	Type	Q Standard	Q max.
045700	DS 120	156	3000
045710	DS 160	200	3000
045720	DS 200	270	3000

Spare parts


Complete carriage DL_P



Additional complete carriage with rollers, eccentrics and wiper end plates for free rolling. Different versions by inquiry.

Code-Nr.	Typ	$Q_{Standard}$	$Q_{max.}$
045904	**DL 120 P**	152	3000
045905	**DL 160 P**	196	3000
045906	**DL 200 P**	260	3000


Complete carriage DS_P



Carriage with four runner blocks and end plates.
Different versions by inquiry.

Code-Nr.	Typ	$Q_{Standard}$	$Q_{max.}$
045731	**DS 120 P**	152	3000
045733	**DS 160 P**	196	3000
045735	**DS 200 P**	248	3000


Carriage QL



Carriage with rollers, eccentrics and end plates.
Different versions by inquiry.

Code-Nr.	Type	$Q_{Standard}$	Number of rollers
04593A	**QL 60**	152	4
04593B	**QL 60**	192	5
04593C	**QL 60**	232	2x3
04594A	**QL 80**	196	4
04594B	**QL 80**	246	5
04594C	**QL 80**	296	2x3
04595A	**QL 100**	260	4
04595B	**QL 100**	320	5
04595C	**QL 100**	388	2x2
04595D	**QL 100**	388	2x3


Carriage QS



Carriage with 2 runner blocks and end plates.
Different versions by inquiry.

Code-Nr.	Type	$Q_{Standard}$	Number of Runnerblocks
045970	**QS 60**	177	2
045973	**QS 60**	242	3
045980	**QS 80**	232	2
045983	**QS 80**	312	3
045990	**QS 100**	268	2
045993	**QS 100**	362	3
04550	**QS 125**	300	2
045502	**QS 125**	365	3

Carriage QST/K




Carriage with 2 runner blocks and end plates without leading nut.
Different versions by inquiry.


Code-Nr.	Type	$Q_{Standard}$	$Q_{max.}$
045974	**QST/K 60**	188	3000
045984	**QST/K 80**	250	3000
045997	**QST/K 100**	288	3000

Carriage LLZ / LLR / CLLZ / CLLT/K

LLZ
CLLZ



LLR
CLLT/K




Carriage with 5 or 4 rollers.
Standard version: 5 rollers


Code-No.	Type		Q1	Q2
045760-5	**LLZ / CLLZ 60**	5 rollers	215	175
045780-5	**LLZ / CLLZ 80**	5 rollers	320	251
045760-4	**LLZ / CLLZ 60**	4 rollers	184	144
045780-4	**LLZ / CLLZ 80**	4 rollers	260	191
045761-5	**LLR / CLLT/K 60**	5 rollers	–	175
045781-5	**LLR / CLLT/K 80**	5 rollers	–	251
045761-4	**LLR / CLLT/K 60**	4 rollers	–	144
045781-4	**LLR / CLLT/K 80**	4 rollers	–	191

Carriage LSZ 60 / LSR 60

LSZ




LSR



Carriage with 2 or 1 runner blocks.

Code-No.	Type	Runner blocks	Q1	Q2
045762-1	**LSZ 60**	2	160	116
045762-2	**LSZ 60**	2	140	96
045762-3	**LSZ 60**	1	100	56
045782-1	**LSZ 80**	2	219	149
045782-2	**LSZ 80**	2	204	134
045782-3	**LSZ 80**	1	146,5	76,5
045763-1	**LSR 60**	2	–	116
045763-2	**LSR 60**	2	–	96
045763-3	**LSR 60**	1	–	56
045783-1	**LSR 80**	2	–	149
045783-2	**LSR 80**	2	–	134
045783-3	**LSR 80**	1	–	76,5


Carriage complete GG / GDG



Complete carriage with slides and end plates.

Code-No.	Type	$Q_{Standard}$	$Q_{max.}$
045825	**GG / GDG 90**	170	400

V-slide EG



Made of low-wear plastic with good sliding characteristics.
2 pieces per carriage.

Code-No.	Type	A	$B_{max.}$	C	D
04233	**30**	9,3	1.000	-	17,6
04243	**40**	8	1.000	9	13
04263	**60**	10	1.000	16	21
04283	**80**	14	1.000	22	29

Made of low-wear plastic with good sliding characteristics.
4 pieces per carriage.

Code-No.	Type	L
042835	**G 90**	45


Carriage roller



Standard roller. Stainless steel upon request.

Code-Nr.	Type	Name
04000	**EL 30**	LFR 687-2Z
04001	**EL 40 / DL 120 / QL 60 CLL 60 / LL 60**	LFR 608-2Z
04002	**EL/ML 60 / DL 160 / QL 80**	LR 10
04039	**EL/ML 60S / DL 200 / QL 100 LL 80**	LFR 5302-2Z
04003	**EL/ML 80**	LR 12
04038	**EL/ML 80S**	LFR 5202-12-2RS
04004	**EL/ML 100**	LFR 5204-16-2RS
04009	**EL 125**	LFR 5206-20-2Z

Carriage roller block DL / QL





Made of aluminium, complete with rollers, eccentric and screws.

Code-No.	Type	Standard	By inqury
04100	**DL 120**	4 rollers	3; 5; 2x3 rollers
04110	**DL 160**	4 rollers	3; 5; 2x3 rollers
04115	**DL 200**	4 rollers	3; 5; 2x3 rollers
04116	**QL 60**	4 rollers	5; 2x2; 2x3 rollers
04117	**QL 80**	4 rollers	5; 2x2; 2x3 rollers
04119	**QL 100**	4 rollers	5; 2x2; 2x3 rollers

* for outside fixed roller
** for inner movable roller

Runner block for DS / QS / LS






Code-No.	Type
04150	**QS 60**
04152	**QS 80**
04154	**QS 100**
04155	**QS 125**
04156	**DS 120**
04157	**DS 160 / LS 60**
04158	**DS 200**
04159	**LS 80**

Eccentric EL/ML

40, 60




30, 60S, 80, 80S, 100, 125

Eccentric made of stainless steel with mounting accessories, screw, shims and safety washer.

Code-No.	Type	For roller
04050	**EL 30**	LFR 687-2Z
04051	**EL 40**	LFR 608-2Z
04052	**EL/ML 60**	LFR 5201-2Z
040521	**EL/ML 60S**	LFR 5302-2Z
04053	**EL/ML 80**	LFR 5201-12-2Z
04049	**EL/ML 80S**	LFR 5202-12-2RS
04054	**EL 100**	LFR 5204-16-2RS
04055	**EL 125**	LFR 5206-20-2Z


Eccentric DL / QL / LL / CLL

QL **



QL *

DL



LLZ ** / CLL **


Eccentric made of stainless steel with mounting set, screw, shims and safety washer. The front side has an embossed marking to enable uniformly adjustment of rollers.

Code-No.	Type	For roller
04057	**DL 120**	LFR 608-2Z
04058	**DL 160**	LFR 5201-2Z
04059	**DL 200**	LR 5302-2Z
06060	**QL 60***	LFR 608-2Z
06061	**QL 60****	LFR 608-2Z
06080	**QL 80***	LFR 5201-2Z
06081	**QL 80****	LFR 5201-2Z
06010	**QL 100 / LL / CLL 80***	LR 5302-2Z
06011	**QL 100 / LL / CLL 80****	LR 5302-2Z
06060	**LL / CLL 60***	LFR 608-2Z
06065	**LL / CLL 60****	LFR 608-2Z


* for outside fixed roller
** for inner movable roller
For arrangement of the different rollers see „carriage roller block" above.

Wiper end plate DL /DS - QL / QS


DL | DS




DL_P | DS_P



DLT/K | DST/K



QL | QS



Code-No.	Type	D	Material
04211	**DL/DS 120**	8	ABS
04212	**DL/DS 160**	10	ABS
04213	**DL/DS 200**	15	ABS
042111	**DLT/K / DST/K 120**	8	ABS
042121	**DLT/K / DST/K 160**	10	ABS
042131	**DLT/K / DST/K 200**	15	ABS
042110	**DL_P/DS_P 120**	6	ABS
042120	**DL_P/DS_P 160**	8	ABS
042130	**DL_P/DS_P 200**	8	ABS
04267	**QL/QS 60**	6	ABS
04287	**QL/QS 80**	8	ABS
04217	**QL/QS 100**	10	ABS
04218	**QL/QS 125**	15	AL

Spare parts

Tool for eccentric adjustment





Fix tool			Adjust tool	
Type	**Code-No.**	**Dimension**	**Code-No.**	**Dimension**
EL 30	**09019**	T 10	**09030**	LK 9,5 ø 1,3
EL 30	**09020**	SW 2	**09030**	LK 9,5 ø 1,3
EL 40	**09021**	SW 4	**09022**	SW 5
EL 60	**09022**	SW 5	**09023**	SW 6
EL 60S	**09023**	SW 6	**09036**	LK 20 ø 2
EL 80	**09022**	SW 5	**09031**	LK 15 ø 2
EL 80S	**09023**	SW 6	**09036**	LK 20 ø 2
EL 100	**09023**	SW 6	**09032**	LK 24 ø 3
EL 125	**09024**	SW 8	**09033**	LK 32 ø 4

Fix tool			Adjust tool	
Type	**Code-No.**	**Dimension**	**Code-No.**	**Dimension**
DL 120	**09025**	SW 3	**09034**	LK 10,5 ø 1,3
DL 160	**09021**	SW 4	**09031**	LK 15 ø 2
DL 200	**09023**	SW 6	**09036**	LK 20 ø 2
LL 60 QL 60	**09038**	LK 8 ø 1,5	**09026**	SW 2,5
	09021	SW 4	**09022**	SW 5
QL 80	**09037**	LK 10 ø 2	**09025**	SW 3
	09022	SW 5	**09023**	SW 6
LL 80 QL 100	**09035**	LK 13 ø 2,5	**09021**	SW 4
	09023	SW 6	**09036**	LK 20 ø 2

End plates EG

Material ABS.




without slider		
Code-No.	**Type**	**A**
04241	**EG 40**	5
04261	**EG 60**	6
04281	**EG 80**	6

with slider		
Code-No.	**Type**	**A**
04246	**EG 40**	5
04266	**EG 60**	6
04286	**EG 80**	6

with slider and output for grease nipple		
Code-No.	**Type**	**A**
042661	**EG 60**	6
042861	**EG 80**	6

Wiper end plate complete for EL/ML

Material ABS.



without slider [1]		
Code-Nr.	**Type**	**A**
04230	**EL 30**	6
04240	**EL 40**	11
04260	**EL/ML 60**	12
04268	**EL/ML 60S**	12
04280	**EL/ML 80**	12
04288	**EL/ML 80S**	12
04210	**EL/ML 100**	15
04220	**EL 125**	15

with slider [2]		
Code-Nr.	**Type**	**A**
04234	**EL 30**	6
04244	**EL 40**	11
04264	**EL 60**	12
04269	**EL 60S**	12
04284	**EL 80**	12
04289	**EL 80S**	12
04214	**EL100**	15
04224	**EL125**	15

with slider and output for grease nipple [3]		
Code-Nr.	**Type**	**A**
042641	**EL 60**	12
042691	**EL 60S**	12
042841	**EL 80**	12
042891	**EL 80S**	12
042141	**EL 100**	15
042241	**EL 125**	15

1) ELZ, ELZT, ELZU, ELZA, ELZQ, MLZ 2) ELT/K, ELVZ, ELHZ 3) ELT/K

Slider for ELT / ELK | Slider set for DLT/K - DST/K






When changing the cover band, it is necessary to replace the slide.

ELT / ELK	
Code-No.	**Type**
03132	**EL 30**
03142	**EL 40**
03162	**EL 60**

DLT/K - DST/K	
Code-No.	**Type**
03164	**120**
03184	**160**
03114	**200**

Cover band




Spring steel (stainless steel)

Code-No.	Type	A x B
01020....	**EL/EG 30**	8 x 0,15
01021....	**EL/EG 40/60/80 DL/DS 120**	13,5 x 0,3
01026....	**DL/DS 160**	17,3 x 0,3
01022....	**EL 100/125 DL/DS 200**	22 x 0,3
01023	**QST/K 60**	24 x 0,3
01024	**QST/K 80**	32,3 x 0,3
01025	**QST/K 100**	38,5 x 0,3

Code-No.	length in mm
01026	2300

Sample ordering code:
Cover band 17,3 x 0,3 2.300 mm long.

Jointing plate for closed carriage






Aluminium plate with connection bores.

Code-No	Type	A	B	C
03045	**EG 40**	70	70	8
03065	**EG 60**	100	98	8
03085	**EG 80**	140	140	8
03036	**EL 30**	70	52	6
03046	**EL 40**	100	70	8
03066	**EL/ML 60**	144	98	8
03067	**EL/ML 60S**	170	106	10
03086	**EL/ML 80**	170	140	8
03087	**EL/ML 80S**	190	142	10
03016	**EL 100**	230	180	8
03026	**EL 125**	295	215	12

Spare parts

Guide rod




Code-No.	Type	Ø	Material	Hardness
04131....	**EL/EG 30**	5 $_{h6}$	Cf 53	HRC 62
04132....	**EL/EG 30**	5 $_{h6}$	x 90 CrMoV18	HRC 56
04141....	**EL 40 / DL 120 LL 60 / CLL 60 QL 60**	6 $_{h6}$	Cf 53	HRC 62
04142....	**EL 40 / DL 120 LL 60 / CLL 60 QL 60**	6 $_{h6}$	x 90 CrMoV18	HRC 56
04161....	**EL 60 (S) DL 160/200 LL 80 / CLL 80 QL 80/100**	10 $_{h6}$	Cf 53	HRC 62
04162....	**EL 60 (S) DL 160/200 QL 80/100**	10 $_{h6}$	x 90 CrMoV18	HRC 56
04181....	**EL 80 (S)**	12 $_{h6}$	Cf 53	HRC 62
04182....	**EL 80 (S)**	12 $_{h6}$	x 90 CrMoV18	HRC 56
04111....	**EL 100**	16 $_{h6}$	Cf 53	HRC 62
04112....	**EL 100**	16 $_{h6}$	x 90 CrMoV18	HRC 56
04113....	**EL 125**	20 $_{h6}$	Cf 53	HRC 62
04114....	**EL 125**	20 $_{h6}$	x 90 CrMoV18	HRC 56

Code-No.	length in mm
04131	2000

Sample ordering code:
Guiding rod steel ø 5 2.000 mm long.

Guide rail



Code-No.	Type	Size
04147-2	**Q 60**	15
04148-2	**Q 80**	20
04149-2	**Q 100**	25
04146-2	**Q 125**	30
04156-2	**D 120**	12
04157-2	**D 160**	15
04158-2	**D 200**	25
04147-2	**L 60**	15
04148-2	**L 80**	20

Code-No.	length in mm
04146-2	2000

Sample ordering code:
Guide rail 2.000 mm long.

Trapezoidal spindle



Code-No.	Type	Pitch	Unit length L max.
04609....	**EL/EG 30**	10x03 R	1.500 mm
04629....	**EL/EG 30**	10x03 L	1.500 mm
04600....	**EL/EG 40**	18x0	3.000 mm
04620....	**EL/EG 40**	18x04 L	3.000 mm
04640....	**DL/DS 120 / QS 60**	18x04 R	3.000 mm
04650....	**DL/DS 120 / QS 60**	18x04 L	3.000 mm
04601....	**EL/EG 40**	18x08 R	3.000 mm
04621....	**EL/EG 40**	18x08 L	3.000 mm
04641....	**DL/DS 120 / QS 60**	18x08 R	3.000 mm
04651....	**DL/DS 120 / QS 60**	18x08 L	3.000 mm
04602....	**EL/EG 60**	24x05 R	3.000 mm
04622....	**EL/EG 60**	24x05 L	3.000 mm
04642....	**DL/DS 160 / QS 80**	24x05 R	3.000 mm
04652....	**DL/DS 160 / QS 80**	24x05 L	3.000 mm
04603....	**EL/EG 60**	24x10 R	3.000 mm

Code-No.	Type	Pitch	Unit length L max.
04623....	**EL/EG 60**	24x10 L	3.000 mm
04643....	**DL/DS 160 / QS 80**	24x10 R	3.000 mm
04643....	**DL/DS 160 / QS 80**	24x10 L	3.000 mm
04604....	**EL/EG 80(S)**	28x05 R	3.000 mm
04624....	**EL/EG 80(S)**	28x05 L	3.000 mm
04605....	**EL/EG 80(S)**	28x10 R	3.000 mm
04625....	**EL/EG 80(S)**	28x10 L	3.000 mm
04606....	**EL / QS 100 DL/DS 200**	32x06 R	4.500 mm
04626....	**EL / QS 100 DL/DS 200**	32x06 L	3.000 mm
04607....	**EL / QS 100 DL/DS 200**	32x12 R	3.000 mm
04627....	**EL / QS 100 DL/DS 200**	32x12 L	3.000 mm
04630....	**EL 125**	40x07 R	4.000 mm
04631....	**EL 125**	40x07 L	3.000 mm
04632....	**EL 125**	40x14 R	3.000 mm
04633....	**EL 125**	40x14 L	3.000 mm

Code-No.	unit length in mm
04603	1000

Sample ordering code:
Trapezoidal spindle Tr 24x10 right, unit length 1000 mm.

Trapezoidal screw made of RG 7



Code-No.	Type	Pitch
04332	**EL/EG 30**	10x03 R
04333	**EL/EG 30**	10x03 L
04340	**EL/EG 40 / DL/DS 120 / QS 60**	18x04 R
04341	**EL/EG 40 / DL/DS 120 / QS 60**	18x04 L
04342	**EL/EG 40 / DL/DS 120 / QS 60**	18x08 R
04343	**EL/EG 40 / DL/DS 120 / QS 60**	18x08 L
04360	**EL/EG 60 / DL/DS 160 / QS 80**	24x05 R
04361	**EL/EG 60 / DL/DS 160 / QS 80**	24x05 L
04362	**EL/EG 60 / DL/DS 160 / QS 80**	24x10 R
04363	**EL/EG 60 / DL/DS 160 / QS 80**	24x10 L
04380	**EL/EG 80(S)**	28x05 R

Code-No.	Type	Pitch
04381	**EL/EG 80(S)**	28x05 L
04382	**EL/EG 80(S)**	28x10 R
04383	**EL/EG 80(S)**	28x10 L
04310	**EL / QS 100 / DL/DS 200**	32x06 R
04311	**EL / QS 100 / DL/DS 200**	32x06 L
04312	**EL / QS 100 / DL/DS 200**	32x12 R
04313	**EL / QS 100 / DL/DS 200**	32x12 L
04320	**EL 125**	40x07 R
04321	**EL 125**	40x07 L
04322	**EL 125**	40x14 R
04323	**EL 125**	40x14 L

Ballscrew spindle



Code-No.	Type	Pitch	Unit length L max
04610....	**EL/EG 30**	Kg 08x2,5 R	2.000 mm
04611....	**EL/EG 40**	Kg 16x05 R	3.000 mm
04612....	**EL/EG 40**	Kg 16x10 R	3.000 mm
04613....	**EL/EG 60**	Kg 20x20 R	3.000 mm
04614....	**EL/EG 60**	Kg 25x05 R	3.000 mm
04615....	**EL/EG 60**	Kg 25x10 R	3.000 mm
04631....	**EL/EG 60**	Kg 20x05 L	3.000 mm
04661....	**DL/DS 120 / QS 60**	Kg 16x05 R	3.000 mm
04661H	**CLL 60**	Kg 16x05 R	3.000 mm
04662....	**DL/DS 120 / QS 60**	Kg 16x10 R	3.000 mm
04662H	**CLL 60**	Kg 16x10 R	3.000 mm
04663....	**DL/DS 120 / QS 80 DL/DS 160**	Kg 20x20 R	3.000 mm
04667....	**DL/DS 120 / QS 60**	Kg 16x16 R	3.000 mm
04667H	**CLL 60**	Kg 16x16 R	3.000 mm

Code-No.	Type	Pitch	Unit length L max
04664....	**DL/DS 120 DL/DS 160 QS 80**	25x05R	3.000 mm
04665....	**DL/DS 120 DL/DS 160 QS 80**	25x10 R	3.000 mm
04616....	**EL/EG 80(S)**	25x25 R	3.000 mm
04666....	**DL/DS 120 DL/DS 160**	25x25 R	3.000 mm
04617....	**EL/EG 80(S) EL/QS 100 DL/DS 200**	32x05 R	3.000 mm
04684....	**EL/EG 80(S) EL/QS 100 DL/DS 200**	32x05 L	3.000 mm
04618....	**EL/EG 80(S) EL/QS 100 DL/DS 200**	32x10 R	3.000 mm
04683....	**EL 100 DL/DS 200**	32x20 R	3.000 mm
04619....	**EL 100 DL/DS 200**	32x32 R	3.000 mm
04634....	**EL 125**	40x10 R	3.000 mm
04635....	**EL 125**	40x20 R	3.000 mm
04636....	**EL 125**	40x40 R	3.000 mm

Code-Nr. unit length in mm

04617	1000

Sample ordering code:
Ballscrew spindle 32x05 right, unit length 1.000 mm.

Ballscrew nut




Code-No.	Type	Pitch	first greasing	re-greasing*
04430	**EL/EG 30**	Kg 08x2,5 R	0,02 g	0,01 g
04440	**EL/EG 40 DL/DS 120 QS 60**	Kg 16x05 R	4,0 g	1,3 g
04440H	**CLL 60**	Kg 16x05 R	4,0 g	1,3 g
04441	**EL/EG 40 DL/DS 120 QS 60**	Kg 16x10 R	2,5 g	0,8 g
04441H	**CLL 60**	Kg 16x10 R	2,5 g	0,8 g
04442	**DL/DS 120 QS 60**	Kg 16x16 R	2,0 g	0,6 g
04442H	**CLL 60**	Kg 16x16 R	2,0 g	0,6 g
04460	**EL/EG 60 DL/DS 120 DL/DS 160 QS 80**	Kg 25x05 R	6,0 g	2,0 g
04461	**EL/EG 60 DL/DS 120 DL/DS 160 QS 80**	Kg 25x10 R	8,0 g	2,6 g
04462	**EL/EG 60 DL/DS 120 DL/DS 160 QS 80**	Kg 20x20 R	8,0 g	2,6 g

Code-No.	Type	Pitch	first greasing	re-greasing*
04463	**EL/EG 60**	20x05 L	5,0 g	2,0 g
04464	**EL/EG 80(S)**	25x25 R	10,0 g	3,0 g
04464-1	**DL/DS 160**	25x25 R	10,0 g	3,0 g
04480	**EL/EG 80(S) EL/QS 100 DL/DS 200**	32x05 R	8,0 g	3,0 g
04485	**EL/EG 80(S) EL/QS 100 DL/DS 200**	32x05 L	8,0 g	3,0 g
04481	**EL/EG 80(S) EL/QS 100 DL/DS 200**	32x10 R	11,0 g	4,0 g
04483	**EL 100 DL/DS 200**	32x20 R	11,8 g	4,0 g
04482	**EL 100 DL/DS 200**	32x32 R	12,6 g	4,0 g
04420	**EL 125**	40x10 R	25,0 g	8,3 g
04421	**EL 125**	40x20 R	29,0 g	9,6 g
04422	**EL 125**	40x40 R	34,0 g	011,3 g

* after approx. 500 hours

Leading nut receiver



Ballscrew EL/EG

Code-No.	Type
03130	30
03140	40
03160	60(S)
03180	80(S)
03110	100
03120	125

Trapezoidal EL/EG

Code-No.	Type
03131	30
03141	40
03161	60(S)
03181	80(S)
03111	100
03121	125

Ballscrew DL/DS

Code-No.	Type
03163	120
03183	160
03113	200

Trapezoidal DL/DS

Code-No.	Type
03168	120
03188	160
03118	200

Ballscrew QS

Code-No.	Type
03167	60
03187	80
03117	100

Trapezoidal QS

Code-No.	Type
03166	60
03186	80
03116	100

Cover caps




Code-No.	Type	D	Position
04206	CLL 60 LL/LS 60 - 80	15	Bearing-block
	QL/QS 60		Servicing bores
04205	ELK 30	19	Bearing-block
	QL/QS 80 - 100, DL/DS 120		Servicing bores
	QL 60		Carriage
04235	ELZ 30	28	Pulley-block
	ELT/K 40, EGT/K 40, W 16		Bearing-block
	DL/DS 160 - 200		Servicing bores
	QL 80 - 100		Carriage
04245	ELZ 40, ELHZ 60, ELVZ 60	37	Pulley-block
04265	LL/LS 60, G 90 ELZ/MLZ 60, ELHZ 80,ELVZ80, DLZ 120, QLZ/QSZ 60	47	Pulley-block
04285	CLL 60, LL/LS 80 ELZ/MLZ 80, ELHZ 100, ELVZ 100, DLZ/DSZ 160, QLZ/QSZ 80	68	Pulley-block
04215	ELZ/MLZ 100, DLZ/DSZ 200, QLZ/QSZ 100	90	Pulley-block
04225	ELZ 125 / QS 125	110	Pulley-block
042650	D 120, Q 60	32	Bearing-block
042850	D 160, Q 80	40	Bearing-block
042150	D 200, Q 100	52	Bearing-block


Spare parts

Belt adjuster ELZ / MLZ

ELZ





MLZ



Code-No.	Type	Material
04060	30	Zinc coated steel
04061	40	Zinc coated steel
04062	ELZ 60(S)	Zinc coated steel
040621	MLZ 60(S)	Zinc coated steel
04063	ELZ 80(S)	Zinc coated steel
040631	MLZ 80(S)	Zinc coated steel
04064	ELZ 100	Zinc coated steel
040641	MLZ 100	Zinc coated steel
04065	125	Zinc coated steel

Belt adjuster ELSZ






Code-No.	Type	Material
04071	30/40	Zinc coated steel
04076	30/40	Nickel faced steel
04072	60(S)	Zinc coated steel
04077	60(S)	Nickel faced steel
04073	80(S)	Zinc coated steel
04078	80(S)	Nickel faced steel
04074	100	Zinc coated steel
04079	100	Nickel faced steel
04075	125	Zinc coated steel
04070	125	Nickel faced steel

Belt adjuster ELHZ




Code-No.	Type	Material
04080	60(S)	Black anodized Al and zinc coated steel
04081	80(S)	Black anodized Al and zinc coated steel
04082	100	Black anodized Al and zinc coated steel
04083	125	Black anodized Al and zinc coated steel

Belt adjuster ELVZ




Code-No.	Type	Material
04090	60(S)	Black anodized Al and zinc coated steel
04091	80(S)	Black anodized Al and zinc coated steel
04092	100	Black anodized Al and zinc coated steel
04093	125	Black anodized Al and zinc coated steel

Belt adjuster



DLZ | DSZ

DLSZ | DSSZ



QLZ | QSZ



Code-No.	Type	Material
04084	DLZ/DSZ 120	Nature anodized Al and zinc coated steel
04086	DLZ/DSZ 160	Nature anodized Al and zinc coated steel
04085	DLZ/DSZ 200	Nature anodized Al and zinc coated steel
040861	DLZ/DSZ 160 HD	Nature anodized Al and zinc coated steel
040851	DLZ/DSZ 200 HD	Nature anodized Al and zinc coated steel
04066	DLSZ 120	Zinc coated steel
04067	DLSZ/DSSZ 160	Zinc coated steel
04087	QLZ/QSZ 60	Nature anodized Al
04088	QLZ/QSZ 80	Nature anodized Al
04089	QLZ/QSZ 100	Nature anodized Al
04094	QSZ 125	Nature anodized Al

Toothed belt Toothed belts are available by the meter. Temperature resistant from -10 ° C to 50 ° C, please call outside this Temperature range our technical service.



Belt with steel reinforcement PU HP PAZ		
Code No.	**Type**	**Toothed belt**
00531	**ELZ 30**	3M 12
00532	**ELZ 40**	5M 15
00534	**ELZ/ML 60 (S)**	5M 25
00536	**ELZ/ML 80 (S)**	8M 30
00538	**ELZ/ML 100**	8M 50
00540	**ELZ 125**	8M 70
00531	**ELZG 30**	3M 12
00532	**ELZG 40**	5M 15
00534	**ELZG 60 (S)**	5M 25
00536	**ELZG 80 (S)**	8M 30
00542	**ELZZ 60 (S)**	5M 09
00543	**ELZZ 80 (S)**	8M 12
00544	**ELZZ 100**	8M 20
00536	**ELZZ 125**	8M 30
00546	**ALLZ 203**	8M 100
00546	**ALLZ 204**	8M 100
00534	**DLZ / DSZ 120**	5M 25
00536	**DLZ / DSZ 160**	8M 30
00538	**DLZ / DSZ 200**	8M 50
00538	**DLZ / DSZ 160 HD**	8M 50
00540	**DLZ / DSZ 200 HD**	8M 70
00534	**QLZ / QSZ 60**	5M 25
00536	**QLZ / QSZ 80**	8M 30
00538	**QLZ / QSZ 100**	8M 50
00540	**QSZ 125**	8M 70
00534	**DLZPVI / DSZPVI 120**	5M 25
00536	**DLZPVI / DSZPVI 160**	8M 30
00538	**DLZPVI / DSZPVI 200**	8M 50
00547	**LLZ / LSZ 60**	5M 30
00548	**LLZ / LSZ 80**	8M 30
00529	**WGVZ / WKVZ 16**	3M 11,4

Belt with steel reinforcement PU HP PAZ		
Code No.	**Type**	**Toothed belt**
005341	**DLVZ 120**	5M 25
005341	**DLVZ 160**	5M 25
005341	**ELHZ / ELVZ 60**	5M 25
005341	**ELHZ / ELVZ 80 (S)**	5M 25
005451	**ELHZ / ELVZ 100**	8M 48
005381	**ELHZ / ELVZ 125**	8M 50
00531	**ELZU 30**	3M 12
00532	**ELZU 40**	5M 15
00534	**ELZU 60 (S)**	5M 25
00536	**ELZU 80 (S)**	8M 30
00538	**ELZU 100**	8M 50
00532	**ELZI 30**	5M 15
00534	**ELZI 40**	5M 25
00536	**ELZI 60**	8M 30



Ex - protection ATEX PU HP PAZ PAR antistatic		
Code No.	**Type**	**Toothed belt**
00532EX	**ELZ 40**	5M 15
00534EX	**ELZ 60/60S**	5M 25
00536EX	**ELZ 80/80S**	8M 30
00538EX	**ELZ 100**	8M 50
00540EX	**ELZ 125**	8M 70
00536EX	**ELFZ 60 S**	8M 30
00538EX	**ELFZ 80 S**	8M 50
00540EX	**ELFZ 100**	8M 70
00546EX	**ELFZ 125**	8M 100
00547EX	**LLZ 60**	5M 30



Code-No	length in mm
00534	5000

Sample ordering code:
Belt 5M 25, PU HP PAZ, 5m long

Spare parts

Toothed belt Toothed belts are available by the meter. Temperature resistant from -10 ° C to 50 ° C, please call outside this Temperature range our technical service.





Ω - redirection pulley block steel reinforcement PU HP PAZ		
Code No.	**Type**	**Toothed belt**
00536	**ELFZ 60 S**	8M 30
00538	**ELFZ 80 S**	8M 50
00540	**ELFZ 100**	8M 70
00546	**ELFZ 125**	8M 100

00531	**ELSZ 30**	3M 12
00532	**ELSZ 30 HD**	5M 15
00532	**ELSZ / ELSD 40**	5M 15
00534	**ELSZ / ELSD 40 HD**	5M 25
00534	**ELSZ / ELSD 60 (S)**	5M 25
00537	**ELSZ / ELSD 60 (S) HD**	8M 30
00536	**ELSZ / ELSD 80 (S)**	8M 30
00538	**ELSZ / ELSD 80 (S) HD**	8M 50
00538	**ELSZ / ELSD 100**	8M 50
00540	**ELSZ / ELSD 100 HD**	8M 70
00540	**ELSZ 125**	8M 70
00546	**ELSZ 125 HD**	8M 100

00532	**QSSZ 60**	5M 15
00534	**QSSZ 80**	5M 25

00536	**DSZS 160** (PU HF PAZ)	8M 30
00536	**DLSZ 120**	8M 30
00538	**DLSZ 160**	8M 50
00540	**DLSZ 200**	8M 70
00536	**DSSZ 120**	8M 30
00538	**DSSZ 160**	8M 50
00540	**DSSZ 200**	8M 70

00534	**ELZT 40**	5M 25	Main belt
00532	**ELZT 40**	5M 15	Rotating belt
00536	**ELZT 60 (S)**	8M 30	Main belt
00534	**ELZT 60 (S)**	5M 25	Rotating belt
00538	**ELZT 80 (S)**	8M 50	Main belt
00536	**ELZT 80 (S)**	8M 30	Rotating belt
00540	**ELZT 100**	8M 70	Main belt
00538	**ELZT 100**	8M 50	Rotating belt

Stainless steel linear units aramid-reinforcement PU PAZ		
Code No.:	**Type**	**Toothed belt**
005341	**QLZE / QSZE 60**	5M 25
005361	**QLZE / QSZE 80**	8M 30
005381	**QLZE / QSZE 100**	8M 50
005401	**QLZE 125**	8M 70

005341	**DLZPVIE / DSZPVIE 120**	5M 25
005361	**DLZPVIE / DSZPVIE 160**	8M 30
005381	**DLZPVIE / DSZPVIE 200**	8M 50

005471	**LLZE 60 / LSZE 60**	5M 30

Nubbed belt with steel reinforcement N10-PAN-HF		
Code No.:	**Type**	**Nubbed belt**
00547N	**LL / LS / CL / ML 60**	N10



Toothed pulleys



coupling claw on one side



coupling claws on both sides



shaft on one side



shaft on both sides

Pulley size 30 - 80 bronzed steel / aluminium, size 100 - 125 aluminium.
Coupling claws compatible with Rotex GS system.

	Code No.		Code No.					
Size	**Coupling claw on one side**	**Coupling claw on both sides**	**Shaft on one side**	**Shaft on both sides**	**Belt**	**Number of teeth**	**mm/ rev.**	**Coupling Rotex**
ELZ / ELSZ / MLZ with standard belt								
30	04010	04020	04828	04829	3M12	25	75	7
40	04011	04021	04830	04831	5M15	20	100	9
60(S)	04012	04022	04832	04833	5M25	26	130	14
80(S)	04013	04023	04834	04835	8M30	24	192	19
100	04014	04024	04836	04837	8M50	32	256	24
125	04015	04025	04838	04839	8M70	38	304	28
ELSZ with widened belt								
30	04011	04021	04830	04831	5M15	20	100	9
40	04012	04022	04832	04833	5M25	26	130	14
60(S)	04013	04023	04834	04835	8M30	24	192	19
80(S)	04014	04024	04836	04837	8M50	32	256	24
100	04015	04025	04838	04839	8M70	38	304	28
125	040150	-	-	-	8M100	38	304	-
ELZG								
30	04820	04821	04840	04841	3M12	40	120	7
40	04822	04823	04842	04843	5M15	32	160	9
60(S)	04824	04825	04844	04845	5M25	44	220	14
80(S)	04826	04827	04846	04847	8M30	40	320	19
ELSD with standard belt								
40	04011	04021	04830	04831	5M15	20	100	9
60(S)	04012	04022	04832	04833	5M25	26	130	14
80(S)	04013	04023	04834	04835	8M30	24	192	19
100	04014	04024	04836	04837	8M50	32	256	24
ELSD with widened belt								
40	04012	04022	04832	04833	5M25	26	130	14
60(S)	04013	04023	04834	04835	8M30	24	192	19
80(S)	04014	04024	04836	04837	8M50	32	256	24
100	04015	04025	04838	04839	8M70	38	304	28
ELZU								
30	04010	04020	04828	04829	3M12	25	75	7
40	04011	04021	04830	04831	5M15	20	100	9
60(S)	04012	04022	04832	04833	5M25	26	130	14
80(S)	04013	04023	04834	04835	8M30	24	192	19

Toothed pulleys

Size	Code No. Coupling claw on one side	Coupling claw on both sides	Code No. Shaft on one side	Shaft on both sides	Belt	Number of teeth	mm/ rev.	Coupling Rotex
ELZT internal belt								
40	04011				5M15	20	100	9
60(S)	04012				5M25	26	130	14
80(S)	04013				8M30	24	192	19
100	04014				8M50	32	256	24
ELZT external belt								
40	04012	04022	04832	04833	5M25	26	130	14
60(S)	04013	04023	04834	04835	8M30	24	192	19
80(S)	04014	04024	04836	04837	8M50	32	256	24
100	04015	04025	04838	04839	8M70	38	304	28
DLZ / DSZ								
DLZ/DSZ 120	04012	04022	04832	04833	5M25	26	130	14
DLZ/DSZ 160	04852	04853	04848	04849	8M30	22	176	19
DLZ/DSZ 200	04854	04855	04850	04851	8M50	28	224	24
DLZT / DSZT internal belt								
120	04012				5M25	26	130	14
DLZT / DSZT external belt								
120	04013	04023	04834	04835	8M30	24	192	19
QLZ / QSZ								
60	04012	04022	04832	04833	5M25	26	130	14
80	04852	04853	04848	04849	8M30	22	176	19
100	04854	04855	04850	04851	8M50	28	224	24
QS 125	048551	048552	–	–	8M70	36	288	28
QLSZ / QSSZ								
80	04012	04022	04832	04833	5M25	26	130	14
CLL / LL / LS								
60	–	04868	04869	–	5M30	26	130	14
80	–	048695	04848	04849	8M30	22	176	19
LL / LS / ML Special toothed pulley for nubbed belt								
60	048685	048686	–	–	5M30	13	130	14

Tensioner pulley	Code No.	Belt	Number of teeth	mm/rev.
CLL / LL / LS 60	048694	5M30	26	130
LL / LS 80	048697	8M30	22	176
CLL / LL / LS 60 for nubbed belt	048687	N10	13/3	130



two shafts short



one shaft long



two shafts long

Size	Code No. Two shafts short	One shaft long	Two shafts long	Belt	Number of teeth	mm/ rev.	Coupling Rotex
ELHZ / ELVZ							
60(S)	04026	04860	04861	5M25	16	80	14
80(S)	04027	04862	04863	5M25	22	110	19
100	04028	04864	04865	8M50	18	144	24
125	04029	04866	04867	8M50	24	192	28

Spare parts

Toothed pulleys



Coupling claw on one side



Shaft on one side





Shafts on both sides

Size	Code No.			Belt	Number of teeth	mm/ rev.	Coupling Rotex
	Coupling claw on one side	Shaft on one side	Shaft on both sides				
			ELZZ				
60(S)	04856	048561	048562	5M09	26	130	14
80(S)	04857	048571	048572	8M12	24	192	19
100	04858	048581	048582	8M20	32	256	24
125	04859	048591	048592	8M30	38	304	28

Plug-in shaft for pulleys

Plug-in shaft made of stainless steel, complete with key and locking rings for retrofitting.





Shaft on one side							Shaft on both sides						
Code-No.	Type	Size	A_{h7}	B	C	D	Code-No.	Type	Size	A_{h7}	B	C	D
04030	**ELZ/ELSZ**	**30**	6	15	2x2x12	57	**04040**	**ELZ/ELSZ**	**30**	6	15	2x2x12	72
04031	**ELZ/ELSZ**	**40**	10	27	3x3x25	85	**04041**	**ELZ/ELSZ**	**40**	10	27	3x3x25	112
04032	**ELZ/ELSZ/ MLZ QLZ/QSZ**	**60**	14	35	5x5x28	115	**04042**	**ELZ/ELSZ QLZ/QSZ**	**60**	14	35	5x5x28	150
	DLZ/DSZ DLZT/DSZT	**120**						**DLZ/DSZ DLZT/DSZT**	**120**				
04033	**ELZ/ELSZ/ MLZ QLZ/QSZ**	**80**	18	45	6x6x40	145	**04043**	**ELZ/ELSZ QLZ/QSZ**	**80**	18	45	6x6x40	190
	DLZ/DSZ	**160**						**DLZ/DSZ**	**160**				
	DLSZ/DSSZ	**120**						**DLSZ/DSSZ**	**120**				
04034	**ELZ/ELSZ/ MLZ**	**100**	22	45	6x6x40	175	**04044**	**ELZ/ELSZ**	**100**	22	45	6x6x40	220
	DLSZ	**160**						**DLSZ**	**160**				
04035	**ELZ**	**125**	30	45	8x7x40	215	**04045**	**ELZ**	**125**	30	45	8x7x40	270

Tensioning set for sizes EL 100 - 125, DL/DS 200, ML / QL / QS 100





Code-No.	Type	Tension ring
00472	**EL/ML 100 DL/DS 200 QL/QS 100**	22 x 32
00476	**E 125**	30 x 41

Pulley with integrated tension set D 120, 160, 200

Dimensions (mm)

120




160



200





Type	Standard Code-No.	stainless Code-No.	A	B	Ø F	Ø G	Ø H
D 120	**04873**	**04874**	39	30	41	16	46
D 160	**04875**	**04876**	45	36,2	54	22	60
D 200	**04877**	**04878**	67,5	57,2	62	32	79

Belt type	Number of teeth
HTD 5M 25	26
HTD 8M 30	22
HTD 8M 50	28

M = Dismounting thread

Type	Clamping screws			Torque / axial force	
	M	z Number	T_A [Nm]	T [Nm]	F_{ax} [N]
D 120	M5	4	10	148	19 000
D 160	M6	4	17	244	22 000
D 200	M6	8	17	689	43 000

Function:

Pulley with integrated tension set for positioning systems DLZPVI (E) and DSZPVI (E). In order to realize a simple and fast assembling we reduced the number of parts. Each tension set has got two dismounting threads in order to disassemble the pulley easily.





Sample for pulley assembling positioning system DSZPVI 120

1.2

Spur gears

Dimensions (mm)

ELZA | ELDZA

Size	1 Shaft			2 Shafts			mm/rev.	Modul
	Steel	Stainless steel	Plastic	Steel	Stainless steel	Plastic		
40	041900	041901	04190	041910	041911	04191	188,5	1,5
60	041920	041921	04192	041930	041931	04193	251,3	2
60 S	041980	041981	04198	041990	041991	04199	314,2	2
80 (S)	041940	041941	04194	041950	041951	04195	358,0	3
100	041960	041961	04196	041970	041971	04197	508,9	3








Accessories

Square nut



DIN 562




Slide nuts position refer to chapter 2.2 page 3
Material: galvanized steel

Code-No.	Type	A	B	C	D
02708	M 4	7	7	2,2	M 4
02710	M 5	8	8	2,7	M 5
02715	M 6	10	10	3,2	M 6
02714	M 8	13	13	4	M 8
02713	M 10	17	17	5	M 10
02721	M 10	25	20	8	M 10


T-nut






Slide nuts position refer to chapter 2.2 page 3
Material: galvanized steel

Code-No.	Type	A	B	C	D	E	F
02717	M3	8	4,2	2,1	M 3	6,9	4,3
02739	M4	10	4,2	2,1	M 4	6,9	3,3
02742	M 5	12	5,3	3	M 5	8	4
02709	M 5	14	8,1	4,5	M 5	14	6
02716	M 6	14	8,1	4,5	M 6	14	6
02718	M 8	18	8,1	4,5	M 8	14	6
02719	M10	22	8,1	4,5	M 10	14	6
02730	M 6	13	10	4	M 6	15	8
02731	M 8	13	10	4	M 8	15	8




DIN 508



Code-No.	Type	A	B	C	D	E	F
02734	M 5	10	8	10	M 5	6	4
02735	M 6	13	10	13	M 6	8	4
02736	M 8	15	12	15	M 8	10	6
02720	M 10	18	14	18	M 10	12	7
02722	M 12	22	16	22	M 12	14	8
02737	M 16	28	20	28	M 16	18	10

Rhombus nut






Slide nuts position refer to chapter 2.2 page 3
Material: galvanized steel

Code-No.	Type	B	C	D	E	F
02732	M 8	15	9	M 8	10	4,2
02733	M 6	15	9	M 6	10	4,2
02760	M 5	10	8	M 5	6	4

Half round nut






For guide body profile EL, ML, QL / QS and for fastening of jointing and mounting blocks. Material: galvanized steel

Size	Code-No.	Type	A	B	D
30	02724	M 3	28	5	2x M 3
40	02725	M 5	14	6	M 5
60 (S)	02726	M 6	18	10	M 6
80 (S)	02728	M 8	22	12	M 8
100	02729	M 8	22	16	M 8
125	02723	M10	25	20	M10


T-nut allocation

Bearing block profile EL




Size	T-slot nut slot AA Code No.	T-slot nut slot NN Code No.
30	02715	02715
40	02710	02715
60 (S)	02710	02718
80 (S)	02714	02719
100	02714	02720
125	02736	02722

Bearing block profile ELZ




Size	T-slot nut slot M Code No.
30	02710
40	02735
60 (S)	02731 / 02719
80 (S)	02736
100	02720
125	02722

Guide body profile E




Size	T-slot nut slot CC Code No.
40	02730 / 02731
60	02730 / 02731
80	02730 / 02731

ALLM



Guide body profile ML/LL/LS/ALL




ML LL LS

Size	T-slot nut slot N Code No.	T-slot nut slot O Code No.
ML 60 (S)	02716 / 02718	02726
ML 80 (S)	02719	02728
ML 100	02720	02729
LL / LS 60	02734	
LL / LS 80	02735	
ALLM 200	02737	

Guide body profile EL / EG


EL/EG ELDZA



Size	T-slot nut slot CC Code No.	T-slot nut slot O Code No.	T-slot nut slot N Code No.
EL 30	02715	02724	-
EL/EG 40	02718	02725	-
EL/EG 60	02718	02726	-
EL/EG 80(S)	02718	02728	-
EL 100	02721	02729	-
EL 125	02721	02723	-
ELDZA 60(S)	02734	02726	02735
ELDZA 80(S)	02730	02728	02720
ELDZA 100	02736	02729	02720

Guide body profile DL/DS QL/QS

DL DS QL QS QS 125




Size	T-slot nut slot N Code No.	T-slot nut slot M Code No.	T-slot nut slot T* Code No.	T-slot nut slot O* Code No.
DL/DS 120	02735	02734	02717	-
DL/DS 160	02736	02735	02739	-
DL/DS 200	02720	02736	02735	-
QL /QS 60	02734**	-	02739	02726
QL /QS 80	02735**	-	02742	02728
QL /QS 100	02720**	-	02716	02729
QS 125	02720	-	02736	02723

* only for DS/QS guide body profile
** not in QST/K guide body profile


Carriage profile EL / EG

Size	T-slot nut slot OO Code No.	T-slot nut slot MM Code No.
30	02715	-
40	02716 / 02709	-
60	02718	-
60 S	02736	-
80	02718 / 02719	02715
80S	02736	02735
100	02720	02713
125	02722	02720

EL/ML




EG




Carriage profile DL / DS / QL / QS

Size	T-slot nut slot O Code No.	T-slot nut slot M Code No.
DL/DS 120	02735	-
DL/DS 160	02736	-
DL/DS 200	02720	-
QL/QS 60	-	02735
QL /QS 80	-	02736
QL/QS 100	-	02720
QS 125	-	02722


DL



DS




QL/QS



Slide nut dimensions refer to chapter 2.2 page 2

Handwheel with keyway and locking screw







A plastic coated aluminium handwheel with a matt black finish. Equiped with a black handle.

Code-No.	Type	A	B	C	D	E	F	G
00050	**30**	70	6	17	13	15	-	20
00100	**40**	100	10	29	14,5	17	3x3	30
00160	**60**	140	14	36	16,5	19	5x5	36
00200	**80**	200	18	42	20,5	24	6x6	45
00222	**100**	200	22	42	20,5	24	6x6	45

Positional indicator







Code No. 00265 - 00268
electronical indicator

SH-FH



SV-FV




Shell made of polyamide orange. Ambient temperature 80°C. Any fitting position possible. Numeral height 6 mm. Accuracy of reading 0,1 mm.

Code-No.	Size	AxBxC	D	Type	pitch (mm)
00231..	**EL / EG** 30	33x47x31	6	SH	2,5 od. 3
00232..		33x47x31	6	FH	2,5 od. 3
00233..		33x47x31	6	SV	2,5 od. 3
00234..		33x47x31	6	FV	2,5 od. 3
00241..	**EL / EG** 40, 60, 80 **QS** 60, 80 **DL / DS** 120, 160	48x67x51	12,17,20	SH	4 od. 8
00242..		48x67x51	12,17,20	FH	4 od. 8
00243..		48x67x51	12,17,20	SV	4 od. 8
00244..		48x67x51	12,17,20	FV	4 od. 8
00251..		48x67x51	12,17,20	SH	5 od. 10
00252..		48x67x51	12,17,20	FH	5 od. 10
00253..		48x67x51	12,17,20	SV	5 od. 10
00254..		48x67x51	12,17,20	FV	5 od. 10
00261..	**EL** 100, 125 **QS** 100 **DL** 200	56x75x64	22,25,30	SH	6 od. 12
00262..		56x75x64	22,25,30	FH	6 od. 12
00263..		56x75x64	22,25,30	SV	6 od. 12
00264..		56x75x64	22,25,30	FV	6 od. 12
00265..	**EL / EG** 40, 60, 80, 100, 125 **QS** 60, 80, 100 **DL / DS** 120, 160, 200	48x76x39	12,17,20,30	SH	0,01 - 10
00266..		48x76x39	12,17,20,30	FH	0,01 - 10
00267..		48x76x39	12,17,20,30	SV	0,01 - 10
00268..		48x76x39	12,17,20,30	FV	0,01 - 10

0024108

Sample odering code: size 40, 8 mm pitch increasing horizontal.

Spindle clamp EL / EG, DL / DS /QST/K







Black anodized aluminium, steel hand lever.

Code-No.	Type	A	B	C	D	Handlever
00291	**EL/EG 30**	43	50	10	6	M 6
00292	**EL/EG 40**	58	70	10	12	M 6
00293	**EL/EG 60**	80	80	15	17	M 8
00294	**EL/EG 80**	100	100	20	20	M10
00295	**E 100**	130	130	20	25	M10
00296	**E 125**	-	-	-	-	-
00283	**DL/DS 120**	62	80	15	12	M 6
00284	**DL/DS 160**	80	90	20	17	M 8
00285	**DL/DS 200** **QS 100**	90	99	20	25	M 8
00286	**QS 80**	80	90	20	17	M 8
00287	**QS 60**	62	80	15	12	M 6

Carriage clamp EL / ML / EG




Carriage with carriage clam. Carriage length can be chosen as required. Depending on type of drive (spindle or belt) the position of clamp can be different. Dimensions by inquiry.

Code-No.	Type
00311	EG 30
00312	EG 40
00313	EG 60
00314	EG 80
00301	EL 30

Code-No.	Type
00302	EL 40
00303	EL/ML 60
00304	EL/ML 80
00305	EL/ML 100
00306	EL 125

Assembly plate







EL/EG



QL/QS




DL/DS

Assembly plate, anodized aluminium, enables various units to be assembled in a simple manner when combinations of linear units are to be used. Complete with screws and slide-nuts. Tapped holes can be made on request.

Code-No.	Type	A	B	C	D	E for	F
00940	EG 40	70	100	52	52	M 6	12
00960	EG 60	100	144	80	126	M 8	15
00980	EG 80	140	170	110	147	M10	15
00935	EL 30	70	70	56	56	M 6	10
00945	EL 40	100	100	66	84	M 6	12
00965	EL/ML 60	144	144	96	126	M 8	15
00964	EL/ML 60 S	170	170	108	152	M 8	15
00985	EL/ML 80	170	170	117	150	M10	15
00984	EL/ML 80 S	190	190	126	172	M 8	15
00915	EL/ML 100	230	270	155	248	M10	20
00925	EL 125	295	335	200	285	M12	20
00966	DL/DS 120	120	140	96	122	M 6	12
00986	DL/DS 160	160	180	130	162	M 8	15
00916	DL/DS 200	200	240	160	218	M 10	20
00967	QL 60	60	140	36	122	M 6	12
00987	QL 80	80	180	50	162	M 8	15
00917	QL 100	100	240	66	218	M10	20
00926	QS 60	60	165	36	147	M6	12
00928	QS 80	80	216	50	198	M8	15
00911	QS 100	100	248	66	226	M10	20
00921	QS 125	125	270	82	244	M12	20
00968	LL 60	54	175	18	93	M6	12
00969	LS 60	54	116	18	93	M6	12
00988	LL 80	74	250	18	90	M6	12
00989	LS 80	74	149	18	120	M6	12

Connecting profiles DL / DS




The millings for the extensions are directly incorporated into the profile, so that there is only one transition point in the profile. The guide shafts or rail guides are jointed at a different position. To ensure that even the smallest tolerance deviations are avoided, only pieces of the same lots are joined to each other.


Code-No.	Type	A	B	C	D	E
03090_02	DS 120	47,5	66	78	56	12
03090_01	DL 120	47,5	66	78	56	12
03091_02	DS 160	39	58	78,5	56,5	12
03091_01	DL 160	39	58	78,5	56,5	12
03092_02	DS 200	53	77	71,3	45,3	17,55
03092_01	DL 200	53	77	71,3	45,3	17,55

Support and mounting block


EG








DL/DS








Black anodized aluminium, for mounting and for supporting long units. These components can be ready mounted on the units by us to customer's specification. Mounting can be clear or tapped holes and slide-nuts.


Code-No.	Type	A	B	C	D	E	F	G	H
03043	EG 40	40	40	6,5	24,0	9	1 hole	50	60
03063	EG 60	60	60	9,0	35,0	11		75	90
03083	EG 80	80	80	10,5	39,0	11	60	100	120


Code-No.	Type	A	B	C	D	E	F	G	H for	K for
03001	DL/DS 120	34	17	14	6	22	10	134	M6	M5
03002	DL/DS 160	40	20	19	8	28	14	179	M8	M6
03003	DL/DS 200	50	30	24	10	34	18	224	M10	M8



Mounting profile EL / ML / Q / L








Black anodized aluminium, for mounting.
Mounting can be clear or tapped holes. Pair (without screws)


Code-No.	Type	A	B	Ø C	D	E	F	G	H
03039	EL 30	24	11,5	5,5	10	3	12	6,5	41
03049	EL 40	32	15,5	6,5	13	4	16	9	54
03069	EL/ML/Q 60	48	17,5	8,5	18	4	24	9,5	77
03089	EL/ML/Q 80	64	19,5	8,5	23,5	4	32	11,5	97
03019	EL / Q 100	80	21,5	10,5	30,5	4	40	12	120
03029	EL / QS 125	100	27	13,5	40	6	50	15,5	149
03009	L 60	64	19,5	9	23,5	4	32	11,5	76
03099	L 80	64	19,5	9	23,5	4	32	11,5	97

Double mounting profile EL / ML / Q / L

Black anodized aluminium. For mounting and joining body profiles longer than standard. Mounting can be clear or tapped holes.
Pair (without screws)



Code-No.	Type	A	B	C	D	E	F1	F2	G	H
03039-2	EL 30	48	11,5	5,5	10	3	12	36	6,5	41
03049-2	EL 40	64	15,5	6,6	13	4	16	48	9	54
03069-2	EL / ML / Q 60	96	17,5	9	18	4	24	72	9,5	77
03089-2	EL / ML / Q 80	128	19,5	9	23,5	4	32	96	11,5	97
03019-2	EL / QL / QS 100	160	21,5	11	30,5	4	40	120	12	120
03029-2	EL / QS 125	200	27,0	13,5	40	6	50	150	15,5	149
03009-2	L 60	128	19,5	9	23,5	4	32	96	11,5	76
03099-2	L 80	128	19,5	9	23,5	4	32	96	11,5	97





Mounting block EL / EH / ML / Q


Black anodized aluminium, for mounting and for supporting long units. These components can be ready mounted on the units by us to customer's specification. Mounting can be clear or tapped holes and slide-nuts.





* only 1 hole

Code-No.	Type	A	B	C	E	F	G	H
030301	EL 30	54	30	*	38	10	4,2	6
030401	EL/EH 40	72	40	*	50	13	6,4	9
030601	EL/EH/ML/Q 60	96	60	*	75	18	8,5	10,8
030801	EL/EH/ML/Q 80	120	80	60	100	23,5	10,5	10,8
030101	EL/EH/ML/Q 100	144	100	70	120	30,5	10,5	14,8
030201	EL/EH/QS 125	180	125	85	150	40	11	20
030091	L 60	100	60	*	76	23,5	9	10,8
030991	L 80	120	80	60	100	23,5	10,5	10,8




Jointing profile EL / ML / Q

Black anodized aluminium. For joining body profiles longer than standard (without screws).





Code-No.	Type	A	B	C	E	F	G	M
030312	EL 30	54	60	50	38	10	4,2	10
030412	EL 40	72	80	66	50	13	6,4	14
030612	EL/ML/Q 60	96	120	100	75	18	8,5	20
030812	EL/ML/Q 80	120	160	140	100	23,5	10,5	20
030112	EL/ML/Q 100	144	200	170	120	30,5	10,5	30
030212	EL/QS 125	180	250	210	150	40	11	40




Jointing block SLT

Anodized aluminium. For joining body profiles longer than standard.





Code-No.	Type	A	B	C	D	E	H
030703	SLT 30	80	160	77	65	100	105
030705	SLT 50	120	200	93,5	79	135	145




Jointing block EL / ML / Q / L

Black anodized aluminium, for jointing, mounting and supporting long units. These components can be ready mounted on the units by us to customer's specification. Mounting can be clear or tapped holes and slide-nuts.








Code-No.	Type	A	B	C	E	F	G	H	M
030311	EL 30	54	60	50	38	10	4,2	6	10
030411	EL 40	72	80	66	50	13	6,4	9	14
030611	EL/ML/Q 60	96	120	100	75	18	8,5	10,8	20
030811	EL/ML/Q 80	120	160	140	100	23,5	10,5	10,8	20
030111	EL/ML/Q 100	144	200	170	120	30,5	10,5	14,8	30
030211	EL/QS 125	180	250	210	150	40	11	20	40
030092	L 60	100	120	100	76	23,5	9	10,8	20
030992	L 80	120	160	140	100	23,5	10,5	10,8	20

Proximity / limit switch holder EG


Black anodized aluminium bracket, fixed by grub screws. Position along the length of the units is adjustable. Fixing holes for proximity and limit switches are provided.



Code-No.	Type	A	B	C	D	E	F	Drill hole
01340	EG 40	72	40	24	15	19	28	8,2
01360	EG 60	92	60	24	15	26	35	12,2
01380	EG 80	114	81	24	15	30	40	12,2

Proximity / limit switch holder EL

Black anodized aluminium bracket, fixed by screws into with half-round nuts in the body half-round-slots, hence position axially adjustable. Fixing holes for proximity and limit switches are provided. Complete with screws and half-round nuts.





Code-No.	Type	A	B	C	D	E	F	Drill hole
01331	EL 30	12	30	12	-	-	6	8,2
01341	EL 40	28	32	25	26	22	8	8,2
01361	EL 60	30	40	25	32	22	11	12,2
01381	EL 80	30	45	25	39	22	10	12,2
01311	EL 100	40	55	20	49	22	12	12,2
01321	EL 125	45	60	25	52	22	12,5	12,2
01300	EL60-125	Reducing sleeve Ø 12 to Ø 8						

Accessories

Limit switch







Fully insulated thermoplastic switch with adjustable operation lever. The operation device can be turned by 90°, the lever can be turned to engage by 360°.

Max. voltage	380 V
Max. constant current	6 A
Max. current at make	16 A
Duty classification	max.6000/h
Mechanical lifetime	1 x 10^7
Operating repeatability	± 0,01
Transit time/snap switch	ca. 10 ms
Protection class	IP 65 (DIN 40050)
Working temperature	-30° C to +80° C

Code-No.	choice
01101	standard
01101ex	Version ATEX

Limit switch









3 electromechanical switches in a row.

Nominal voltage	250 V
Cont. current	6 A
Switch rate	max.300/min.
Mech. Lifetime	>30 Mio.
Repeatability	± 0,01 mm
Transit time/snap switch	ca. 10 ms
Protection class	IP 67 (DIN 60529)
Working temperature	-5° C bis +80° C

Code-No.	choice
01105	switch system *

* consisting of 2 cam ledges and 3 cams

Proximity switch







Inductive proximity switches. Protection class IP67

Code-No.	Type	Switching distance	Voltage	Output	Function
01003	M8	1 mm	10 - 30 V	200 mA	PNP NC
01004	M8	1 mm	10 - 30 V	200 mA	PNP NO
01001	M12	2 mm	10 - 30 V	200 mA	PNP NC
01002	M12	2 mm	10 - 30 V	200 mA	PNP NO
010014	Q 8x8	2 mm	10 - 30 V	200 mA	PNP NC
010013	Q 8x8	2 mm	10 - 30 V	200 mA	PNP NO

PNP NO (normally open) =




PNP NC (normally closed) =




Accessories


Proximity / limit switch holder
DL / DS / QL / QS / LL / LS




Code-Nr.	Type
01327-0	Base holder for a limit switch
01327-1	Base holder for a proximity and a limit switch
01327-4	Base holder for a sensor bracket
01328-0	plug in holder for a proximity switch M8x1
01329-0	plug in holder for a proximity switch M12x1
01330-0	plug in holder for a proximity switch Q 8x8
01335-0	Sensor holder DL/DS 120 / QL/QS 60 H = 46,5mm
01335-1	Sensor holder DL/DS 160 H = 50,5mm
01335-2	Sensor holder QL/QS 80 H = 52,5mm
01335-3	Sensor holder DL/DS 200 H = 48 mm
01335-4	Sensor holder QL/QS 100 H = 57 mm

* stainless steel grub screws











Activating sheet EL / ML / EG



Activating sheet QL / QS - DL / DS



Activating strip LL / LS


only on combination with matching assembly plate*

*Assembly plate

LL 60 00968, **LL 80** 00988

LS 60 00969, **LS 80** 00989

*




For external mounting proximity switches.

Code-No.	Type	Länge - L
01000	**EL 30**	Q
01005	**EL 40**	Q
01006	**EL/ML 60**	Q
01011	**EL/ML 60S**	Q
01007	**EL/ML 80**	Q
01010	**EL/ML 80S**	Q
01008	**EL/ML 100**	Q
01009	**EL 125**	Q
010000	**EG 30**	Q
010050	**EG 40**	Q – 7
010060	**EG 60**	Q – 9
010070	**EG 80**	Q – 11
01018	**DL/DS 120**	Q – 16
01017	**DL/DS 160**	Q – 20
01016	**DL/DS 200**	Q – 30
01030	**QL/QS 60**	Q – 12
01031	**QL/QS 80**	Q – 16
01032	**QL/QS 100**	Q – 20
01032	**QS 125**	Q – 30
01015	**LL/LS 60**	Q2
01019	**LL/LS 80**	Q2

Q = Carriage lenght

Complete bellows DL / DS



Bellow ERA7815, max. 120°, bellow frame PVC.

Code-No.	Type	A	B	C	Fold	
					L_{min}	L_{max}
02901	**DL/DS 120**	120	19	1	4	22
02902	**DL/DS 160**	160	24	1	4	31
02903	**DL/DS 200**	200	28	1	4	28

02902	500

Sample ordering code: Size 160, unit length L = 500 mm.



Motor adapter

Black anodized aluminium, can be designed for any motor. Simple assembly, accurate alignment.



Code-No.	Typ spindle
01531	EL/EG 30
01541	EL/EG 40
01561	EL/ML/EG 60 / DL/DS 120 QS 60
01581	EL/ML/EG 80 / DL/DS 160 QS 80
01511	EL/ML 100 DL/DS 200 QS 100
01521	EL 125

Code-No.	Typ belt-drive
01831	EL 30
01832	ELZI 30
01841	EL 40
01842	ELZI 40
01861	EL/ML 60 / DL/DS 120 QL/QS 60 / LL/LS 60
01862	ELZI 60
01881	EL/ML 80 / DL/DS 160 QL/QS 80
01811	EL/ML 100 / DL/DS 200 QL/QS 100
01821	EL 125 /QS 125



DL





EL

Bevel gear pair EL / EG

C 45 steel, helical gear, with keyway.








Code-No.	Type	i	Modul	Number of teeth	A_{h7}	B	C	D	E	F	max. rpm (min^{-1})
00641	40	1:1	2	16	10	13	28	-	22	35	560
00642	40	1:1,5	1,5	16	10	17	30	24	20	27	560
				24		17,5	27	36	26	38	840
00661	60	1:1	2,5	16	14	18,5	33	-	30	43	750
00662	60	1:1,5	2	16	14	21	38	32	26	36	560
				24		23	35	48	35	51	840
00681	80	1:1	3	16	18	23	40	-	35	51,5	750
00682	80	1:1,5	3	16	18	28	54	48	40	53	560
				24	19	30	49	72	50	76	840
00611	100	1:1	4	16	22	35,5	54	-	45	69,7	750
00612	100	1:1,5	3	16	22	27,7	50	48	34	53	560
				24		31	44	72	38	76	840

Combination cube EL / EG
Cover caps







Combination cube					
Code-No.	Type	A	B	C	D
00830	30	52	35	40	M 4
00840	40	66	47	48	M 6
00860	60	92	69	62	M 8
00880	80	112	88	80	M 8
00810	100	148	112	110	M10

Cover caps			
Code-No.	Type	E	
01830	30	2	Black plastic. To cover empty cube sides.
01840	40	5	
01860	60	6	
01880	80	6	
01810	100	3	

Black anodized aluminium. Used for connecting modules at right angles or in line.

Accessories

Splined shaft EL / ML / EG - DL / DS




Steel splined shaft, for torque transfer between two parallel drives.
Shafts longer than 1000 mm are hollow shafts with welded journals.

Code-No.	Type	A	B1	B2	C	D	L_{max}
02230	**EL/EG 30**	15	8	12	2x2x12	6_{h7}	1.500
02240	**EL/EG 40**	27	16	20	3x3x25	10_{h7}	3.000
02260	**EL/ML/EG 60 Q 60 D 120**	35	20	24	5x5x28	14_{h7}	3.000
02280	**EL/ML/EG 80 Q 80 D 160**	45	24	30	6x6x40	18_{h7}	3.000
02210	**EL/ML 100 Q 100 D 200**	55	30	40	6x6x50	22_{h7}	4.500
02220	**EL/QS 125**	55	40	50	8x7x50	30_{h7}	5.000


02240	0500

Sample order code:
Size 40, length L = 500 mm


B1 splined shaft < 1000 mm
B2 splined shaft > 1000 mm









Splined shafts








Aluminum splined shaft parallel to the torque transmission with adjustment units arranged. The splined shaft consists of an aluminum hollow shaft with bonded journals of stainless steel.


Code-No.	Type	A	B	C	D	L_{max}
02264	**EL/ML/EG 60 Q 60 D 120**	35	27	5x5x28	14_{h7}	3000
02284	**EL/ML/EG 80 Q 80 D 160**	45	40	6x6x40	18_{h7}	3000
02214	**EL/ML 100 Q 100 D 200**	55	50	6x6x40	22_{h7}	4500
02224	**EL/QS 125**	55	60	8x7x50	30_{h7}	5000

Sample ordering code:

Code-No.	L
02214	2000

Spindle shaft for EL/QL/QS 100 and DL/DS 200 with keyway, length 2000 mm






2.2

Coupling





Torsionally elastic coupling with keyway and clamp. Light pre-load provides backlash-free torque transmission. Standard spider type is 98-A. For higher torques spider type 64-D could be used as an opintion.


Code-No.	Type	ØA/B (min/max)	C	D	E	F	Gear ring	Shore-Scala	Torque [Nm]	
									T_{KN}	$T_{K\ max}$
01400-	7	3 / 7	7	14	22	DIN-key	98	A	2	4
							64	D	2,4	4,8
01401-	9	5 / 12	10	20	30		98	A	5	10
							64	D	6	12
01410-	14	5 / 16	11	30	35		98	A	12,5	25
							64	D	16	32
01420-	19	6 / 22	25	40	66		98	A	21	42
							64	D	26	52
01430-	24	10 / 28	30	55	78		98	A	60	120
							64	D	75	150
01440-	28	18 / 38	35	65	90		98	A	160	320
							64	D	200	400
01450-	38	30 / 45	45	80	114		98	A	325	650
							64	D	405	810

01401-	08	10

Sample ordering code:
Coupling type 9, ØA = 8 mm, ØB = 10 mm

Coupling for toothed belt units





Torsionally elastic coupling with keyway and clamp. Light pre-load provides backlash-free torque transmission.


Code-No.	Type	Ø A (min/max)	L	Size	F	Gear ring	Shore-Scala	Torque [Nm]	
								T_{KN}	$T_{K\ max}$
03400-	7	3 / 7	7	EL 30	DIN-key	98	A	2	4
						64	D	2,4	4,8
03401-	9	5 / 12	10	EL 40		98	A	5	10
						64	D	6	12
03410-	14	5 / 16	11	EL/ML 60 D 120 Q 60		98	A	12,5	25
						64	D	16	32
03420-	19	6 / 22	25	EL/ML 80 D 160 Q 80		98	A	21	42
						64	D	26	52
03430-	24	10 / 28	30	EL/ML 100 D 200 Q 100		98	A	60	120
						64	D	75	150
03440-	28	18 / 38	35	EL/QS 125		98	A	160	320
						64	D	200	400

03410-	12

Sample ordering code:
Coupling type 14, ØA = 12 mm

Coupling with tension ring





Coupling, to be clamped by tension ring.

Code-No.	Type	Ø A	L	Size	Gear ring	Shore-Scala	Torque [Nm]	
							T_{KN}	$T_{K\ max}$
03501-	14	5, 10, 14	19	EL/ML 60 D 120 Q 60	98	A	12,5	25
					64	D	16	32
03510-	19	10, 14, 16, 19	25	EL/ML 80 D 160 Q 80	98	A	21	42
					64	D	26	52
03520-	24	19, 20, 22, 24	30	EL/ML 100 D 200 Q 100	98	A	60	120
					64	D	75	150
03530-	28	38	35	EL/QS 125	98	A	160	320
					64	D	200	400

03510-	16

Sample ordering code:
Coupling type 19, ØA = 16 mm


BAHR Modultechnik
EDELSTAHL Rost frei
TÜV NORD
AEO


Accessories

Synchronous coupling


Coupling for synchronizing of two parallel units.
Light pre-load provides backlash-free torque transmission.

Code-No.	Type	Ø A	Ø D	E	Ø F	G	H	Gear ring	Shore-Scala	Torque [Nm]	
										TKN	TK max
03411	**14**	14	30	35	33,6	23,5	11,5	98	A	12,5	25
								64	D	16	32
03421	**19**	18	40	41	46	25	16	98	A	21	42
								64	D	26	52











Code-No.	Type	Ø A	Ø D	E	Ø F	G	H	J	Gear ring	Shore-Scala	Torque [Nm]	
											TKN	TK max
03412	**14**	19 | 19,05 22 | 24	40	50	44	38,5	11,5	32	98	A	12,5	25
									64	D	16	32









Flange coupling

Code-No.	Type	Ø A	Ø B	Ø C	Ø D	E	F	G	H	Gear ring	Shore-Scala	Torque [Nm]	
												TKN	TK max
039265	**14**	43	40	31,5	5	24	12,5	3	5	98	A	12,5	25
										64	D	16	32











Angular gear box EL / EG







Code No.	Type	i	m	A	B	R	S Ø x l	Torque	max. rpm(min^{-1})
00731	30	1:1	1	42	38	–	5x15	2 Nm	250
00741	40	1:1	2	58	50	3x3	10x27	5 Nm	560
00742	40	1:1,5	1,5	58	50	3x3	10x27	5 Nm	560
									840
00761	60	1:1	2,5	82	70	5x5	14x35	15 Nm	750
00762	60	1:1,5	2	82	70	5x5	14x35	15 Nm	560
									840
00781	80	1:1	3	102	90	6x6	18x45	25 Nm	750
00782	80	1:1,5	3	102	90	6x6	18x45	25 Nm	560
									840
00711	100	1:1	4	130	110	6x6	22x45	30 Nm	750
00712	100	1:1,5	3	130	110	6x6	22x45	30 Nm	560
									840

Complete self- centering gear. Can easily be retrofitted to any EG or EL unit. Packed with grease for lubrication.

Transmission unit EL / EG

A shaft carried on ball bearings in an aluminium hollow section can be used to transmit torque or as a joining element for combining parallel linear units or as an individual element in angular operation.






Code-No.	Type	A	B	C	D	E	L_{min}	L_{max}
01931	30	30	42	40 x 0,7	-	5 x 15	38	3.000
01932	30 no shaft	30	42	40 x 0,7	-	-	38	3.000
01941	40	40	58	48 x 1	3 x 3	10 x 27	50	6.000
01942	40 no shaft	40	58	48 x 1	-	-	50	6.000
01961	60	60	82	62 x 1	5 x 5	14 x 35	100	6.000
01962	60 no shaft	60	82	62 x 1	-	-	100	6.000
01981	80	80	102	80 x 1	6 x 6	18 x 45	90	6.000
01982	80 no shaft	80	102	80 x 1	-	-	90	6.000
01911	100	100	130	110 x 1	6 x 6	22 x 45	110	6.000
01912	100 no shaft	100	130	110 x 1	-	-	110	6.000

01941	0750	Sample order code: Size 40, length L = 750 mm

Toothed pulley HTD

Material St 50, secured with key.





Code-No.	Type	A	B	C	D	E	F	Number of teeth	Spacing
00450	EL/EG 30	6	23	26	18,3	15	2x2	20	3x15
00451	EL/EG 40	10	36	26	30,7	15	3x3	20	5x15
00452	EL/EG 60 DL/DS120	14	44	38	40,2	25	5x5	26	5x25
00453	EL/EG 80 DL/DS160	18	54	38	49,8	25	6x6	32	5x25
00454	EL100	22	66	48	61,1	38	6x6	24	8x30

Toothed belt endless HTD



Code-No.	Type	Belt	Tensile force
00550	**EL/EG 30**	3M15	200 N
00551	**EL/EG 40**	5M15	390 N
00556	**EL/EG 40**	5M09	298 N
00552	**EL/EG60**	5M25	894 N
00553	**EL/EG80**	5M25	894 N
00554	**EL100**	8M30	1070 N
00555	**EL100**	8M20	980 N


00551	0700

Sample order code:
Belt 5M15 perimeter: 700 mm


Parallel transfer unit for spindle drives

DL / DS





EL / EG / Q



04099

Black anodized aluminium tube with plastic end caps, pulleys fixed with keys or tension rings. Spindle centers are multiples of 5 or 8 mm, according to belt pitch.

Code-No.	Type	A	B	C	L_{max}	Belt
T13030	**EL/EG 30**	50	25	25	1.200	5M 9
T13040	**EL/EG 40**	80	40	30	1.500	5M 15
T13060	**EL/EG/Q 60**	100	50	42	2.000	5M 25
T13061	**DL/DS 120 ***	60	50		2.000	5M 25
T13080	**EL/EG/Q 80**	120	50	52	2.000	5M 25
T13081	**DL/DS 160 ***	80	50		2.000	5M 25
T13010	**EL/Q 100**	160	80	66	3.000	8M 30

* Parallel transfers are special disigned parts. Demensions given in the documentation are samples.


T13060	500

Sample ordering code: Center-distance of axis L = 500 mm

For center-distances higher than 800mm you have to use an additional tensioning device code-number 04099.

Tensioning device	
Code-No.	**B**
04099-40	40
04099-50	50
04099-60	60

Cable conduit EL / ML / QS




Slotted plastic tube for cabling directly onto body of linear unit. The tube can simply be pressed into the half-round slot in the body and will be securely retained there.

Code-No.	Type	A	B	L
02806	**EL 40**	6	4	max. 50m
02810	**EL/ML/Q 60**	10	7,5	max. 50m
02812	**EL/ML/Q 80**	12	8,5	max. 50m
02816	**EL/ML/Q 100**	16	12	max. 50m
02820	**EL/QS 125**	20	15	max. 50m

02816	1000


Sample ordering code:
Plastic tube for EL 100, 1000 mm long.

Cable chain



Black plastic, one floating and one fixed mounting bracket. The inner face opens like a zip, enabling cable to be inserted easily.

Code-No.	Type	Name	A	B	C	D
02115	**15**	Cable chain	25,5	15	18	23
02125	**25**	Cable chain	35,5	25	18	23
02138	**38**	Cable chain	48	38	18	23
02150	**50**	Cable chain	60	50	18	23
02116	**15**	fixing brackets (2 pieces)				
02126	**25**	fixing brackets (2 pieces)				
02139	**38**	fixing brackets (2 pieces)				
02151	**50**	fixing brackets (2 pieces)				





System profiles

3.2

Angular bracket profile









x		x	
0	uncoated, without machining	2	uncoated, with machining
1	anodized, without machining	3	anodized, with machining

Function:
Various assemblies and axis types can be connected to the angular bracket profile. It can also be used to reinforce self-supporting positioning systems or to mount portals on profile frames.

Code-No.	A	B	C	D	E	F	G	H	I	J	K	L	M for	N	P	Q	R	m [kg/m]	$L_{max.}$
4200x	227	140	142	130	15	80	15	8,05	10	15	27	10	M 6	17	28	13	16	19,9	6000

Angular bracket LL 60 / LS 60








Function:
This mounting bracket can be used to link LL 60 and LS 60 axis types.


Code-No.	A	B	B1	B2	B3	B4	C	E	F	G	H	K	N	O	P	S	T	U	m [kg/m]
038L602L60	255	140	207	183	77	53	6,60	10	14,33	15	Ø 5,5	Ø 10	12	58	18	134	72	10	1,0 kg

Angular bracket for combination of Q60 and D120












Function:
Various assemblies and axis types can be connected to the angular bracket. It can also be used to reinforce self-supporting positioning systems or to mount portals on profile frames.


Code-No.	A	B	C	D	E	F	G	O	P	R	S	T	U	V	W	Z	[kg/m]
038 060 120	131	108	120	102	90	15,5	16,5	60	36	70	15	15	6,5	78	21	46	0,765 kg

Angular bracket for combination of Q80 and D160










Function:
Various assemblies and axis types can be connected to the angular bracket. It can also be used to reinforce self-supporting positioning systems or to mount portals on profile frames.

Code-No.	A	B	G	H	I	K	M	N	R	O	P	U	V	W	Z	[kg/m]
038 080 160	163	111	17	9	15	9	130	13	71	80	50	9	90	37	50	1,174 kg

3.2

Mounting profiles




Code-No.	Type	Mass [kg/m]
05030	**30**	0,917
05040	**40**	1,780
05060	**60**	3,880
05048	**40 x 80**	3,340
05080	**80**	5,817
05061	**60 x 120**	7,500
05062	**120 x 120**	11,500
05081	**80 x 160**	12,096
05082	**160 x 160**	21,955

Code-No. Length in mm

05030	2000

Sample ordering code: Mounting profile Type 30, 2.000 mm long.

Mounting profiles




Code-No.	Type	A	B	C	D	m [kg/m]	$L_{max.}$
40098	**30**	12	10	41	54	0,302	3.000
40068	**40**	16	13	54	72	0,53	3.000
40059	**60**	18	18	77	96	0,93	3.000
40079	**80**	20	23,5	97	120	1,37	3.000
40088	**100**	22	30,5	120	144	2,07	3.000
40108	**125**	27,5	40	149	180	3,39	3.000

Code-No. Length in mm

40059	2000

Sample ordering code: Mounting profile Type 60, 2.000 mm long.






Specifications

Calculation of toothed belt

Calculation of the max. acceleration





To calculate your load data, please use the timing belt calculation of Continental:

www.conti-professional.com


Act as follows:


- Register an account
- Create a new project
- Select "Open ended belts" in the project editor
- Select drive type "Linear slide"
- Enter tooth belt type and parameters
- Calculate





Calculation of toothed belt





Calculation of toothed belt

Resulting report:: **Vertical linear drive, closed**

Given data

Mass of carriage	MH	25.00	[kg]
Mass of counterweight	MG		[kg]
Number of teeth	z	26	[-]
Overall belt length	LB	4000.00	[m]
req. factor of break resistance	sgefb	7	[-]
req. safety against permissible force	sgefzul	1	[-]

Carriage downwards - emergency stop

Acceleration force of carriage	FHbes	212.50	[N]
Weight force of carriage	FHgew	245.25	[N]
Acceleration force of counterweight	FGbes	0.00	[N]
Weight force of counterweight	FGgew	0.00	[N]
Force at motor shaft	Fmot	457.75	[N]
Braking torque	Mmot	9.47	[Nm]
Maximum load	Fmax	370.25	[N]

Load values

Force during start	Fanf.	370.25	[N]
Force during braking	Fbrems	457.75	[N]
Required pretension	FV	457.75	[N/Tr.]
Measuring Length below mass	L_p	1300.00	[mm]
Set-Frequency	f_{stat}	25.83	[Hz]
Bearing load in motor shaft	FLmot	1373.25	[N]
Bearing load idler	FLuml	1743.50	[N]
Belt force 1/1	Ftr	686.63	[N]
Maximum belt force	Ftr max	915.50	[N]
Safety rope	Sr	1.77	[-]
Safety break	St	7.10	[-]
Safety teeth	Sz	1.88	[-]
Permissible force	Fzul	1625.00	[N]

Carriage upwards

Acceleration force of carriage	FH_{bes}	-125.00	[N]
Weight force of carriage	FH_{gew}	245.25	[N]
Acceleration force of counterweight	FG_{bes}	0.00	[N]
Weight force of counterweight	FG_{gew}	0.00	[N]
Force at motor shaft	F_{mot}	457.75	[N]
Motor torque	M_{mot}	7.66	[Nm]
Maximum load	F_{max}	457.75	[N]

Kinematic values

Velocity	v	2.00	[m/s]
Relative starting acceleration	aan r	5.00	[m/s²]
Absolute starting acceleration	aan a	14.81	[m/s²]
Relative braking acceleration	abr r	8.50	[m/s²]
Absolute braking acceleration	abr a	18.31	[m/s²]
Braking distance	sbr	0.24	[m]
Braking time	tbr	0.24	[s]
R.P.M.	n	923.08	[1/min]


Specifications

Weights


Sizes	Guide body profile	Internal profile	guide rod	Belt	per pulley	Toothed rack	Standard carriage	Carriage profile	Coupling
30	1,08 kg/m	-	0,15 kg/m	0,037 kg/m	0,06 kg	-	0,176 kg	1,78 kg/m	0,007 kg
40	1,92 kg/m	-	0,22 kg/m	0,074 kg/m	0,14 kg	0,70 kg/m	0,520 kg	3,42 kg/m	0,010 kg
60	3,86 kg/m	-	0,61 kg/m	0,123 kg/m	0,39 kg	4,30 kg/m	1,565 kg	7,66 kg/m	0,040 kg
60S	3,86 kg/m	-	0,61 kg/m	0,123 kg/m	0,39 kg	4,30 kg/m	2,420 kg	8,60 kg/m	0,040 kg
80	7,41 kg/m	-	0,88 kg/m	0,256 kg/m	1,04 kg	6,20 kg/m	2,644 kg	12,96 kg/m	0,085 kg
80S	7,41 kg/m	-	0,88 kg/m	0,256 kg/m	1,04 kg	6,20 kg/m	3,520 kg	13,80 kg/m	0,085 kg
100	11,1 kg/m	-	1,58 kg/m	0,355 kg/m	0,81 kg	6,20 kg/m	6,550 kg	19,40 kg/m	0,200 kg
125	15,91 kg/m	-	2,45 kg/m	0,480 kg/m	1,54 kg	-	12,100 kg	26,63 kg/m	0,395 kg
DL 120	5,50 kg/m	1,52 kg/m	0,22 kg/m	0,123 kg/m	0,39 kg	-	1,100 kg	4,19 kg/m	0,040 kg
DL 160	10,33 kg/m	2,66 kg/m	0,61 kg/m	0,256 kg/m	0,90 kg	-	3,280 kg	7,99 kg/m	0,085 kg
DL 200	16,08 kg/m	3,48 kg/m	0,61 kg/m	0,355 kg/m	0,688 kg	-	4,950 kg	11,05 kg/m	0,200 kg
DS 120	5,06 kg/m	1,52 kg/m	0,65 kg/m	0,123 kg/m	0,39 kg	-	0,920 kg	5,57 kg/m	0,040 kg
DS 160	10,52 kg/m	2,66 kg/m	2,21 kg/m	0,256 kg/m	0,86 kg	-	2,250 kg	10,01 kg/m	0,085 kg
DS 200	14,16 kg/m	3,48 kg/m	3,21 kg/m	0,355 kg/m	1,83 kg	-	5,345 kg	15,01 kg/m	0,200 kg
QL 60	3,29 kg/m	-	0,22 kg/m	0,123 kg/m	0,39 kg	-	0,456 kg	2,05 kg/m	0,040 kg
QL 80	7,05 kg/m	-	0,61 kg/m	0,256 kg/m	0,90 kg	-	1,229 kg	3,85 kg/m	0,085 kg
QL 100	10,48 kg/m	-	0,61 kg/m	0,355 kg/m	1,83 kg	-	2,920 kg	5,49 kg/m	0,200 kg
QS 60	3,74 kg/m	-	1,45 kg/m	0,123 kg/m	0,39 kg	-	0,860 kg	2,05 kg/m	0,040 kg
QS 80	6,82 kg/m	-	2,21 kg/m	0,256 kg/m	0,90 kg	-	2,339 kg	3,85 kg/m	0,085 kg
QS 100	10,56 kg/m	-	3,21 kg/m	0,355 kg/m	1,83 kg	-	4,320 kg	5,49 kg/m	0,200 kg
QS 125	16,08 kg/m	-	4,47 kg/m	0,480 kg/m	0,60 kg	-	5,544 kg	10,03 kg/m	0,395 kg
ALL	27,45 kg/m	-							
QST/K 60	2,77 kg/m		1,45 kg/m					3,39 kg/m	
QST/K 80	5,47 kg/m		2,21 kg/m					5,88 kg/m	
QST/K 100	8,48 kg/m		3,21 kg/m					9,54 kg/m	

Diagram for maximum rpm of spindle units

ballscrew units




trapezoidal units



$n_{max.}$ = table value x 0,8

Specifications

Calculation of torsional twist




$$f° = L \times M_{t\,max.} \times I_p \qquad \left[\frac{° \times Nm \times m}{Nm \times m}\right]$$


f°= max. twisting angle	(°)
L = unit length	(m)
$M_{t\,max}$= max. torque	(Nm)
I_p= see table	(°/Nm²)

Aluminium profiles
Stiffness F25 (250 N/mm²)
Thickness of anodizing coat 20 to 30 µm

4.2


Size	I_p Faktor	Size	I_p Faktor	Size	I_p Faktor
EL 30	0,49000 °/Nm x m	DL 120	0,03282 °/Nm x m	QL 60	0,02995 °/Nm x m
EL 40	0,18000 °/Nm x m	DL 160	0,01286 °/Nm x m	QL 80	0,01257 °/Nm x m
EG 40	0,14000 °/Nm x m	DL 200	0,00787 °/Nm x m	QL 100	0,00705 °/Nm x m
EL 60	0,05765 °/Nm x m	DS 160	0,01336 °/Nm x m	QS 60	0,03797 °/Nm x m
EG 60	0,04387 °/Nm x m			QS 80	0,01563 °/Nm x m
EL 80	0,01463 °/Nm x m			QS 100	0,00644 °/Nm x m
EG 80	0,01511 °/Nm x m				
EL 100	0,00492 °/Nm x m				
EL 125	0,00616 °/Nm x m				





Service manuals

Spindle lubrication EG 30 / EL 30




- Unscrew the cylindric screws (1) and push the wiper end plate (2) to the side.
- Unbend screws (3), push slide (S) to other side
- Unscrew the grub screw (4) and lift the coverband (5).
- Grease can be filled now with grease gun.

  For mass of greasing look at table below.


Type	Pitch	Regreasing
30	Kg 08 x 2,5	0,1 g

Spindle lubrication EG 40, 60, 80 / EL 60, 80, 100, 125

EG 40 / EL 40



EG 60, 80 / EL 60 -125



Type	Pitch	Regreasing	Type	Pitch	Regreasing
30	Kg 08 x 2,5	0,1 g	**60**	Kg 20 x 05	3,00 g
40	Kg 16 x 05	1,33 g	**80**	Kg 25 x 25	3,00 g
40	Kg 16 x 10	0,84 g	**80 / 100**	Kg 32 x 05	3,00 g
60	Kg 25 x 05	2,00 g	**80 / 100**	Kg 32 x 10	4,00 g
60	Kg 25 x 10	3,00 g	**100**	Kg 32 x 32	4,00 g
60	Kg 20 x 20	3,00 g	**125**	Kg 40 x 10	4,00 g


Ⓐ = carriage Ⓑ = wiper end plate

EG / EL 40
with greasing nipple behind the wiper end plate

EG 60, 80 / EL 60 - 125
with external greasing nipple

For mass of greasing look at table below.
Spindle greasing every 500-1000 working hours.


Guiding rods lubrication EL | ML



Rods will be greased by the strippers of carriage. There are 2 oil nipples in each wiper end plate **(4)**, where the tanks for the strippers can be filled with an oil gun.


Viscosity of oil: 200 mm²/s, T= 40° C. Interval of greasing depends on environmental conditions, min. once a month. Minimum stroke must be same than length of slide.

Rollers size lubrication EL 100, 125 | ML 100



Rollers should be greased each 1.000 working hours or each 6 months with a grease gun. For greaser nipple look at the eccentric at carriage bottom. Use roller grease.


Adjusting the carriage EG 30, 40, 60, 80



- Fix all 4 grub screws **(1)** with a hexagon socket wrench **(A)** at a centered position of the carriage.
- Loose all grub screws **(1)** about ⅛ rotation and hit the carriage carefully free by a soft-head hammer.
- Pay attention to a centered position of the carriage. (Check by a caliper.)

The grub screws **(1)** shoud be locked by bonding.

Changing cover band EL | EG 30, 40




- Unscrew cylindric screws (1) on both sides of carriage (5).
- Push wiper endplate (4) to the side.
- Unscrew the screws (2) on both bearing parts and remove the cover band clamp (3).
- Pull out the coverband (6).

- Mount the new cover band and the cover band clamp (3). Then fix the screws (2) on one side of bearing block (7), tense the band with a pointed pliers and fix with the screws (2).
- Mount the wiper end plates (4) with the cylindric screws (1) on both sides of carriage (5). Pay attention to the seat of the slides (8).


5.2

Changing cover band EL 100, 125




- Unscrew cylindric screws (1), push plastic wiper endplate (4) to one bearing-block (7).
- Unbend grub screws (2), push carriage (5) to other side.
- Unscrew screws (3) and pull out the coverband (6).
- Mount the new coverband, fix the screws (3) at one side, tense the band with a pointed pliers and fix the screws (3).
- Fix the carriage (5) by the grub screws (2)and mount the wiper end plate (4).

Changing cover band ELHZ / ELVZ 60, 80



- Unscrew cylindric screws (9) on both sides of carriage (5).
- Push the wiper end plates (4) to the side.
- Unscrew the grub screwes (2) and pull out the old coverband (6).
- Push the new coverband under both sliding block (8) in the carriage (5) and wiper end plates (4) into the bearing block (1).
- Fix the grub screw (3) on one side.
- Tense the coverband with a pointed pliers and fix the screws (3) on the opposite side.


Changing cover band ELHZ / ELVZ 100, 125



- Unscrew cylindric screws (9) on both sides of carriage (5).
- Push the wiper end plates (4) to the side.
- Unscrew the grub screwes (2) and pull out the old coverband (6).
- Push the new coverband under both sliding block (8) in the carriage (5) and wiper end plates (4) into the bearing block (1).
- Fix the grub screw (3) on one side.
- Tense the coverband with a pointed pliers and fix the screws (3) on the opposite side.

Important:
Measure the distance "s" between the corner of carriage and the head of the grub screw for belt-tension!


ALLZ 203, 204 belt tension adjustment



Ⓑ Hexagon socket wrench SW 10
for belt adjustment screw (1)

Adjust the belt adjustment screws (1) evenly and in accordance with the respective application.

ALLZ 203, 204 roller adjustment




Ⓐ Ring wrench (cranked)
for tightening and fixing the hexagon nut.

Ⓑ Hexagon socket wrench
for adjusting the eccentrics.

- Loosen the hexagon screw (1), so that the eccentric can be rotated.
- Adjust the carriage without backlash by rotating the eccentrics (2) in small increments.
- After the eccentrics have been adjusted, fix the eccentric using the hexagon socket wrench (B) and tighten the hexagon socket (1) using the cranked ring wrench (A).

ALL roller lubrication




The rollers are lubricated by means of an oiled felt insert.


- The felt can be relubricated through lubricating nipples (1) in the carriage.

Viscosity of oil: 200 mm²/s, T= 40° C. Interval of greasing depends on environmental conditions, min. once a month. Minimum stroke must be same than length of slide.


Belt tension ELZ




- Push the carriage (5) close to one bearing-block (7).
- Unscrew grub screws (2) of the wiper endplate (4) and push it to the other bearing-block (7).
- Pull the spring balance with force of table and measure the sag (f) of the belt. Compare the measured value with the table.
- Tense or release the belt by the grub screws (2).
- Both grub screws (2) must have the same distance between the corner of the carriage (5) and the head of the grub screw (2).
- The grub screws (2) have to be secured by bonding.
- Measure the distance (s) with a metal rule.
- Mount the wiper endplate (4).




Baugröße / Size	Kraft / Force
30	20 N
40	20 N
60	30 N
80	50 N
100	50 N
125	50 N




Adjusting the rollers, sizes EL 40, 60






- Fasten eccentric bolt with screw key (1).
- Unscrew screw with hexagon socket screw key (2) as far as eccentric bolt can be turned, upper surface is stamped, broken line of stamp (3) must coincide with drawing groove of slide.
- Adjust at other side without initial tension.
- Stamps must be in same position and eccentric bolt must be adjusted into right direction.


Adjusting the rollers, sizes EL 30, 80, 100, 125



Exchange of rollers ELZ

Example: ELZU with upper and lower carriage






1. Clamping screw with schnorr washer
2. Eccentric bolt
3. Roller
4. Adjusting washer

- Unscrew clamping screws **(F)** and dismount the wiper end plates **(A)** and put them aside.
- Unscrew clamping screws **(1)** and push the connecting flange **(B)** to the side.
- Loosen the grub screws **(C)** from the belt tensioner **(D)**. Now the carriage can be freely moved.
- Unscrew the clamping screws **(1)** in the carriage **(E)** and remove eccentric bolt **(2)**.
- Remove rollers **(3)** and adjusting washers **(4)**.
- Insert new rollers: Put the adjusting washer **(4)** into the existing milled opening. Place the roller **(3)** onto the adjusting washer **(4)** so that it accurately fits. Re-insert eccentric bolt **(2)**. Tighten the clamping screws **(1)** carefully so that the eccentric bolt **(2)** is still freely movable.

- Adjust the rollers!
- After the rollers have been successfully adjusted, fix the clamping screws **(1)**.

Belt exchange ELZ



Measure and record
the screw depth.


- Unscrew cylindric screws (1) and dismount wiper end plates (2) on both sides of the carriage.
  Take care, that the felt wipers (F) don`t drop out.
- The belt adjusters are fixed by grub screws (3) in the carriage (S); to reach the right belt tension measure the distance between the edge of the carriage and the head of the grub screws. *Notice: the distance must be the same on both sides in axial direction.*
- Unscrew the grub screws (3) and dismount the belt adjusters (8).
- Unscrew the grub screws (4 + 5) and the cylindric screws (6) and separate the bearing-block (7) from the unit.
- Pull out the toothed belt (10). In most cases it is not necessary to separate both bearing blocks for inserting the new belt.

The reconstruction of the unit takes place in opposite order.

- Shorten the new belt to the length of the old one.
- Insert the toothed belt with the toothed side to the profile (P) into the not dismounted pulley block (A). Rotate the toothed pulley (11) until the toothed belt (10) appears at the end of the profile (P) and pull the belt through the dismounted pulley block (7).
- Mount the pulley block (7) on the profile (P) and tighten the grub screws (4 + 5) and the cylindric screws (6).
- Mount the belt adjusters (8) on the ends of the toothed belt and *secure the countersunk screws (9) by bonding.*
- Insert the belt adjusters into the carriage (S) and *secure the grub screws (3) by bonding.*
- Tension the belt as per description above and finally mount the wiper end plates (2) on the carriage.
  (Notice: the easiest way for mounting the wiper end plates is to secure the wipers with a rubberband while mounting.)

Leading-nut

Applies to all positioning systems from 2017 onwards.



DLK / DLT 120, 160, 200
DSK / DST 120, 160, 200


- The leading-nut can be relubricated through a lubricating nipple (1) in the carriage.
- Regrease with a grease gun.

For the quantity of grease see table below.
Spindle greasing every 500 - 1000 working hours.

Type	Pitch	Quantity	Type	Pitch	Quantity
120	KG 16 x 05	1,33 g	**120/160**	KG 25 x 25	3,00 g
120	KG 16 x 10	0,84 g	**200**	KG 32 x 05	3,00 g
120	KG 16 x 16	1,00 g	**200**	KG 32 x 10	4,00 g
120/160	KG 20 x 20	3,00 g	**200**	KG 32 x 20	4,00 g
120/160	KG 25 x 05	2,00 g	**200**	KG 32 x 32	4,00 g
120/160	KG 25 x 10	3,00 g			

5.2

Leading-nut




DLK / DLT 120, 200
DSK / DST 120, 200

Applies to all positioning systems up to December 2016.

- Drive the carriage (S) to the service position (1).
- Remove the fillister head screws (2) and dismount cover cap (3).
- Remove the middle slider (4) and unscrew set screws (5).
- Push carriage (S) to the side.
- Release the set screw (7) and remove it using the sliding nut (N).
- Pull out and lift the cover band (8), now the lubrication hole is visible in the leading-nut receptacle (9).
- Regrease with grease gun.

For the quantity of grease see table below.



DLT / DLK 160
DST / DSK 160

Applies to all positioning systems up to December 2016.


- Drive the carriage to the service position (1).
- Remove the fillister head screws (2) and dismount cover cap (3).
- Remove the middle slider (4).
- Insert the regreasing adapter (A) into the lubrication hole of the leading-nut receptacle.
- Regrease now with grease gun. For the quantity of grease see table below.

Spindle greasing every 500 - 1000 working hours.

Type	Gewinde/ Pitch	Nachfettung/ Regreasing	Type	Gewinde/ Pitch	Nachfettung/ Regreasing
120	KG 16 x 05	1,33 g	**120/160**	KG 25 x 25	3,00 g
120	KG 16 x 10	0,84 g	**200**	KG 32 x 05	3,00 g
120	KG 16 x 16	1,00 g	**200**	KG 32 x 10	4,00 g
120/160	KG 20 x 20	3,00 g	**200**	KG 32 x 20	4,00 g
120/160	KG 25 x 05	2,00 g	**200**	KG 32 x 32	4,00 g
120/160	KG 25 x 10	3,00 g			

5.2

Leading-nut




DST/K 120 P, 160 P and 200 P


- Drive the carriage to the service position (A).
- Dismount the cover cap (2).
- Drive the carriage until you can see the greasing nipple in the grease hole.
- Regrease with an grease gun (1). For the quantity of grease see table below.

Spindle greasing every 500 - 1000 working hours.

Type	Gewinde/ Pitch	Nachfettung/ Regreasing	Type	Gewinde/ Pitch	Nachfettung/ Regreasing
120	KG 16 x 05	1,33 g	**120/160**	KG 25 x 25	3,00 g
120	KG 16 x 10	0,84 g	**200**	KG 32 x 05	3,00 g
120	KG 16 x 16	1,00 g	**200**	KG 32 x 10	4,00 g
120/160	KG 20 x 20	3,00 g	**200**	KG 32 x 20	4,00 g
120/160	KG 25 x 05	2,00 g	**200**	KG 32 x 32	4,00 g
120/160	KG 25 x 10	3,00 g			

Guiding rods






DL 120, 160, 200
QL 60, 80, 100

Lubrication is effected by an oiled felt insert. The felt can be re-oiled through lubrication nipples attached laterally to the ends of the roller packs.

- Dismount cover cap (1).
- Drive the carriage through the service position until you can see the first lubricating nipple (2) in the lubrication hole.
- Re-oiled felt now with an oil gun.
- Move the carriage to the second lubricating nipple and re-oiled here as well.

Oils with a viscosity of approx. 200 mm²/s at T=40°C are recommended. The required regreasing intervals depend on environmental conditions, the standard recommendation is once per month. To ensure a sufficient lubrication, the minimum stroke must equal the carriage length, so that sufficient greasing is achieved also in the final positions.


Runner blocks DS 120



- Dismount cover cap (1).
- Drive the carriage through the service position until you can see the first runner block in the lubrication hole.
- Re-greasing with a cartridge with cannula.
- Move the carriage to the next runnerblock and re-grease here as well.




Runner blocks DS 120, 160, 200 QS 60, 80, 100




Runner blocks have to be regreased with high quality bearing grease.

- Dismount cover cap (1)
- Drive the carriage through the service position until you can see the first greasing nipple (2) in the lubrication hole.
- Re-greasing with grease gun.
- Move the carriage to the second greasing nipple and re-grease here as well.

We recommended bearing grease based on DIN 51825. The required regreasing intervals depend on environmental conditions, the standard recommendation is once per 1.000 km. *DS 120: 150 km*




Runner blocks QS 125



Re-greasing with a grease gun directly at the carriage side.

Relubrication			
Type	**Quantity**	**Type**	**Quantity**
DS 120	0,3ml	QS 60,	0,4ml
DS 160	0,4ml	QS 80	0,5ml
DS 200	0,8ml	QS 100,	0,8ml
		QS 125	1,2ml

Leading-nut



QST / QSK 60, 80, 100


Leading-nuts have to be regreased with high quality bearing grease.

- Dismount cover cap (1).
- Drive the carriage through the service position until you can see the first greasing nipple (2) in the grease hole.
- Regrease felt now with an grease gun.
- Move the carriage to the second greasing nipple and re-grease here as well.

We recommended bearing grease based on DIN 51825. The required regreasing intervals depend on environmental conditions, the standard recommendation is once per 1.000 km.


Type	Gewinde/ Pitch	Nachfettung/ Regreasing	Type	Gewinde/ Pitch	Nachfettung/ Regreasing
60	KG 16 x 05	1,33 g	**100**	KG 32 x 05	3,00 g
60	KG 16 x 10	0,84 g	**100**	KG 32 x 10	4,00 g
60	KG 16 x 16	1,00 g	**100**	KG 32 x 32	4,00 g
80	KG 20 x 20	3,00 g			
80	KG 25 x 05	2,00 g			
80	KG 25 x 10	3,00 g			

Belt tension adjustment DLZ / DSZ 120, 160, 200




- Push the carriage (1) close to one bearing block (2).
- Remove fillister head screws (3).
- Unscrew set screws (4) for middle cover band (5) at the opposite bearing block.
- Pull cover band out of bearing block and turn it to the side.
- Use springe balance (6) to exert the applicable amount of force (see table) on the center of the belt and measure the sag (f).
  - Compare the measured value with the diagram below, and tense of release belt as required by tightening or unscrewing the set screws (7).
  - The set screws (7) must be bonded in place with screw locking device.
  - Both screws (7) must be screwed in to exactly the same level. Check with sliding caliper.

Baugröße / Size	Hub / Stroke (mm)	Kraft / Force (N)
120	< 2500 2500 - 6000	20 10
160	< 2500 2500 - 6000	20 10
200	< 2500 2500 - 6000	40 20



Changing cover band




DLZ / DSZ 120, 160, 200
DLT / DLK / DST / DSK 120, 160, 200


- Drive the carriage (S) to servicing position.
- Remove fillister head screws (1) and wiper end plate (2).
- Size 160 and 200: Unscrew set screws (3) at both bearing-block plates (4) and pull the cover band out of the bearing block.
- Size 120: Unscrew set screws (3) and remove them with T-nut (N).
- Remove the sliders (5) and (6) from both sides of the carriage (S).
- Pull the cover bands (8) out of the carriage (S).
- Insert the new cover bands into the carriage (S).
- Thread the lateral sliders (6) onto the cover band and insert it into the carriage with middle slider (5).
- Size 160 and 200: Tighten cover bands on one side of the bearing block with set screws (3), tense cover band (8) at the other bearing block using pliers and tighten with set screws (3).
- Size 120: Insert T-nut together with set screw into the bearing block plates (4) and tighten cover band (8) with set screw (3).

5.2


Adjusting the rollers
DL 120, 160, 200



- Dismount cover cap (5) from servicing hole.
- Fasten eccentric bolt with screw key (1).
- Release screws with hexagon socket screw key (2) until the eccentric bolt can be turned.
- Adjust the gap dimension (A) between top of the carriage and body ground of guiding profile by turning the eccentric bolts (3). Turning towards + will increase the dimension A.
  DL 120: A=79 mm; DL 160: A=106 mm; DL 200: A=129 mm
- Turn the eccentric bolts (4) to adjust the carriage free of play by the touch (without initial tension).
- Ensure that the eccentric bolts are adjusted to the right.




Adjusting the rollers
QL 60, 80, 100



- Dismount cover cap (5) from servicing hole.
- Fasten eccentric bolt with screw key (1).
- Release screws with hexagon socket screw key (2) until the eccentric bolt can be turned.
- Turn the eccentric bolts to adjust the carriage free of play (without initial tension).
- Ensure that the eccentric bolts are adjusted to the right.

5.2

Belt exchange DL / DS 120, 160, 200




Measure and record the screw depth.

- Unscrew cylindric screws (1) and dismount the wiper end plates (2) on both sides of the carriage.
- Unscrew grub screws (3) on both sides of the unit and pull out only the middle cover band (4) of the bearing-block plate (5).
- Pull only the middle sliding block (7) out of the carriage.
- The belt adjusters are fixed by grub screws (6) in the carriage (S); to reach the right belt tension, measure the distance between the edge of the carriage (S) and the head of the grub screws (6).
- Unscrew grub crews (6) on both sides of the carriage (S).
- Unscrew cylindric screws (8) at the bearing-block plates (5) and dismount them completely with the bearing-blocks (9) at both ends of the unit.
- Pull out the belt-adjusters (11) completely with the belt out of the carriage (S) and the guiding-profile (P).
- Unscrew the countersunk head screws (13) and dismount the belt-adjuster (11,14).

Reconstruction of the unit in opposed order.

- Shorten the new belt to the length of the old one.
- Push the belt with teeth side up to the carriage (S) into the slot of the guiding-profile (10) and push it with the ends through each bearing-block (9).
- Mount the belt-adjusters (11,14) by the countersunk head screws (13). *Secure the countersunk head screws (13) by bonding.*
- Push them again together with the belt (Z) into the guiding-profile (P) and then into the carriage (S).
- Mount the bearing-block plates (5) again together with the bearing-blocks (9) at the ends of the unit.
- Screw the grub screws (6) into the carriage (S) as far as the recorded screwing depth. *Secure the grub screws (6) by bonding.*
- Pull the middle cover-band (4) through the carriage (S).
- Pull in the middle sliding block (7) into the slot of the carriage (S).
- Mount the grub screws (3) on one side of the unit and tension the 3 cover-bands from the other side and fix them too by the grub-screws (3).
- Finally mount the wiper end plates (2) on the carriage.

Belt exchange QL / QS




- Unscrew cylindric screws (1) and dismount the wiper end plates (2) on both sides of the carriage.
- Unscrew cylindric screws (3) on both sides of the carriage (S).
- Unscrew cylindric screws (4) and the grub screws (5) at the bearing-block (6) and dismount them completely at both ends of the unit.
- Pull out the belt-adjusters (7) completely with the belt out of the carriage (S) and the guiding-profile (P).
- Dismount the belt-adjusters. Unscrew the countersunk screws (12) from the belt-adjusters. Press the belt sideways out of both belt-adjusters (7).
- Pull the belt (9) completely out of the bearing-blocks (6).

Reconstruction of the unit in opposed order.

- Shorten the new belt to the length of the old one. The pre-existing holes must be drilled into the new toothed belt in the flank diameter of the screw (12).
- Push the belt with teeth side up to the carriage (S) into the slot of the guiding-profile (11) and push it with the ends through each bearing-block (6). Tip: rotate the toothed pulley (8) until the toothed belt appears through the bearing-block (6).
- Press the belt again into the belt-adjusters (7). *Secure the countersunk screws (12) by bonding.*
- Push them again together with the belt into the guiding-profile (P) and then into the carriage (S).
- Mount the bearing-blocks (6) again.
- Mount both belt-adjusters (7) into the carriage (S). *Secure the cylindric screws (3) by bonding.* You have to tension the belt with dosed force and test the soft running of the pulleys by turning them.
- Mount the the wiper end plates (2) again.


Lubrication LLZ 60 / LLZE 60



Rods will be greased by the strippers of carriage.
There are 2 oil nipples (1) in the carriage (2), where the tanks for the strippers can be filled with an oil gun.

Viscosity of oil: 200 mm²/s, T= 40° C. Interval of greasing depends on environmental conditions, min. once a month. Minimum stroke must be same than length of slide.

Adjusting the rollers LLZ / LLZE



① Eccentric key for tightening the 2-hole counternut.


② Hexagon socket for adjusting the eccentric.

③ Adjustable rollers

④ Non adjustable rollers

- Loose the 2-hole counter nut with the eccentric key (1).
- Try to turn the eccentric with the hexagon socket (2). The eccentric must be movable.
- Turn the eccentric with the hexagon socket closly and delicately to the right, until the eccentric is playless.
- Now fix the eccentric with the hexagon socket (2) and tighten the 2-hole nut by a turn to the right.

Lubrication LSZ / LSZE



In the carriage (2) are two greasing nipples (1) , where the runner blocks can be filled with an grease gun.

We recommended bearing grease based on DIN 51825. The required regreasing intervals depend on environmental conditions, the standard recommendation is once per 1.000 km.*

Relubrication	
Type	**Quantity**
LS 60	0,4 ml
LS 80	0,5 ml

Lubricants

Lubricants
















Code-No.	Name
09001	Molyduval, 1 litre, ISO-VG 220, range of temperature -30 °C bis 100 °C
09003	Steel oil gun for carriage rollers
09010	One hand oil gun 125cm³ (with cone tip und angle adapter)*
09004	Steel grease gun for ballscrew
09009	regreasing adapter DLT/K 160
09012	One hand grease gun 125cm³ (with cone tip und angle adapter)*
09002	SKF grease LGMT 2/1 (1 kg)
09006	Grease gun filling device LAGF 5 (for 5 kg canister)
09007	SKF grease LGMT 2/5 (5 kg)
09013	Grease gun filling device LAGF 18 (for 18 kg canister)
09014	SKF grease LGMT 2/18 (18 kg)
09016	Grease cartridge with cannula (5ml) for DS 120

* for from outside difficult to reach nipples







Anfrage 1-Achssystem/Inquiry 1-direction system
Anfrage 2-Achssystem/Inquiry 2-direction system
Anfrage 3-Achssystem/Inquiry 3-direction system

Fax inquiry


Anfrage 1-Achssystem/Inquiry 1-direction system




Firma/Company		Name	
Tel/Fax		Zykluszeit/Cycle time	s
Hub/Stroke	mm m kg	**Motore, Steuerung/Motors, Controllers**	
Genauigkeit/Repeatability	mm	Angebot/Offer	ja ☐ yes nein ☐ no
Geschwindigkeit/Velocity	m/s	Schrittmotor/Steppingmotor	☐
Beschleunigung/Acceleration	m/s^2	Servo	☐
Horizontal	☐	Drehstrom/AC	☐
Vertikal	☐	Gleichstrom/DC	☐

	Kräfte/Force	Momente/Torques
X	N	Nm
Y	N	Nm
Z	N	Nm


1 ☐




2 ☐




3 ☐




4 ☐




5 ☐




6 ☐




7 ☐




8 ☐



9 ☐




Anfrage 2-Achssystem/Inquiry 2-direction system




Firma/Company				Name			
Tel/Fax				Zykluszeit/Cycle time	s		
Masse/Mass			kg	**Motore, Steuerung/Motors, Controllers**			
	Hub/Stroke(mm)	a(m/s²)	v(m/s)	Angebot/Offer ja ☐ yes nein ☐ no			
X				Schrittmotor/Steppingmotor ☐		Kräfte/Force	Momente/Torques
Y				Servo ☐	X	N	Nm
Z				Drehstrom/AC ☐	Y	N	Nm
Drehachse/Rotation axis			1/min	Gleichstrom/DC ☐	Z	N	Nm


1 ☐




2 ☐




3 ☐




4 ☐




5 ☐




6 ☐




7 ☐




8 ☐



9 ☐




Anfrage 3-Achssystem/Inquiry 3-direction system




Firma/Company				Name			
Tel/Fax				Zykluszeit/Cycle time		s	
Masse/Mass			kg	**Motore, Steuerung/Motors, Controllers**			
	Hub/Stroke(mm)	a(m/s²)	v(m/s)	Angebot/Offer ja ☐ yes nein ☐ no			
X				Schrittmotor/Steppingmotor ☐		Kräfte/Force	Momente/Torques
Y				Servo ☐	X	N	Nm
Z				Drehstrom/AC ☐	Y	N	Nm
Drehachse/Rotation axis			1/min	Gleichstrom/DC ☐	Z	N	Nm


1 ☐




2 ☐




3 ☐




4 ☐




5 ☐




6 ☐




7 ☐



8 ☐



9 ☐





Terms and conditions of sale and payment

Terms and conditions of sale and payment

§ 1 Scope of the General Terms and Conditions

(1) The Supplier's deliveries, services and offers are made solely on the basis of these General Terms and Conditions. Thus, these General Terms and Conditions shall also apply to all future business relations, even if not explicitly agreed upon again. At the latest, these General Terms and Conditions shall be considered accepted upon acceptance of the goods or services. Any counter confirmations made by the Customer with reference to its own terms and conditions are hereby rejected.

(2) All agreements made between the Supplier and the Customer for the purpose of the fulfilment of this contract must be in writing.

§ 2 Offer and Conclusion of Contract

(1) Offers made by the Supplier are non-binding and subject to change. Any declarations of acceptance and all orders require the Supplier's confirmation in writing or by fax to be legally binding. The contract is deemed to be concluded upon the Supplier's sending a written declaration (acknowledgement of order), which shall be the decisive document determining the scope of its obligations. The delivery substitutes a written acknowledgement of order.

(2) The performance parameters specified in our catalogues and offers, such as illustrations, drawings etc., shall be considered as approximate only. Drawings, illustrations, dimensions, weights or other performance data are only binding if they have been explicitly agreed on in writing. The Supplier reserves, without restriction, all rights of ownership and copyright to any quotations, drawings and other documents (hereinafter collectively referred to as the "Documents"). These Documents may not be made accessible to any third parties without the Supplier's prior consent; should the order not be placed with the Supplier, such documents are to be returned to the Supplier immediately on request.

(3) The Supplier's sales staff is not authorised to make any verbal collateral agreements or to give any verbal assurances that go beyond the content of the written contract.

(4) The Customer is liable for the accuracy, correctness and completeness of the order documents and order information provided by it; this includes in particular drawings as well as technical specifications and samples. Any verbal information, also with regard to modifications or amendments to the documents and data already submitted, must be confirmed in writing. If an order is neither confirmed in writing nor executed by the Supplier within one month of its receipt, or in particular cases (e.g. in case of custom-made products) within three months of receipt – in which case the Customer is bound by its order during such period – the Customer shall be entitled to revoke its order without having the right to claim damages from the Supplier.

§ 3 Prices

(1) Unless stated otherwise, the Supplier is bound by the prices given in its quotations for a period of 30 days from their date of issue. Otherwise the prices mentioned in the Supplier's acknowledgement of order shall apply, which do not include the applicable legal value added tax, nor any cost of installation, start-up and assembly. Additional deliveries and services will be invoiced separately. Minimum order value 25 Euro.

(2) Unless otherwise agreed, the prices are FOB Luhden warehouse, excluding packaging, freight, postage and insurance cost. The type of packaging shall be chosen by the Supplier at its discretion. The packaging shall be invoiced to the Customer at cost price and will not be taken back by the Supplier.

§ 4 Time of Delivery and Performance / Acceptance

(1) Delivery dates or periods, which may be agreed upon in a binding or non-binding manner, must be specified in writing. Our delivery period begins with the date of our acknowledgement of order, provided that at this time all of the documents required from the Customer, the necessary permits, releases, clarifications and approvals of plans have been submitted and the agreed payment terms and other obligations have been fulfilled and, in addition, any and all technical issues that were still open when the contract was signed have been mutually agreed upon. If these prerequisites are not met in time, the delivery period will be prolonged accordingly.

(2) The Supplier is not liable for delays in delivery and performance, even if binding dates and times have been agreed upon, in cases of force majeure or in case of circumstances which substantially and not only temporarily impede the delivery or make it impossible - this includes in particular strike, lock-out, government orders, malfunction or breakdown of important production facilities/machines, delays in the supply of essential raw materials and utilities, delays in transport, etc.; this applies also when these circumstances affect our suppliers or their sub-suppliers. In such cases, the Supplier shall be entitled to delay the supply and/or performance for the duration of the hindrance plus an appropriate start-up time or to withdraw totally or in part from that part of the contract which is not yet fulfilled.

(3) If the hindrance lasts for longer than 3 months, the Customer shall be entitled, after granting a reasonable extension of time, to withdraw from that part of the contract which is not yet fulfilled. Should the delivery time be extended or should the Supplier be released from its obligations, the Customer shall have no right to claim compensation for damages. The Supplier may only invoke the aforementioned circumstances, if the Customer is informed accordingly without delay.

(4) In as far as the Supplier is responsible for the non-compliance with bindingly promised deadlines and dates, or in as far as the Supplier is in default, the Customer shall be entitled to compensation for delayed performance at the amount of 1/2% of the invoice value for each complete week of the delayed performance, but limited in total to a maximum of 5% of the invoice value of all deliveries and services affected by the delay. Any claims beyond this are excluded, unless the delayed performance is based on at least gross negligence by the Supplier.

(5) The Supplier is at all times entitled to make partial deliveries or to render partial services, unless such partial deliveries or partial services are not of interest to the Customer.

(6) If a formal acceptance procedure of the delivered materials is desired, the conditions of such procedure must be established at the latest upon conclusion of the contract. The acceptance procedure must be carried out at the Supplier's premises immediately after it has declared its readiness for acceptance. The cost of the acceptance procedure shall be borne by the Customer. Partial deliveries are permissible.
In all other cases, the delivery object is deemed to be accepted when it is taken into operation in accordance with its intended use, however at the latest 3 weeks after delivery to the Customer.

(7) If the Customer is in default of acceptance, the Supplier shall be entitled to claim compensation for any damages it has incurred; upon default of acceptance, the risk of accidental deterioration or accidental loss passes to the Buyer.

§ 5 Transfer of Risk

The risk is transferred to the Customer as soon as the consignment has been handed over to the person responsible for the transport or has left the Supplier's warehouse for the purpose of dispatch, irrespective of who bears the freight costs. If the delivery is delayed upon the Customer's request, the risk shall pass to the Customer when the notice is given that the goods are ready for delivery. Any storage costs incurred after the transfer of risk shall be borne by the Customer. At the Customer's request and expense, the Supplier shall insure shipments against the usual transport risks.

§ 6 Customer's Rights in Case of Defects

(1) The products are delivered free of defects in design, manufacturing and materials; the period for assertion of claims for defects is one year from the transfer of risk. This does not apply to claims for damages caused by defects. In case of claims for damages caused by defects, section 13 shall apply.

Terms and conditions of sale and payment

(2) Should the Supplier's operating or maintenance instructions not be observed, or should the products be modified, parts exchanged or consumables used which do not comply with the original specifications, then any claims for defects of the products shall become void, if the Customer cannot refute a relevant substantiated statement claiming that one of these circumstances has caused the defect. The same applies if the deficiencies are due to poor installation, wrong assembly, poor maintenance, defective or negligent treatment or storage, defective repairs not executed by the Supplier, modifications made without our written consent, excessive load, unsuitable conditions of use and inappropriate operating materials or to any chemical, electro-chemical or electrical influences for which we are not responsible as well as weather or other natural influences.

(3) Any claims made by the Customer relating to defects require the Customer to have duly fulfilled its obligations according to section 377 of the German Commercial Code (HGB) in terms of examining the goods and lodging a complaint, otherwise any claims shall be insubstantial: The Customer shall notify the Supplier's customer service manager of any defects in writing immediately, at the latest within one week of receipt of the delivery. In case of defects which cannot be detected within this period despite careful inspection, the Supplier shall be informed in writing immediately after they have been discovered.

(4) If the Customer has notified the Supplier of a defect, the Supplier shall demand, at its choice and expense, that either:

a) the defective part or unit be sent to the Supplier for repair and subsequent return; or

b) the Customer shall keep the defective part or unit ready and the Supplier shall send a service technician to carry out the repair on the Buyer's premises.

Should the Customer request that rectification work be carried out at a certain location, the Supplier may do so; in this case, any exchanged parts shall not be invoiced, however, working time and travelling expenses shall have to be paid according to the Supplier's standard rates.

(5) If the rectification should fail after an appropriate period, the Customer can, at its choice, either demand a price reduction or withdraw from the contract.

(6) Liability for normal wear is excluded.

(7) Only the immediate Customer is entitled to claims due to defects against the Supplier and such claims are not transferable.

(8) In case of parts used for completion, refurbishment or modification sent by the Customer to the Supplier, the latter will assume no liability for their behaviour during processing; should the materials become damaged during processing, the Supplier shall be indemnified for the processing costs incurred up to that point, unless the damage is due to an intentional or grossly negligent breach of duty by the Supplier or its vicarious agent or a breach of duty that is of material importance to the object of the contract. This limitation of liability does not apply to personal injury or death.

§ 7 Replacement Parts

For a period of five years following delivery of a machine, the Supplier shall deliver replacement parts for that machine at the current prices.

§ 8 Retention of Title

(1) Until settlement of all accounts receivable to which the Supplier should be entitled from the Customer now or in future arising from any legal grounds (including all balance claims from current account), the following securities shall be granted to the Supplier, which it will release on request at its choice insofar as their value exceeds the accounts receivable lastingly by more than 10%.

(2) The goods remain the property of the Supplier. Processings or modifications of the goods are always made for the Supplier as manufacturer, but without any obligation for it. Should the Supplier's (co-)ownership expire as a result of combination of items, it is agreed upon already now that the Customer's (co-)ownership of this combined item is transferred to the Supplier in a pro rata manner (with regard to the invoice value). The Customer shall store the Supplier's (co-)property free of charge. Goods for which the Supplier is entitled to (co-)ownership will hereinafter be referred to as 'goods under reservation'.

(3) The Customer is entitled to process and sell the goods under reservation in proper business dealings, provided that it is not in default of payment. Pledging or assignment as security is inadmissible. Any other accounts receivable (including all balance claims from current account) arising from resale or any other legal ground (insurance, unlawful act) regarding the goods under reservation are already now assigned in full by the Customer to the Supplier as security. The Supplier authorises the Customer irrevocably to collect the accounts receivable transferred to the Supplier for the Supplier's account in its own name. This collection authorisation can only be revoked if the Customer does not duly meet its payment obligations.

(4) Should any third parties have access of any kind to the goods under reservation, especially by orders of attachment, the Customer shall draw attention to the fact that the goods are the Supplier's property and shall inform the Supplier immediately, so that the Supplier can enforce its rights of ownership. In as far as the third party is unable to reimburse the Supplier for judicial or out-of-court costs arising in this context, the Customer shall be liable for such costs.

(5) In the event of conduct in violation of the contract on the part of the Customer – in particular default of payment – the Supplier shall be entitled to withdraw from the contract and to demand the return of the goods under reservation.

(6) Up to the complete payment of the goods under reservation, the Customer is obliged to keep the Supplier informed about the location of the goods under reservation at any time.

§ 9 Payment

(1) Unless agreed otherwise, the Supplier's invoices are payable 30 days after invoicing without deductions.
The Supplier is entitled, despite provisions made by the Customer stipulating otherwise, at first to credit payments made by the Customer against its older debts and shall inform the Customer of the type of transaction made. In the case that expenses have been incurred or interest accrued, the Supplier is entitled to credit the payment at first against the expenses, then the interest and finally against the main service.

(2) A payment is deemed to have been made only when the Supplier has the amount at its disposal. In case of cheques the payment is deemed as having been made when the cheque is cashed.

(3) Should the Customer be in default of payment, the Supplier shall be entitled to demand interest at a rate of 8 percentage points above the base rate as lump-sum compensation from the relevant time onwards. A lower rate is to be applied if the Customer can provide evidence of a lower burden; the Supplier may provide evidence of a higher damage.

(4) Should the Supplier learn of any circumstances that call the Customer's credit standing into question, in particular in case that a cheque is not cashed or payments are suspended, or should the Supplier learn of any other circumstances which call the Customer's credit standing into question, the Supplier shall be entitled to deem the total remaining debt as due, even if it has accepted cheques. In this case the Supplier is also entitled to demand payments in advance or securities.

(5) The Customer is only entitled to set-off, retention or reduction, even in case that complaints have been made or compensating claims pleaded, when the compensating claims have been determined to be final and beyond dispute. The Customer is, however, also entitled to retention due to compensation claims arising from the same contractual relationship.

Terms and conditions of sale and payment

§ 10 Design Changes

The Supplier reserves the right to make design changes at any time; however, it is not obliged to include such changes also in products already delivered.

§ 11 Patents

(1) In case of custom-made products, the examination and the liability with respect to any third party's property rights is exclusively the responsibility of the Customer. The Customer shall be responsible towards the Supplier in full scope that any third party's property rights will not be infringed hereby and shall hold the Supplier harmless from any possible claims for damages made by third parties due to such an infringement.

(2) The Supplier, in turn, shall indemnify the Customer and its customers with regard to claims arising from violation of copyrights, trademarks or patents, unless the design of a delivery item originates from the Customer. As far as the amount of the indemnification is concerned, the Supplier's obligation to indemnify is limited to the expected damage.
An additional prerequisite for the indemnification is that the conducting of legal proceedings is to be left to the Supplier and that the stated violation of rights is to be assigned exclusively to the design of the Supplier's delivery items without combination or usage together with other products.

(3) The Supplier has the choice to release itself from the obligations taken on in paragraph 1 by either

a) procuring the required licences with regard to the alleged violated patents
or
b) putting an altered delivery item or parts thereof at the Customer's disposal, which in case of exchange with the violating delivery item or part thereof will eliminate the accusation of violation with regard to the delivery item.

§ 12 Secrecy

The Supplier's technical documents, drawings, service and operating manuals as well as any and all information received from the Supplier during the contract negotiations regarding the function and the structure of the goods are subject to secrecy. The Customer agrees to prevent unauthorized persons from getting access to the corresponding information.

(2) Unless expressly otherwise agreed in writing, the information submitted to the Supplier in connection with the orders are deemed as non-confidential.

§ 13 Liability

(1) Claims for damages are excluded regardless of the type of violation, including unlawful acts, insofar as they are not due to intention or gross negligence.

(2) As far as the violation of material contractual obligations is concerned, the Supplier is liable for any negligence, however only up to the amount of the foreseeable damage. Claims for lost profit, saved expenditure, claims for damages by third parties as well as claims for other indirect and consequential damages cannot be made unless an essential quality feature guaranteed by the Supplier has the express purpose of protecting the Customer from such damage.

(3) The liability limitations and exclusions in paragraphs 1 and 2 are not applicable to claims which are due to deceitful conduct on the part of the Supplier, nor in case of a liability for guaranteed quality features, nor to claims according to the product liability law, nor to injuries to life, body or health.

(4) Insofar as the liability of the Supplier is excluded or limited, this shall also apply to the Supplier's clerical staff, employees, representatives and vicarious agents.

§ 14 Final Provisions

(1) A transfer of the contractual rights and obligations to third parties by the Customer is not permitted unless the Supplier has given its written consent.

(2) These General Terms and Conditions and the complete legal relationship between Supplier and Customer are subject to the laws of the Federal Republic of Germany. The provisions of the UN Convention on Contracts for the International Sale of Goods shall not apply.

(3) Bückeburg shall be the exclusive place of jurisdiction for any disputes arising directly or indirectly out of the contractual relationship if the Customer is a trader, a legal person under public law or a special fund under public law. The Supplier shall also have the right to institute legal proceedings at the Customer's place of business.

(4) In accordance with section 33 of the German Data Protection Law (BDSG) it is hereby pointed out that the Customer's data will be stored by the Supplier. These data will be processed in accordance with both the Federal Data Protection Law (BDSG) and the Teleservices Data Protection Law.

(5) Should one of the provisions of these General Terms and Conditions or a provision of any other agreement be or become ineffective, this will not affect the validity of any other provisions or agreements.